



11A Ant1 5580



11A Ant1 5700



11A Ant1 5720_UNII-2C

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn




CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



11AC20SISO_Ant1_5240



11AC20SISO_Ant1_5260



11AC20SISO_Ant1_5280

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



11AC20SISO_Ant1_5320



11AC20SISO_Ant1_5500



11AC20SISO_Ant1_5580

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



11AC40SISO_Ant1_5190



11AC40SISO_Ant1_5230



11AC40SISO_Ant1_5270

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



11AC40SISO_Ant1_5310



11AC40SISO_Ant1_5510



11AC40SISO_Ant1_5550

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



11AC40SISO Ant1 5670



11AC40SISO Ant1 5710 UNII-2C



11AC40SISO Ant1 5710 UNII-3

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



11AC80SISO_Ant1_5290



11AC80SISO_Ant1_5530



11AC80SISO_Ant1_5610

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



11AC80SISO Ant1 5690 UNII-2C



11AC80SISO Ant1 5690 UNII-3



11AC80SISO Ant1 5775

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn




3.7. Frequency Stability

Limit

FCC CFR Title 47 Part 15 Subpart E Section 15.407(g) / RSS-Gen 6.11

Test Item	Limit	Frequency Range (MHz)
Frequency Stability	Specified in the user's manual, the transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification)	5150~5250
		5250~5350
		5500~5700
		5725~5850

Test Configuration



Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyzer center frequency to transmitting frequency.
- (3) Set the span to encompass the entire emissions bandwidth (EBW) of the signal.
- (4) Set the RBW to: 8MHz, VBW=8MHz with peak detector and max hold settings.
- (5) The test extreme voltage is to change the primary supply voltage from 12Vdc to 19Vdc percent of the nominal value.
- (6) Extreme temperature is 0°C~50°C

NOTE: The EUT was set to continuously transmitting in continuously un-modulation transmitting mode.

Test Mode

Please refer to the clause 2.4.

**Test Result**

Voltage							
Test Mode	Freq(MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
20M Bandwidth	5180	NV	NT	3500.00	0.675676	20	PASS
		LV	NT	3500.00	0.675676	20	PASS
		HV	NT	3500.00	0.675676	20	PASS
	5200	NV	NT	4500.00	0.865385	20	PASS
		LV	NT	4000.00	0.769231	20	PASS
		HV	NT	4000.00	0.769231	20	PASS
	5240	NV	NT	4000.00	0.763359	20	PASS
		LV	NT	4000.00	0.763359	20	PASS
		HV	NT	3500.00	0.667939	20	PASS
	5260	NV	NT	4000.00	0.760456	20	PASS
		LV	NT	4000.00	0.760456	20	PASS
		HV	NT	4000.00	0.760456	20	PASS
	5280	NV	NT	4000.00	0.757576	20	PASS
		LV	NT	4000.00	0.757576	20	PASS
		HV	NT	3500.00	0.662879	20	PASS
	5320	NV	NT	4000.00	0.751880	20	PASS
		LV	NT	4000.00	0.751880	20	PASS
		HV	NT	3500.00	0.657895	20	PASS
	5500	NV	NT	5500.00	1.000000	20	PASS
		LV	NT	4500.00	0.818182	20	PASS
		HV	NT	4000.00	0.727273	20	PASS
	5580	NV	NT	4500.00	0.806452	20	PASS
		LV	NT	4000.00	0.716846	20	PASS
		HV	NT	4500.00	0.806452	20	PASS
	5700	NV	NT	4500.00	0.789474	20	PASS
		LV	NT	4000.00	0.701754	20	PASS
		HV	NT	4000.00	0.701754	20	PASS
	5745	NV	NT	4500.00	0.783290	20	PASS
		LV	NT	4000.00	0.696258	20	PASS
		HV	NT	4000.00	0.696258	20	PASS
	5785	NV	NT	5000.00	0.864304	20	PASS
		LV	NT	4500.00	0.777874	20	PASS
		HV	NT	4000.00	0.691443	20	PASS
	5825	NV	NT	5000.00	0.858369	20	PASS
		LV	NT	4500.00	0.772532	20	PASS
		HV	NT	4500.00	0.772532	20	PASS
40M Bandwidth	5190	NV	NT	4500.00	0.867052	20	PASS
		LV	NT	4000.00	0.770713	20	PASS
		HV	NT	4000.00	0.770713	20	PASS
	5230	NV	NT	4000.00	0.764818	20	PASS
		LV	NT	4000.00	0.764818	20	PASS
		HV	NT	3500.00	0.669216	20	PASS
	5270	NV	NT	4000.00	0.759013	20	PASS
		LV	NT	4000.00	0.759013	20	PASS
		HV	NT	4000.00	0.759013	20	PASS
	5310	NV	NT	4500.00	0.847458	20	PASS
		LV	NT	4000.00	0.753296	20	PASS
		HV	NT	4000.00	0.753296	20	PASS
	5510	NV	NT	5000.00	0.907441	20	PASS
		LV	NT	4000.00	0.725953	20	PASS
		HV	NT	4000.00	0.725953	20	PASS
	5550	NV	NT	4000.00	0.720721	20	PASS
		LV	NT	4000.00	0.720721	20	PASS
		HV	NT	4000.00	0.720721	20	PASS

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing
Society : yz.cnca.cn



	5670	NV	NT	4500.00	0.793651	20	PASS
		LV	NT	4000.00	0.705467	20	PASS
		HV	NT	4000.00	0.705467	20	PASS
	5755	NV	NT	4500.00	0.781929	20	PASS
		LV	NT	4000.00	0.695048	20	PASS
		HV	NT	4000.00	0.695048	20	PASS
	5795	NV	NT	4500.00	0.776531	20	PASS
		LV	NT	4500.00	0.776531	20	PASS
		HV	NT	4500.00	0.776531	20	PASS
80M Bandwidth	5210	NV	NT	4500.00	0.863724	20	PASS
		LV	NT	4000.00	0.767754	20	PASS
		HV	NT	3500.00	0.671785	20	PASS
	5290	NV	NT	4000.00	0.756144	20	PASS
		LV	NT	3500.00	0.661626	20	PASS
		HV	NT	3500.00	0.661626	20	PASS
	5530	NV	NT	4000.00	0.723327	20	PASS
		LV	NT	4000.00	0.723327	20	PASS
		HV	NT	4000.00	0.723327	20	PASS
	5610	NV	NT	5000.00	0.891266	20	PASS
		LV	NT	3500.00	0.623886	20	PASS
		HV	NT	4000.00	0.713012	20	PASS
	5775	NV	NT	4500.00	0.779221	20	PASS
		LV	NT	4000.00	0.692641	20	PASS
		HV	NT	4000.00	0.692641	20	PASS



Temperature							
Test Mode	Freq(MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
20M Bandwidth	5180	NV	0	3500.00	0.675676	20	PASS
		NV	10	4000.00	0.772201	20	PASS
		NV	20	4000.00	0.772201	20	PASS
		NV	30	3500.00	0.675676	20	PASS
		NV	40	3500.00	0.675676	20	PASS
		NV	50	4000.00	0.772201	20	PASS
	5200	NV	0	4000.00	0.769231	20	PASS
		NV	10	4000.00	0.769231	20	PASS
		NV	20	3500.00	0.673077	20	PASS
		NV	30	3500.00	0.673077	20	PASS
		NV	40	3500.00	0.673077	20	PASS
		NV	50	3500.00	0.673077	20	PASS
	5240	NV	0	3500.00	0.667939	20	PASS
		NV	10	4000.00	0.763359	20	PASS
		NV	20	4000.00	0.763359	20	PASS
		NV	30	4000.00	0.763359	20	PASS
		NV	40	3500.00	0.667939	20	PASS
		NV	50	4000.00	0.763359	20	PASS
	5260	NV	0	4000.00	0.760456	20	PASS
		NV	10	4000.00	0.760456	20	PASS
		NV	20	4000.00	0.760456	20	PASS
		NV	30	3500.00	0.665399	20	PASS
		NV	40	4000.00	0.760456	20	PASS
		NV	50	3500.00	0.665399	20	PASS
	5280	NV	0	4000.00	0.757576	20	PASS
		NV	10	3500.00	0.662879	20	PASS
		NV	20	4000.00	0.757576	20	PASS
		NV	30	3500.00	0.662879	20	PASS
		NV	40	4000.00	0.757576	20	PASS
		NV	50	3500.00	0.662879	20	PASS
	5320	NV	0	4000.00	0.751880	20	PASS
		NV	10	4000.00	0.751880	20	PASS
		NV	20	3500.00	0.657895	20	PASS
		NV	30	3500.00	0.657895	20	PASS
		NV	40	4000.00	0.751880	20	PASS
		NV	50	4000.00	0.751880	20	PASS
	5500	NV	0	4500.00	0.818182	20	PASS
		NV	10	4000.00	0.727273	20	PASS
		NV	20	3500.00	0.636364	20	PASS
		NV	30	4000.00	0.727273	20	PASS
		NV	40	4000.00	0.727273	20	PASS
		NV	50	4000.00	0.727273	20	PASS
	5580	NV	0	4000.00	0.716846	20	PASS
		NV	10	4000.00	0.716846	20	PASS
		NV	20	4000.00	0.716846	20	PASS
		NV	30	4000.00	0.716846	20	PASS
		NV	40	4000.00	0.716846	20	PASS
		NV	50	4000.00	0.716846	20	PASS
	5700	NV	0	4000.00	0.701754	20	PASS
		NV	10	4500.00	0.789474	20	PASS
		NV	20	4000.00	0.701754	20	PASS
		NV	30	4000.00	0.701754	20	PASS
		NV	40	4000.00	0.701754	20	PASS
		NV	50	4000.00	0.701754	20	PASS
	5745	NV	0	4000.00	0.696258	20	PASS

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



		NV	10	4000.00	0.696258	20	PASS
		NV	20	4000.00	0.696258	20	PASS
		NV	30	3500.00	0.609225	20	PASS
		NV	40	4000.00	0.696258	20	PASS
		NV	50	4000.00	0.696258	20	PASS
	5785	NV	0	4000.00	0.691443	20	PASS
		NV	10	4500.00	0.777874	20	PASS
		NV	20	4000.00	0.691443	20	PASS
		NV	30	4000.00	0.691443	20	PASS
		NV	40	4000.00	0.691443	20	PASS
	5825	NV	50	4500.00	0.777874	20	PASS
		NV	0	4000.00	0.686695	20	PASS
		NV	10	4000.00	0.686695	20	PASS
		NV	20	4000.00	0.686695	20	PASS
		NV	30	4500.00	0.772532	20	PASS
40M Bandwidth	5190	NV	40	4000.00	0.686695	20	PASS
		NV	50	4000.00	0.686695	20	PASS
		NV	0	4000.00	0.770713	20	PASS
		NV	10	4000.00	0.770713	20	PASS
		NV	20	4000.00	0.770713	20	PASS
	5230	NV	30	3500.00	0.674374	20	PASS
		NV	40	3500.00	0.674374	20	PASS
		NV	50	3500.00	0.674374	20	PASS
		NV	0	3500.00	0.669216	20	PASS
		NV	10	3500.00	0.669216	20	PASS
	5270	NV	20	4000.00	0.764818	20	PASS
		NV	30	3500.00	0.669216	20	PASS
		NV	40	3500.00	0.669216	20	PASS
		NV	50	3500.00	0.669216	20	PASS
		NV	0	4000.00	0.759013	20	PASS
	5310	NV	10	3500.00	0.664137	20	PASS
		NV	20	4000.00	0.759013	20	PASS
		NV	30	4000.00	0.759013	20	PASS
		NV	40	4000.00	0.759013	20	PASS
		NV	50	3500.00	0.664137	20	PASS
	5510	NV	0	4000.00	0.753296	20	PASS
		NV	10	4000.00	0.753296	20	PASS
		NV	20	4000.00	0.753296	20	PASS
		NV	30	3500.00	0.659134	20	PASS
		NV	40	4000.00	0.753296	20	PASS
	5550	NV	50	3500.00	0.659134	20	PASS
		NV	0	3500.00	0.635209	20	PASS
		NV	10	4500.00	0.816697	20	PASS
		NV	20	4000.00	0.725953	20	PASS
		NV	30	3500.00	0.635209	20	PASS
	5670	NV	40	3500.00	0.635209	20	PASS
		NV	50	3500.00	0.635209	20	PASS
		NV	0	4000.00	0.720721	20	PASS
		NV	10	3500.00	0.630631	20	PASS
		NV	20	4000.00	0.720721	20	PASS
		NV	30	4000.00	0.720721	20	PASS
		NV	40	4000.00	0.720721	20	PASS
		NV	50	4000.00	0.720721	20	PASS
		NV	0	3500.00	0.617284	20	PASS
		NV	10	4000.00	0.705467	20	PASS
		NV	20	4000.00	0.705467	20	PASS
		NV	30	4000.00	0.705467	20	PASS
		NV	40	4000.00	0.705467	20	PASS
		NV	50	4000.00	0.705467	20	PASS
		NV	0	3500.00	0.617284	20	PASS

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing
Society : yz.cnca.cn



	5755	NV	0	4000.00	0.695048	20	PASS
		NV	10	4000.00	0.695048	20	PASS
		NV	20	4000.00	0.695048	20	PASS
		NV	30	3500.00	0.608167	20	PASS
		NV	40	3500.00	0.608167	20	PASS
		NV	50	4000.00	0.695048	20	PASS
	5795	NV	0	4000.00	0.690250	20	PASS
		NV	10	4000.00	0.690250	20	PASS
		NV	20	4000.00	0.690250	20	PASS
		NV	30	4500.00	0.776531	20	PASS
		NV	40	4000.00	0.690250	20	PASS
		NV	50	4500.00	0.776531	20	PASS
80M Bandwidth	5210	NV	0	3500.00	0.671785	20	PASS
		NV	10	4000.00	0.767754	20	PASS
		NV	20	3500.00	0.671785	20	PASS
		NV	30	3500.00	0.671785	20	PASS
		NV	40	4000.00	0.767754	20	PASS
		NV	50	3500.00	0.671785	20	PASS
	5290	NV	0	3000.00	0.567108	20	PASS
		NV	10	3500.00	0.661626	20	PASS
		NV	20	4000.00	0.756144	20	PASS
		NV	30	3500.00	0.661626	20	PASS
		NV	40	4000.00	0.756144	20	PASS
		NV	50	3500.00	0.661626	20	PASS
	5530	NV	0	4000.00	0.723327	20	PASS
		NV	10	3500.00	0.632911	20	PASS
		NV	20	4000.00	0.723327	20	PASS
		NV	30	3500.00	0.632911	20	PASS
		NV	40	4000.00	0.723327	20	PASS
		NV	50	3500.00	0.632911	20	PASS
	5610	NV	0	4000.00	0.713012	20	PASS
		NV	10	4000.00	0.713012	20	PASS
		NV	20	3500.00	0.623886	20	PASS
		NV	30	4000.00	0.713012	20	PASS
		NV	40	4000.00	0.713012	20	PASS
		NV	50	3500.00	0.623886	20	PASS
	5775	NV	0	4000.00	0.692641	20	PASS
		NV	10	4000.00	0.692641	20	PASS
		NV	20	4000.00	0.692641	20	PASS
		NV	30	4500.00	0.779221	20	PASS
		NV	40	3500.00	0.606061	20	PASS
		NV	50	3500.00	0.606061	20	PASS



3.8. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Test Result

The gain of the antenna is 6.27dBi, please refer to the EUT internal photographs antenna photo.

RSS-Gen Issue 5 Section 6.8

The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the licence-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. Licence-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power(e.i.r.p.) limits specified in the applicable standard (RSS) for licence-exempt apparatus.

Result

PASS.

The EUT has 1 antenna: a FPC Antenna for 5G WIFI.

Note: ☐ Antenna use a permanently attached antenna which is not replaceable.

☒ Not using a standard antenna jack or electrical connector for antenna replacement.

☐ The antenna has to be professionally installed (please provide method of installation).

Which in accordance to RSS-Gen 6.8, please refer to the internal photos.



3.9. Dynamic Frequency Selection

Requirement

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	Yes
Channel Move Time	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

**Limit****1. DFS Detection Thresholds**

Table 3: DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm

Note 1: This is the level at the input of the receiver assuming a 0dBi receive antenna.
Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.
Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

2. DFS Response Requirements

Table 4: DFS Response Requirement Values

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.
Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required facilitating a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.
Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

Radar Test Waveforms

This section provides the parameters for required test waveforms, minimum percentage of successful detections, and the minimum number of trials that must be used for determining DFS conformance. Step intervals of 0.1 microsecond for Pulse Width, 1 microsecond for PRI, 1 MHz for chirp width and 1 for the number of pulses will be utilized for the random determination of specific test waveforms.



Table 5 Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a	$\text{Roundup} \left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right\}$	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

For example if in Short Pulse Radar Type 1 Test B a PRI of 3066 μsec is selected, the number of pulses

$$\left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{3066} \right) \right\}$$

would be Round up $\{17.2\} = \text{Round up } \{17.2\} = 18$.

Table 5a - Pulse Repetition Intervals Values for Test A

Pulse Repetition Frequency Number	Pulse Repetition Frequency (Pulses Per Second)	Pulse Repetition Interval (Microseconds)
1	1930.5	518
2	1858.7	538
3	1792.1	558
4	1730.1	578
5	1672.2	598
6	1618.1	618
7	1567.4	638
8	1519.8	658

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



Pulse Repetition Frequency Number	Pulse Repetition Frequency (Pulses Per Second)	Pulse Repetition Interval (Microseconds)
9	1474.9	678
10	1432.7	698
11	1392.8	718
12	1355	738
13	1319.3	758
14	1285.3	778
15	1253.1	798
16	1222.5	818
17	1193.3	838
18	1165.6	858
19	1139	878
20	1113.6	898
21	1089.3	918
22	1066.1	938
23	326.2	3066

Table 6 – Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

The parameters for this waveform are randomly chosen. Thirty unique waveforms are required for the Long Pulse Radar Type waveforms. If more than 30 waveforms are used for the Long Pulse Radar Type waveforms, then each additional waveform must also be unique and not repeated from the previous waveforms.

Table 7 – Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Number of Trials
6	1	333	9	0.333	300	70%	30

For the Frequency Hopping Radar Type, the same Burst parameters are used for each wave form. The hopping sequence is different for each wave form and a 100-length segment is selected from the hopping sequence defined by the following algorithm:


The first frequency in a hopping sequence is selected randomly from the group of 475 integer frequencies from 5250–5724MHz. Next, the frequency that was just chosen is removed from the group and a frequency is randomly selected from the remaining 474 frequencies in the group. This process continues until all 475 frequencies are chosen for the set. For selection of a random frequency, the frequencies remaining within the group are always treated as equally likely.

Calibration of Radar Waveform

Radar Waveform Calibration Procedure


- 1) A 50 ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to place of the master.
- 2) The interference Radar Detection Threshold Level is $-62\text{dBm} + 3.47\text{dBi} + 1\text{dB} = -57.53\text{dBm}$ that had been taken into account the output power range and antenna gain.
- 3) The following equipment setup was used to calibrate the conducted radar waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the master or client device. The spectrum analyzer was switched to the zero spans (time domain) at the frequency of the radar waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz. The spectrum analyzer had offset -1.0dB to compensate RF cable loss 1.0dB.
- 4) The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was $-62\text{dBm} + 3.47\text{dBi} + 1\text{dB} = -57.53\text{dBm}$. Capture the spectrum analyzer plots on short pulse radar waveform.

Conducted Calibration Setup




Test Configuration

Setup for Client with injection at the Master





Radar Waveform Calibration Result



Test Procedure

1. The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device
3. A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
4. EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
5. When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel Measure and record the transmissions from the UUT during the observation time (Channel Move

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn



Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type

7. Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
8. Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

Test Mode


Please refer to the clause 2.4.

**Test Result**☒ **Passed**☐ **Not Applicable**

The product in this report belongs to Client Without Radar Detection.

Test Mode	Frequency[MHz]	CCTT[ms]	Limit[ms]	CMT[ms]	Limit[ms]	Verdict
802.11A	5320	15.6	200+60	2121.6	10000	PASS
	5500	15.6	200+60	1953.9	10000	PASS

Test Mode	Frequency[MHz]	Result	Limit[s]	Verdict
802.11A	5320	see test graph	≥1800	PASS
	5500	see test graph	≥1800	PASS



CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn


TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn




802.11A 5320

Non-Occupancy Period



802.11A 5500

Non-Occupancy Period



*****THE END OF REPORT*****

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn