

RF Exposure Report

Report No.: MFBHQC-WTW-P22030336

FCC ID: 2AQ68RLP0003

Test Model: RLP0003

Received Date: Mar. 08, 2022

Test Date: May 12 ~ Jun. 23, 2022

Issued Date: Jun. 30, 2022

Applicant: Hon Lin Technology Co., Ltd.

Address: 11F, No. 32, Jihu Rd., Neihu Dist., Taipei City 114, Taiwan R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
MFBHQC-WTW-P22030336	Original release	Jun. 30, 2022

1 Certificate of Conformity

Product: Wi-Fi 6E BT5.2 WLAN Module

Brand: Foxconn

Test Model: RLP0003

Sample Status: Engineering sample

Applicant: Hon Lin Technology Co., Ltd.

Test Date: May 12 ~ Jun. 23, 2022

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Jun. 30, 2022
Celine Chou / Senior Specialist

Approved by : Jeremy Lin , **Date:** Jun. 30, 2022
Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Description of Antenna

The antenna gain was declared by client; please refer to the following table:

Antenna Set	RF Chain No.	Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length
1	Chain0/1	HONGBO	260-25094	3.53	2.40~2.4835	0.76	PIFA	i-pex (MHF 4L)	300mm
				3.06	5.150~5.250	1.16			
				3.07	5.250~5.350	1.18			
				4.81	5.470~5.725	1.20			
				4.20	5.725~5.850	1.27			
2	Chain0/1	HONGBO	260-25083	5.09	5.850~5.895	1.29	PIFA	i-pex (MHF 4L)	300mm
				5.14	5.925~6.425	1.32			
				5.09	6.425~6.525	1.35			
				5.16	6.525~6.875	1.40			
				5.12	6.875~7.125	1.45			
3	Chain0/1	HONGBO	260-25084	3.22	2.40~2.4835	0.50	Monopole	i-pex (MHF 4L)	200mm
				3.35	5.150~5.250	0.76			
				3.42	5.250~5.350	0.78			
				4.77	5.470~5.725	0.81			
				4.72	5.725~5.850	0.85			
				4.71	5.850~5.895	0.86			
				4.75	5.925~6.425	0.87			
				4.29	6.425~6.525	0.91			
				4.81	6.525~6.875	0.96			
4.74	6.875~7.125	0.98							
4	Chain0/1	Auden	ANTRG6U123-1801 / ANTRG6U123-1802	5.13 / 4.64	2.40~2.4835	-	PIFA (Slot)	i-pex (MHF 4L)	460mm / 740mm
				2.70 / 3.36	5.150~5.250				
				2.70 / 3.07	5.250~5.350				
				2.50 / 1.08	5.470~5.725				
				2.68 / 0.42	5.725~5.850				
				2.68 / 0.42	5.850~5.895				
				2.18 / 1.20	5.925~6.425				
				1.98 / 0.59	6.425~6.525				
				2.42 / 1.72	6.525~6.875				
				1.48 / 0.62	6.875~7.125				

Note:

1. Antenna Set 4 is the new antenna to be applied for this time.
2. The above Antenna information refers to the manufacturer's antenna specifications, the laboratory shall not be held responsible.

3 Calculation Result of Maximum Conducted Power

Operation Mode	Max AV Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	24.50	7.90	20	0.346	1.00
WLAN 5.0GHz	22.50	7.82	20	0.214	1.00
WLAN 5.9GHz	20.00	8.10	20	0.128	1.00
WLAN 6.0GHz	22.50	8.17	20	0.232	1.00
Bluetooth	16.00	5.13	20	0.026	1.00

Note:

1. This power include tune-up tolerance range that specified in QCNFA765 Tune Up power table.
2. BT-LE and BT-EDR can't transmit simultaneously.
3. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
4. The above Antenna information refers to the manufacturer's antenna specifications, the laboratory shall not be held responsible.

2.4GHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 7.90\text{dBi}$

5GHz: Directional gain = $4.81\text{dBi} + 10\log(2) = 7.82\text{dBi}$

5.9GHz: Directional gain = $5.09\text{dBi} + 10\log(2) = 8.10\text{dBi}$

6GHz: Directional gain = $5.16\text{dBi} + 10\log(2) = 8.17\text{dBi}$

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

Simultaneously transmission condition.

Condition	Technology	
1	WLAN (2.4GHz)	WLAN (6GHz)
2	WLAN (2.4GHz)	WLAN (5GHz)
3	WLAN (2.4GHz)	WLAN (5.9GHz)
4	WLAN (6GHz)	Bluetooth
5	WLAN (5GHz)	Bluetooth
6	WLAN (5.9GHz)	Bluetooth

WLAN 2.4GHz + WLAN 6GHz = $0.346 / 1 + 0.232 / 1 = 0.578 < 1$

WLAN 2.4GHz + WLAN 5GHz = $0.346 / 1 + 0.214 / 1 = 0.560 < 1$

WLAN 2.4GHz + WLAN 5.9GHz = $0.346 / 1 + 0.128 / 1 = 0.474 < 1$

WLAN 6GHz + Bluetooth = $0.232 / 1 + 0.026 / 1 = 0.258 < 1$

WLAN 5GHz + Bluetooth = $0.214 / 1 + 0.026 / 1 = 0.240 < 1$

WLAN 5.9GHz + Bluetooth = $0.128 / 1 + 0.026 / 1 = 0.154 < 1$

---END---