

FCC Test Report (Spot Check: Part 22)

Report No.: RF200109E02E

FCC ID: 2AQ68T99W175M

Original FCC ID: 2AQ68T99W175

Test Model: T99W175M

Received Date: May 29, 2020

Test Date: Jul. 03 ~ Aug. 02, 2020

Issued Date: Aug. 10, 2020

Applicant: Hon Lin Technology Co., Ltd.

Address: 11F, No. 32, Jihu Rd., Neihu Dist., Taipei City 114, Taiwan R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty.....	5
2.2 Test Site and Instruments.....	6
3 General Information	7
3.1 General Description of EUT.....	7
3.2 Configuration of System under Test.....	11
3.2.1 Description of Support Units.....	11
3.3 Test Mode Applicability and Tested Channel Detail.....	12
3.4 EUT Operating Conditions.....	14
3.5 General Description of Applied Standards and References.....	14
4 Test Types and Results	15
4.1 Output Power Measurement.....	15
4.1.1 Limits of Output Power Measurement.....	15
4.1.2 Test Procedures.....	15
4.1.3 Test Setup.....	15
4.1.4 Test Results.....	16
4.2 Radiated Emission Measurement.....	36
4.2.1 Limits of Radiated Emission Measurement.....	36
4.2.2 Test Procedure.....	36
4.2.3 Deviation from Test Standard.....	36
4.2.4 Test Setup.....	37
4.2.5 Test Results.....	38
5 Pictures of Test Arrangements	46
Appendix – Information of the Testing Laboratories	47

Release Control Record

Issue No.	Description	Date Issued
RF200109E02E	Original release	Aug. 10, 2020

1 Certificate of Conformity

Product: 5G WWAN Module

Brand: Foxconn

Test Model: T99W175M

Sample Status: Engineering Sample

Applicant: Hon Lin Technology Co., Ltd.

Test Date: Jul. 03 ~ Aug. 02, 2020

Standards: FCC Part 22, Subpart H

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen , **Date:** Aug. 10, 2020
Pettie Chen / Senior Specialist

Approved by : Bruce Chen , **Date:** Aug. 10, 2020
Bruce Chen / Senior Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 22 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 22.913 (a)	Effective radiated power	Pass	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -1.1dB at 82.01MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (\pm)
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.04 dB
	30MHz ~ 200MHz	3.63 dB
	200MHz ~ 1000MHz	3.64 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver KEYSIGHT	N9038A	MY55420137	Apr. 16, 2020	Apr. 15, 2021
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Jun. 12, 2020	Jun. 11, 2021
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Nov. 07, 2019	Nov. 06, 2020
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-1169	Nov. 24, 2019	Nov. 23, 2020
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Nov. 24, 2019	Nov. 23, 2020
Preamplifier Agilent (Below 1GHz)	8447D	2944A10638	Jun. 08, 2020	Jun. 07, 2021
Preamplifier Agilent (Above 1GHz)	8449B	3008A02367	Feb. 18, 2020	Feb. 17, 2021
RF signal cable HUBER+SUHNER&EMCI	SUCOFLEX 104 & EMC104-SM-SM80 00	CABLE-CH9-02 (248780+171006)	Jan. 18, 2020	Jan. 17, 2021
RF signal cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(250795/4)	Jan. 18, 2020	Jan. 17, 2021
RF signal cable Woken	8D-FB	Cable-CH9-01	Jun. 08, 2020	Jun. 07, 2021
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower & Turn BV ADT	AT100	AT93021705	NA	NA
Turn Table BV ADT	TT100	TT93021705	NA	NA
Turn Table Controller BV ADT	SC100	SC93021705	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
WIT Standard Temperature And Humidity Chamber	TH-4S-C	W981030	Jun. 01, 2020	May 31, 2021
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
True RMS Clamp Meter Fluke	325	31130711WS	Jun. 06, 2020	Jun. 05, 2021
DC power supply	U8002A	MY56330015	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 9.

3 General Information

3.1 General Description of EUT

Product	5G WWAN Module				
Brand	Foxconn				
Test Model	T99W175M				
Sample Status	Engineering Sample				
Power Supply Rating	5 Vdc (Host equipment) 3.135Vdc~3.63Vdc (Module)				
Modulation Type	WCDMA: BPSK, QPSK HSDPA: BPSK HSUPA: QPSK LTE: QPSK, 16QAM, 64QAM, 256QAM				
Operating Frequency	WCDMA Band 5	826.4~846.6MHz			
	LTE Band 5 (Channel Bandwidth 1.4MHz)	824.7~848.3MHz			
	LTE Band 5 (Channel Bandwidth 3MHz)	825.5~847.5MHz			
	LTE Band 5 (Channel Bandwidth 5MHz)	826.5~846.5MHz			
	LTE Band 5 (Channel Bandwidth 10MHz)	829.0~844.0MHz			
	LTE Band 26 (Channel Bandwidth 1.4MHz)	824.7~848.3MHz			
	LTE Band 26 (Channel Bandwidth 3MHz)	825.5~847.5MHz			
	LTE Band 26 (Channel Bandwidth 5MHz)	826.5~846.5MHz			
	LTE Band 26 (Channel Bandwidth 10MHz)	829.0~844.0MHz			
	LTE Band 26 (Channel Bandwidth 15MHz)	831.5~841.5MHz			
Max. ERP Power	WCDMA Band 5	311.172mW (24.93dBm)			
		QPSK	16QAM	64QAM	256QAM
	LTE Band 5 (Channel Bandwidth 1.4MHz)	341.193mW (25.33dBm)	272.898mW (24.36dBm)	202.768mW (23.07dBm)	164.816mW (22.17dBm)
	LTE Band 5 (Channel Bandwidth 3MHz)	345.939mW (25.39dBm)	292.415mW (24.66dBm)	214.783mW (23.32dBm)	186.209mW (22.70dBm)
	LTE Band 5 (Channel Bandwidth 5MHz)	343.558mW (25.36dBm)	302.691mW (24.81dBm)	219.786mW (23.42dBm)	191.426mW (22.82dBm)
	LTE Band 5 (Channel Bandwidth 10MHz)	337.287mW (25.28dBm)	303.389mW (24.82dBm)	219.280mW (23.41dBm)	191.867mW (22.83dBm)
	LTE Band 26 (Channel Bandwidth 1.4MHz)	341.979mW (25.34dBm)	282.488mW (24.51dBm)	208.930mW (23.20dBm)	184.077mW (22.65dBm)
	LTE Band 26 (Channel Bandwidth 3MHz)	345.144mW (25.38dBm)	307.610mW (24.88dBm)	212.324mW (23.27dBm)	182.810mW (22.62dBm)
	LTE Band 26 (Channel Bandwidth 5MHz)	344.350mW (25.37dBm)	293.765mW (24.68dBm)	203.704mW (23.09dBm)	178.649mW (22.52dBm)
	LTE Band 26 (Channel Bandwidth 10MHz)	341.979mW (25.34dBm)	299.226mW (24.76dBm)	212.814mW (23.28dBm)	178.649mW (22.52dBm)
	LTE Band 26 (Channel Bandwidth 15MHz)	342.768mW (25.35dBm)	305.492mW (24.85dBm)	221.820mW (23.46dBm)	194.984mW (22.90dBm)

Emission Designator	WCDMA Band 5	4M16F9W			
		QPSK	16QAM	64QAM	256QAM
	LTE Band 5 (Channel Bandwidth 1.4MHz)	1M09G7D	1M09D7W	1M09D7W	1M09D7W
	LTE Band 5 (Channel Bandwidth 3MHz)	2M70G7D	2M70D7W	2M70D7W	2M70D7W
	LTE Band 5 (Channel Bandwidth 5MHz)	4M49G7D	4M49D7W	4M49D7W	4M49D7W
	LTE Band 5 (Channel Bandwidth 10MHz)	8M96G7D	8M96D7W	8M95D7W	8M98D7W
	LTE Band 26 (Channel Bandwidth 1.4MHz)	1M09G7D	1M09D7W	1M09D7W	1M09D7W
	LTE Band 26 (Channel Bandwidth 3MHz)	2M70G7D	2M70D7W	2M70D7W	2M70D7W
	LTE Band 26 (Channel Bandwidth 5MHz)	4M49G7D	4M49D7W	4M49D7W	4M49D7W
	LTE Band 26 (Channel Bandwidth 10MHz)	8M95G7D	8M96D7W	8M95D7W	8M98D7W
	LTE Band 26 (Channel Bandwidth 15MHz)	13M4G7D	13M4D7W	13M4D7W	13M5D7W
Antenna Type	Refer to Note as below				
Antenna Connector	Refer to Note as below				
Accessory Device	NA				
Cable Supplied	NA				

Note:

1. This report is a supplementary report to the original BV CPS report no.: RF200109E02B. The difference compared with original report is only adding mmWave hardware, mmWave function is disabled by software. Exhibit prepared for FCC Spot Check Verification report, the format, test items and amount of spot-check test data are decided by applicant's engineering judgment, for more details please refer to declaration letter exhibit. Radiated emission and output power verification worst test refer to original report.
2. There are four Difference HW of T99W175M.

Brand	Model	HW
Foxconn	T99W175M	1. 3G+LTE+Sub6+mmWave+eSIM
		2. 3G+LTE+Sub6+mmWave+w/o eSIM
		3. 3G+LTE+Sub6+mmWave+eSIM+GNSS connector
		4. 3G+LTE+Sub6+mmWave+w/o eSIM+GNSS connector

*After pre-testing, "HW: 1. 3G+LTE+Sub6+mmWave+eSIM" is the worst for the final tests.

3. The following antennas were provided to the EUT.

Antenna No.	RF Chain No.	Brand	Model	Antenna Net Gain(dBi)	Frequency range (MHz)	Antenna Type	Connector Type
1		WHA YU	C107-511720-A	4.41	660~803	PCB	I-PEX
2		WHA YU	C107-511721-A	3.81 4.03	791~960 1447.9~1606	PCB	I-PEX
3		WHA YU	C107-511722-A	4.27 5.31	1710~2170 2500~2690	PCB	I-PEX
4		WHA YU	C107-511723-A	2.99 0.92	2300~2400 3500~3700	PCB	I-PEX
5		WHA YU	C107-511724-A	6.45	5150~5925	PCB	I-PEX
6		WHA YU	C107-511725-A	4.89	3400~3700	PCB	I-PEX
7		AVX	5000106-R1-X01	2.91	699~803	Monopole	I-PEX
8		AVX	5000107-R1-X01	2.59	791~960	Monopole	I-PEX
9		AVX	5000108-R1-X01	2.85	1427~1610	Monopole	I-PEX
10		AVX	5000109-R1-X01	2.23 2.94	1710~2200 5150~5925	Monopole	I-PEX
11		AVX	5000110-R1-X01	0.9	2300~2690	Monopole	I-PEX
12		AVX	5000111-R1-X01	0.87	3300~5000	Monopole	I-PEX
13	Tx1/ Rx1	Ethertronics	5003806	0.4 -1.61 0.39 2.95 1.98 0.38 0.83 2.31	698-821 824-960 1425-1515 1710-2200 2300-2690 3300-4200 4400-5000 5150-5925	PIFA	I-PEX
	Rx2	Ethertronics	5003807	-2.24 -4.52 2.87 2.99 2.93 2.91 2.23 -0.85 -3.04	716-821 824-960 1425-1515 1557-1610 1805-2200 2300-2690 3300-4200 4400-5000 5150-5925	PIFA	I-PEX
	Tx2/ Rx3	Ethertronics	5003806	2.21 2.25 -0.45 2.6	1710-2200 2300-2690 3300-4200 4400-5000	PIFA	I-PEX
	Rx4	Ethertronics	5003700	1.38 2.87 0.6 -2.09	1805-2200 2300-2690 3300-4200 4400-5000	PIFA	I-PEX


Antenna No.	RF Chain No.	Brand	Model	Antenna Net Gain(dBi)	Frequency range (MHz)	Antenna Type	Connector Type
14	Ant. 0 (TX/RX)	Master Wave	NA	2.4	880~960	PCB	I-PEX
				2.2	1020~2170		
				2.9	2545~2595		
				2.9	3565~3600		
				2.9	3900~4000		
	NA	GPS					
	Ant. 2 (TX/RX)	Master Wave	NA	NA	880~960	PCB	I-PEX
				2.2	1020~2170		
				2.8	2545~2595		
				2.9	3565~3600		
				2.8	3900~4000		
	NA	GPS					
	Ant. 1 (RX)	Master Wave	NA	NA	880~960	PCB	I-PEX
				5.3	1020~2170		
				5.1	2545~2595		
				4.3	3565~3600		
4.5				3900~4000			
NA	GPS						
Ant. 3 (RX)	Master Wave	NA	1.3	880~960	PCB	I-PEX	
			6.8	1020~2170			
			3.7	2545~2595			
			6.4	3565~3600			
			6.2	3900~4000			
			3.7	GPS			

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.


*The antenna for the final tests as following table.

	Band	Antenna
WCDMA	2	Antenna 3
	4	Antenna 3
	5	Antenna 2
LTE	2	Antenna 3
	4	Antenna 3
	5	Antenna 2
	7	Antenna 3
	12	Antenna 1
	13	Antenna 1
	14	Antenna 1
	17	Antenna 1
	25	Antenna 3
	26	Antenna 2
	30	Antenna 4
	66	Antenna 3
	71	Antenna 1
	38	Antenna 3
	41	Antenna 3
42	Antenna 4	
48	Antenna 4	

3.2 Configuration of System under Test



Remote site



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Radio Communication Analyzer	Anritsu	MT8821C	6261806803	NA	-
B.	Adapter	LITEON	PA-1050-39	NA	NA	-
C.	Fixture	NA	NA	NA	NA	Provided by client.

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	USB cable	1	1.5	Y	0	-

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Z-plane. Following channel(s) was (were) selected for the final test as listed below.

WCDMA Band 5

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	ERP	4132 to 4233	4132 (826.4MHz), 4182 (836.4MHz), 4233 (846.6MHz)	WCDMA
-	Radiated Emission Below 1GHz	4132 to 4233	4233 (846.6MHz)	WCDMA
-	Radiated Emission Above 1GHz	4132 to 4233	4233 (846.6MHz)	WCDMA

LTE Band 5

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	ERP	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 2 RB Offset 1 RB / 5 RB Offset 3 RB / 0 RB Offset 3 RB / 1 RB Offset 3 RB / 3 RB Offset 6 RB / 0 RB Offset
		20415 to 20635	20415(825.5MHz), 20525(836.5MHz), 20635(847.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 7 RB Offset 1 RB / 14 RB Offset 8 RB / 0 RB Offset 8 RB / 3 RB Offset 8 RB / 7 RB Offset 15 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	20415 to 20635	20415(825.5MHz)	3MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	20415 to 20635	20415(825.5MHz)	3MHz	QPSK	1 RB / 0 RB Offset

LTE Band 26

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	ERP	26797 to 27033	26797 (824.7MHz), 26915 (836.5MHz), 27033 (848.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 2 RB Offset 1 RB / 5 RB Offset 3 RB / 0 RB Offset 3 RB / 1 RB Offset 3 RB / 3 RB Offset 6 RB / 0 RB Offset
		26805 to 27025	26805 (825.5MHz), 26915 (836.5MHz), 27025 (847.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 7 RB Offset 1 RB / 14 RB Offset 8 RB / 0 RB Offset 8 RB / 3 RB Offset 8 RB / 7 RB Offset 15 RB / 0 RB Offset
		26815 to 27015	26815 (826.5MHz), 26915 (836.5MHz), 27015 (846.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		26840 to 26990	26840 (829MHz), 26915 (836.5MHz), 26990 (844MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
		26865 to 26965	26865 (831.5MHz), 26915 (836.5MHz), 26965 (841.5MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 37 RB Offset 1 RB / 74 RB Offset 36 RB / 0 RB Offset 36 RB / 19 RB Offset 36 RB / 39 RB Offset 75 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	26805 to 27025	26805 (825.5MHz)	3MHz	QPSK	1 RB / 14 RB Offset
-	Radiated Emission Above 1GHz	26805 to 27025	26805 (825.5MHz)	3MHz	QPSK	1 RB / 14 RB Offset

Test Condition:

Test Item	Environmental Conditions	Input Power (system)	Tested By
ERP	25deg. C, 70%RH	5Vdc	James Yang
Radiated Emission	22deg. C, 68%RH 22deg. C, 66%RH	120Vac, 60Hz	Greg Lin

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and References:

Test Standard:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 971168 D01 Power Meas License Digital Systems v03r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 7 watts e.r.p.

4.1.2 Test Procedures

Conducted Power Measurement:

The EUT was set up for the maximum power with WCDMA, LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

Maximum EIRP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_{\text{T}}$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively
(expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_{T} gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

4.1.3 Test Setup

Conducted Power Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

Conducted Output Power (dBm)

Band	WCDMA V		
	4132	4182	4233
TX Channel	4132	4182	4233
Rx Channel	4357	4407	4458
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	23.02	23.08	23.27
HSDPA Subtest-1	21.95	21.70	22.00
HSDPA Subtest-2	22.05	21.91	22.05
HSDPA Subtest-3	21.88	21.82	21.97
HSDPA Subtest-4	21.99	21.94	21.84
HSUPA Subtest-1	20.99	21.16	21.09
HSUPA Subtest-2	20.89	20.89	21.01
HSUPA Subtest-3	20.84	20.83	21.03
HSUPA Subtest-4	20.91	20.80	20.99

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20407	20525	20643
		Frequency (MHz)		824.7	836.5	848.3
1.4M	QPSK	1	0	23.57	23.38	23.20
		1	2	23.49	23.40	23.32
		1	5	23.44	23.52	23.21
		3	0	23.52	23.33	23.18
		3	1	23.65	23.50	23.39
		3	3	23.67	23.47	23.34
		6	0	22.57	22.66	22.22
	16QAM	1	0	22.70	22.60	22.51
		1	2	22.63	22.64	22.57
		1	5	22.49	22.56	22.48
		3	0	22.56	22.44	22.38
		3	1	22.68	22.54	22.47
		3	3	22.63	22.54	22.32
		6	0	21.67	21.57	21.41
	64QAM	1	0	21.33	21.21	20.99
		1	2	21.41	21.23	21.04
		1	5	21.22	21.19	21.08
		3	0	21.13	21.07	20.76
		3	1	21.27	21.20	20.81
		3	3	21.18	21.10	21.14
		6	0	20.15	20.14	20.15
	256QAM	1	0	20.42	20.49	19.82
		1	2	20.37	20.51	20.15
		1	5	20.41	20.33	19.96
		3	0	20.33	20.36	20.12
		3	1	20.29	20.41	20.15
		3	3	20.16	20.43	19.83
		6	0	20.29	20.48	20.23

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20415	20525	20635
		Frequency (MHz)		825.5	836.5	847.5
3M	QPSK	1	0	23.73	23.69	23.52
		1	7	23.52	23.44	23.42
		1	14	23.56	23.58	23.58
		8	0	22.78	22.71	22.71
		8	3	22.63	22.58	22.56
		8	7	22.58	22.59	22.58
		15	0	22.80	22.65	22.52
	16QAM	1	0	22.80	22.75	23.00
		1	7	22.80	22.74	22.88
		1	14	22.58	22.75	22.92
		8	0	21.73	21.68	21.75
		8	3	21.73	21.70	21.72
		8	7	21.65	21.74	21.59
		15	0	21.70	21.56	21.55
	64QAM	1	0	21.14	21.60	21.45
		1	7	21.15	21.20	21.45
		1	14	21.03	21.66	21.54
		8	0	20.19	20.09	20.08
		8	3	20.21	20.14	20.11
		8	7	20.30	20.23	19.99
		15	0	20.09	20.08	20.16
	256QAM	1	0	20.98	21.04	20.63
		1	7	20.71	20.49	20.37
		1	14	20.79	20.54	20.95
		8	0	20.52	20.34	20.32
		8	3	21.02	20.43	20.60
		8	7	20.53	20.43	20.62
		15	0	20.98	20.70	20.63

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20425	20525	20625
		Frequency (MHz)		826.5	836.5	846.5
5M	QPSK	1	0	23.56	23.53	23.70
		1	12	23.59	23.49	23.58
		1	24	23.49	23.65	23.43
		12	0	22.86	22.61	22.79
		12	6	22.75	22.68	22.73
		12	13	22.61	22.65	22.57
		25	0	22.82	22.64	22.73
	16QAM	1	0	22.86	22.93	23.06
		1	12	23.15	22.68	23.03
		1	24	23.05	22.87	23.00
		12	0	21.79	21.73	21.63
		12	6	21.83	21.63	21.67
		12	13	21.81	21.63	21.70
		25	0	21.73	21.69	21.63
	64QAM	1	0	21.22	21.54	21.37
		1	12	21.26	21.67	21.29
		1	24	21.63	21.76	21.36
		12	0	20.12	20.04	19.94
		12	6	20.09	20.19	20.10
		12	13	20.08	20.18	20.10
		25	0	20.22	20.25	19.99
	256QAM	1	0	20.91	20.66	21.16
		1	12	21.05	20.30	21.14
		1	24	20.75	20.60	20.48
		12	0	20.70	20.67	20.70
		12	6	20.69	20.71	21.09
		12	13	20.81	20.66	21.07
		25	0	20.65	20.75	20.31

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20450	20525	20600
		Frequency (MHz)		829	836.5	844
10M	QPSK	1	0	23.60	23.54	23.40
		1	24	23.62	23.24	23.49
		1	49	23.38	23.45	23.04
		25	0	22.74	22.62	22.55
		25	12	22.70	22.72	22.71
		25	25	22.55	22.67	22.81
		50	0	22.63	22.80	22.75
	16QAM	1	0	22.57	22.82	23.11
		1	24	22.46	23.09	23.16
		1	49	22.63	23.12	22.75
		25	0	21.54	21.47	21.72
		25	12	21.57	21.66	21.65
		25	25	21.73	21.55	21.78
		50	0	21.73	21.66	21.65
	64QAM	1	0	21.35	21.75	21.47
		1	24	21.33	21.20	21.40
		1	49	21.69	21.74	21.19
		25	0	20.04	20.07	19.80
		25	12	20.20	20.20	19.95
		25	25	20.33	20.08	20.21
		50	0	20.17	20.15	20.15
	256QAM	1	0	21.16	20.63	21.00
		1	24	20.69	20.65	20.91
		1	49	21.15	20.73	21.09
		25	0	20.83	20.97	20.66
		25	12	20.71	20.91	21.17
		25	25	20.87	20.64	20.71
		50	0	20.96	20.67	20.56

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26797	26915	27033
		Frequency (MHz)		824.7	836.5	848.3
1.4M	QPSK	1	0	23.49	23.38	22.89
		1	2	23.55	23.45	23.17
		1	5	23.51	23.39	23.08
		3	0	23.51	23.46	22.92
		3	1	23.68	23.45	23.14
		3	3	23.66	23.44	22.98
		6	0	22.46	22.58	22.13
	16QAM	1	0	22.65	22.45	22.73
		1	2	22.85	22.64	22.70
		1	5	22.42	22.71	22.47
		3	0	22.66	22.57	22.08
		3	1	22.69	22.49	22.37
		3	3	22.58	22.58	22.05
		6	0	21.48	21.53	21.04
	64QAM	1	0	21.46	21.21	21.13
		1	2	21.54	21.32	21.14
		1	5	21.45	21.01	20.98
		3	0	21.08	21.22	20.95
		3	1	21.01	21.19	21.05
		3	3	21.03	20.86	21.01
		6	0	20.20	20.07	20.21
	256QAM	1	0	20.30	20.30	20.64
		1	2	20.37	20.50	20.75
		1	5	20.60	20.70	20.99
		3	0	20.62	20.45	20.54
		3	1	20.88	20.16	20.65
		3	3	20.87	20.67	20.60
		6	0	20.50	20.55	20.37

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26805	26915	27025
		Frequency (MHz)		825.5	836.5	847.5
3M	QPSK	1	0	23.59	23.58	23.53
		1	7	23.69	23.44	23.32
		1	14	23.72	23.47	23.45
		8	0	22.69	22.49	22.41
		8	3	22.73	22.51	22.38
		8	7	22.53	22.41	22.30
		15	0	22.69	22.48	22.54
	16QAM	1	0	22.43	22.74	23.22
		1	7	22.54	23.01	22.69
		1	14	22.48	23.15	22.75
		8	0	21.73	21.58	21.52
		8	3	21.68	21.58	21.61
		8	7	21.55	21.55	21.40
		15	0	21.68	21.52	21.64
	64QAM	1	0	21.29	21.06	21.45
		1	7	21.11	21.34	21.61
		1	14	21.25	21.24	21.42
		8	0	20.41	20.12	20.24
		8	3	20.33	20.21	20.10
		8	7	20.27	20.22	20.09
		15	0	20.34	20.01	20.14
	256QAM	1	0	20.54	20.69	20.31
		1	7	20.81	20.22	20.96
		1	14	20.55	20.82	20.83
		8	0	20.40	20.41	20.36
		8	3	20.85	20.35	20.88
		8	7	20.30	20.41	20.62
		15	0	20.89	20.15	20.78

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26815	26915	27015
		Frequency (MHz)		826.5	836.5	846.5
5M	QPSK	1	0	23.34	23.50	23.46
		1	12	23.38	23.71	23.61
		1	24	23.50	23.58	23.67
		12	0	22.65	22.58	22.68
		12	6	22.64	22.59	22.48
		12	13	22.56	22.45	22.51
		25	0	22.56	22.43	22.58
	16QAM	1	0	22.81	23.02	22.58
		1	12	22.79	22.95	22.70
		1	24	22.95	22.99	22.50
		12	0	21.51	21.62	21.56
		12	6	21.61	21.44	21.67
		12	13	21.65	21.55	21.64
		25	0	21.46	21.59	21.57
	64QAM	1	0	21.18	21.25	21.36
		1	12	21.27	21.17	21.43
		1	24	21.26	21.26	21.41
		12	0	20.20	19.99	20.09
		12	6	20.24	20.10	20.04
		12	13	20.13	20.09	20.04
		25	0	20.24	20.01	19.93
	256QAM	1	0	20.76	20.86	20.42
		1	12	20.35	20.60	20.56
		1	24	20.33	20.37	20.37
		12	0	20.68	20.36	20.54
		12	6	20.74	20.73	20.40
		12	13	20.55	20.54	20.63
		25	0	20.69	20.25	20.57

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26840	26915	26990
		Frequency (MHz)		829	836.5	844
10M	QPSK	1	0	23.41	23.21	23.68
		1	24	23.40	23.14	23.37
		1	49	23.38	23.56	23.10
		25	0	22.54	22.54	22.53
		25	12	22.52	22.45	22.51
		25	25	22.54	22.51	22.48
		50	0	22.47	22.51	22.35
	16QAM	1	0	23.10	22.86	22.73
		1	24	22.75	22.94	22.71
		1	49	22.84	22.87	22.23
		25	0	21.52	21.42	21.51
		25	12	21.55	21.59	21.44
		25	25	21.30	21.57	21.64
		50	0	21.58	21.57	21.39
	64QAM	1	0	21.34	21.27	21.52
		1	24	21.59	21.59	21.44
		1	49	21.22	21.62	21.25
		25	0	20.09	19.96	19.97
		25	12	20.02	20.04	20.06
		25	25	19.99	20.33	19.95
		50	0	20.10	20.11	20.10
	256QAM	1	0	20.70	20.22	20.23
		1	24	20.64	20.04	20.14
		1	49	20.51	20.86	20.21
		25	0	20.39	19.86	20.23
		25	12	20.20	20.06	20.07
		25	25	20.63	19.99	20.11
		50	0	20.51	19.98	20.11

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26865	26915	26965
		Frequency (MHz)		831.5	836.5	841.5
15M	QPSK	1	0	23.59	23.63	23.64
		1	37	23.67	23.57	23.60
		1	74	23.61	23.69	23.20
		36	0	22.74	22.89	22.75
		36	19	22.83	22.69	22.63
		36	39	22.67	22.81	22.82
		75	0	22.64	22.64	22.71
	16QAM	1	0	22.95	22.70	22.75
		1	37	23.17	22.75	22.74
		1	74	23.19	22.64	22.18
		36	0	21.79	21.86	21.75
		36	19	21.89	21.71	21.56
		36	39	21.65	21.73	21.76
		75	0	21.63	21.79	21.80
	64QAM	1	0	21.35	21.80	21.58
		1	37	21.65	21.37	21.38
		1	74	21.39	21.29	21.62
		36	0	20.24	20.24	20.10
		36	19	20.35	20.29	20.10
		36	39	20.33	20.46	20.40
		75	0	20.29	20.43	20.36
	256QAM	1	0	20.52	20.08	20.26
		1	37	20.71	21.24	20.18
		1	74	20.63	19.96	20.29
		36	0	20.62	20.08	20.12
		36	19	20.54	20.12	20.13
		36	39	20.48	20.11	20.23
		75	0	20.36	20.04	20.39

ERP Power (dBm)

Band	WCDMA V		
TX Channel	4132	4182	4233
Rx Channel	4357	4407	4458
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	24.68	24.74	24.93
HSDPA Subtest-1	23.61	23.36	23.66
HSDPA Subtest-2	23.71	23.57	23.71
HSDPA Subtest-3	23.54	23.48	23.63
HSDPA Subtest-4	23.65	23.60	23.50
HSUPA Subtest-1	22.65	22.82	22.75
HSUPA Subtest-2	22.55	22.55	22.67
HSUPA Subtest-3	22.50	22.49	22.69
HSUPA Subtest-4	22.57	22.46	22.65

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20407	20525	20643
		Frequency (MHz)		824.7	836.5	848.3
1.4M	QPSK	1	0	25.23	25.04	24.86
		1	2	25.15	25.06	24.98
		1	5	25.10	25.18	24.87
		3	0	25.18	24.99	24.84
		3	1	25.31	25.16	25.05
		3	3	25.33	25.13	25.00
		6	0	24.23	24.32	23.88
	16QAM	1	0	24.36	24.26	24.17
		1	2	24.29	24.30	24.23
		1	5	24.15	24.22	24.14
		3	0	24.22	24.10	24.04
		3	1	24.34	24.20	24.13
		3	3	24.29	24.20	23.98
		6	0	23.33	23.23	23.07
	64QAM	1	0	22.99	22.87	22.65
		1	2	23.07	22.89	22.70
		1	5	22.88	22.85	22.74
		3	0	22.79	22.73	22.42
		3	1	22.93	22.86	22.47
		3	3	22.84	22.76	22.80
		6	0	21.81	21.80	21.81
	256QAM	1	0	22.08	22.15	21.48
		1	2	22.03	22.17	21.81
		1	5	22.07	21.99	21.62
		3	0	21.99	22.02	21.78
		3	1	21.95	22.07	21.81
		3	3	21.82	22.09	21.49
		6	0	21.95	22.14	21.89

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20415	20525	20635
		Frequency (MHz)		825.5	836.5	847.5
3M	QPSK	1	0	25.39	25.35	25.18
		1	7	25.18	25.10	25.08
		1	14	25.22	25.24	25.24
		8	0	24.44	24.37	24.37
		8	3	24.29	24.24	24.22
		8	7	24.24	24.25	24.24
		15	0	24.46	24.31	24.18
	16QAM	1	0	24.46	24.41	24.66
		1	7	24.46	24.40	24.54
		1	14	24.24	24.41	24.58
		8	0	23.39	23.34	23.41
		8	3	23.39	23.36	23.38
		8	7	23.31	23.40	23.25
		15	0	23.36	23.22	23.21
	64QAM	1	0	22.80	23.26	23.11
		1	7	22.81	22.86	23.11
		1	14	22.69	23.32	23.20
		8	0	21.85	21.75	21.74
		8	3	21.87	21.80	21.77
		8	7	21.96	21.89	21.65
		15	0	21.75	21.74	21.82
	256QAM	1	0	22.64	22.70	22.29
		1	7	22.37	22.15	22.03
		1	14	22.45	22.20	22.61
		8	0	22.18	22.00	21.98
		8	3	22.68	22.09	22.26
		8	7	22.19	22.09	22.28
		15	0	22.64	22.36	22.29

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20425	20525	20625
		Frequency (MHz)		826.5	836.5	846.5
5M	QPSK	1	0	25.22	25.19	25.36
		1	12	25.25	25.15	25.24
		1	24	25.15	25.31	25.09
		12	0	24.52	24.27	24.45
		12	6	24.41	24.34	24.39
		12	13	24.27	24.31	24.23
		25	0	24.48	24.30	24.39
	16QAM	1	0	24.52	24.59	24.72
		1	12	24.81	24.34	24.69
		1	24	24.71	24.53	24.66
		12	0	23.45	23.39	23.29
		12	6	23.49	23.29	23.33
		12	13	23.47	23.29	23.36
		25	0	23.39	23.35	23.29
	64QAM	1	0	22.88	23.20	23.03
		1	12	22.92	23.33	22.95
		1	24	23.29	23.42	23.02
		12	0	21.78	21.70	21.60
		12	6	21.75	21.85	21.76
		12	13	21.74	21.84	21.76
		25	0	21.88	21.91	21.65
	256QAM	1	0	22.57	22.32	22.82
		1	12	22.71	21.96	22.80
		1	24	22.41	22.26	22.14
		12	0	22.36	22.33	22.36
		12	6	22.35	22.37	22.75
		12	13	22.47	22.32	22.73
		25	0	22.31	22.41	21.97

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20450	20525	20600
		Frequency (MHz)		829	836.5	844
10M	QPSK	1	0	25.26	25.20	25.06
		1	24	25.28	24.90	25.15
		1	49	25.04	25.11	24.70
		25	0	24.40	24.28	24.21
		25	12	24.36	24.38	24.37
		25	25	24.21	24.33	24.47
		50	0	24.29	24.46	24.41
	16QAM	1	0	24.23	24.48	24.77
		1	24	24.12	24.75	24.82
		1	49	24.29	24.78	24.41
		25	0	23.20	23.13	23.38
		25	12	23.23	23.32	23.31
		25	25	23.39	23.21	23.44
		50	0	23.39	23.32	23.31
	64QAM	1	0	23.01	23.41	23.13
		1	24	22.99	22.86	23.06
		1	49	23.35	23.40	22.85
		25	0	21.70	21.73	21.46
		25	12	21.86	21.86	21.61
		25	25	21.99	21.74	21.87
		50	0	21.83	21.81	21.81
	256QAM	1	0	22.82	22.29	22.66
		1	24	22.35	22.31	22.57
		1	49	22.81	22.39	22.75
		25	0	22.49	22.63	22.32
		25	12	22.37	22.57	22.83
		25	25	22.53	22.30	22.37
		50	0	22.62	22.33	22.22

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26797	26915	27033
		Frequency (MHz)		824.7	836.5	848.3
1.4M	QPSK	1	0	25.15	25.04	24.55
		1	2	25.21	25.11	24.83
		1	5	25.17	25.05	24.74
		3	0	25.17	25.12	24.58
		3	1	25.34	25.11	24.80
		3	3	25.32	25.10	24.64
		6	0	24.12	24.24	23.79
	16QAM	1	0	24.31	24.11	24.39
		1	2	24.51	24.30	24.36
		1	5	24.08	24.37	24.13
		3	0	24.32	24.23	23.74
		3	1	24.35	24.15	24.03
		3	3	24.24	24.24	23.71
		6	0	23.14	23.19	22.70
	64QAM	1	0	23.12	22.87	22.79
		1	2	23.20	22.98	22.80
		1	5	23.11	22.67	22.64
		3	0	22.74	22.88	22.61
		3	1	22.67	22.85	22.71
		3	3	22.69	22.52	22.67
		6	0	21.86	21.73	21.87
	256QAM	1	0	21.96	21.96	22.30
		1	2	22.03	22.16	22.41
		1	5	22.26	22.36	22.65
		3	0	22.28	22.11	22.20
		3	1	22.54	21.82	22.31
		3	3	22.53	22.33	22.26
		6	0	22.16	22.21	22.03

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26805	26915	27025
		Frequency (MHz)		825.5	836.5	847.5
3M	QPSK	1	0	25.25	25.24	25.19
		1	7	25.35	25.10	24.98
		1	14	25.38	25.13	25.11
		8	0	24.35	24.15	24.07
		8	3	24.39	24.17	24.04
		8	7	24.19	24.07	23.96
		15	0	24.35	24.14	24.20
	16QAM	1	0	24.09	24.40	24.88
		1	7	24.20	24.67	24.35
		1	14	24.14	24.81	24.41
		8	0	23.39	23.24	23.18
		8	3	23.34	23.24	23.27
		8	7	23.21	23.21	23.06
		15	0	23.34	23.18	23.30
	64QAM	1	0	22.95	22.72	23.11
		1	7	22.77	23.00	23.27
		1	14	22.91	22.90	23.08
		8	0	22.07	21.78	21.90
		8	3	21.99	21.87	21.76
		8	7	21.93	21.88	21.75
		15	0	22.00	21.67	21.80
	256QAM	1	0	22.20	22.35	21.97
		1	7	22.47	21.88	22.62
		1	14	22.21	22.48	22.49
		8	0	22.06	22.07	22.02
		8	3	22.51	22.01	22.54
		8	7	21.96	22.07	22.28
		15	0	22.55	21.81	22.44

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26815	26915	27015
		Frequency (MHz)		826.5	836.5	846.5
5M	QPSK	1	0	25.00	25.16	25.12
		1	12	25.04	25.37	25.27
		1	24	25.16	25.24	25.33
		12	0	24.31	24.24	24.34
		12	6	24.30	24.25	24.14
		12	13	24.22	24.11	24.17
		25	0	24.22	24.09	24.24
	16QAM	1	0	24.47	24.68	24.24
		1	12	24.45	24.61	24.36
		1	24	24.61	24.65	24.16
		12	0	23.17	23.28	23.22
		12	6	23.27	23.10	23.33
		12	13	23.31	23.21	23.30
		25	0	23.12	23.25	23.23
	64QAM	1	0	22.84	22.91	23.02
		1	12	22.93	22.83	23.09
		1	24	22.92	22.92	23.07
		12	0	21.86	21.65	21.75
		12	6	21.90	21.76	21.70
		12	13	21.79	21.75	21.70
		25	0	21.90	21.67	21.59
	256QAM	1	0	22.42	22.52	22.08
		1	12	22.01	22.26	22.22
		1	24	21.99	22.03	22.03
		12	0	22.34	22.02	22.20
		12	6	22.40	22.39	22.06
		12	13	22.21	22.20	22.29
		25	0	22.35	21.91	22.23

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26840	26915	26990
		Frequency (MHz)		829	836.5	844
10M	QPSK	1	0	25.07	24.87	25.34
		1	24	25.06	24.80	25.03
		1	49	25.04	25.22	24.76
		25	0	24.20	24.20	24.19
		25	12	24.18	24.11	24.17
		25	25	24.20	24.17	24.14
		50	0	24.13	24.17	24.01
	16QAM	1	0	24.76	24.52	24.39
		1	24	24.41	24.60	24.37
		1	49	24.50	24.53	23.89
		25	0	23.18	23.08	23.17
		25	12	23.21	23.25	23.10
		25	25	22.96	23.23	23.30
		50	0	23.24	23.23	23.05
	64QAM	1	0	23.00	22.93	23.18
		1	24	23.25	23.25	23.10
		1	49	22.88	23.28	22.91
		25	0	21.75	21.62	21.63
		25	12	21.68	21.70	21.72
		25	25	21.65	21.99	21.61
		50	0	21.76	21.77	21.76
	256QAM	1	0	22.36	21.88	21.89
		1	24	22.30	21.70	21.80
		1	49	22.17	22.52	21.87
		25	0	22.05	21.52	21.89
		25	12	21.86	21.72	21.73
		25	25	22.29	21.65	21.77
		50	0	22.17	21.64	21.77

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26865	26915	26965
		Frequency (MHz)		831.5	836.5	841.5
15M	QPSK	1	0	25.25	25.29	25.30
		1	37	25.33	25.23	25.26
		1	74	25.27	25.35	24.86
		36	0	24.40	24.55	24.41
		36	19	24.49	24.35	24.29
		36	39	24.33	24.47	24.48
		75	0	24.30	24.30	24.37
	16QAM	1	0	24.61	24.36	24.41
		1	37	24.83	24.41	24.40
		1	74	24.85	24.30	23.84
		36	0	23.45	23.52	23.41
		36	19	23.55	23.37	23.22
		36	39	23.31	23.39	23.42
		75	0	23.29	23.45	23.46
	64QAM	1	0	23.01	23.46	23.24
		1	37	23.31	23.03	23.04
		1	74	23.05	22.95	23.28
		36	0	21.90	21.90	21.76
		36	19	22.01	21.95	21.76
		36	39	21.99	22.12	22.06
		75	0	21.95	22.09	22.02
	256QAM	1	0	22.18	21.74	21.92
		1	37	22.37	22.90	21.84
		1	74	22.29	21.62	21.95
		36	0	22.28	21.74	21.78
		36	19	22.20	21.78	21.79
		36	39	22.14	21.77	21.89
		75	0	22.02	21.70	22.05

*ERP = Conducted + antenna gain (3.81dBi)-2.15

4.2 Radiated Emission Measurement

4.2.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.2.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $\text{E.R.P power} = \text{E.I.R.P power} - 2.15\text{dBi.}$


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.2.3 Deviation from Test Standard


No deviation.

4.2.4 Test Setup

For radiated emission 30MHz to 1GHz



For radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.5 Test Results


Below 1GHz
WCDMA Band 5

Mode	TX channel 4233 (846.6MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	31.41	-49.5	-37.0	-12.0	-49.0	-13.0	-36.0
2	82.01	-36.1	-43.1	-1.1	-44.2	-13.0	-31.2
3	138.25	-43.5	-51.3	-0.3	-51.6	-13.0	-38.6
4	184.64	-42.7	-56.7	3.5	-53.2	-13.0	-40.2
5	319.59	-52.8	-64.0	5.2	-58.8	-13.0	-45.8
6	403.94	-59.7	-67.4	5.2	-62.2	-13.0	-49.2

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB) + 2.15dB.




Mode	TX channel 4233 (846.6MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	39.84	-45.2	-45.8	-10.9	-56.7	-13.0	-43.7
2	76.39	-37.4	-42.4	-2.8	-45.2	-13.0	-32.2
3	191.67	-47.8	-56.9	4.4	-52.5	-13.0	-39.5
4	288.67	-50.5	-56.6	5.2	-51.4	-13.0	-38.4
5	374.42	-63.6	-71.2	5.3	-65.9	-13.0	-52.9
6	784.91	-69.2	-67.3	4.2	-63.1	-13.0	-50.1

Remarks:

- ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
- Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB) + 2.15dB.




LTE Band 5, Channel Bandwidth: 3MHz

Mode	TX channel 20415 (825.5MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	30.00	-48.0	-34.9	-12.2	-47.1	-13.0	-34.1
2	83.42	-36.8	-44.6	-0.7	-45.3	-13.0	-32.3
3	141.06	-44.8	-52.2	-0.3	-52.5	-13.0	-39.5
4	184.64	-43.0	-57.1	3.5	-53.6	-13.0	-40.6
5	325.22	-51.2	-62.3	5.2	-57.1	-13.0	-44.1
6	392.70	-59.0	-67.0	5.2	-61.8	-13.0	-48.8

Remarks:

- ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
- Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB) + 2.15dB.




Mode	TX channel 20415 (825.5MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	39.84	-46.4	-47.0	-10.9	-57.9	-13.0	-44.9
2	77.80	-37.6	-42.7	-2.3	-45.0	-13.0	-32.0
3	187.45	-47.5	-56.5	3.9	-52.6	-13.0	-39.6
4	305.54	-50.5	-56.8	5.1	-51.7	-13.0	-38.7
5	375.83	-63.2	-70.7	5.3	-65.4	-13.0	-52.4
6	829.90	-68.2	-66.0	4.0	-62.0	-13.0	-49.0

Remarks:

- ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
- Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB) + 2.15dB.




LTE Band 26, Channel Bandwidth 3MHz

Mode	TX channel 26805 (825.5MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	30.00	-48.1	-35.0	-12.2	-47.2	-13.0	-34.2
2	84.83	-36.7	-45.3	-0.3	-45.6	-13.0	-32.6
3	186.04	-42.1	-56.3	3.7	-52.6	-13.0	-39.6
4	313.97	-51.5	-62.7	5.2	-57.5	-13.0	-44.5
5	395.51	-58.6	-66.3	5.2	-61.1	-13.0	-48.1
6	748.36	-59.8	-62.4	4.7	-57.7	-13.0	-44.7

Remarks:

- ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
- Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB) + 2.15dB.




Mode	TX channel 26805 (825.5MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	30.00	-50.2	-48.5	-12.2	-60.7	-13.0	-47.7
2	77.80	-37.6	-42.7	-2.3	-45.0	-13.0	-32.0
3	184.64	-46.4	-55.3	3.5	-51.8	-13.0	-38.8
4	313.97	-50.0	-57.1	5.2	-51.9	-13.0	-38.9
5	661.20	-68.8	-69.7	4.9	-64.8	-13.0	-51.8
6	981.72	-69.3	-64.9	3.9	-61.0	-13.0	-48.0

Remarks:

- ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
- Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB) + 2.15dB.



Above 1GHz
WCDMA Band 5

Mode	TX channel 4233 (846.6MHz)	Frequency Range	1GHz ~ 10GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1693.20	-60.8	-53.2	0.7	-52.5	-13.0	-39.5
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1693.20	-65.3	-58.0	0.7	-57.3	-13.0	-44.3

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB) + 2.15dB.

LTE Band 5, Channel Bandwidth: 3MHz

Mode	TX channel 20415 (825.5MHz)	Frequency Range	1GHz ~ 10GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1651.00	-64.2	-56.4	0.9	-55.5	-13.0	-42.5
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1651.00	-62.1	-54.9	0.9	-54.0	-13.0	-41.0

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB) + 2.15dB.

LTE Band 26, Channel Bandwidth 3MHz

Mode	TX channel 26805 (825.5MHz)	Frequency Range	1GHz ~ 10GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1651.00	-62.5	-54.8	0.9	-53.9	-13.0	-40.9
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1651.00	-59.8	-52.5	0.9	-51.6	-13.0	-38.6

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB) + 2.15dB.

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---