



Highest	5184	-56.48	-25	-31.48	-80.6	-63.74	2.44	9.70	H
	7770	-53.91	-25	-28.91	-81.72	-63.53	2.34	11.96	H
	10368	-49.71	-25	-24.71	-82.15	-59.36	2.69	12.35	H
									H
									H
									H
	5184	-55.09	-25	-30.09	-79.06	-62.35	2.44	9.70	V
	7770	-53.19	-25	-28.19	-81.37	-62.81	2.34	11.96	V
	10368	-49.62	-25	-24.62	-81.88	-59.27	2.69	12.35	V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



<Ant. 0 + Ant. 2>

EN-DC 71A-n2A

EN-DC 71A-n2A / 20MHz / PI/2 BPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3702	-57.63	-13	-44.63	-78.4	-64.2	1.67	8.24	H
	5550	-55.58	-13	-42.58	-81.01	-62.65	2.65	9.72	H
	7404	-51.01	-13	-38.01	-78.11	-60.16	2.46	11.61	H
									H
									H
									H
	3702	-55.00	-13	-42.00	-75.76	-61.57	1.67	8.24	V
	5550	-55.01	-13	-42.01	-80.41	-62.08	2.65	9.72	V
	7404	-45.86	-13	-32.86	-73.17	-55.01	2.46	11.61	V
									V
									V
									V
Middle	3744	-57.01	-13	-44.01	-77.78	-63.62	1.68	8.29	H
	5610	-55.73	-13	-42.73	-81.27	-62.79	2.69	9.74	H
	7482	-52.82	-13	-39.82	-79.95	-62.15	2.44	11.76	H
									H
									H
									H
	3744	-54.44	-13	-41.44	-75.26	-61.05	1.68	8.29	V
	5610	-55.29	-13	-42.29	-80.78	-62.35	2.69	9.74	V
	7482	-46.99	-13	-33.99	-74.18	-56.32	2.44	11.76	V
									V
									V
									V



Highest	3780	-56.42	-13	-43.42	-77.16	-63.06	1.69	8.34	H
	5670	-55.46	-13	-42.46	-81.08	-62.51	2.72	9.77	H
	7560	-50.35	-13	-37.35	-77.68	-59.78	2.41	11.84	H
									H
									H
									H
	3780	-52.57	-13	-39.57	-73.35	-59.21	1.69	8.34	V
	5670	-55.09	-13	-42.09	-80.7	-62.14	2.72	9.77	V
	7560	-48.01	-13	-35.01	-75.6	-57.44	2.41	11.84	V
									V
									V
									V

Remark:

- 1. Spurious emissions within 30-1000MHz were found more than 20dB below line.
- 2. Test combination is EN-DC B71 + n2 (Antenna 0+2)



EN-DC 13A-n25A

EN-DC 13A-n25A / 40MHz / PI/2 BPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3702	-57.84	-13	-44.84	-78.61	-64.41	1.67	8.24	H
	5550	-55.76	-13	-42.76	-81.19	-62.83	2.65	9.72	H
	7398	-54.78	-13	-41.78	-81.87	-63.91	2.46	11.60	H
									H
									H
									H
	3702	-57.65	-13	-44.65	-78.41	-64.22	1.67	8.24	V
	5550	-55.52	-13	-42.52	-80.92	-62.59	2.65	9.72	V
	7398	-54.39	-13	-41.39	-81.68	-63.52	2.46	11.60	V
									V
									V
									V
Middle	3726	-58.15	-13	-45.15	-78.93	-64.75	1.68	8.27	H
	5586	-55.47	-13	-42.47	-80.98	-62.53	2.67	9.73	H
	7452	-54.62	-13	-41.62	-81.76	-63.88	2.44	11.70	H
									H
									H
									H
	3726	-57.89	-13	-44.89	-78.67	-64.49	1.68	8.27	V
	5586	-55.70	-13	-42.70	-81.19	-62.76	2.67	9.73	V
	7452	-53.52	-13	-40.52	-80.88	-62.78	2.44	11.70	V
									V
									V
									V



Highest	3750	-57.86	-13	-44.86	-78.62	-64.48	1.68	8.30	H
	5625	-55.71	-13	-42.71	-81.27	-62.76	2.70	9.75	H
	7500	-54.61	-13	-41.61	-81.77	-63.98	2.43	11.80	H
									H
									H
									H
	3750	-56.95	-13	-43.95	-77.73	-63.57	1.68	8.30	V
	5625	-55.64	-13	-42.64	-81.19	-62.69	2.70	9.75	V
	7500	-54.11	-13	-41.11	-81.51	-63.48	2.43	11.80	V
									V
									V
									V

Remark:

- 1. Spurious emissions within 30-1000MHz were found more than 20dB below line.
- 2. Test combination is EN-DC B13 + n25 (Antenna 0+2)



EN-DC 5A-n66A

EN-DC 5A-n66A / 40MHz / PI/2 BPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3420	-57.02	-13	-44.02	-77.57	-63.09	1.58	7.65	H
	5130	-56.09	-13	-43.09	-80.2	-63.38	2.41	9.70	H
	6840	-54.67	-13	-41.67	-81.73	-62.64	2.64	10.61	H
									H
									H
									H
	3420	-54.54	-13	-41.54	-75.14	-60.61	1.58	7.65	V
	5130	-56.27	-13	-43.27	-80.22	-63.56	2.41	9.70	V
	6840	-54.44	-13	-41.44	-81.55	-62.41	2.64	10.61	V
									V
									V
									V
Middle	3450	-57.65	-13	-44.65	-78.41	-63.84	1.59	7.78	H
	5175	-56.06	-13	-43.06	-80.22	-63.32	2.44	9.70	H
	6900	-54.88	-13	-41.88	-81.78	-62.94	2.62	10.68	H
									H
									H
									H
	3450	-51.30	-13	-38.30	-71.97	-57.49	1.59	7.78	V
	5175	-56.05	-13	-43.05	-80.07	-63.31	2.44	9.70	V
	6900	-54.71	-13	-41.71	-81.6	-62.77	2.62	10.68	V
									V
									V
									V



Highest	3480	-56.72	-13	-43.72	-77.58	-63.03	1.60	7.91	H
	5220	-56.07	-13	-43.07	-80.3	-63.31	2.46	9.70	H
	6960	-55.08	-13	-42.08	-81.86	-63.23	2.60	10.75	H
									H
									H
									H
	3480	-55.43	-13	-42.43	-76.17	-61.74	1.60	7.91	V
	5220	-56.12	-13	-43.12	-80.22	-63.36	2.46	9.70	V
	6960	-55.13	-13	-42.13	-81.94	-63.28	2.60	10.75	V
									V
									V
									V

Remark:

- 1. Spurious emissions within 30-1000MHz were found more than 20dB below line.
- 2. Test combination is EN-DC B5 + n66 (Antenna 0+2)



EN-DC 12A-n7A

EN-DC 12A-n7A / 20MHz / PI/2 BPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	5004	-56.51	-25	-31.51	-80.56	-63.87	2.34	9.70	H
	7500	-52.56	-25	-27.56	-79.76	-61.93	2.43	11.80	H
	10008	-51.17	-25	-26.17	-82.77	-60.68	2.70	12.20	H
									H
									H
									H
	5004	-54.22	-25	-29.22	-77.99	-61.58	2.34	9.70	V
	7500	-50.85	-25	-25.85	-78.22	-60.22	2.43	11.80	V
	10008	-50.98	-25	-25.98	-82.22	-60.49	2.70	12.20	V
									V
									V
									V
Middle	5052	-55.82	-25	-30.82	-79.85	-63.15	2.37	9.70	H
	7578	-54.23	-25	-29.23	-81.58	-63.67	2.40	11.85	H
	10098	-50.92	-25	-25.92	-82.55	-60.46	2.70	12.24	H
									H
									H
									H
	5052	-55.78	-25	-30.78	-79.57	-63.11	2.37	9.70	V
	7578	-52.81	-25	-27.81	-80.34	-62.25	2.40	11.85	V
	10098	-50.92	-25	-25.92	-82.51	-60.46	2.70	12.24	V
									V
									V
									V



Highest	5100	-56.08	-25	-31.08	-80.18	-63.39	2.39	9.70	H
	7650	-52.23	-25	-27.23	-79.74	-61.74	2.38	11.89	H
	10206	-50.64	-25	-25.64	-82.64	-60.23	2.70	12.28	H
									H
									H
									H
	5100	-55.58	-25	-30.58	-79.5	-62.89	2.39	9.70	V
	7650	-52.11	-25	-27.11	-79.94	-61.62	2.38	11.89	V
	10206	-51.07	-25	-26.07	-82.98	-60.66	2.70	12.28	V
									V
									V
									V

Remark:

- 1. Spurious emissions within 30-1000MHz were found more than 20dB below line.
- 2. Test combination is EN-DC B12 + n7 (Antenna 0+2)