

Assessment report

REP0027308-3R1ARFWL

Date of issue: April 27, 2023

Applicant:

VIE Technologies Inc

Product:

MYVIE SPIN

Model:

M04C100R02

FCC ID:

2AQ6J-M04C100R02

IC:

24331-M04C100R02

Type of assessment:

MPE Calculation Report

Specifications:

- ◆ FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ KDB 447498 D01 General RF Exposure Guidance v06
- ◆ RSS-102 Issue 5 Amendment 1, (February 2021)

Lab and test locations

Company name	Nemko USA, Inc.
Address	1110 Faraday Ave, Suite 150
City	Carlsbad
State	California
Postal code	92008
Country	USA
Telephone	+1 760 444 3500
Website	www.nemko.com

Prepared by	Martha Espinoza, Wireless Test Engineer
Reviewed by	James Cunningham, EMC/MIL/WL Supervisor
Review date	April 28, 2023
Reviewer signature	

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko USA's ISO/IEC 17025 accreditation.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government

Copyright notification

Nemko USA Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko USA Inc. accepts no responsibility for damages, if any, suffered by any third party because of decisions made or actions based on this report.

© Nemko USA Inc.

Table of Contents

Table of Contents	3
Section 1 Declaration	4
Section 2 Evaluation summary	5
2.1 MPE exemption for stand-alone transmission	5

Section 1 Declaration

RSS-102 Annex B - Declaration of RF exposure compliance:

Attestation:

I attest that the information provided in Annex A is correct; that the Technical Brief was prepared, and the information contained therein is correct; that the device evaluation was performed and/or supervised by me; that the applicable measurement methods and evaluation methodologies have been followed; and that the device meets the SAR and/or RF field strength limits of RSS-102.

Date of issue: March 1, 2023

Martha Espinoza, Wireless Test Engineer

Prepared by



Signature

Section 2 Evaluation summary

2.1 MPE exemption for stand-alone transmission

2.1.1 References, definition, and limits

FCC §2.1091(d)

- (2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from the whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

Table 2.1-1: Table 1 to §1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842 / f	4.89 / f	*(900 / f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1500			f / 300	<6
1500–100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824 / f	2.19 / f	*(180 / f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1500			f / 1500	<30
1500–100000			1.0	<30

Notes: f = frequency in MHz. * = Plane-wave equivalent power density.

RSS-102, Section 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance)
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $0.031f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Equation from Page 18 of OET Bulletin 64, Edition 97-01:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm² or W/m²)
P = power input to the antenna (mW or W)
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna (cm or m)

2.1.2 EUT technical information

Operational frequency	CH1: 2402 MHz; CH6: 2440 MHz; CH11: 2480 MHz
Antenna type	Unique antenna coupling/non-detachable
Antenna gain	3 dBi
Number of antennas	1
Maximum transmitter conducted power	9.66 dBm (9.246981 mW)
Maximum EIRP	12.66 dBm (18.45015 mW)

2.1.3 MPE exemption calculations

Fundamental transmit (prediction) frequency:	<u>2402</u> MHz	
Maximum measured conducted peak output power:	<u>9.66</u> dBm	
Cable and/or jumper loss:	<u>0</u> dB	
Maximum peak power at antenna input terminal:	<u>9.66</u> dBm	
Tx On time:	<u>100.000</u> ms	
Tx period time:	<u>100.000</u> ms	
Average factor:	<u>100</u> %	
Maximum calculated average power at antenna input terminal:	<u>9.246981</u> mW	
Single Antenna gain (typical):	<u>3</u> dBi	
Number of antennas:	<u>1</u>	
Total system gain:	<u>3.00</u> dBi	
	FCC limit:	ISED limit:
MPE limit for uncontrolled exposure at prediction frequency:	<u>1.000000</u> mW/cm ²	<u>0.535080</u> mW/cm ²
	<u>10.000000</u> W/m ²	<u>5.350805</u> W/m ²
Minimum calculated prediction distance for compliance:	<u>20</u> cm	<u>20</u> cm
Typical (declared) distance:	<u>20</u> cm	<u>20</u> cm
Average power density at prediction frequency:	<u>0.003671</u> mW/cm ²	<u>0.003671</u> mW/cm ²
	<u>0.036705</u> W/m ²	<u>0.036705</u> W/m ²
Margin of Compliance:	<u>24.35</u> dB	<u>21.64</u> dB
Maximum allowable antenna gain:	<u>27.35</u> dBi	<u>24.64</u> dBi

2.1.4 Verdict

The calculation is below the limit; therefore, the product is compliant with the RF exposure requirements for the declared distance.