

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640 Fax: +86-755-26648637

Fax: +86-755-26648637 Report Template Version: V03
Website: www.cqa-cert.com Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No.: CQASZ20181000056E-02

Applicant: Dogness Group LLC.

Address of Applicant: 4116 W Spring Creek Parkway, Plano, TX75024, Dallas, TEXAS, USA

Manufacturer: DONGGUAN JIASHENG ENTERPRISE CO.,LTD.

Address of Manufacturer: TONGSHA NEW INDUSTRIAL ZONE, TONGSHA COMMUNITY, DONGCHENG

STREET OF DONGGUAN CITY, GUANGDONG PROVINCE, 523127 CHINA

Factory: Dogness Smart Technology (Donguan) Co., LTD.

Address of Factory: 3F, No.1, Tongsha Industrial zone, East district of Dongguan city

Equipment Under Test (EUT):

Product: Bluetooth Speaker

All Model No.: JS04-B, JS04-B-WP, JS04-B-WG, JS04-B-BO, JS04-B-BR, JS04-B-BP

Test Model No.: JS04-B

Brand Name: N/A

 FCC ID:
 2AQ6Q-JS04-B

 Standards:
 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-11-01 to 2018-11-29

Date of Issue: 2018-11-29
Tost Bosult: PASS*

Test Result : PASS*

Tested By:

(Daisy Qin)

Reviewed By: Joron / Va

(Aaron Ma)

Approved By: [Jack Ai]



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: CQASZ20181000056E-02

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20181000056E-02	Rev.01	Initial report	2018-11-29





Report No.: CQASZ20181000056E-02

2 Contents

		Page
1	VERSION	2
2	2 CONTENTS	3
3	GENERAL INFORMATION	4
	3.1 CLIENT INFORMATION	4
	SAR EVALUATION	
	4.1 RF Exposure Compliance Requirement 4.1.1 Standard Requirement	5
	4.1.2 Limits	5
	4.1.3 EUT RF Exposure	6



Report No.: CQASZ20181000056E-02

3 General Information

3.1 Client Information

Applicant:	Dogness Group LLC.
Address of Applicant:	4116 W Spring Creek Parkway, Plano, TX75024, Dallas, TEXAS, USA
Manufacturer:	DONGGUAN JIASHENG ENTERPRISE CO.,LTD.
Address of Manufacturer:	TONGSHA NEW INDUSTRIAL ZONE, TONGSHA COMMUNITY, DONGCHENG STREET OF DONGGUAN CITY, GUANGDONG PROVINCE, 523127 CHINA
Factory:	Dogness Smart Technology (Donguan) Co., LTD.
Address of Factory:	3F, No.1, Tongsha Industrial zone, East district of Dongguan city

3.2 General Description of EUT

Product Name:	Bluetooth Speaker
Model No.:	JS04-B, JS04-B-WP, JS04-B-WG, JS04-B-BO, JS04-B-BR, JS04-B-BP
Trade Mark:	JS04-B
Hardware Version:	N/A
Software Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	☐ Mobile ☐ Portable ☐ Fix Location
Test Software of EUT:	RDA Toolkit 8.03.03 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	lithium battery: DC3.7V, 500mAh, Charge by DC5.0V

Note:

All model: JS04-B, JS04-B-WP, JS04-B-WG, JS04-B-BO, JS04-B-BR, JS04-B-BP

Only the model JS04-B was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.



Report No.: CQASZ20181000056E-02

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where
☐ f(GHz) is the RF channel transmit frequency in GHz ☐ Power and distance are rounded to the nearest mW and mm before calculation 17 ☐ The result is rounded to one decimal place for comparison
The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and
for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation
distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion





Report No.: CQASZ20181000056E-02

4.1.3 EUT RF Exposure

Measurement Data

Measurement Data				
	GFSK	mode		
Test channel	Peak Output Power	Tune up tolerance	Maximum tune-up Power	
	(dBm)	(dBm)	(dBm)	(mW)
Lowest(2402MHz)	0.940	0±1	1.0	1.259
Middle(2441MHz)	0.960	0±1	1.0	1.259
Highest(2480MHz)	0.540	0±1	1.0 1.259	
	π/4DQPS	SK mode		
Test channel	Peak Output Power	Tune up tolerance	Maximum tune-up Power	
	(dBm)	(dBm)	(dBm)	(mW)
Lowest(2402MHz)	0.100	0±1	1.0	1.259
Middle(2441MHz)	0.040	0±1	1.0	1.259
Highest(2480MHz)	-0.640	-1±1	0	1.000
	8DPSK	mode		
Test channel	Peak Output Power	Tune up tolerance	Maximum tune-up Power	
	(dBm)	(dBm)	(dBm)	(mW)
Lowest(2402MHz)	0.210	0±1	1.0 1.259	
Middle(2441MHz)	0.040	0±1	1.0	1.259
Highest(2480MHz)	-0.620	-1±1	0	1.000

	Maximum		Maximum tune-			
	Peak	Tune up	up P	ower	Calculated	Exclusion threshold
Channel	Conducted Output Power (dBm)	tolerance (dBm)	(dBm)	(mW)	value	
Lowest (2402MHz)	0.940	0±1	1.0	1.259	0.39	
Middle (2440MHz)	0.960	0±1	1.0	1.259	0.39	3.0
Highest (2480MHz)	0.540	0±1	1.0	1.259	0.40	

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20181000056E-01