



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No. :** CQASZ20181000050E-02

**Applicant:** Dogness Group LLC.

**Address of Applicant:** 4116 W Spring Creek Parkway,Plano,TX75024,Dallas, TEXAS, USA

**Manufacturer:** DONGGUAN JIASHENG ENTERPRISE CO.,LTD.

**Address of Manufacturer:** TONGSHA NEW INDUSTRIAL ZONE, TONGSHA COMMUNITY, DONGCHENG STREET OF DONGGUAN CITY, GUANGDONG PROVINCE, 523127 CHINA

**Factory:** Dogness Smart Technology (Donguan) Co., LTD.

**Address of Factory:** 3F, No.1, Tongsha Industrial zone, East district of Dongguan city

**Equipment Under Test (EUT):**

**Product:** SMART IPET ROBOT

**Model No.:** SP01, SP01-W, SP01-BO, SP01-R, SP01-B, SP01-P

**Test Model No.:** SP01

**Brand Name:** N/A

**FCC ID:** 2AQ6Q-SP01

**Standards:** 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB447498D01 General RF Exposure Guidance v06

**Date of Test:** 2018-10-22 to 2018-11-21

**Date of Issue:** 2018-11-22

**Test Result :** **PASS\***

**Tested By:** \_\_\_\_\_  
*Daisy Qin*

(Daisy Qin)

**Reviewed By:** \_\_\_\_\_  
*Aaron Ma*

(Aaron Ma)

**Approved By:** \_\_\_\_\_  
*Jack Ai*  
( Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20181000050E-02	Rev.01	Initial report	2018-11-22

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION .....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 RF EXPOSURE EVALUATION .....	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	6
4.1.1 <i>Limits</i> .....	6
4.1.2 <i>Test Procedure</i> .....	6
4.2 1.1.3 EUT RF EXPOSURE EVALUATION .....	7

### 3 General Information

#### 3.1 Client Information

Applicant:	Dogness Group LLC.
Address of Applicant:	4116 W Spring Creek Parkway,Plano,TX75024,Dallas, TEXAS, USA
Manufacturer:	DONGGUAN JIASHENG ENTERPRISE CO.,LTD.
Address of Manufacturer:	TONGSHA NEW INDUSTRIAL ZONE, TONGSHA COMMUNITY, DONGCHENG STREET OF DONGGUAN CITY, GUANGDONG PROVINCE, 523127 CHINA
Factory:	Dogness Smart Technology (Donguan) Co., LTD.
Address of Factory:	3F, No.1, Tongsha Industrial zone, East district of Dongguan city

#### 3.2 General Description of EUT

Product Name:	SMART IPET ROBOT
All Model No.:	SP01, SP01-W, SP01-BO, SP01-R, SP01-B, SP01-P
Test Model No.:	SP01
Trade Mark:	N/A
Hardware version:	V1.0
Software version:	V1.0
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps
Product Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	RF test (manufacturer declare )
Antenna Type:	internal antenna with ipex connector
Antenna Gain:	1dBi
Power Supply:	Battery DC10.8V; Charge by Adaptor Adaptor model:CP1215 Input: 100~240V, 50/60Hz, 0.8A; Output: 12.6C, 1.5A

Note:

1. All model: SP01, SP01-W, SP01-BO, SP01-R, SP01-B, SP01-P
2. Only the model SP01, was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 4.2 1.1.3 EUT RF Exposure Evaluation

### 1) For 2.4G WIFI

Antenna Gain: 1dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.26 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

### Measurement Data

802.11b mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	12.95	12.5±1.0	13.5	22.387
Middle(2437MHz)	13.02	12.5±1.0	13.5	22.387
Highest(2462MHz)	13.43	12.5±1.0	13.5	22.387
802.11g mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	11.69	12±1.0	13	19.953
Middle(2437MHz)	11.78	12±1.0	13	19.953
Highest(2462MHz)	12.49	12±1.0	13	19.953
802.11n(HT20)mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	11.02	11±1.0	12	15.849
Middle(2437MHz)	11.33	11±1.0	12	15.849
Highest(2462MHz)	11.79	11±1.0	12	15.849

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
22.387	1	0.00561	1.0	PASS

Note: 1) Refer to report No. CQASZ20181000050E-01 for EUT test Max Conducted average Output Power value.

2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (22.387 * 1.26) / (4 * 3.1416 * 20^2) = 0.00561$