

FCC TEST REPORT

For

QPS ELECTRONICS CO., Limited

Tablet PC

Test Model: TL11

Additional Model No.: N/A

Prepared for : QPS ELECTRONICS CO., Limited
Address : 5th Floor, 64th Building, Baotian Industrial Zone, Qianjin 2nd Road,
Xixiang, Bao'an District, Shenzhen, Guangdong, China 518126

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan
District, Shenzhen, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : March 23, 2020
Number of tested samples : 1
Serial number : Prototype
Date of Test : March 23, 2020~ March 31, 2020
Date of Report : April 03, 2020

**FCC TEST REPORT
FCC CFR 47 PART 15 E(15.407)**

Report Reference No. : **LCS200319041AEF**

Date of Issue..... : April 03, 2020

Testing Laboratory Name : **Shenzhen LCS Compliance Testing Laboratory Ltd.**

Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street,
Baoan District, Shenzhen, China

Testing Location/ Procedure..... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □

Applicant's Name..... : **QPS ELECTRONICS CO., Limited**

Address..... : 5th Floor, 64th Building, Baotian Industrial Zone, Qianjin 2nd Road,
Xixiang, Bao'an District, Shenzhen, Guangdong, China 518126

Test Specification

Standard : FCC CFR 47 PART 15 E(15.407)

Test Report Form No...... : LCSEMC-1.1

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description..... : **Tablet PC**

Trade Mark..... : Bright Life

Test Model : TL11


Ratings..... : DC 3.8V by Rechargeable Li-Polymer Battery(7500mAh)
Recharged by DC 5V/2A adapter

Result : **Positive**

Compiled by:

Supervised by:

Approved by:



Linda He/ File administrators

Jin Wang/ Technique principal

Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCS200319041AEF	<u>April 03, 2020</u> Date of issue
---	--

EUT.....	: Tablet PC
Test Model.....	: TL11
Applicant.....	: QPS ELECTRONICS CO., Limited
Address.....	: 5th Floor, 64th Building, Baotian Industrial Zone, Qianjin 2nd Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China 518126
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Shenzhen Peicheng Technology Co., Ltd.
Address.....	: 5th Floor, 64th Building, Baotian Industrial Zone, Qianjin 2nd Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China 518126
Telephone.....	: /
Fax.....	: /
Factory.....	: /
Address.....	: /
Telephone.....	: /
Fax.....	: /

Test Result:	Positive
---------------------	-----------------

The test report merely corresponds to the test sample.
 It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	April 03, 2020	Initial Issue	Gavin Liang

TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. DESCRIPTION OF DEVICE (EUT)	6
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS	8
1.3. EXTERNAL I/O CABLE	8
1.4. DESCRIPTION OF TEST FACILITY	8
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY	8
1.6. MEASUREMENT UNCERTAINTY	9
1.7. DESCRIPTION OF TEST MODES	9
2. TEST METHODOLOGY	11
2.1. EUT CONFIGURATION	11
2.2. EUT EXERCISE	11
2.3. GENERAL TEST PROCEDURES	11
3. SYSTEM TEST CONFIGURATION.....	12
3.1. JUSTIFICATION	12
3.2. EUT EXERCISE SOFTWARE.....	12
3.3. SPECIAL ACCESSORIES	12
3.4. BLOCK DIAGRAM/SCHEMATICS.....	12
3.5. EQUIPMENT MODIFICATIONS	12
3.6. TEST SETUP	12
4. SUMMARY OF TEST RESULTS.....	13
5. TEST RESULT	14
5.1. ON TIME AND DUTY CYCLE	14
5.2. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT.....	15
5.3. POWER SPECTRAL DENSITY MEASUREMENT	17
5.4. 6DB EMISSION BANDWIDTH MEASUREMENT.....	19
5.5. RADIATED EMISSIONS MEASUREMENT.....	20
5.6. POWER LINE CONDUCTED EMISSIONS.....	33
5.7 UNDESIRABLE EMISSIONS MEASUREMENT	36
5.8. FREQUENCY STABILITY.....	38
5.9. ANTENNA REQUIREMENTS.....	40
6. LIST OF MEASURING EQUIPMENTS	41
7. TEST SETUP PHOTOGRAPHS OF EUT.....	42
8. EXTERIOR PHOTOGRAPHS OF THE EUT	42
9. INTERIOR PHOTOGRAPHS OF THE EUT	42

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Tablet PC
 Test Model : TL11
 Power Supply : DC 3.8V by Rechargeable Li-Polymer Battery(7500mAh)
 : Recharged by DC 5V/2A adapter
 Hardware version : K980-6763-V1.0
 Software version : K980V1.0_EN_PC_03_IPS_TP_FL_WUXGA_2+32_20200327

Bluetooth

Frequency Range : 2402MHz-2480MHz
 Bluetooth Version : V4.2
 Bluetooth Channel Number : 79 channels for Bluetooth V4.2 (BT Classics)
 : 40 channels for Bluetooth V4.2 (BT LE)
 Bluetooth Channel Spacing : 1MHz for Bluetooth V4.2 (BT Classics)
 : 2MHz for Bluetooth V4.2 (BT LE)
 Bluetooth Modulation Type : GFSK, $\pi/4$ -DQPSK, 8DPSK for Bluetooth V4.2 (BT Classics)
 : GFSK for Bluetooth V4.2 (BT LE)
 Antenna Description : FPC Antenna, 1dBi(Max.)

2.4G WLAN

Frequency Range : 2412 – 2462 MHz
 Channel Number : 11 Channels for 20MHz bandwidth (2412~2462MHz)
 : 7 Channels for 40MHz bandwidth (2422~2452MHz)
 Channel Spacing : 5MHz
 Modulation Type : IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)
 : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
 : IEEE 802.11n: OFDM (64QAM, 16QAM,QPSK,BPSK)
 Antenna Description : FPC Antenna, 1dBi(Max.)

WIFI 5GWLAN Band 1

Frequency Range : 5180 – 5240 MHz
 : 4 channels for 20MHz bandwidth (5180-5240MHz)
 Channel Number : 2 channels for 40MHz bandwidth (5190~5230MHz)
 : 1 channels for 80MHz bandwidth(5210MHz)
 Modulation Type : IEEE 802.11a/n/ac: OFDM (64QAM, 16QAM, QPSK, BPSK)

WIFI(5.8G Band)

Frequency Range : 5745 – 5825 MHz
 : 5 channels for 20MHz bandwidth (5745-5825MHz)
 Channel Number : 2 channels for 40MHz bandwidth (5755~5795MHz)
 : 1 channels for 80MHz bandwidth(5775MHz)
 Modulation Type : IEEE 802.11a/n/ac: OFDM (64QAM, 16QAM, QPSK, BPSK)
 Antenna Description : FPC Antenna, 1dBi (Max.)
 : The 5.2GWIFI and 5.8G WIFI shares the same antenna.

GSM

GSM/EDGE/GPRS Operation : GSM850/PCS1900/GPRS850/GPRS1900/EDGE850/EDGE1900
 Frequency Band
 GSM/EDGE/GPRS Supported GSM/GPRS/EDGE

GSM Release Version	: R7
GSM/EDGE/GPRS Power Class	: GSM850:Power Class 4/ PCS1900:Power Class 1
GPRS/EDGE Multislot Class	: GPRS/EDGE: Multi-slot Class 12
GPRS operation mode	: Class B
Modulation Type	: GMSK for GSM/GPRS, 8-PSK for EDGE
Antenna Gain	: FPC Antenna 1dBi (max.) for GSM 850; 1dBi (max.) for GSM 900; 1dBi (max.) for DCS 1800; 1dBi (max.) for PCS 1900;
WCDMA	:
UMTS Operation Frequency Band	: UMTS FDD Band II /V
WCDMA Release Version	: R8
HSDPA Release Version	: Release 8
HSUPA Release Version	: Release 6
DC-HSUPA Release Version	: Not Supported
Modulation Type	: QPSK for UMTS
Antenna Gain	: FPC Antenna 1dBi (max.) for WCDMA Band II; 1dBi (max.) for WCDMA Band V;
LTE	:
LTE Operation Frequency Band	: LTE Band 2, 4, 5, 7, 12, 17
LTE Release Version	: Release 9
LTE/UMTS Power Class	: Class 3
Modulation Type	: QPSK, 16QAM for LTE
Antenna Gain	: FPC Antenna 1dBi (max.) for LTE Band 2; 1dBi (max.) for LTE Band 4; 1dBi (max.) for LTE Band 5; 1dBi (max.) for LTE Band 7; 1dBi (max.) for LTE Band 12; 1dBi (max.) for LTE Band 17;
GPS function	: Support and only RX
FM function	: Support and only RX
Extreme temp. Tolerance	-10 °C to +50 °C
Extreme vol. Limits	3.23VDC to 4.37VDC (nominal: 3.8VDC)

1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
Shenzhen Tianqineng Technology Co., Ltd.	Adapter	Q-520	--	FCC

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
Type-C Interface	1	N/A
Earphone Jack	1	N/A

1.4. Description of Test Facility

FCC Registration Number is 254912.
 Industry Canada Registration Number is 9642A.
 EMSD Registration Number is ARCB0108.
 UL Registration Number is 100571-492.
 TUV SUD Registration Number is SCN1081.
 TUV RH Registration Number is UA 50296516-001.
 NVLAP Accreditation Code is 600167-0.
 FCC Designation Number is CN5024.
 CAB identifier: CN0071

The 3m-Fully anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 VSWR requirement for radiated emission above 1GHz.

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	±3.10dB	(1)
	30MHz~200MHz	±2.96dB	(1)
	200MHz~1000MHz	±3.10dB	(1)
	1GHz~26.5GHz	±3.80dB	(1)
	26.5GHz~40GHz	±3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	±1.63dB	(1)
Power disturbance	30MHz~300MHz	±1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worst case.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, that was determined to be IEEE 802.11ac VHT80 mode..

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be IEEE 802.11ac VHT80 mode.

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

- IEEE 802.11a Mode: 6 Mbps, OFDM.
- IEEE 802.11ac VHT20 Mode: MCS0
- IEEE 802.11n HT20 Mode: MCS0, OFDM.
- IEEE 802.11ac VHT40 Mode: MCS0, OFDM.
- IEEE 802.11n HT40 Mode: MCS0, OFDM.
- IEEE 802.11ac VHT80 Mode: MCS0, OFDM.

Frequency Band	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
5745~5825MHz	149	5745	155	5775
	151	5755	159	5795
	153	5765	161	5805
	157	5785	165	5825

For IEEE 802.11a/n HT20/ac VHT20, Channel 149, 157 and 165 were tested.
 For IEEE 802.11n HT40/ac VHT40, Channel 151 and 159 were tested.
 For IEEE 802.11ac VHT80, Channel 155 was tested.

Antenna & Bandwidth

Antenna	Chain		
Bandwidth Mode	20MHz	40MHz	80MHz
IEEE 802.11a	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
IEEE 802.11n	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
IEEE 802.11ac	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Directional Antenna Gain

The TX chains are correlated and antenna gain is unequal among the chains. The directional gain is:

Antenna Gain (dBi)
1

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB 789033 D02 General UNII Test Procedures New Rules v02r01 and KDB 662911 D01 Multiple Transmitter Output v02r01 are required to be used for this kind of FCC 15.407 Ull device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.407 under the FCC Rules Part 15 Subpart E.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

The sample will be controlled by dialing *##3646633##* to enter RF test mode to control sample change channel, modulation and so on.

3.3. Special Accessories

N/A.

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart E			
FCC Rules	Description of Test	Result	Remark
/	On Time and Duty Cycle	/	Appendix F.1
§15.407(a)	Maximum Conducted Output Power	Compliant	Appendix F.2
§15.407(a)	Power Spectral Density	Compliant	Appendix F.3
§15.407(e)	6dB Bandwidth&	Compliant	Appendix F.4
§15.209 §15.407(b)	Radiated Emissions	Compliant	Note 1
§15.205	Emissions at Restricted Band	Compliant	Appendix F.5
§15.407(g)	Frequency Stability	Compliant	Note 1
§15.207(a)	Power Line Conducted Emissions	Compliant	Note 1
§15.203	Antenna Requirements	Compliant	Note 1
§2.1093	RF Exposure	Compliant	Note 2

Remark:

1. Note 1 – Test results inside test report;
2. Note 2 – Test results in other test report (SAR test report);

5. TEST RESULT

5.1. On Time and Duty Cycle

5.1.1. Standard Applicable

None; for reporting purpose only.


5.1.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.

5.1.3. Test Procedures

1. Set the Centre frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=8MHz, VBW=50MHz, Sweep time=10.13ms;
3. Detector = peak;
4. Trace mode = Single hold.

5.1.4. Test Setup Layout



5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.6. Test result

For reporting purpose only.

Please refer to Appendix F.1

5.2. Maximum Conducted Output Power Measurement

5.2.1. Standard Applicable

For 5725~5850MHz

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the power meter.


5.2.3. Test Procedures

The transmitter output (antenna port) was connected to the power meter.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Section 3 (a) Method PM (Measurement using an RF average power meter):

- (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.
- The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
 - At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 - The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- (ii) If the transmitter does not transmit continuously, measure the duty cycle, x , of the transmitter output signal as described in section II.B.
- (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

5.2.4. Test Setup Layout



5.2.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.6. Test Result of Maximum Conducted Output Power

PASS

Please refer to Appendix F.2

Remark:

1. *Measured output power at difference data rate for each mode and recorded worst case for each mode.*
2. *Test results including cable loss;*
3. *Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;*
4. *Report conducted power = Measured conducted average power + Duty Cycle factor;*

5.3. Power Spectral Density Measurement

5.3.1. Standard Applicable

For 5725~5850MHz

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.


5.3.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

5.3.3. Test Procedures

- 1). The transmitter was connected directly to a Spectrum Analyzer through a directional couple.
- 2). The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
- 3). Set the RBW = 300 kHz
- 4). Set the VBW $\geq 3 \times$ RBW
- 5). Span=Encompass the entire emissions bandwidth (EBW) of the signal
- 6). Detector = RMS.
- 7). Sweep time = auto couple.
- 8). Trace mode = max hold.
- 9). Allow trace to fully stabilize.
- 10). If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500 \text{ kHz}/\text{RBW})$ to the measured result, whereas RBW ($< 500 \text{ kHz}$) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- 11). If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/\text{RBW})$ to the measured result, whereas RBW ($< 1 \text{ MHz}$) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- 12). Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

5.3.4. Test Setup Layout



5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.3.6. Test Result of Power Spectral Density

PASS

Please refer to Appendix F.3

Remark:

1. Measured power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;
4. Report conducted PSD = measured conducted PSD + Duty Cycle factor + RBW factor;
5. RBW factor = $10 \log (500 \text{ KHz} / 300 \text{ KHz}) = 2.218 \text{ dB}$;

5.4. 6dB Emission Bandwidth Measurement

5.4.1. Standard Applicable

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

5.4.2. Measuring Instruments and Setting


Please refer to equipment list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
RBW	100 KHz
VBW	300 KHz
Trace	Max Hold
Sweep Time	Auto

5.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 KHz and the video bandwidth of 300 KHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

5.4.4. Test Setup Layout



5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.4.6. Test Result of 6dB Emission Bandwidth

PASS

Please refer to Appendix F.4

Remark:

1. Measured 6dB bandwidth at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;

5.5. Radiated Emissions Measurement

5.5.1. Standard Applicable

According to §15.209/ §15.205

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

For transmitters operating in the 5.725-5.85 GHz band:

All emissions shall be limited to a level of -27 dBm/MHz(68.2dBuV/m at 3m) at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz(105.2dBuV/m at 3m) at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6(110.8dBuV/m at 3m) dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz(122.2dBuV/m at 3m) at the band edge.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

5.5.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 ^m carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T kHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

5.5.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.


Premeasurement:

- The antenna is moved spherical over the EUT in different polarizations of the antenna.


Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


5.5.4. Test Setup Layout



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.6.6. Results of Radiated Emissions (9 KHz~30 MHz)

Temperature	22.2°C	Humidity	54.5%
Test Engineer	Diamond Lu	Configurations	IEEE 802.11a/n/ac

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dB)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log$ (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

5.5.7. Results of Radiated Emissions (30 MHz~1 GHz)


Test result for IEEE 802.11ac VHT80 mode

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	42.3022	35.21	-16.97	18.24	40.00	-21.76	QP
2	90.8554	37.26	-19.82	17.44	43.50	-26.06	QP
3	109.7960	37.14	-18.37	18.77	43.50	-24.73	QP
4	210.7860	40.43	-17.87	22.56	43.50	-20.94	QP
5	272.2776	44.67	-16.21	28.46	46.00	-17.54	QP
6	520.8882	28.93	-11.05	17.88	46.00	-28.12	QP

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	42.8997	36.30	-16.86	19.44	40.00	-20.56	QP
2	110.9570	35.57	-18.54	17.03	43.50	-26.47	QP
3	170.1947	43.33	-20.70	22.63	43.50	-20.87	QP
4	191.7450	44.97	-18.97	26.00	43.50	-17.50	QP
5	262.8955	38.12	-16.37	21.75	46.00	-24.25	QP
6	517.2479	28.99	-11.13	17.86	46.00	-28.14	QP

Note:

- 1). Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11ac VHT80 mode).
- 2). Emission level (dBuV/m) = 20 log Emission level (uV/m). Margin=Measured Level-Limit
- 3). Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

5.5.8. Results for Radiated Emissions (1GHz~40GHz)

IEEE 802.11a

Channel 149 / 5745 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.490	55.53	33.20	34.96	3.88	57.65	68.20	-10.55	Peak	Horizontal
11.490	42.96	33.20	34.96	3.88	45.08	54.00	-8.92	Average	Horizontal
11.490	56.07	33.20	34.96	3.88	58.19	68.20	-10.01	Peak	Vertical
11.490	41.10	33.20	34.96	3.88	43.22	54.00	-10.78	Average	Vertical
17.235	57.50	33.23	35.04	3.91	59.60	68.20	-8.60	Peak	Horizontal
17.235	43.67	33.23	35.04	3.91	45.77	54.00	-8.23	Average	Horizontal
17.235	59.66	33.23	35.04	3.91	61.76	68.20	-6.44	Peak	Vertical
17.235	41.23	33.23	35.04	3.91	43.33	54.00	-10.67	Average	Vertical

Channel 157 / 5785 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.570	59.71	33.25	35.08	3.92	61.80	68.20	-6.40	Peak	Horizontal
11.570	40.51	33.25	35.08	3.92	42.60	54.00	-11.40	Average	Horizontal
11.570	52.32	33.25	35.08	3.92	54.41	68.20	-13.79	Peak	Vertical
11.570	38.41	33.25	35.08	3.92	40.50	54.00	-13.50	Average	Vertical
17.355	57.43	33.27	35.15	3.93	59.48	68.20	-8.72	Peak	Horizontal
17.355	46.59	33.27	35.15	3.93	48.64	54.00	-5.36	Average	Horizontal
17.355	55.27	33.27	35.15	3.93	57.32	68.20	-10.88	Peak	Vertical
17.355	37.61	33.27	35.15	3.93	39.66	54.00	-14.34	Average	Vertical

Channel 163 / 5825 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.650	53.06	33.29	35.13	3.95	55.17	68.20	-13.03	Peak	Horizontal
11.650	38.12	33.29	35.13	3.95	40.23	54.00	-13.77	Average	Horizontal
11.650	53.10	33.29	35.13	3.95	55.21	68.20	-12.99	Peak	Vertical
11.650	39.62	33.29	35.13	3.95	41.73	54.00	-12.27	Average	Vertical
17.475	59.56	33.32	35.14	3.97	61.71	68.20	-6.49	Peak	Horizontal
17.475	44.16	33.32	35.14	3.97	46.31	54.00	-7.69	Average	Horizontal
17.475	60.42	33.32	35.14	3.97	62.57	68.20	-5.63	Peak	Vertical
17.475	44.60	33.32	35.14	3.97	46.75	54.00	-7.25	Average	Vertical

IEEE 802.11n HT20

Channel 149 / 5745 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.490	56.75	33.20	34.96	3.88	58.87	68.20	-9.33	Peak	Horizontal
11.490	41.48	33.20	34.96	3.88	43.60	54.00	-10.40	Average	Horizontal
11.490	54.85	33.20	34.96	3.88	56.97	68.20	-11.23	Peak	Vertical
11.490	40.03	33.20	34.96	3.88	42.15	54.00	-11.85	Average	Vertical
17.235	59.33	33.23	35.04	3.91	61.43	68.20	-6.77	Peak	Horizontal
17.235	44.82	33.23	35.04	3.91	46.92	54.00	-7.08	Average	Horizontal
17.235	60.07	33.23	35.04	3.91	62.17	68.20	-6.03	Peak	Vertical
17.235	41.79	33.23	35.04	3.91	43.89	54.00	-10.11	Average	Vertical

Channel 157 / 5785 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.570	58.77	33.25	35.08	3.92	60.86	68.20	-7.34	Peak	Horizontal
11.570	40.41	33.25	35.08	3.92	42.50	54.00	-11.50	Average	Horizontal
11.570	51.49	33.25	35.08	3.92	53.58	68.20	-14.62	Peak	Vertical
11.570	42.76	33.25	35.08	3.92	44.85	54.00	-9.15	Average	Vertical
17.355	58.52	33.27	35.15	3.93	60.57	68.20	-7.63	Peak	Horizontal
17.355	43.63	33.27	35.15	3.93	45.68	54.00	-8.32	Average	Horizontal
17.355	55.01	33.27	35.15	3.93	57.06	68.20	-11.14	Peak	Vertical
17.355	38.76	33.27	35.15	3.93	40.81	54.00	-13.19	Average	Vertical

Channel 163 / 5825 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.650	55.68	33.29	35.13	3.95	57.79	68.20	-10.41	Peak	Horizontal
11.650	41.00	33.29	35.13	3.95	43.11	54.00	-10.89	Average	Horizontal
11.650	53.05	33.29	35.13	3.95	55.16	68.20	-13.04	Peak	Vertical
11.650	42.08	33.29	35.13	3.95	44.19	54.00	-9.81	Average	Vertical
17.475	58.67	33.32	35.14	3.97	60.82	68.20	-7.38	Peak	Horizontal
17.475	46.71	33.32	35.14	3.97	48.86	54.00	-5.14	Average	Horizontal
17.475	59.34	33.32	35.14	3.97	61.49	68.20	-6.71	Peak	Vertical
17.475	45.43	33.32	35.14	3.97	47.58	54.00	-6.42	Average	Vertical

IEEE 802.11n HT40

Channel 151 / 5755 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.510	60.72	33.20	34.96	3.88	62.84	68.20	-5.36	Peak	Horizontal
11.510	37.56	33.20	34.96	3.88	39.68	54.00	-14.32	Average	Horizontal
11.510	53.14	33.20	34.96	3.88	55.26	68.20	-12.94	Peak	Vertical
11.510	41.26	33.20	34.96	3.88	43.38	54.00	-10.62	Average	Vertical
17.265	57.61	33.23	35.04	3.91	59.71	68.20	-8.49	Peak	Horizontal
17.265	39.71	33.23	35.04	3.91	41.81	54.00	-12.19	Average	Horizontal
17.265	59.26	33.23	35.04	3.91	61.36	68.20	-6.84	Peak	Vertical
17.265	38.95	33.23	35.04	3.91	41.05	54.00	-12.95	Average	Vertical

Channel 159 / 5795 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.590	54.50	33.25	35.08	3.92	56.59	68.20	-11.61	Peak	Horizontal
11.590	38.64	33.25	35.08	3.92	40.73	54.00	-13.27	Average	Horizontal
11.590	52.70	33.25	35.08	3.92	54.79	68.20	-13.41	Peak	Vertical
11.590	38.16	33.25	35.08	3.92	40.25	54.00	-13.75	Average	Vertical
17.385	56.43	33.27	35.15	3.93	58.48	68.20	-9.72	Peak	Horizontal
17.385	38.11	33.27	35.15	3.93	40.16	54.00	-13.84	Average	Horizontal
17.385	54.90	33.27	35.15	3.93	56.95	68.20	-11.25	Peak	Vertical
17.385	41.82	33.27	35.15	3.93	43.87	54.00	-10.13	Average	Vertical

IEEE 802.11ac VHT20

Channel 149 / 5745 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.490	57.52	33.20	34.96	3.88	59.64	68.20	-8.56	Peak	Horizontal
11.490	39.46	33.20	34.96	3.88	41.58	54.00	-12.42	Average	Horizontal
11.490	52.54	33.20	34.96	3.88	54.66	68.20	-13.54	Peak	Vertical
11.490	42.78	33.20	34.96	3.88	44.90	54.00	-9.10	Average	Vertical
17.235	59.00	33.23	35.04	3.91	61.10	68.20	-7.10	Peak	Horizontal
17.235	45.64	33.23	35.04	3.91	47.74	54.00	-6.26	Average	Horizontal
17.235	61.69	33.23	35.04	3.91	63.79	68.20	-4.41	Peak	Vertical
17.235	40.26	33.23	35.04	3.91	42.36	54.00	-11.64	Average	Vertical

Channel 157 / 5785 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.570	59.60	33.25	35.08	3.92	61.69	68.20	-6.51	Peak	Horizontal
11.570	42.15	33.25	35.08	3.92	44.24	54.00	-9.76	Average	Horizontal
11.570	51.29	33.25	35.08	3.92	53.38	68.20	-14.82	Peak	Vertical
11.570	39.26	33.25	35.08	3.92	41.35	54.00	-12.65	Average	Vertical
17.355	60.60	33.27	35.15	3.93	62.65	68.20	-5.55	Peak	Horizontal
17.355	46.47	33.27	35.15	3.93	48.52	54.00	-5.48	Average	Horizontal
17.355	55.52	33.27	35.15	3.93	57.57	68.20	-10.63	Peak	Vertical
17.355	40.50	33.27	35.15	3.93	42.55	54.00	-11.45	Average	Vertical

Channel 163 / 5825 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.650	56.23	33.29	35.13	3.95	58.34	68.20	-9.86	Peak	Horizontal
11.650	40.24	33.29	35.13	3.95	42.35	54.00	-11.65	Average	Horizontal
11.650	52.46	33.29	35.13	3.95	54.57	68.20	-13.63	Peak	Vertical
11.650	39.43	33.29	35.13	3.95	41.54	54.00	-12.46	Average	Vertical
17.475	61.54	33.32	35.14	3.97	63.69	68.20	-4.51	Peak	Horizontal
17.475	44.12	33.32	35.14	3.97	46.27	54.00	-7.73	Average	Horizontal
17.475	57.94	33.32	35.14	3.97	60.09	68.20	-8.11	Peak	Vertical
17.475	44.28	33.32	35.14	3.97	46.43	54.00	-7.57	Average	Vertical

IEEE 802.11ac VHT40

Channel 151 / 5755 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.510	56.86	33.20	34.96	3.88	58.98	68.20	-9.22	Peak	Horizontal
11.510	39.85	33.20	34.96	3.88	41.97	54.00	-12.03	Average	Horizontal
11.510	53.41	33.20	34.96	3.88	55.53	68.20	-12.67	Peak	Vertical
11.510	40.09	33.20	34.96	3.88	42.21	54.00	-11.79	Average	Vertical
17.265	56.97	33.23	35.04	3.91	59.07	68.20	-9.13	Peak	Horizontal
17.265	41.35	33.23	35.04	3.91	43.45	54.00	-10.55	Average	Horizontal
17.265	60.07	33.23	35.04	3.91	62.17	68.20	-6.03	Peak	Vertical
17.265	41.42	33.23	35.04	3.91	43.52	54.00	-10.48	Average	Vertical

Channel 159 / 5795 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.590	57.86	33.25	35.08	3.92	59.95	68.20	-8.25	Peak	Horizontal
11.590	38.89	33.25	35.08	3.92	40.98	54.00	-13.02	Average	Horizontal
11.590	52.32	33.25	35.08	3.92	54.41	68.20	-13.79	Peak	Vertical
11.590	40.17	33.25	35.08	3.92	42.26	54.00	-11.74	Average	Vertical
17.385	53.92	33.27	35.15	3.93	55.97	68.20	-12.23	Peak	Horizontal
17.385	36.46	33.27	35.15	3.93	38.51	54.00	-15.49	Average	Horizontal
17.385	51.22	33.27	35.15	3.93	53.27	68.20	-14.93	Peak	Vertical
17.385	40.33	33.27	35.15	3.93	42.38	54.00	-11.62	Average	Vertical

IEEE 802.11ac VHT80

Channel 155 / 5775 MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.550	56.50	33.22	35.00	3.90	58.62	68.20	-9.58	Peak	Horizontal
11.550	39.45	33.22	35.00	3.90	41.57	54.00	-12.43	Average	Horizontal
11.550	51.37	33.22	35.00	3.90	53.49	68.20	-14.71	Peak	Vertical
11.550	43.25	33.22	35.00	3.90	45.37	54.00	-8.63	Average	Vertical
17.325	56.91	33.25	35.82	3.92	58.26	68.20	-9.94	Peak	Horizontal
17.325	40.69	33.25	35.82	3.92	42.04	54.00	-11.96	Average	Horizontal
17.325	50.63	33.25	35.82	3.92	51.98	68.20	-16.22	Peak	Vertical
17.325	42.18	33.25	35.82	3.92	43.53	54.00	-10.47	Average	Vertical

Notes:

- 1). Measuring frequencies from 9 KHz ~ 40 GHz, No emission found between lowest internal used/generated frequency to 30MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz ~ 40 GHz were made with an instrument using Peak detector mode.
- 3). 18~40GHz at least have 20dB margin. No recording in the test report.
- 4). Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;
- 5). Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 6). Margin=Reading Level+Ant Fac+Cab Loss-Pre Fac-Limit

5.6. Power Line Conducted Emissions


5.6.1 Standard Applicable

According to §15.207(a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency

5.6.2 Block Diagram of Test Setup



5.6.3 Test Results


PASS.

Please refer to the following page.

Temperature	24.5°C	Humidity	54.4%
Test Engineer	Diamond Lu	Configurations	IEEE 802.11a/n/ac


AC Conducted Emission of charge from power adapter mode @ AC 120V/60Hz (worst case)

Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1500	38.99	19.14	58.13	66.00	-7.87	QP	
2		0.1500	8.86	19.14	28.00	56.00	-28.00	AVG	
3		0.9825	27.93	19.27	47.20	56.00	-8.80	QP	
4		1.0275	11.04	19.26	30.30	46.00	-15.70	AVG	
5		1.4415	25.61	19.33	44.94	56.00	-11.06	QP	
6		1.4730	13.65	19.34	32.99	46.00	-13.01	AVG	
7		2.8770	24.71	19.46	44.17	56.00	-11.83	QP	
8		2.9400	13.19	19.47	32.66	46.00	-13.34	AVG	
9		8.1465	27.41	19.64	47.05	60.00	-12.95	QP	
10		8.3354	12.84	19.65	32.49	50.00	-17.51	AVG	
11		12.8445	30.77	19.95	50.72	60.00	-9.28	QP	
12		13.3845	18.51	19.98	38.49	50.00	-11.51	AVG	

Neutral



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1500	26.85	19.14	45.99	66.00	-20.01	QP	
2	0.1532	-13.18	19.14	5.96	55.82	-49.86	AVG	
3 *	0.9734	28.17	19.27	47.44	56.00	-8.56	QP	
4	1.0048	14.00	19.25	33.25	46.00	-12.75	AVG	
5	1.4189	19.70	19.32	39.02	56.00	-16.98	QP	
6	1.4774	7.36	19.33	26.69	46.00	-19.31	AVG	
7	8.2365	22.14	19.63	41.77	60.00	-18.23	QP	
8	8.4975	6.21	19.64	25.85	50.00	-24.15	AVG	
9	13.0649	27.23	19.98	47.21	60.00	-12.79	QP	
10	13.4160	12.16	20.00	32.16	50.00	-17.84	AVG	
11	16.3905	4.03	20.17	24.20	60.00	-35.80	QP	
12	16.7055	-10.90	20.15	9.25	50.00	-40.75	AVG	

***Note: Pre-scan all modes and recorded the worst case results in this report. Margin=Measure Level-Limit


5.7 Undesirable Emissions Measurement

5.7.1 Limit

According to §15.407 (b) Undesirable emission limits. Except as shown in paragraph (b) (7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (a) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (b) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (c) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (d) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (e) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (f) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.
- (g) The provisions of §15.205 apply to intentional radiators operating under this section.
- (h) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

5.8.2 Test Configuration



5.7.3 Test Procedure

1. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
2. Set the RBW = 1MHz.
3. Set the VBW \geq 3MHz
4. Number of points in sweep $\geq 2 \times$ span / RBW. (This ensures that bin-to-bin spacing is \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
5. Manually set sweep time $\geq 10 \times$ (number of points in sweep) \times (total on/off period of the transmitted signal).
6. Set detector = power averaging (rms).
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.

5.7.4 Test Results

PASS.

Please refer to Appendix F.5.

Remark:

1. Measured unwanted emission at difference data rate for each mode and recorded worst case for each mode;
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11a VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;
4. $E.I.R.P = \text{Conducted power} + \text{Antenna Gain}$;
5. EIRP calculation. A value representative of an upper bound on out-of-band antenna gain (in dBi) shall be added to the measured antenna-port conducted emission power to compute EIRP within the specified measurement bandwidth. (For emissions in the restricted bands, additional calculations are required to convert EIRP to field strength at the specified distance.) The upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands or 2 dBi, whichever is greater.³ However, for devices that operate in multiple bands using the same transmit antenna, the highest gain of the antenna within the operating band nearest to the out-of-band frequency being measured may be used in lieu of the overall highest gain when measuring emissions at frequencies within 20% of the absolute frequency at the nearest edge of that band, but in no case shall a value less than 2 dBi be selected;

5.8. Frequency Stability


5.8.1 Standard Applicable

According to FCC §15.407(g) “Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.”

According to FCC §2.1055(a) “The frequency stability shall be measured with variation of ambient temperature as follows:”

- (1) From -30° to $+50^{\circ}$ centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.
- (2) From -20° to $+50^{\circ}$ centigrade for equipment to be licensed for use in the Maritime Services under part 80 of this chapter, except for Class A, B, and S Emergency Position Indicating Radiobeacons (EPIRBS), and equipment to be licensed for use above 952 MHz at operational fixed stations in all services, stations in the Local Television Transmission Service and Point-to-Point Microwave Radio Service under part 21 of this chapter, equipment licensed for use aboard aircraft in the Aviation Services under part 87 of this chapter, and equipment authorized for use in the Family Radio Service under part 95 of this chapter.
- (3) From 0° to $+50^{\circ}$ centigrade for equipment to be licensed for use in the Radio Broadcast Services under part 73 of this chapter.

5.8.2 Test Configuration



5.8.3 Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20 degree operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30 degree. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10 degree increased per stage until the highest temperature of +50 degree reached.

5.8.4 Test Results

PASS

Remark: Measured all conditions and recorded worst case.

IEEE 802.11a Mode / 5745 – 5825 MHz / 5745 MHz

Environment Temperature (Degree)	Voltage (Vdc)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	3.40	5744.982700	5725 – 5850	PASS
20	4.35	5744.975901	5725 – 5850	PASS
50	3.80	5744.999153	5725 – 5850	PASS
40	3.80	5744.896004	5725 – 5850	PASS
30	3.80	5744.901857	5725 – 5850	PASS
20	3.80	5744.857023	5725 – 5850	PASS
10	3.80	5745.026037	5725 – 5850	PASS
5	3.80	5744.913030	5725 – 5850	PASS
0	3.80	5744.864146	5725 – 5850	PASS
-5	3.80	5744.896486	5725 – 5850	PASS
-10	3.80	5744.957582	5725 – 5850	PASS

5.9. Antenna Requirements

5.9.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.9.2 Antenna Connected Construction

5.9.2.1. Standard Applicable

According to § 15.203 & RSS-Gen, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.9.2.2. Antenna Connector Construction

The gains of antenna used for transmitting is 1dBi (Max.), and the antenna is FPC Antenna which no consideration of replacement. Please see EUT photo for details.

5.9.2.3. Results: Compliance.

6. LIST OF MEASURING EQUIPMENTS

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Power Meter	R&S	NRVS	100444	2019-06-11	2020-06-10
2	Power Sensor	R&S	NRV-Z81	100458	2019-06-11	2020-06-10
3	Power Sensor	R&S	NRV-Z32	10057	2019-06-11	2020-06-10
4	Test Software	Tonscend	JS1120-2	/	N/A	N/A
5	RF Control Unit	Tonscend	JS0806-2	N/A	2019-06-11	2020-06-10
6	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2019-06-11	2020-06-10
7	DC Power Supply	Agilent	E3642A	N/A	2019-11-15	2020-11-16
8	EMI Test Software	AUDIX	E3	/	N/A	N/A
9	3m Fully Anechoic Chamber	MRDIANZI	FAC-3M	MR009	2019-09-27	2020-09-26
10	Positioning Controller	MF	MF-7082	N/A	2019-06-12	2020-06-11
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2019-07-26	2020-07-26
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2019-07-26	2020-07-26
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2019-07-01	2020-06-30
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2019-09-20	2020-09-21
15	Broadband Preamplifier	SCHWARZBECK	BBV 9719	9719-025	2019-09-20	2020-09-21
16	EMI Test Receiver	R&S	ESR 7	101181	2019-06-12	2020-06-11
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2019-11-15	2020-11-16
18	Broadband Preamplifier	phx	BP-01M18G	P190501	2019-07-01	2020-06-30
19	RF Cable-R03m	Jye Bao	RG142	CB021	2019-06-12	2020-06-11
20	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2019-06-12	2020-06-11
21	6dB Attenuator	/	100W/6dB	1172040	2019-06-11	2020-06-10
22	3dB Attenuator	/	2N-3dB	/	2019-06-11	2020-06-10
23	EMI Test Receiver	R&S	ESPI	101840	2019-06-11	2020-06-10
24	Artificial Mains	R&S	ENV216	101288	2019-06-12	2020-06-11
25	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2019-06-11	2020-06-10
26	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2019-09-19	2020-09-18

Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.

7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----