

**Label: paster**

**Size: 11\*2.5cm**

**Material: silver paper**

**LED Retrofit trim**

Model No: D826-B

INPUT: 120VAC0.13A 60Hz

POWER: 15W CRI>90

Date code:XXYY

LUMENS: 1000 LMSCCT:2700-5000K

Taizhou Jiao Guang Lighting Co.,Ltd

CONFORMS TO UL STD. 1598C

CERTIFIED TO CSA STD. C22.2 NO. 250.1

**CAUTION:**

SUITABLE FOR WET LOCATIONS

CONVIENT AUX EMPLACEMENTS MOUILLÉS

SUITABLE FOR TYPE IC or SUITABLE FOR

TYEP NON-IC

APPROPRIÉ POUR LE TYPE IC OU APPROPRIÉ

POUR LE TYPE NON-IC"

USE ONLY IN OPEN LUMINAIRES

UTILISER UNIQUEMENT DANS L'OUVERTURE

DES LUMINAIRES

MIN LAMP COMPARTMENT 6 in. DIAMETER

and 8 in. DEPTH

LA CHAMBRE DE LAMPE MINIMALE DE

6 POUCES DE DIAMÈTRE ET MIN 8 POUCES

DE PROFONDEUR

THIS LUMINAIRE HAS BEEN MODIFIED AND

CAN NO LONGER OPERATE THE ORIGINALLY

INTENDED LAMP

CE LUMINAIRE A ÉTÉ MODIFIÉ ET NE PEUT

PAS FONCTIONNER LA LAMPE

**FCC ID: 2AQ7X-DZTE**

This device complies with part 15 of the FCC

Rules. Operation is subject to the following two

conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

ETL CLASSIFIED



Intertek  
4008281