

FCC CFR47 PART 24E, 27 CERTIFICATION TEST REPORT FCC ID:2AQ8SCHAPERONT300

Product: Mobile Phone
Trade Mark: Easyfone
Model Number: Chaperon-T300
Family Model: N/A
Report No.: STR220517001004E
Issue Date: Jun 28. 2022

Prepared for

Shen Zhen Yixun Electronic Technology Co., Ltd.
14D, HuaqiaoXinyuan, WanzhongCity, Xinniu Community, Minzhi St.,
Longhua Dist., Shenzhen, Guangdong, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen 518126 P.R. China
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090
Website:<http://www.ntek.org.cn>


TEST RESULT CERTIFICATION

Applicant's name	Shen Zhen Yixun Electronic Technology Co., Ltd.
Address.....	14D, HuaqiaoXinyuan, WanzhongCity, Xinniu Community, Minzhi St., Longhua Dist., Shenzhen, Guangdong, China
Manufacturer's Name	Shen Zhen Yixun Electronic Technology Co., Ltd.
Address.....	14D, HuaqiaoXinyuan, WanzhongCity, Xinniu Community, Minzhi St., Longhua Dist., Shenzhen, Guangdong, China
Product name.....	Mobile Phone
Model and/or type reference ..	Chaperon-T300
Family Model:	N/A
Standards	FCC CFR 47 Part 24E, Part 27
Test procedure	ANSI C63.26:2015 ANSI/TIA-603-E-2016

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test	
Date (s) of performance of tests.....	May 20. 2022 ~ Jun 28. 2022
Date of Issue	Jun 28. 2022
Test Result	Pass

Testing Engineer : 
(Mukzi Lee)


Authorized Signatory : 
(Alex Li)

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	5
1.1 PRODUCT DESCRIPTION.....	5
1.2 RELATED SUBMITTAL(S) / GRANT (S)	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	6
MEASUREMENT UNCERTAINTY	6
1.5 SPECIAL ACCESSORIES.....	6
1.6 WORST-CASE CONFIGURATION AND MODE.....	6
1.6 SUMMARY OF TEST RESULTS	7
2. SYSTEM TEST CONFIGURATION	8
2.1 EUT CONFIGURATION.....	8
2.2 EUT EXERCISE	8
2.3 CONFIGURATION OF EUT SYSTEM.....	8
2.4 TEST SETUP	9
3.TEST AND MEASUREMENT EQUIPMENT.....	10
4. OUTPUT POWER.....	12
4.1 OUTPUT POWER MEASUREMENT	12
6. BANDEDGE AND EMISSION MASK.....	15
7. OUT OF BAND EMISSIONS	16
7.1 MEASUREMENT METHOD	17
8. RADIATED MEASUREMENT	18
8.1. RADIATED POWER (ERP & EIRP).....	18
8.2 LTE BAND 2.....	19
8.3 LTE BAND 4.....	23
9. SPURIOUS RADIATION EMISSION	27

9.1 LTE BAND 2..... 29

9.2 LTE BAND 4..... 31

10. FREQUENCY STABILITY33

10.1 LTE BAND 2 34

10.2 LTE BAND 4 36

11. PEAK-TO-AVERAGE RATIO.....38

11.1 Description of the PAR Measurement 38

11.2 Measuring Instruments 38

11.3 Test Procedures..... 38

11.4 Test Setup..... 38

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

Product Designation:	Mobile Phone
Trade Mark	Easyfone
Model Name	Chaperon-T300
Family Model	N/A
Model Difference	N/A
FCC ID:	2AQ8SCHAPERONT300
Frequency Bands:	U.S. Bands: <input checked="" type="checkbox"/> LTE FDD Band 2, 4
Frequency Range:	LTE FDD Band 2 Uplink: 1850MHz-1910MHz, Downlink: 1930MHz-1990MHz; LTE FDD Band 4 Uplink: 1710MHz-1755MHz, Downlink: 2110MHz-2155MHz;
Type of Modulation:	QPSK/16QAM
Power Class	Class 3
Antenna:	PIFA Antenna
Antenna gain:	0.7dBi
Adapter	Model: ES007-U050055XOF Input: AC 100-240V~50/60Hz 0.3A Output: DC 5.0V $\overline{\text{---}}$ 0.55A
Battery	DC 3.7V, 1500mAh, 5.55Wh
Rating	DC 3.7V from battery or DC 5V from Adapter.
Extreme Vol. Limits:	DC 3.2V to DC 4.3V (Nominal DC 3.7V) (Note 1)
HW Version	GS052 V1.0
SW Version	GS052-Easyfone-Prime-A1-4G-20211117-LC-V1.07
** Note1: The High Voltage 4.3V and Low Voltage 3.2V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage.	

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AQ8SCHAPERONT300** filing to comply with the FCC Part 24E &27.

1.3 TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI/TIA-603-E-2016, FCC CFR 47 Part 2, Part 24, Part 27, ANSI C63.26:2015.

1.4 TEST FACILITY

The test site used to collect the radiated data is located at:

ShenZhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R.China.

The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.26:2015& ANSI C63.4: 2014.

FCC Registration No.:463705

IC Registration No.:9270A-1,

CNAS Registration No.:L5516

MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5dB
2	Conducted Emission Test	± 1.38 dB
3	RF power, conducted	± 0.16 dB
4	Spurious emissions, conducted	± 0.21 dB
5	All emissions, radiated(<1G)	± 4.68 dB
6	All emissions, radiated(>1G)	± 4.89 dB
7	Temperature	± 0.5 °C
8	Humidity	± 2 %
9	Frequency error, conducted	± 0.19 ppm

1.5 SPECIAL ACCESSORIES

The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

1.6 WORST-CASE CONFIGURATION AND MODE

The worst-case scenario for all measurements is based on the investigation results.

The device has LTE Bands of: Band 2, Band 4

The RB Size was selected to measure for peak or average ERP and EIRP, which was based on the conducted power verification baseline data.

For the fundamental investigation of radiated emissions, the EUT is investigated for vertical and horizontal antenna orientations and X Y and Z orientations of the EUT alone. After the investigations

the worst case was determined to be at X orientation for all LTE bands.

1.6 SUMMARY OF TEST RESULTS

FCC Part24, Subpart E, FCC Part27, Subpart L, KDB 971168 D01 Power Meas License Digital Systems v03			
FCC Rule	Test Item	Verdict	Remark
2.1046	Conducted Output Power	PASS	
24.232(d) 27.50(d)(5) KDB 971168 D01 Clause 5.7	Peak-to-Average Ratio	PASS	
2.1049 24.238(b) KDB 971168 D01 Clause 4.2	Occupied Bandwidth	PASS	
2.1051 24.238(a) 27.53(c), (g), (h) KDB 971168 D01 Clause 6	Band Edge	PASS	
27.50(b)(10), (c)(10) KDB 971168 D01 Clause 5.6	Effective Radiated Power	PASS	
24.232(c) 27.50(h)(2), (d)(4) KDB 971168 D01 Clause 5.6	Equivalent Isotropic Radiated Power	PASS	
2.1053 24.238(a) 27.53(c)(g)(h)(m) KDB 971168 D01 Clause 7	Field Strength of Spurious Radiation	PASS	
2.1055 24.235 27.54 KDB 971168 D01 Clause 9	Frequency Stability for Temperature & Voltage	PASS	
2.1051 24.238(a) 27.53(c)(g)(h)(m) KDB 971168 D01 Clause 6	Conducted Emission	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.
3. No modifications are made to the EUT during all test items.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

2.3 CONFIGURATION OF EUT SYSTEM

Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	Mobile Phone	Chaperon-T300	FCC ID: 2AQ8SCHAPERONT300	EUT


*Note: All the accessories have been used during the test.
the following "EUT" in setup diagram means EUT system.*

2.4 TEST SETUP


For Radiated Test Cases




For Conducted Output Power



For Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band edge and Conducted Spurious Emission



For Frequency Stability



Note: EUT built-in battery-powered, the battery is fully-charged.

3. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	MXA Signal Analyzer	Agilent	N9020A	MY49100060	2022.04.01	2023.03.31	1 year
2	Test Receiver	R&S	ESPI	101318	2022.04.06	2023.04.05	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2022.03.30	2023.03.29	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
5	Horn Antenna	EM	EM-AH-10180	2011071402	2022.03.31	2023.03.30	3 year
6	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2022.04.06	2023.04.05	1 year
7	Amplifier	EM	EM-30180	060538	2021.07.01	2022.06.30	1 year
8	Loop Antenna	ARA	PLA-1030/B	1029	2022.03.30	2023.03.29	1 year
9	Power Meter	R&S	NRVS	100696	2021.07.01	2022.06.30	1 year
10	Power Sensor	R&S	URV5-Z4	0395.1619.05	2022.04.06	2023.04.05	1 year
11	Test Cable	N/A	R-01	N/A	2019.08.06	2022.08.05	3 year
12	Test Cable	N/A	R-02	N/A	2019.08.06	2022.08.05	3 year
13	Test Cable	N/A	R-03	N/A	2019.08.06	2022.08.05	3 year
14	Test Receiver	R&S	ESCI	101160	2022.04.06	2023.04.05	1 year
15	LISN	R&S	ENV216	101313	2022.04.06	2023.04.05	1 year
16	LISN	EMCO	3816/2	00042990	2022.04.06	2023.04.05	1 year
17	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2022.04.06	2023.04.05	1 year
18	Passive Voltage Probe	R&S	ESH2-Z3	100196	2020.05.11	2023.05.10	3 year
19	Test Cable	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
20	Test Cable	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
21	Test Cable	N/A	C03	N/A	2020.05.11	2023.05.10	3 year
22	Spectrum Analyzer	agilent	e4440a	us44300399	2022.04.01	2023.03.31	1 year
23	test receiver	R&S	ESCI	a0304218	2022.04.06	2023.04.05	1 year
24	Communication Tester	R&S	CMU200	A0304247	2022.04.06	2023.04.05	1 year
25	Thermal Chamber	Ten Billion	TTC-B3C	TBN-960502	2022.04.06	2023.04.05	1 year

26	DC Power Source	N/A	PS-6005D	2017040292 3	2020.05.11	2023.05.10	3 year
----	-----------------	-----	----------	-----------------	------------	------------	--------

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& DC Power Source which is scheduled for calibration every 3 years.

4. OUTPUT POWER

4.1 OUTPUT POWER MEASUREMENT

LTE Measurement Procedure:

All LTE bands conducted power peak and average are obtained from the CMW500 telecommunication test set. The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".3

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
				Table 6.2.4-3	
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

Test data reference attachment.

5. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049

LIMITS

For reporting purposes only

TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The -26dB bandwidth was also measured and recorded.

MODES TESTED

- LTE Band 2
- LTE Band 4

RESULTS

PASS

Test data reference attachment.

6. BANDEDGE AND EMISSION MASK

RULE PART(S)

FCC: §2.1051, §24.238(a), §27.53(c)(g)(h)(m)

FCC: §2.1046, §24.232

LIMITS

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P[\text{Watts}])$, where P is the transmitter power in Watts.

The minimum permissible attenuation level for Band 7 is as following.

Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

Per 27.53(c.5) for operations in the 776-788 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

For all plots showing emissions in the 763 – 775MHz and 793 – 805MHz band, the FCC limit per 27.53(c.4) is $65 + 10\log_{10}(P) = -35\text{dBm}$ in a 6.25kHz bandwidth.

Per 27.53(m) for operations in the BRS/EBS bands, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth.

TEST PROCEDURE

The transmitter output was connected to a CMW500Test Set and configured to operate at maximum power. The band edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer.

For each band edge measurement:

Set the spectrum analyzer span to include the block edge frequency

Set a marker to point the corresponding band edge frequency in each test case.

Set display line

Set resolution bandwidth to at least 1% of emission bandwidth.

MODES TESTED

- LTE Band 2/4

RESULTS

Test data reference attachment.

7. OUT OF BAND EMISSIONS

RULE PART(S)

FCC: §2.1051, §24.238(a), §27.53(c)(g)(h)(m)

LIMITS

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P[\text{Watts}])$, where P is the transmitter power in Watts.

The minimum permissible attenuation level for Band 7 is as following.

Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

Per 27.53(c.5) for operations in the 776-788 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

For all plots showing emissions in the 763 – 775MHz and 793 – 805MHz band, the FCC limit per 27.53(c.4) is $65 + 10\log_{10}(P) = -35\text{dBm}$ in a 6.25kHz bandwidth.

Per 27.53(m) for operations in the BRS/EBS bands, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth.

TEST PROCEDURE

The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band Emissions, if any, up to 10th harmonic. Multiple sweeps were recorded in maximum hold mode using a peak detector to ensure that the worst-case emissions were caught.

For each out of band emissions measurement:

- Set display line
- Set RBW & VBW to 100 kHz for the measurement below 1 GHz, and 1 MHz for the measurement above 1 GHz.

MODES TESTED

- LTE Band2
- LTE Band 4

7.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

Test data reference attachment.

Note: For LTE band 2/4, the frequency range above the 5th harmonic, the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

8. RADIATED MEASUREMENT

8.1. RADIATED POWER (ERP & EIRP)

RULE PART(S)

FCC: §2.1046, §24.232(c) and §27.50 (h)(2), (b)(10), (c)(10), (d)(4)

LIMITS:

22.913(a) (2)- The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.
24.232 (c) Mobile and portable stations are limited to 2 watts EIRP.
27.50 (c) (10) the following power and antenna height requirements apply to stations transmitting in the 698–746 MHz band, the portable stations (hand-held devices) are limited to 3 watts ERP.
27.50 (b)(10) Portable stations (hand-held devices) transmitting in the 746–757 MHz, 758–763 MHz, 776–793 MHz, and 805–806 MHz bands are limited to 3 watts ERP.
27.50 (d)(4) The following power and antenna height requirements apply to stations transmitting in the 1710–1755 MHz and 2110–2155 MHz bands: Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.
27.50 (h)(2) Mobile and other user stations in the 2500–2570 MHz and 2620–2690 MHz bands. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

TEST PROCEDURE

ANSI/TIA-603-E Clause 2.2.17

KDB 971168 v02r01 RF power output using broadband peak and average power meter method.

KDB 971168 D01 Power Meas License Digital Systems v02r01, “Measurement Guidance for Certification of Licensed Digital Transmitters”

MODES TESTED

- LTE Band2
- LTE Band 4

RESULTS

Pass

8.2 LTE BAND 2

Radiated Power (EIRP) for Band 2									
Mode	RB/RB SIZE	Frequency	Result					Polarization Of Max. ERP	Conclusion
			SG Level (dBm)	Cable Loss (dBm)	Antenna Gain (dB)	Max. EIRP Average (dBm)	Max. EIRP		
							Average (mW)		
1.4MHz Band QPSK	1/#Mid	1850.7	-2.11	3.76	28.24	22.37	172.584	Horizontal	Pass
		1880	-1.82	3.91	28.22	22.49	177.419	Horizontal	Pass
		1909.3	-1.77	3.93	28.20	22.50	177.828	Horizontal	Pass
3.0MHz Band QPSK	1/#Mid	1851.5	-1.97	3.77	28.23	22.49	177.419	Horizontal	Pass
		1880	-1.90	3.91	28.24	22.43	174.985	Horizontal	Pass
		1908.5	-1.87	3.94	28.25	22.44	175.388	Horizontal	Pass
5.0MHz Band QPSK	1/#Mid	1852.5	-2.21	3.77	28.31	22.33	171.002	Horizontal	Pass
		1880	-1.96	3.91	28.22	22.35	171.791	Horizontal	Pass
		1907.5	-1.83	3.94	28.20	22.43	174.985	Horizontal	Pass
10.0MHz Band QPSK	1/#Mid	1855	-2.08	3.79	28.33	22.46	176.198	Horizontal	Pass
		1880	-1.82	3.95	28.22	22.45	175.792	Horizontal	Pass
		1905	-1.81	3.97	28.19	22.41	174.181	Horizontal	Pass
15.0MHz Band QPSK	1/#Mid	1857.5	-2.18	3.79	28.34	22.37	172.584	Horizontal	Pass
		1880	-1.84	3.95	28.22	22.43	174.985	Horizontal	Pass
		1902.5	-1.75	3.97	28.18	22.46	176.198	Horizontal	Pass
20.0MHz Band QPSK	1/#Mid	1860	-2.06	3.81	28.35	22.48	177.011	Horizontal	Pass
		1880	-1.81	3.96	28.22	22.45	175.792	Horizontal	Pass
		1900	-1.68	4.00	28.16	22.48	177.011	Horizontal	Pass
1.4MHz Band QPSK	1/#Mid	1850.7	-2.08	3.76	28.24	22.40	173.780	Vertical	Pass
		1880	-1.86	3.91	28.22	22.45	175.792	Vertical	Pass
		1909.3	-1.79	3.93	28.20	22.48	177.011	Vertical	Pass
3.0MHz Band QPSK	1/#Mid	1851.5	-2.05	3.77	28.23	22.41	174.181	Vertical	Pass
		1880	-1.88	3.91	28.24	22.45	175.792	Vertical	Pass
		1908.5	-1.91	3.94	28.25	22.40	173.780	Vertical	Pass
5.0MHz Band QPSK	1/#Mid	1852.5	-2.06	3.77	28.31	22.48	177.011	Vertical	Pass
		1880	-1.99	3.91	28.22	22.32	170.608	Vertical	Pass
		1907.5	-1.79	3.94	28.20	22.47	176.604	Vertical	Pass
10.0MHz Band QPSK	1/#Mid	1855	-2.13	3.79	28.33	22.41	174.181	Vertical	Pass
		1880	-1.91	3.95	28.22	22.36	172.187	Vertical	Pass
		1905	-1.78	3.97	28.19	22.44	175.388	Vertical	Pass
15.0MHz Band	1/#Mid	1857.5	-2.07	3.79	28.34	22.48	177.011	Vertical	Pass
		1880	-1.92	3.95	28.22	22.35	171.791	Vertical	Pass

QPSK		1902.5	-1.71	3.97	28.18	22.50	177.828	Vertical	Pass
20.0MHz	1/#Mid	1860	-2.03	3.81	28.35	22.51	178.238	Vertical	Pass
Band		1880	-1.73	3.96	28.22	22.53	179.061	Vertical	Pass
QPSK		1900	-1.61	4.00	28.16	22.55	179.887	Vertical	Pass

Note:

SG Level= Signal generator output

Max. EIRP Average (dBm)= Antenna Gain(dB)+ SG Level (dBm)- Cable Loss(dBm)

Radiated Power (EIRP) for Band 2									
Mode	RB/RB SIZE	Frequency	Result					Polarization Of Max. ERP	Conclusion
			SG Level (dBm)	Cable Loss (dBm)	Antenna Gain (dB)	Max. EIRP Average (dBm)	Max. EIRP		
							Average (mW)		
1.4MHz Band 16 QAM	1/#Mid	1850.7	-2.70	3.76	28.24	21.78	150.661	Horizontal	Pass
		1880	-2.51	3.91	28.22	21.80	151.356	Horizontal	Pass
		1909.3	-2.51	3.93	28.20	21.76	149.968	Horizontal	Pass
3.0MHz Band 16 QAM	1/#Mid	1851.5	-2.70	3.77	28.23	21.76	149.968	Horizontal	Pass
		1880	-2.47	3.91	28.24	21.86	153.462	Horizontal	Pass
		1908.5	-2.54	3.94	28.25	21.77	150.314	Horizontal	Pass
5.0MHz Band 16 QAM	1/#Mid	1852.5	-2.75	3.77	28.31	21.79	151.008	Horizontal	Pass
		1880	-2.50	3.91	28.22	21.81	151.705	Horizontal	Pass
		1907.5	-2.43	3.94	28.20	21.83	152.405	Horizontal	Pass
10.0MHz Band 16 QAM	1/#Mid	1855	-2.76	3.79	28.33	21.78	150.661	Horizontal	Pass
		1880	-2.46	3.95	28.22	21.81	151.705	Horizontal	Pass
		1905	-2.37	3.97	28.19	21.85	153.109	Horizontal	Pass
15.0MHz Band 16 QAM	1/#Mid	1857.5	-2.80	3.79	28.34	21.75	149.624	Horizontal	Pass
		1880	-2.50	3.95	28.22	21.77	150.314	Horizontal	Pass
		1902.5	-2.36	3.97	28.18	21.85	153.109	Horizontal	Pass
20.0MHz Band 16 QAM	1/#Mid	1860	-2.66	3.81	28.35	21.88	154.170	Horizontal	Pass
		1880	-2.48	3.96	28.22	21.78	150.661	Horizontal	Pass
		1900	-2.30	4.00	28.16	21.86	153.462	Horizontal	Pass
1.4MHz Band 16 QAM	1/#Mid	1850.7	-2.61	3.76	28.24	21.87	153.815	Vertical	Pass
		1880	-2.56	3.91	28.22	21.75	149.624	Vertical	Pass
		1909.3	-2.46	3.93	28.20	21.81	151.705	Vertical	Pass
3.0MHz Band 16 QAM	1/#Mid	1851.5	-2.64	3.77	28.23	21.82	152.055	Vertical	Pass
		1880	-2.47	3.91	28.24	21.86	153.462	Vertical	Pass
		1908.5	-2.50	3.94	28.25	21.81	151.705	Vertical	Pass
5.0MHz Band 16 QAM	1/#Mid	1852.5	-2.68	3.77	28.31	21.86	153.462	Vertical	Pass
		1880	-2.56	3.91	28.22	21.75	149.624	Vertical	Pass
		1907.5	-2.36	3.94	28.20	21.90	154.882	Vertical	Pass
10.0MHz Band 16 QAM	1/#Mid	1855	-2.69	3.79	28.33	21.85	153.109	Vertical	Pass
		1880	-2.42	3.95	28.22	21.85	153.109	Vertical	Pass
		1905	-2.46	3.97	28.19	21.76	149.968	Vertical	Pass
15.0MHz Band 16	1/#Mid	1857.5	-2.70	3.79	28.34	21.85	153.109	Vertical	Pass
		1880	-2.41	3.95	28.22	21.86	153.462	Vertical	Pass

QAM		1902.5	-2.31	3.97	28.18	21.90	154.882	Vertical	Pass
20.0MHz	1/#Mid	1860	-2.62	3.81	28.35	21.92	155.597	Vertical	Pass
Band 16		1880	-2.33	3.96	28.22	21.93	155.955	Vertical	Pass
QAM		1900	-2.23	4.00	28.16	21.93	155.955	Vertical	Pass

Note:

SG Level= Signal generator output

Max. EIRP Average (dBm)= Antenna Gain(dB)+ SG Level (dBm)- Cable Loss(dBm)

8.3 LTE BAND 4

Radiated Power (EIRP) for Band 4									
Mode	RB/RB SIZE	Frequency	Result					Polarization Of Max. ERP	Conclusion
			SG Level (dBm)	Cable Loss (dBm)	Antenna Gain (dB)	Max. EIRP	Max. EIRP		
						Average (dBm)	Average (mW)		
1.4MHz Band QPSK	1/#Mid	1710.7	-3.28	3.12	27.58	21.18	131.220	Horizontal	Pass
		1732.5	-3.22	3.27	27.61	21.12	129.420	Horizontal	Pass
		1754.3	-3.27	3.29	27.63	21.07	127.938	Horizontal	Pass
3.0MHz Band QPSK	1/#Mid	1711.5	-3.39	3.13	27.61	21.09	128.529	Horizontal	Pass
		1732.5	-3.24	3.27	27.61	21.10	128.825	Horizontal	Pass
		1753.5	-3.20	3.30	27.62	21.12	129.420	Horizontal	Pass
5.0MHz Band QPSK	1/#Mid	1712.5	-3.39	3.13	27.63	21.11	129.122	Horizontal	Pass
		1732.5	-3.23	3.27	27.61	21.11	129.122	Horizontal	Pass
		1752.5	-3.24	3.30	27.60	21.06	127.644	Horizontal	Pass
10.0MHz Band QPSK	1/#Mid	1715	-3.37	3.15	27.64	21.12	129.420	Horizontal	Pass
		1732.5	-3.10	3.31	27.61	21.20	131.826	Horizontal	Pass
		1750	-3.13	3.33	27.59	21.13	129.718	Horizontal	Pass
15.0MHz Band QPSK	1/#Mid	1717.5	-3.44	3.15	27.65	21.06	127.644	Horizontal	Pass
		1732.5	-3.23	3.31	27.61	21.07	127.938	Horizontal	Pass
		1747.5	-3.14	3.33	27.57	21.10	128.825	Horizontal	Pass
20.0MHz Band QPSK	1/#Mid	1720	-3.40	3.17	27.66	21.09	128.529	Horizontal	Pass
		1732.5	-3.10	3.32	27.61	21.19	131.522	Horizontal	Pass
		1745	-3.06	3.36	27.56	21.14	130.017	Horizontal	Pass
1.4MHz Band QPSK	1/#Mid	1710.7	-3.37	3.12	27.58	21.09	128.529	Vertical	Pass
		1732.5	-3.28	3.27	27.61	21.06	127.644	Vertical	Pass
		1754.3	-3.24	3.29	27.63	21.10	128.825	Vertical	Pass
3.0MHz Band QPSK	1/#Mid	1711.5	-3.38	3.13	27.61	21.10	128.825	Vertical	Pass
		1732.5	-3.21	3.27	27.61	21.13	129.718	Vertical	Pass
		1753.5	-3.20	3.30	27.62	21.12	129.420	Vertical	Pass
5.0MHz Band QPSK	1/#Mid	1712.5	-3.38	3.13	27.63	21.12	129.420	Vertical	Pass
		1732.5	-3.14	3.27	27.61	21.20	131.826	Vertical	Pass
		1752.5	-3.13	3.30	27.60	21.17	130.918	Vertical	Pass
10.0MHz Band QPSK	1/#Mid	1715	-3.41	3.15	27.64	21.08	128.233	Vertical	Pass
		1732.5	-3.16	3.31	27.61	21.14	130.017	Vertical	Pass
		1750	-3.11	3.33	27.59	21.15	130.317	Vertical	Pass
15.0MHz Band	1/#Mid	1717.5	-3.40	3.15	27.65	21.10	128.825	Vertical	Pass
		1732.5	-3.14	3.31	27.61	21.16	130.617	Vertical	Pass

QPSK		1747.5	-3.20	3.33	27.57	21.04	127.057	Vertical	Pass
20.0MHz	1/#Mid	1720	-3.29	3.17	27.66	21.20	131.826	Vertical	Pass
Band		1732.5	-3.08	3.32	27.61	21.21	132.130	Vertical	Pass
QPSK		1745	-2.99	3.36	27.56	21.21	132.130	Vertical	Pass

Note:

SG Level= Signal generator output

Max. EIRP Average (dBm)= Antenna Gain(dB)+ SG Level (dBm)- Cable Loss(dBm)

Radiated Power (EIRP) for Band 4									
Mode	RB/RB SIZE	Frequency	Result					Polarization Of Max. ERP	Conclusion
			SG Level (dBm)	Cable Loss (dBm)	Antenna Gain (dB)	Max. EIRP	Max. EIRP		
						Average (dBm)	Average (mW)		
1.4MHz Band 16 QAM	1/#Mid	1710.7	-4.09	3.12	27.58	20.37	108.893	Horizontal	Pass
		1732.5	-3.98	3.27	27.61	20.36	108.643	Horizontal	Pass
		1754.3	-3.94	3.29	27.63	20.40	109.648	Horizontal	Pass
3.0MHz Band 16 QAM	1/#Mid	1711.5	-4.00	3.13	27.61	20.48	111.686	Horizontal	Pass
		1732.5	-3.89	3.27	27.61	20.45	110.917	Horizontal	Pass
		1753.5	-3.89	3.30	27.62	20.43	110.408	Horizontal	Pass
5.0MHz Band 16 QAM	1/#Mid	1712.5	-4.17	3.13	27.63	20.33	107.895	Horizontal	Pass
		1732.5	-3.99	3.27	27.61	20.35	108.393	Horizontal	Pass
		1752.5	-3.96	3.30	27.60	20.34	108.143	Horizontal	Pass
10.0MHz Band 16 QAM	1/#Mid	1715	-4.07	3.15	27.64	20.42	110.154	Horizontal	Pass
		1732.5	-3.94	3.31	27.61	20.36	108.643	Horizontal	Pass
		1750	-3.86	3.33	27.59	20.40	109.648	Horizontal	Pass
15.0MHz Band 16 QAM	1/#Mid	1717.5	-4.09	3.15	27.65	20.41	109.901	Horizontal	Pass
		1732.5	-3.89	3.31	27.61	20.41	109.901	Horizontal	Pass
		1747.5	-3.78	3.33	27.57	20.46	111.173	Horizontal	Pass
20.0MHz Band 16 QAM	1/#Mid	1720	-4.11	3.17	27.66	20.38	109.144	Horizontal	Pass
		1732.5	-3.79	3.32	27.61	20.50	112.202	Horizontal	Pass
		1745	-3.72	3.36	27.56	20.48	111.686	Horizontal	Pass
1.4MHz Band 16 QAM	1/#Mid	1710.7	-4.07	3.12	27.58	20.39	109.396	Vertical	Pass
		1732.5	-3.93	3.27	27.61	20.41	109.901	Vertical	Pass
		1754.3	-3.96	3.29	27.63	20.38	109.144	Vertical	Pass
3.0MHz Band 16 QAM	1/#Mid	1711.5	-4.04	3.13	27.61	20.44	110.662	Vertical	Pass
		1732.5	-3.90	3.27	27.61	20.44	110.662	Vertical	Pass
		1753.5	-3.90	3.30	27.62	20.42	110.154	Vertical	Pass
5.0MHz Band 16 QAM	1/#Mid	1712.5	-4.03	3.13	27.63	20.47	111.429	Vertical	Pass
		1732.5	-3.93	3.27	27.61	20.41	109.901	Vertical	Pass
		1752.5	-3.87	3.30	27.60	20.43	110.408	Vertical	Pass
10.0MHz Band 16 QAM	1/#Mid	1715	-4.10	3.15	27.64	20.39	109.396	Vertical	Pass
		1732.5	-3.91	3.31	27.61	20.39	109.396	Vertical	Pass
		1750	-3.77	3.33	27.59	20.49	111.944	Vertical	Pass
15.0MHz Band 16	1/#Mid	1717.5	-4.09	3.15	27.65	20.41	109.901	Vertical	Pass
		1732.5	-3.93	3.31	27.61	20.37	108.893	Vertical	Pass

QAM		1747.5	-3.89	3.33	27.57	20.35	108.393	Vertical	Pass
20.0MHz	1/#Mid	1720	-3.97	3.17	27.66	20.52	112.720	Vertical	Pass
Band 16		1732.5	-3.74	3.32	27.61	20.55	113.501	Vertical	Pass
QAM		1745	-3.65	3.36	27.56	20.55	113.501	Vertical	Pass

Note:

SG Level= Signal generator output

Max. EIRP Average (dBm)= Antenna Gain(dB)+ SG Level (dBm)- Cable Loss(dBm)

9. SPURIOUS RADIATION EMISSION

RULE PART(S)

FCC: §2.1051, §24.238(a), §27.53(c)(g)(h)(m)

LIMIT

For Band 7, the minimum permissible attenuation level of any spurious emission is $55 + \log_{10}(P)$ [Watts]).

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P)$ [Watts]), where P is the transmitter power in Watts.

TEST PROCEDURE

For Cellular equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

For PCS equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

The unwanted emission power shall be measured with a resolution bandwidth of at least 1% of the occupied bandwidth in the 1 MHz band immediately outside and adjacent to the channel edge of the equipment. Beyond the 1 MHz band immediately outside the channel edge of the equipment, a resolution bandwidth of 1 MHz shall be employed. A narrower resolution bandwidth is allowed to be used provided that the measured power is integrated over the full required measurement bandwidth of 1 MHz or 1% of the occupied bandwidth as applicable.

The power of any unwanted emissions measured from the channel edge of the equipment shall be attenuated below the transmitter power, P (dBW), as follows:

- a. for base station and subscriber equipment, other than mobile subscriber equipment, the attenuation shall not be less than $43 + 10 \text{ Log}_{10} (p)$, dB; and
- b. for mobile subscriber equipment, the attenuation shall not be less than $43 + 10 \text{ Log}_{10} (p)$, dB at the channel edges and $55 + 10 \text{ Log}_{10} (p)$ at 5.5 MHz away and beyond the channel edges where p in (a) and (b) is the transmitter power measured in watts.

MODES TESTED

- LTE Band 2
- LTE Band 4
-

RESULTS

PASS

9.1 LTE BAND 2

QPSK EIRP POWER FOR LTE BAND 2 (1.4MHZ BANDWIDTH)

Test Results for Low Channel 1850.7MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Gain(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
3701.4	-48.74	4.04	33.51	-19.27	-13	-6.27	Horizontal
3701.4	-44.74	4.04	33.51	-15.27	-13	-2.27	Vertical
5552.1	-52.26	5.24	35.84	-21.66	-13	-8.66	Vertical
5552.1	-51.95	5.24	35.84	-21.35	-13	-8.35	Horizontal
192.9	-34.02	1.43	16.02	-19.43	-13	-6.43	Vertical
391.4	-39.88	1.30	17.99	-23.19	-13	-10.19	Horizontal
Test Results for Mid Channel 1880MHz							
3760.0	-48.46	4.04	33.56	-18.94	-13	-5.94	Horizontal
3760.0	-47.79	4.04	33.56	-18.27	-13	-5.27	Vertical
5640.0	-50.49	5.24	35.91	-19.82	-13	-6.82	Vertical
5640.0	-51.78	5.24	35.91	-21.11	-13	-8.11	Horizontal
206.2	-37.91	1.62	16.97	-22.56	-13	-9.56	Vertical
440.2	-34.27	1.74	15.98	-20.04	-13	-7.04	Horizontal
Test Results for High Channel 1909.3MHz							
3818.6	-51.51	4.04	34.00	-21.55	-13	-8.55	Horizontal
3818.6	-46.71	4.04	34.00	-16.75	-13	-3.75	Vertical
5727.9	-45.09	5.24	36.04	-14.29	-13	-1.29	Vertical
5727.9	-52.27	5.24	36.04	-21.47	-13	-8.47	Horizontal
181.7	-42.12	1.42	17.29	-26.25	-13	-13.25	Vertical
380.2	-35.34	1.50	17.90	-18.93	-13	-5.93	Horizontal

QPSK EIRP POWER FOR LTE BAND 2 (20.0MHZ BANDWIDTH)

Test Results for Low Channel 1860MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Gain(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
3720.0	-53.91	4.07	33.54	-24.44	-13	-11.44	Horizontal
3720.0	-49.79	4.07	33.54	-20.32	-13	-7.32	Vertical
5580.0	-45.30	5.28	35.86	-14.72	-13	-1.72	Vertical
5580.0	-52.64	5.28	35.86	-22.06	-13	-9.06	Horizontal
200.9	-43.50	1.58	16.89	-28.18	-13	-15.18	Vertical
369.0	-34.98	1.76	17.26	-19.48	-13	-6.48	Horizontal
Test Results for Mid Channel 1880MHz							
3760.0	-51.22	4.04	33.56	-21.70	-13	-8.70	Horizontal
3760.0	-52.33	4.04	33.56	-22.81	-13	-9.81	Vertical
5640.0	-49.70	5.24	35.91	-19.03	-13	-6.03	Vertical
5640.0	-49.64	5.24	35.91	-18.97	-13	-5.97	Horizontal
177.1	-39.72	1.46	16.27	-24.91	-13	-11.91	Vertical
286.3	-40.91	1.59	15.15	-27.35	-13	-14.35	Horizontal
Test Results for High Channel 1900MHz							
3800.0	-46.57	4.04	34.00	-16.61	-13	-3.61	Horizontal
3800.0	-49.59	4.04	34.00	-19.63	-13	-6.63	Vertical
5700.0	-45.57	5.24	36.04	-14.77	-13	-1.77	Vertical
5700.0	-52.88	5.24	36.04	-22.08	-13	-9.08	Horizontal
186.4	-34.42	1.36	17.39	-18.38	-13	-5.38	Vertical
399.9	-34.56	1.66	15.39	-20.83	-13	-7.83	Horizontal

Note: $P_{Mea}(dBm) = Power(dBm) + ARpl(dBm)$

Over Limit = $P_{Mea}(dBm) - Limit(dBm)$

Both QPSK and 16QAM has been tested, the worst case is QPSK mode, the report just reported the worst case.

9.2 LTE BAND 4

QPSK EIRP POWER FOR LTE BAND 4 (1.4MHZ BANDWIDTH)

Test Results for Low Channel 1710.7MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Gain(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
3421.4	-46.12	4.02	29.80	-20.34	-13	-7.34	Horizontal
3421.4	-52.67	4.02	29.80	-26.89	-13	-13.89	Vertical
5132.1	-44.53	5.24	35.84	-13.93	-13	-0.93	Vertical
5132.1	-50.71	5.24	35.84	-20.11	-13	-7.11	Horizontal
205.6	-36.99	1.68	16.04	-22.63	-13	-9.63	Vertical
350.7	-34.81	1.78	17.74	-18.85	-13	-5.85	Horizontal
Test Results for Mid Channel 1732.5MHz							
3465.0	-50.60	4.03	30.00	-24.63	-13	-11.63	Horizontal
3465.0	-46.52	4.03	30.00	-20.55	-13	-7.55	Vertical
5197.5	-49.27	5.25	35.86	-18.66	-13	-5.66	Vertical
5197.5	-52.56	5.25	35.86	-21.95	-13	-8.95	Horizontal
205.9	-40.08	1.72	17.69	-24.11	-13	-11.11	Vertical
457.6	-37.68	1.62	16.02	-23.27	-13	-10.27	Horizontal
Test Results for High Channel 1754.3MHz							
3508.6	-48.29	4.05	30.01	-22.33	-13	-9.33	Horizontal
3508.6	-48.43	4.05	30.01	-22.47	-13	-9.47	Vertical
5262.9	-51.77	5.26	35.86	-21.17	-13	-8.17	Vertical
5262.9	-52.12	5.26	35.86	-21.52	-13	-8.52	Horizontal
209.4	-38.19	1.80	16.69	-23.30	-13	-10.30	Vertical
246.2	-39.81	1.75	16.66	-24.91	-13	-11.91	Horizontal

QPSK EIRP POWER FOR LTE BAND 4 (20.0MHZ BANDWIDTH)

Test Results for Low Channel 1710.7MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Gain(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
3440.0	-46.58	4.02	29.80	-20.80	-13	-7.80	Horizontal
3440.0	-47.02	4.02	29.80	-21.24	-13	-8.24	Vertical
5160.0	-45.19	5.24	35.84	-14.59	-13	-1.59	Vertical
5160.0	-49.82	5.24	35.84	-19.22	-13	-6.22	Horizontal
192.6	-40.02	1.57	17.26	-24.33	-13	-11.33	Vertical
244.6	-42.91	1.78	16.35	-28.34	-13	-15.34	Horizontal
Test Results for Mid Channel 1732.5MHz							
3465.0	-46.22	4.03	30.00	-20.25	-13	-7.25	Horizontal
3465.0	-53.61	4.03	30.00	-27.64	-13	-14.64	Vertical
5197.5	-49.07	5.25	35.86	-18.46	-13	-5.46	Vertical
5197.5	-50.54	5.25	35.86	-19.93	-13	-6.93	Horizontal
187.1	-43.46	1.44	17.95	-26.95	-13	-13.95	Vertical
372.1	-37.31	1.65	16.09	-22.87	-13	-9.87	Horizontal
Test Results for High Channel 1754.3MHz							
3490.0	-46.06	4.05	27.68	-22.43	-13	-9.43	Horizontal
3490.0	-49.58	4.05	27.68	-25.95	-13	-12.95	Vertical
5235.0	-46.27	5.26	35.86	-15.67	-13	-2.67	Vertical
5235.0	-51.96	5.26	35.86	-21.36	-13	-8.36	Horizontal
175.5	-41.65	1.61	16.85	-26.41	-13	-13.41	Vertical
232.5	-39.31	1.61	15.19	-25.73	-13	-12.73	Horizontal

Note: P_{Mea}(dBm)= Power(dBm)+ AR_{pl} (dBm)

. Over Limit= : P_{Mea}(dBm)-Limit(dBm)

. Both QPSK and 16QAM has been tested, the worst case is QPSK mode, the report just reported the worst case.

10. FREQUENCY STABILITY

RULE PART(S)

FCC: §2.1055, §24.235, §27.54

LIMITS

§24.235 - The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

TEST PROCEDURE

Use CMW 500 with Frequency Error measurement capability.

- Temp. = -30° to $+50^{\circ}\text{C}$
- Voltage = low voltage, DC 3.3V, Normal, DC 3.7V and High voltage, DC 4.2V.

Frequency Stability vs Temperature:

The EUT is placed inside a temperature chamber. The temperature is set to -30°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until $+50^{\circ}\text{C}$ is reached.

Frequency Stability vs Voltage:

The peak frequency error is recorded (worst-case).

MODES TESTED

- LTE Band 2
- LTE Band 4
-

RESULTS

See the following pages.

10.1 LTE BAND 2

Band 2 QPSK, (20MHz BANDWIDTH RB size 100 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.2	1880	12.4	0.006598	2.5
3.7	1880	13.9	0.007379	2.5
4.3	1880	13.4	0.007129	2.5

Frequency error vs. Temperature

Temperature [° C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	1880	12.9	0.006882	2.5
Extreme (50C)	1880	11.9	0.006354	2.5
Extreme (40C)	1880	14.2	0.007537	2.5
Extreme (30C)	1880	13.6	0.007214	2.5
Extreme (10C)	1880	13.6	0.007227	2.5
Extreme (0C)	1880	12.5	0.006643	2.5
Extreme (-10C)	1880	13.4	0.007114	2.5
Extreme (-20C)	1880	14.3	0.007621	2.5
Extreme (-30C)	1880	14.8	0.007899	2.5

Band 2 16QAM, (20MHz BANDWIDTH RB size 100 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.2	1880	10.0	0.005303	2.5
3.7	1880	9.1	0.004853	2.5
4.3	1880	7.9	0.004213	2.5

Frequency error vs. Temperature

Temperature [° C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	1880	10.0	0.005326	2.5
Extreme (50C)	1880	9.3	0.004968	2.5
Extreme (40C)	1880	8.1	0.004315947	2.5
Extreme (30C)	1880	8.6	0.004599149	2.5
Extreme (10C)	1880	9.1	0.00483228	2.5
Extreme (0C)	1880	8.0	0.004259321	2.5
Extreme (-10C)	1880	8.8	0.004675522	2.5
Extreme (-20C)	1880	8.4	0.004488633	2.5
Extreme (-30C)	1880	8.4	0.004457242	2.5

*Note: Frequency error measurements were made by using the build-in capability of the Wireless Communication Test Set.

10.2 LTE BAND 4

Band 4 QPSK, (20MHz BANDWIDTH RB size 100 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.2	1732.5	8.8	0.005105	2.5
3.7	1732.5	9.4	0.005407	2.5
4.3	1732.5	8.3	0.004764	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	1732.5	8.1	0.004685	2.5
Extreme (50C)	1732.5	8.6	0.004991	2.5
Extreme (40C)	1732.5	7.8	0.004524	2.5
Extreme (30C)	1732.5	6.1	0.003520	2.5
Extreme (10C)	1732.5	7.1	0.004102	2.5
Extreme (0C)	1732.5	9.2	0.005299	2.5
Extreme (-10C)	1732.5	8.2	0.004757	2.5
Extreme (-20C)	1732.5	7.0	0.004046	2.5
Extreme (-30C)	1732.5	8.2	0.004741	2.5

Band 4 16QAM, (20MHz BANDWIDTH RB size 100 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.2	1732.5	9.9	0.005714	2.5
3.7	1732.5	8.7	0.005037	2.5
4.3	1732.5	7.9	0.004574	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	1732.5	9.7	0.005592	2.5
Extreme (50C)	1732.5	8.4	0.004868	2.5
Extreme (40C)	1732.5	8.4	0.004855	2.5
Extreme (30C)	1732.5	9.3	0.005395	2.5
Extreme (10C)	1732.5	9.1	0.005225	2.5
Extreme (0C)	1732.5	7.6	0.004413	2.5
Extreme (-10C)	1732.5	8.9	0.005131	2.5
Extreme (-20C)	1732.5	9.3	0.005391	2.5
Extreme (-30C)	1732.5	7.7	0.004426	2.5

***Note:** Frequency error measurements were made by using the build-in capability of the Wireless Communication Test Set.

11. Peak-to-Average Ratio

11.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


11.2 Measuring Instruments

See list of measuring instruments of this test report.

11.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. For LTE operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

11.4 Test Setup



MODES TESTED

- LTE Band 2/4

Test data reference attachment.

----END OF REPORT----