



FCC PART 15, SUBPART C ISED C RSS-247, ISSUE 2, FEBRUARY 2017

TEST REPORT

For

Culvert-IoT Corporation

1999 S Bascom Ave #230
Campbell, CA 95008, USA

FCC ID: 2AQ98-C0
IC: 26298-C0

Report Type: Original Report	Product Type: 48 Handheld Positioning Unit Charger
Prepared By:	Christian McCaig Test Engineer 
Report Number	R2008102-247
Report Issue Date:	2020-08-19
Reviewed By:	Simon Ma RF Supervisor 
Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162, Fax: (408) 732-9164	



Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by A2LA*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*" Rev 01

TABLE OF CONTENTS

1	General Description.....	5
1.1	Product Description for Equipment Under Test (EUT)	5
1.2	Objective.....	5
1.3	Related Submittal(s)/Grant(s)	5
1.4	Test Methodology	5
1.5	Measurement Uncertainty	6
1.6	Test Facility Registrations	6
1.7	Test Facility Accreditations	6
2	System Test Configuration.....	9
2.1	Justification	9
2.2	EUT Exercise Software.....	9
2.3	Duty Cycle Correction Factor	9
2.4	Equipment Modifications.....	10
2.5	Local Support Equipment	10
2.6	Support Equipment	10
2.7	Power Supply/Adapter	10
2.8	Interface Ports and Cabling.....	11
3	Summary of Test Results	12
4	FCC §15.203 & ISEDC RSS-Gen §6.8 - Antenna Requirements	13
4.1	Applicable Standards	13
4.2	Antenna Description	13
5	FCC §2.1091, §15.247(i) & ISEDC RSS-102 - RF Exposure.....	14
5.1	Applicable Standards	14
5.2	MPE Prediction.....	15
5.3	MPE Results	15
5.4	RF exposure evaluation exemption for IC	15
6	FCC §15.207 & ISEDC RSS-Gen §8.8 - AC Line Conducted Emissions.....	16
6.1	Applicable Standards	16
6.2	Test Setup	16
6.3	Test Procedure	16
6.4	Corrected Amplitude and Margin Calculation	17
6.5	Test Setup Block Diagram	17
6.6	Test Equipment List and Details.....	18
6.7	Test Environmental Conditions	18
6.8	Summary of Test Results	18
6.9	Conducted Emissions Test Plots and Data.....	19
6	FCC §15.209, §15.247(d) & ISEDC RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions.....	20
6.1	Applicable Standards	20
6.2	Test Setup	21
6.3	Test Procedure	22
6.4	Corrected Amplitude and Margin Calculation	22
6.5	Test Equipment List and Details.....	23
6.6	Test Environmental Conditions	23
6.7	Summary of Test Results	24
6.8	Spurious Emissions Test Results	25
7	FCC §15.247(a) (2) & ISEDC RSS-247 §5.2 -Emission Bandwidth	29
7.1	Applicable Standards	29
7.2	Measurement Procedure.....	29
7.3	Test Equipment List and Details.....	29
7.4	Test Environmental Conditions	29

7.5	Test Results.....	30
8	FCC §15.247(b) (3) & ISEDC RSS-247 §5.4 (4) - Output Power Measurement	34
8.1	Applicable Standards	34
8.2	Measurement Procedure.....	34
8.3	Test Equipment List and Details.....	34
8.4	Test Environmental Conditions	35
8.5	Test Results.....	35
9	FCC §15.247(d) and ISEDC RSS-247 §5.5 – 100 kHz Bandwidth of Band Edges.....	37
9.1	Applicable Standards	37
9.2	Measurement Procedure.....	37
9.3	Test Equipment List and Details.....	37
9.4	Test Environmental Conditions	38
9.5	Test Results.....	39
10	FCC §15.247(e) & ISEDC RSS-247 §5.2(2) - Power Spectral Density.....	40
10.1	Applicable Standards	40
10.2	Measurement Procedure.....	40
10.3	Test Equipment List and Details.....	40
10.4	Test Environmental Conditions	40
10.5	Test Results.....	41
11	Annex A - EUT Photographs	43
12	Annex B (Normative) - A2LA Electrical Testing Certificate	44

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R2008102-247	Original Report	2020-09-09

1 General Description

1.1 Product Description for Equipment Under Test (EUT)

This test report was prepared on behalf of *Culvert-IoT Corporation*, and their product model: *C0*, *FCC ID: 2AQ98-C0*, *IC: 26298-C0* or the “EUT” as referred to in this report. The EUT is a 48 Handheld Positioning Unit Charger with BLE capabilities.

1.2 Objective

This report was prepared on behalf of *Culvert-IoT Corporation*, in accordance with Part 2, Subpart J, and Part 15, Subpart and C of the Federal Communication Commission’s rules and ISED RSS-247 Issue 2, February 2017.

The objective was to determine compliance with FCC Part 15.247 and ISED RSS-247 rules for Output Power, Antenna Requirements, 6 dB Bandwidth, Power Spectral Density, 100 kHz Bandwidth of Band Edges Measurement, and Radiated Spurious Emissions.

1.3 Related Submittal(s)/Grant(s)

N/A

1.4 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

1.5 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Parameter	Measurement uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.57 dB
Power Spectral Density, conducted	±1.48dB
Unwanted Emissions, conducted	±1.57dB
All emissions, radiated	±4.0 dB
AC power line Conducted Emission	±2.0 dB
Temperature	±2 ° C
Humidity	±5 %
DC and low frequency voltages	±1.0 %
Time	±2 %
Duty Cycle	±3 %

1.6 Test Facility Registrations

BACLs test facilities that are used to perform Radiated and Conducted Emissions tests are currently recognized by the Federal Communications Commission as Accredited with NIST Designation Number US1129.

BACL's test facilities that are used to perform Radiated and Conducted Emissions tests are currently registered with Industry Canada under Registration Numbers: 3062A-1, 3062A-2, and 3062A-3.

BACL is a Chinese Taipei Bureau of Standards Metrology and Inspection (BSMI) validated Conformity Assessment Body (CAB), under Appendix B, Phase I Procedures of the APEC Mutual Recognition Arrangement (MRA). BACL's BSMI Lab Code Number is: SL2-IN-E-1002R.

BACL's test facilities that are used to perform AC Line Conducted Emissions, Telecommunications Line Conducted Emissions, Radiated Emissions from 30 MHz to 1 GHz, and Radiated Emissions from 1 GHz to 6 GHz are currently recognized as Accredited in accordance with the Voluntary Control Council for Interference [VCCI] Article 15 procedures under Registration Number A-0027.

1.7 Test Facility Accreditations

Bay Area Compliance Laboratories Corp. (BACL) is:

A- An independent, 3rd-Party, Commercial Test Laboratory accredited to ISO/IEC 17025:2005 by A2LA (Test Laboratory Accreditation Certificate Number 3297.01), in the fields of: Electromagnetic Compatibility and Telecommunications. Unless noted by an Asterisk (*) in the Compliance Matrix (See Section 3 of this Test Report), BACL's ISO/IEC 17025:2005 Scope of Accreditation includes all of the Test Method Standards and/or the Product Family Standards detailed in this Test Report.

BACL's ISO/IEC 17025:2005 Scope of Accreditation includes a comprehensive suite of EMC Emissions, EMC Immunity, Radio, RF Exposure, Safety and wireline Telecommunications test methods applicable to a wide range of product categories. These product categories include Central Office Telecommunications Equipment [including NEBS - Network Equipment Building Systems], Unlicensed and Licensed Wireless and RF devices, Information Technology Equipment (ITE); Telecommunications Terminal Equipment (TTE); Medical Electrical Equipment; Industrial, Scientific and Medical Test Equipment; Professional Audio and Video Equipment; Industrial and Scientific Instruments and Laboratory Apparatus; Cable Distribution Systems, and Energy Efficient Lighting.

B- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.02) to certify

- For the USA (Federal Communications Commission):

- 1- All Unlicensed radio frequency devices within FCC Scopes A1, A2, A3, and A4;
- 2- All Licensed radio frequency devices within FCC Scopes B1, B2, B3, and B4;
- 3- All Telephone Terminal Equipment within FCC Scope C.

- For the Canada (Industry Canada):

- 1 All Scope 1-Licence-Exempt Radio Frequency Devices;
- 2 All Scope 2-Licensed Personal Mobile Radio Services;
- 3 All Scope 3-Licensed General Mobile & Fixed Radio Services;
- 4 All Scope 4-Licensed Maritime & Aviation Radio Services;
- 5 All Scope 5-Licensed Fixed Microwave Radio Services
- 6 All Broadcasting Technical Standards (BETS) in the Category I Equipment Standards List.

- For Singapore (Info-Communications Development Authority (IDA)):

- 1 All Line Terminal Equipment: All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2011, Annex 2
2. All Radio-Communication Equipment: All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2011, Annex 2

- For the Hong Kong Special Administrative Region:

- 1 All Radio Equipment, per KHCA 10XX-series Specifications;
- 2 All GMDSS Marine Radio Equipment, per HKCA 12XX-series Specifications;
- 3 All Fixed Network Equipment, per HKCA 20XX-series Specifications.

- For Japan:

- 1 MIC Telecommunication Business Law (Terminal Equipment):
 - All Scope A1 - Terminal Equipment for the Purpose of Calls;
 - All Scope A2 - Other Terminal Equipment
- 2 Radio Law (Radio Equipment):
 - All Scope B1 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 1 of the Radio Law
 - All Scope B2 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 2 of the Radio Law
 - All Scope B3 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 3 of the Radio Law

C- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.03) to certify Products to USA's Environmental Protection Agency (EPA) ENERGY STAR Product Specifications for:

- 1 Electronics and Office Equipment:
 - for Telephony (ver. 3.0)
 - for Audio/Video (ver. 3.0)
 - for Battery Charging Systems (ver. 1.1)
 - for Set-top Boxes & Cable Boxes (ver. 4.1)
 - for Televisions (ver. 6.1)

- for Computers (ver. 6.0)
- for Displays (ver. 6.0)
- for Imaging Equipment (ver. 2.0)
- for Computer Servers (ver. 2.0)
- 2 Commercial Food Service Equipment
 - for Commercial Dishwashers (ver. 2.0)
 - for Commercial Ice Machines (ver. 2.0)
 - for Commercial Ovens (ver. 2.1)
 - for Commercial Refrigerators and Freezers
- 3 Lighting Products
 - For Decorative Light Strings (ver. 1.5)
 - For Luminaires (including sub-components) and Lamps (ver. 1.2)
 - For Compact Fluorescent Lamps (CFLs) (ver. 4.3)
 - For Integral LED Lamps (ver. 1.4)
- 4 Heating, Ventilation, and AC Products
 - for Residential Ceiling Fans (ver. 3.0)
 - for Residential Ventilating Fans (ver. 3.2)
- 5 Other
 - For Water Coolers (ver. 3.0)

D- A NIST Designated Phase-I and Phase-II Conformity Assessment Body (CAB) for the following economies and regulatory authorities under the terms of the stated MRAs/Treaties:

- Australia: ACMA (Australian Communication and Media Authority) – APEC Tel MRA -Phase I;
- Canada: (Innovation, Science and Economic development Canada - ISEDC) Foreign Certification Body – FCB – APEC Tel MRA -Phase I & Phase II;
- Chinese Taipei (Republic of China – Taiwan):
 - o BSMI (Bureau of Standards, Metrology and Inspection) APEC Tel MRA -Phase I;
 - o NCC (National Communications Commission) APEC Tel MRA -Phase I;
- European Union:
 - o EMC Directive 2014/30/EU US-EU EMC & Telecom MRA CAB (NB)
 - o Radio Equipment (RE) Directive 2014/53/EU US-EU EMC & Telecom MRA CAB (NB)
 - o Low Voltage Directive (LVD) 2014/35/EU
- Hong Kong Special Administrative Region: (Office of the Telecommunications Authority – OFTA) APEC Tel MRA -Phase I & Phase II
- Israel – US-Israel MRA Phase I
- Republic of Korea (Ministry of Communications - Radio Research Laboratory) APEC Tel MRA -Phase I
- Singapore: (Infocomm Media Development Authority - IMDA) APEC Tel MRA -Phase I & Phase II;
- Japan: VCCI - Voluntary Control Council for Interference US-Japan Telecom Treaty VCCI Side Letter-
- USA:
 - o ENERGY STAR Recognized Test Laboratory – US EPA
 - o Telecommunications Certification Body (TCB) – US FCC;
 - o Nationally Recognized Test Laboratory (NRTL) – US OSHA
- Vietnam: APEC Tel MRA -Phase I;

2 System Test Configuration

2.1 Justification

The EUT was configured for testing according to ANSI C63.10-2013 and FCC KDB 558074 D01 DTS Meas Guidance v05r02.

The EUT was tested in a testing mode to represent worst-case results during the final qualification test.

The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the average power, peak power and PPSD across all data rates bandwidths, and modulations.

2.2 EUT Exercise Software

Putty was used and software is compliant with the standard requirements being tested against.

Modulation	Frequency (MHz)	Power Setting
BLE	2402	8
	2426	8
	2480	8

2.3 Duty Cycle Correction Factor

According to KDB 558074 D01 DTS Meas Guidance v05r02 section 6.0:


Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be utilized to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data is being acquired (i.e., no transmitter off-time is to be considered).

Radio Mode	Total On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
BLE	2.13	2.50	85.2	0.70

Duty Cycle = On Time (ms)/ Period (ms)

Duty Cycle Correction Factor (dB) = $10 \cdot \log(1/\text{Duty Cycle})$

Please refer to the following plots.



2.4 Equipment Modifications

None

2.5 Local Support Equipment

Manufacturer	Description	Model	Serial Number
Dell	Laptop	Latitude E6410	3CKRAQ1

2.6 Support Equipment

Manufacturer	Description	Model
Culvert	Debug Board	Culvert Dongle

2.7 Power Supply/Adapter

Manufacturer	Description	Model
Apple	USB-C Power Adapter	A1719

2.8 Interface Ports and Cabling

Description	Length (m)	To	From
USB to Micro USB	< 1 m	Laptop	Debug Board
USB C to USB C	< 1 m	Debug Board	EUT
USB C to USB C	< 1 m	Charging Block	EUT

3 Summary of Test Results

Results reported relate only to the product tested.

FCC and ISED Rules	Description of Test	Results
FCC §15.203 ISED RSS-Gen §6.8	Antenna Requirement	Compliant
FCC §15.207 ISED RSS-Gen §8.8	AC Line Conducted Emissions	Compliant
FCC §2.1091, §15.247(i) ISED RSS-102	RF Exposure	Compliant
FCC §2.1053, §15.205, §15.209, §15.247 (d) ISED RSS-247 §5.5 ISED RSS-Gen §8.9 and §8.10	Radiated Spurious Emissions	Compliant
FCC §15.247(a)(2) ISED RSS-247 §5.2(a)	6 dB and 99% Emission Bandwidth	Compliant
FCC §15.247(b)(3) ISED RSS-247 §5.4(d)	Output Power	Compliant
FCC §15.247(d) ISED RSS-247 §5.5	100 kHz Bandwidth of Frequency Band Edge	Compliant
FCC §15.247(e) ISED RSS-247 §5.2(b)	Power Spectral Density	Compliant

4 FCC §15.203 & ISEDC RSS-Gen §6.8 - Antenna Requirements

4.1 Applicable Standards

According to FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to FCC §15.247 (b) (4), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to ISEDC RSS-Gen §6.8: Transmitter Antenna

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.2 Antenna Description

External/Internal/Integral	Maximum Antenna Gain (dBi)	Antenna Type
Integral	4.4	Stamped Metal Antenna

5 FCC §2.1091, §15.247(i) & ISEDC RSS-102 - RF Exposure

5.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

According to ISED RSS-102 Issue 5:

2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

5.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

5.3 MPE Results

<u>Maximum output power at antenna input terminal (dBm):</u>	<u>7.72</u>
<u>Maximum output power at antenna input terminal (mW):</u>	<u>5.92</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>2402</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>4.4</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>2.754</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.0032</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.0032 W/cm². Limit is 1.0 mW/cm².

5.4 RF exposure evaluation exemption for IC

$$12.12 \text{ dBm} < 1.31 \times 10^{-2} f^{0.6834} = 2.676 \text{ W} = 34.3 \text{ dBm}$$

Therefore the RF exposure is not required.

6 FCC §15.207 & ISEDC RSS-Gen §8.8 - AC Line Conducted Emissions

6.1 Applicable Standards

As per FCC §15.207 and ISEDC RSS-Gen §8.8 Conducted limits:

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56 ^{Note1}	56 to 46 ^{Note2}
0.5-5	56	46
5-30	60	50

Note1: Decreases with the logarithm of the frequency.

Note2: A linear average detector is required

6.2 Test Setup

The measurement was performed at shield room, using the setup per ANSI C63.10-2013 measurement procedure. The specification used were FCC §15.207 and ISEDC RSS-Gen §8.8 limits.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The AC/DC power adapter of the EUT was connected with LISN-1 which provided 120 V / 60 Hz AC power.

6.3 Test Procedure

During the conducted emissions test, the power cord of the EUT host system was connected to the mains outlet of the LISN-1 and the power cords of support equipment were connected to LISN-2.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data were recorded in the peak, quasi-peak, and average detection mode. Quasi-Peak readings are distinguished with a "QP." Average readings are distinguished with an "Ave".

6.4 Corrected Amplitude and Margin Calculation

The Corrected Amplitude (CA) is calculated by adding the Cable Loss (CL), the Attenuator Factor (Atten) to indicated Amplitude (Ai) reading. The basic equation is as follows:


$$CA = Ai + CL + Atten$$

For example, a corrected amplitude of 46.2 dBuV = Indicated Reading (32.5 dBuV) + Cable Loss (3.7 dB) + Attenuator (10 dB)

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

6.5 Test Setup Block Diagram



6.6 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde and Schwarz	Receiver, EMI Test	ESCI 1166.5950.03	100338	2018-07-05	2.5 years
Rohde and Schwarz	Impulse Limiter	ESH3-Z2	101964	2020-07-02	1 year
Solar Electronics Company	High Pass Filter	Type 7930-100	7930150202	2020-02-27	1 year
Suirong	30 ft conductive emission cable	LMR 400	-	N/R	N/A
FCC	LISN	FCC-LISN-50-25-2-10-CISPR16	160129	2019-07-11	14 months
Vasona	Test software	V6.0 build 11	10400213	N/R	N/R

Statement of Traceability: **BACL** attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 02 October 2018) "A2LA Policy on Metrological Traceability".

6.7 Test Environmental Conditions

Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	101.31 kPa

The testing was performed by Christian McCaig on 2020-08-14 in 5m3 chamber.


6.8 Summary of Test Results

According to the recorded data in following table, the EUT complied with the FCC 15C and ISEDC RSS-Gen standard's conducted emissions limits.


6.9 Conducted Emissions Test Plots and Data

Worst Case: 2402 MHz

120 V, 60 Hz – Line



120 V, 60 Hz – Neutral



Note: All emissions measured were more than 20dB from limits, therefore no points were selected for formal scan.

6 FCC §15.209, §15.247(d) & ISEDC RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions

6.1 Applicable Standards

As per FCC §15.35(b): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As Per FCC §15.205(a) and RSS-Gen except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	960 – 1240	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	1300 – 1427	5.35 – 5.46
2.1735 – 2.1905	25.5 – 25.67	1435 – 1626.5	7.25 – 7.75
4.125 – 4.128	37.5 – 38.25	1645.5 – 1646.5	8.025 – 8.5
4.17725 – 4.17775	73 – 74.6	1660 – 1710	9.0 – 9.2
4.20725 – 4.20775	74.8 – 75.2	1718.8 – 1722.2	9.3 – 9.5
6.215 – 6.218	108 – 121.94	2200 – 2300	10.6 – 12.7
6.26775 – 6.26825	123 – 138	2310 – 2390	13.25 – 13.4
6.31175 – 6.31225	149.9 – 150.05	2483.5 – 2500	14.47 – 14.5
8.291 – 8.294	156.52475 – 156.52525	2690 – 2900	15.35 – 16.2
8.362 – 8.366	156.7 – 156.9	3260 – 3267	17.7 – 21.4
8.37625 – 8.38675	162.0125 – 167.17	3332 – 3339	22.01 – 23.12
8.41425 – 8.41475	167.72 – 173.2	3345.8 – 3358	23.6 – 24.0
12.29 – 12.293	240 – 285	3600 – 4400	31.2 – 31.8
12.51975 – 12.52025	322 – 335.4		36.43 – 36.5
12.57675 – 12.57725	399.9 – 410		Above 38.6
13.36 – 13.41	608 – 614		

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz.

However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per FCC §15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

As per ISED RSS-Gen §8.9, except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in the table below. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

General Field Strength Limits at Frequencies above 30 MHz

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at 3 meters)
30-88	100
88-216	150
216-960	200
Above 960	500

As per ISED RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

6.2 Test Setup

The radiated emissions tests were performed in the 5-meter Chamber, using the setup in accordance with ANSI C63.10-2013. The specification used was the FCC 15 Subpart C and ISED RSS-247 limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

6.3 Test Procedure

The EUT host, and all support equipment power cords were connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

For radiated testing the EUT was set 3 meter away from the testing antenna, which was varied from 1-4 meter, and the EUT was placed on a turntable, which was 0.8 meter and 1.5 meter above the ground plane for below and above 1000 MHz measurements, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna's polarity should be changed between horizontal and vertical.

The spectrum analyzer or receiver was set as:

Below 1000 MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000 MHz:

- (1) Peak: $\text{RBW} = 1\text{MHz} / \text{VBW} = 3\text{MHz} / \text{Sweep} = 100 \text{ ms}$
- (2) Average: Peak – DC Correction

6.4 Corrected Amplitude and Margin Calculation

The Corrected Amplitude (CA) is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) to indicated Amplitude (Ai) reading. The basic equation is as follows:

$$\text{CA} = \text{Ai} + \text{AF} + \text{CL} + \text{Atten} - \text{Ga}$$

For example, a corrected amplitude of 40.3 dBuV/m = Indicated Reading (32.5 dBuV) + Antenna Factor (+23.5dB) + Cable Loss (3.7 dB) + Attenuator (10 dB) - Amplifier Gain (29.4 dB)

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

6.5 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Spectrum Analyzer	E4446A	MY48250238	2019-06-26	18 months
Rhode & Schwarz	EMI Test Receiver	ESCI 1166.5950K03	100044	2018-10-26	2 years
BACL	5m3 Sensitivity Box	1	2	2019-10-02	1 year
Sunol Sciences	System Controller	SC99V	011003-1	N/R	N/A
Sunol Sciences	Biconilog Antenna	JB3	A020106-2	2019-11-20	2 years
ETS Lindgren	Horn Antenna	3117	00218973	2019-02-13	2 years
Wisewave	Horn Antenna	ARH-2823-02	10555-01	2020-02-05	2 years
-	SMA cable	-	-	Each time ¹	N/A
IW Microwave	150 Series 2.92mm Cable	KPS1501AN-3780-KPS	DC 1925	2019-09-11	1 year
IW Microwave	157 Series Cable Armored with 2.92mm Male Plugs on Both Sides	KPS-1571AN-2400	DC 1922	2020-06-06	1 year
MDP Digital	Times Microwave LMR 400 UltraFlex Coaxial Cable 35'	LMR400UF	BACL1904161	2020-05-20	1 year
AH Systems	Preamplifier	PAM 1840 VH	170	2019-09-24	1 year
Agilent	Preamplifier	8449B	3147A00400	2020-02-27	1 year
HP	Preamplifier	8447D	2443A04374	2019-08-13	13 months
Vasona	Test software	V6.0 build 11	10400213	N/R	N/R

Note¹: cables and notch filter included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 02 October 2018) "A2LA Policy on Metrological Traceability".

6.6 Test Environmental Conditions

Temperature:	20-22 °C
Relative Humidity:	42-50 %
ATM Pressure:	102.7 kPa

The testing was performed by Christian McCaig from 2020-08-12 to 2020-08-14 in 5m chamber 3.

6.7 Summary of Test Results

According to the data hereinafter, the EUT complied with FCC Title 47, Part 15C and ISED RSS-247 standard's radiated emissions limits, and had the worst margin of:


Mode: Transmitting		
Margin (dB)	Frequency (MHz)	Mode, channel
-2.67	17950.1	BLE, low channel

Please refer to the following table and plots for specific test result details

6.8 Spurious Emissions Test Results

1) 30 MHz – 1 GHz Worst case measured at 3 meters

Worst Case Channel: 2402MHz



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dBμV/m)	Margin (dB)	Comment
33.29325	21.81	267	V	239	40	-18.19	QP
37.334	18.73	172	H	166	40	-21.27	QP
42.4495	17.91	194	H	102	40	-22.09	QP
139.3595	25.24	203	H	115	43.5	-18.26	QP
44.9115	17.02	185	H	78	40	-22.98	QP
55.29275	18.86	115	V	176	40	-21.14	QP

2) 1-26.5 GHz Measured at 3 meters


Frequency (MHz)	S.A. Reading (dBμV)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre- Amp. (dB)	Cord. Reading (dBμV/m)	FCC/ISED		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	
Low Channel 2402 MHz											
2402	68.19	4	250	V	32	5.72	-	105.91	-	-	Peak
2402	69.63	355	145	H	32	5.72	-	107.35	-	-	Peak
2390	48.23	175	105	V	32	6.33	36.42	50.14	74	-23.86	Peak
2390	49.14	0	145	H	32	6.33	36.42	51.05	74	-22.95	Peak
2390	37.4875	175	105	V	32	6.33	36.42	39.3975	54	-14.60	Ave
2390	38.3725	0	145	H	32	6.33	36.42	40.2825	54	-13.72	Ave
4804	49.42	152	300	V	34.6	9.89	35.43	58.48	74	-15.52	Peak
4804	46.16	340	300	H	34.6	9.89	35.43	55.22	74	-18.78	Peak
4804	41.1295	152	300	V	34.6	9.89	35.43	50.1895	54	-3.81	Ave
4804	36.6155	340	300	H	34.6	9.89	35.43	45.6755	54	-8.32	Ave
7206	46.94	101	300	V	35.7	9.83	35.82	56.65	75.91	-19.26	Peak ¹
7206	45.52	332	300	H	35.7	9.83	35.82	55.23	77.35	-22.12	Peak ¹
Middle Channel 2426 MHz											
4856	47.97	154	290	V	34.6	10.96	35.43	58.1	74	-15.90	Peak
4856	45.27	319	290	H	34.6	10.96	35.43	55.4	74	-18.60	Peak
4856	40.7705	154	290	V	34.6	10.96	35.43	50.9005	54	-3.10	Ave
4856	36.3035	319	290	H	34.6	10.96	35.43	46.4335	54	-7.57	Ave
7284	47.87	100	290	V	35.7	10.95	35.82	58.7	74	-15.30	Peak
7284	46.97	348	290	H	35.7	10.95	35.82	57.8	74	-16.20	Peak
7284	37.7925	100	290	V	35.7	10.95	35.82	48.6225	54	-5.38	Ave
7284	35.7665	348	290	H	35.7	10.95	35.82	46.5965	54	-7.40	Ave
High Channel 2480 MHz											
2483.5	58.82	360	240	V	32.2	5.65	36.34	60.33	74	-13.67	Peak
2483.5	59.37	350	210	H	32.2	5.65	36.34	60.88	74	-13.12	Peak
2483.5	41.5935	360	240	V	32.2	5.65	36.34	43.1035	54	-10.90	Ave
2483.5	42.1515	350	210	H	32.2	5.65	36.34	43.6615	54	-10.34	Ave
4960	47.32	155	300	V	34.6	11.07	35.43	57.56	74	-16.44	Peak
4960	45.27	340	300	H	34.6	11.07	35.43	55.51	74	-18.49	Peak
4960	37.0675	155	300	V	34.6	11.07	35.43	47.3075	54	-6.69	Ave
4960	35.2115	340	300	H	34.6	11.07	35.43	45.4515	54	-8.55	Ave
7440	47.19	98	300	V	35.8	12.73	35.9	59.82	74	-14.18	Peak
7440	45.38	320	300	H	35.8	12.73	35.9	58.01	74	-15.99	Peak
7440	37.1995	98	300	V	35.8	12.73	35.9	49.8295	54	-4.17	Ave
7440	34.6655	320	300	H	35.8	12.73	35.9	47.2955	54	-6.70	Ave

Note¹: Outside of Restricted Bands. Limit is 30dB down from peak Fundamental Field Strength.


3) Above 1 GHz Worst Case Scans measured at 1meter

Worst Case Channel: 2402MHz

1-18 GHz



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dBμV/m)	Margin (dB)	Comment
17950.1	72.07	134	H	167	84	-11.93	Peak
4805.855	55.43	228	H	334	84	-28.57	Peak
17950.1	61.33	134	H	167	64	-2.67	Average
4805.855	46.61	228	H	334	64	-17.39	Average

18-26.5 GHz

Note: test was done with Notch filter.

7 FCC §15.247(a) (2) & ISEDC RSS-247 §5.2 -Emission Bandwidth

7.1 Applicable Standards

According to ECFR §15.247(a) (2) and ISEDC RSS-247 §5.2(a), systems using digital modulation techniques may operate in the 902~928 MHz, 2400~2483.5 MHz, and 5725~5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz

7.2 Measurement Procedure

The 6 dB bandwidth, i.e., DTS bandwidth, measurements were based on FCC KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.2: DTS bandwidth.

The 99% occupied bandwidth was measured in accordance with IC RSS-Gen Issue 5, Section 6.7.

7.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Spectrum Analyzer	E4446A	MY48250238	2019-06-26	18 months
Sunol Sciences	System Controller	SC99V	011003-1	N/R	N/A
IW Microwave	150 Series 2.92mm Cable	KPS1501AN-3780-KPS	DC 1925	2019-09-11	1 year
ETS Lindgren	Horn Antenna	3117	00218973	2019-02-13	2 years

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy PI02 (dated 02 October 2018) "A2LA Policy on Metrological Traceability".

7.4 Test Environmental Conditions

Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.7 KPa

The testing was performed by Christian McCaig on 2020-08-12 in 5m chamber 3.


7.5 Test Results

99% and 6 dB Bandwidth


Channel	Frequency (MHz)	99% OBW (MHz)	6 dB BW (kHz)	6 dB BW limit (kHz)
Low	2402	1.05	703	>500
Middle	2426	1.06	709	>500
High	2480	1.05	695	>500

Please refer to the following plots.


2402 MHz 99% OBW




2426 MHz 99% OBW



2480 MHz 99% OBW




2402 MHz 6 dB OBW



2426 MHz 6 dB OBW



2480 MHz 6 dB OBW



8 FCC §15.247(b) (3) & ISEDC RSS-247 §5.4 (4) - Output Power Measurement

8.1 Applicable Standards

According to FCC §15.247(b)(3): For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

According to RSS-247 §5.4(d): For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

8.2 Measurement Procedure

The measurements were based on FCC KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.3: DTS fundamental emission output power, 8.3.1.1 RBW \geq DTS bandwidth, and ANSI C63.10 Subclause 11.9.1. RBW \geq DTS bandwidth.

Corrected Average Field Strength (dB μ V/m) = Measured Average Field Strength (dB μ V) + Cable Loss (dB) + Antenna Factor (dB/m)

EIRP (dBm) = Field Strength (dB μ V/m) + 20log(D(m)) - 104.77

Conducted Output Power = EIRP – Antenna Gain

8.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Spectrum Analyzer	E4446A	MY48250238	2019-06-26	18 months
Sunol Sciences	System Controller	SC99V	011003-1	N/R	N/A
IW Microwave	150 Series 2.92mm Cable	KPS1501AN-3780-KPS	DC 1925	2019-09-11	1 year
ETS Lindgren	Horn Antenna	3117	00218973	2019-02-13	2 years

Statement of Traceability: *BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 02 October 2018) "A2LA Policy on Metrological Traceability".*

8.4 Test Environmental Conditions

Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.7 KPa

The testing was performed by Christian McCaig on 2020-08-12 in 5m chamber 3.

8.5 Test Results


Output Power

Channel	Frequency (MHz)	Measured Average Field Strength (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Corrected Average Field Strength (dBμV/m at 3m)	Conversion Factor (dB)	E.I.R.P (dBm)	Antenna Gain (dBi)	Conducted Output Power (dBm)	Limit (dBm)
Low	2402	69.63	32	5.72	107.35	-95.23	12.12	4.4	7.72	30
Middle	2426	68.39	32.2	6.09	103.68	-95.23	8.45	4.4	4.05	30
High	2480	68.30	32.2	5.44	105.94	-95.23	10.71	4.4	6.31	30


Note: Measured at 3 meters.

Please refer to the following plots.


2402 MHz OP



2426 MHz OP



2480 MHz OP



9 FCC §15.247(d) and ISEDC RSS-247 §5.5 – 100 kHz Bandwidth of Band Edges

9.1 Applicable Standards

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to ISEDC RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

9.2 Measurement Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.7: DTS band-edge emission measurements.

9.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Spectrum Analyzer	E4446A	MY48250238	2019-06-26	18 months
Sunol Sciences	System Controller	SC99V	011003-1	N/R	N/A
IW Microwave	150 Series 2.92mm Cable	KPS1501AN-3780-KPS	DC 1925	2019-09-11	1 year
ETS Lindgren	Horn Antenna	3117	00218973	2019-02-13	2 years

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 02 October 2018) “A2LA Policy on Metrological Traceability”.


9.4 Test Environmental Conditions

Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.7 KPa


The testing was performed by Christian McCaig on 2020-08-12 in 5m chamber 3.

9.5 Test Results

2402 MHz



2480 MHz



10 FCC §15.247(e) & ISEDC RSS-247 §5.2(2) - Power Spectral Density

10.1 Applicable Standards

According to FCC §15.247(e) and RSS-247 §5.2(b), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

10.2 Measurement Procedure

The measurements were based on FCC KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.4: DTS maximum power spectral density level in the fundamental emission, and ANSI C63.10 Subclause 11.10.2 Method PKPSD.

Corrected Average Field Strength (dBμV/m) = Measured Average Field Strength (dBμV) + Cable Loss (dB) + Antenna Factor (dB/m)

EIRP (dBm) = Field Strength (dBμV/m) + 20log(D(m)) - 104.77

Conducted Output Power = EIRP – Antenna Gain

10.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Spectrum Analyzer	E4446A	MY48250238	2019-06-26	18 months
Sunol Sciences	System Controller	SC99V	011003-1	N/R	N/A
IW Microwave	150 Series 2.92mm Cable	KPS1501AN-3780-KPS	DC 1925	2019-09-11	1 year
ETS Lindgren	Horn Antenna	3117	00218973	2019-02-13	2 years

Statement of Traceability: *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 02 October 2018) “A2LA Policy on Metrological Traceability”.

10.4 Test Environmental Conditions

Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.7 KPa

The testing was performed by Christian McCaig on 2020-08-12 in 5m chamber 3.


10.5 Test Results

Channel Frequency (MHz)	Measured Average Field Strength (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Corrected Average Field Strength (dB μ V/m at 3m)	E.I.R.P (dBm)	Antenna Gain (dBi)	Duty Cycle Correction Factor (dB)	Average PSD (dBm/3 kHz)	Limit (dBm/3 kHz)
2402	54.42	32	5.72	92.14	-3.09	4.4	0.7	-6.79	8
2426	52.97	32.2	6.09	91.26	-3.97	4.4	0.7	-7.67	8
2480	53.21	32.2	5.44	90.85	-4.38	4.4	0.7	-8.08	8


Note: Measurements made at 3 meters

Please refer to the following plots.


2402 MHz PSD



2426 MHz PSD



2480 MHz PSD



11 Annex A - EUT Photographs

Please see attachments:

- Exhibit – EUT Test Setup Photographs
- Exhibit – EUT External Photographs
- Exhibit – EUT Internal Photographs

12 Annex B (Normative) - A2LA Electrical Testing Certificate

Please follow the web link below for a full ISO 17025 scope

<https://www.a2la.org/scopepdf/3297-02.pdf>

--- END OF REPORT ---