

# FCC TEST REPORT

For

Limitless Innovations, Inc

Wireless Charger Power Bank

Model No.: W11, CRG-WPB-C-001

Prepared For : Limitless Innovations, Inc  
Address : 4800 Metalmaster Way, McHenry, Illinois, United States 60050

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited  
Address : 1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102  
Tel: (86) 755-26066440 Fax: (86) 755-26014772

Report Number : SZAWW180905001-01

Date of Receipt : Sept. 05, 2018

Date of Test : Sept. 05~Nov. 28, 2018

Date of Report : Nov. 28, 2018

# Contents

1. General Information.....	4
1.1. Client Information.....	4
1.2. Description of Device (EUT).....	4
1.3. Auxiliary Equipment Used During Test.....	4
1.4. Description of Test Modes.....	5
1.5. Description Of Test Setup.....	6
1.6. Test Equipment List.....	7
1.7. Description of Test Facility.....	8
2. Summary of Test Results.....	9
3. Conducted Emission Test.....	10
3.1. Test Standard and Limit.....	10
3.2. Test Setup.....	10
3.3. Test Procedure.....	10
3.4. Test Data.....	10
4. Radiation Spurious Emission and Band Edge.....	15
4.1. Test Standard and Limit.....	15
4.2. Test Setup.....	15
4.3. Test Procedure.....	16
4.4. Test Data.....	17
5. Antenna Requirement.....	21
5.1. Test Standard and Requirement.....	21
5.2. Antenna Connected Construction.....	21
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	22
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	24
APPENDIX III -- INTERNAL PHOTOGRAPH.....	28

# TEST REPORT

Applicant : Limitless Innovations, Inc  
Manufacturer : Shenzhen Orebo Technologies Ltd.  
Product Name : Wireless Charger Power Bank  
Model No. : W11, CRG-WPB-C-001  
Trade Mark : N.A.  
Rating(s) : Input: DC 5V, 2A  
Wireless Output: 5W  
USB output: DC 5V, 2A  
(with DC 3.7V, 5000mAh Battery inside)

**Test Standard(s) : FCC Part15 Subpart C 2018, Paragraph 15.209**

**Test Method(s) : ANSI C63.10: 2013**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test : Sept. 05~Nov. 28, 2018

Prepared By



*Oliay Yang*

(Engineer / Oliay Yang)

Reviewer

*Snowy Meng*

(Supervisor / Snowy Meng)

Approved & Authorized Signer

*Sally Zhang*

(Manager / Sally Zhang)

# 1. General Information

## 1.1. Client Information

Applicant	:	Limitless Innovations, Inc
Address	:	4800 Metalmaster Way, McHenry, Illinois, United States 60050
Manufacturer	:	Shenzhen Orebo Technologies Ltd.
Address	:	Room 616-617, Building B, Cheng shi shan hai Centre, ZhongXing Road, Bantian Town, Longgang dist, Shenzhen, 518129 China
Factory	:	Shenzhen Orebo Technologies Ltd.
Address	:	Room 616-617, Building B, Cheng shi shan hai Centre, ZhongXing Road, Bantian Town, Longgang dist, Shenzhen, 518129 China

## 1.2. Description of Device (EUT)

Product Name	:	Wireless Charger Power Bank	
Model No.	:	W11, CRG-WPB-C-001 (Note: All samples are the same except the name, so we prepare "W11" for test only.)	
Trade Mark	:	N.A.	
Test Power Supply	:	AC 240V, 60Hz for adapter/ AC 120V, 60Hz for adapter/ DC 3.7V battery inside	
Test Sample No.	:	S1(Normal Sample), S2(Engineering Sample)	
Product Description	:	Operation Frequency:	111~205KHz
	:	Modulation Type:	MSK
	:	Antenna Type:	Inductive loop coil Antenna
	:	Antenna Gain(Peak):	0 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.			

## 1.3. Auxiliary Equipment Used During Test

Adapter	:	Manufacturer: Samsung M/N: ETA-U90CBC S/N: RT6FB17ZS/B-E Input: 100-240V~ 50-60Hz, 0.35A Output: DC 5V, 2A
Mouse	:	Model: WM-799W

### 1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Charge+TX Mode
Mode 2	TX Mode



For Conducted Emission	
Final Test Mode	Description
Mode 1	Charge+TX Mode
Mode 2	TX Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	Charge+TX Mode
Mode 2	TX Mode

Note: (1) Test channel is 0.1439MHz.

(2) All the situation (full load, half load and empty load) has been tested, only the worst situation (full load) was recorded in the report.

### 1.5. Description Of Test Setup



### 1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 05, 2018	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESPI3	101604	Nov. 05, 2018	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 05, 2018	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	Nov. 05, 2018	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 05, 2018	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Nov. 05, 2018	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 19, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 19, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 19, 2018	1 Year
10.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Nov. 20, 2018	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Nov. 05, 2018	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 05, 2018	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 05, 2018	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 05, 2018	1 Year
16.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 05, 2018	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 05, 2018	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 05, 2018	1 Year
19.	DC Power Supply	IVYTECH	IV3605	1804D360510	Apr. 02, 2018	1 Year
20.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Nov. 01, 2018	1 Year

## 1.7. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### **FCC-Registration No.: 184111**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

### **ISED-Registration No.: 8058A-1**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

### **Test Location**

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



## 2. Summary of Test Results

Standard Section	Test Item	Result
FCC Part 15, Paragraph 15.207	Conducted Emission Test	PASS
FCC Part 15, Paragraph 15.209(a)(f)	Spurious Emission	PASS
Part 15.203	Antenna Requirement	PASS


### 3. Conducted Emission Test

#### 3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
5MHz~30MHz	60	50	

**Remark:** (1) \*Decreasing linearly with logarithm of the frequency.  
(2) The lower limit shall apply at the transition frequency.

#### 3.2. Test Setup



#### 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

#### 3.4. Test Data

Please to see the following pages

**Conducted Emission Test Data**


Test Site: 1# Shielded Room  
 Operating Condition: Mode 1  
 Test Specification: AC 240V, 60Hz for adapter  
 Comment: Live Line  
 Tem.: 22.2°C Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2020	19.18	19.90	39.08	53.52	-14.44	AVG	
2	0.2060	33.81	19.90	53.71	63.36	-9.65	QP	
3	0.2620	14.05	19.89	33.94	51.36	-17.42	AVG	
4	0.4100	26.58	19.94	46.52	57.65	-11.13	QP	
5	0.4340	25.75	19.95	45.70	57.18	-11.48	QP	
6	0.5420	11.98	19.99	31.97	46.00	-14.03	AVG	
7	0.5620	27.72	20.00	47.72	56.00	-8.28	QP	
8	0.8620	10.07	20.08	30.15	46.00	-15.85	AVG	
9	1.6700	24.01	20.13	44.14	56.00	-11.86	QP	
10	1.7220	8.42	20.13	28.55	46.00	-17.45	AVG	
11	2.4020	24.34	20.15	44.49	56.00	-11.51	QP	
12	2.4700	9.60	20.15	29.75	46.00	-16.25	AVG	

**Conducted Emission Test Data**


Test Site: 1# Shielded Room  
 Operating Condition: Mode 1  
 Test Specification: AC 240V, 60Hz for adapter  
 Comment: Neutral Line  
 Tem.: 22.2°C Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1860	32.06	19.90	51.96	64.21	-12.25	QP	
2	0.6180	14.23	20.02	34.25	46.00	-11.75	AVG	
3	0.6220	28.28	20.02	48.30	56.00	-7.70	QP	
4	0.9460	13.77	20.11	33.88	46.00	-12.12	AVG	
5	0.9540	28.22	20.11	48.33	56.00	-7.67	QP	
6	1.2540	24.82	20.13	44.95	56.00	-11.05	QP	
7	1.2940	9.62	20.13	29.75	46.00	-16.25	AVG	
8	1.7100	11.64	20.13	31.77	46.00	-14.23	AVG	
9	1.8780	25.08	20.14	45.22	56.00	-10.78	QP	
10	2.4219	24.95	20.15	45.10	56.00	-10.90	QP	
11	2.4660	12.32	20.15	32.47	46.00	-13.53	AVG	
12	4.3740	10.65	20.19	30.84	46.00	-15.16	AVG	

**Conducted Emission Test Data**


Test Site: 1# Shielded Room  
 Operating Condition: Mode 1  
 Test Specification: AC 120V, 60Hz for adapter  
 Comment: Live Line  
 Tem.: 22.2°C Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2779	27.98	19.89	47.87	60.88	-13.01	QP	
2	0.2779	14.31	19.89	34.20	50.88	-16.68	AVG	
3	0.3180	11.90	19.90	31.80	49.76	-17.96	AVG	
4	0.3379	25.35	19.91	45.26	59.25	-13.99	QP	
5	0.4820	26.40	19.97	46.37	56.30	-9.93	QP	
6	0.4820	11.22	19.97	31.19	46.30	-15.11	AVG	
7	0.6820	24.93	20.03	44.96	56.00	-11.04	QP	
8	0.6900	9.46	20.04	29.50	46.00	-16.50	AVG	
9	1.6620	23.05	20.13	43.18	56.00	-12.82	QP	
10	2.2340	22.40	20.14	42.54	56.00	-13.46	QP	
11	2.3540	6.96	20.15	27.11	46.00	-18.89	AVG	
12	3.6420	7.47	20.17	27.64	46.00	-18.36	AVG	

**Conducted Emission Test Data**

Test Site: 1# Shielded Room  
 Operating Condition: Mode 1  
 Test Specification: AC 120V, 60Hz for adapter  
 Comment: Neutral Line  
 Tem.: 22.2°C Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.3220	25.72	19.90	45.62	59.65	-14.03	QP	
2	0.3220	11.73	19.90	31.63	49.65	-18.02	AVG	
3	0.3780	10.00	19.93	29.93	48.32	-18.39	AVG	
4	0.4060	25.40	19.94	45.34	57.73	-12.39	QP	
5	0.8740	12.51	20.09	32.60	46.00	-13.40	AVG	
6	0.9180	27.10	20.10	47.20	56.00	-8.80	QP	
7	1.2220	22.93	20.12	43.05	56.00	-12.95	QP	
8	1.7820	9.42	20.14	29.56	46.00	-16.44	AVG	
9	1.9300	23.64	20.14	43.78	56.00	-12.22	QP	
10	2.3580	22.07	20.15	42.22	56.00	-13.78	QP	
11	2.3580	9.56	20.15	29.71	46.00	-16.29	AVG	
12	3.5580	8.78	20.17	28.95	46.00	-17.05	AVG	

## 4. Radiation Spurious Emission and Band Edge

### 4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	-	74.0	Peak

**Remark:**

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

### 4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

### 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:



RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

#### 4.4. Test Data


**PASS**

Note: The data is in TX mode, and this is the worst mode.

**Test Results**

(Between 9KHz – 30MHz)

<b>Job No.:</b>	<b>SZAWW180905001-01</b>		
<b>Standard:</b>	<b>FCC PART15 C_3m</b>	<b>Power Source:</b>	<b>AC 120V, 60Hz for adapter</b>
<b>Test item:</b>	<b>Radiation Test</b>	<b>Temp.(C)/Hum.(%RH):</b>	<b>24.7°C/51%RH</b>
<b>Test Mode:</b>	<b>Mode 2</b>	<b>Distance:</b>	<b>3m</b>



Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	degree
									(dge)
0.0792	30.93	19.30	2.54	0	52.77	129.54	-76.77	Peak	217
0.0792	17.61	19.30	2.54	0	39.45	109.54	-70.09	AV	217
0.1439	58.51	19.53	2.59	0	80.63	124.38	-43.75	Peak	53
0.1439	49.05	19.53	2.59	0	71.17	104.38	-33.21	AV	53
0.2740	38.87	19.53	2.59	0	60.99	118.82	-57.83	Peak	269
0.2740	28.95	19.53	2.59	0	51.07	98.82	-47.75	AV	269
0.5260	29.15	20.34	2.59	0	52.08	73.18	-21.10	QP	328
1.2459	15.10	20.87	2.70	0	38.67	65.69	-27.02	QP	46
7.8700	12.49	21.33	2.91	0	36.73	69.54	-32.81	QP	118

**Remark:** According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.


(Between 30MHz -1000 MHz)

**Job No.:** SZAWW180905001-01      **Polarization:** Horizontal  
**Standard:** FCC PART15 C\_3m      **Power Source:** DC 3.7V battery inside  
**Test item:** Radiation Test      **Temp.(C)/Hum.(%RH):** 24.3°C/55%RH  
**Test Mode:** Mode 2      **Distance:** 3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	92.7871	58.37	-22.13	36.24	43.50	-7.26	QP	300	0	
2	103.8055	58.35	-20.71	37.64	43.50	-5.86	QP	300	96	
3	173.8135	52.80	-19.67	33.13	43.50	-10.37	QP	300	165	
4	241.6763	55.61	-17.58	38.03	46.00	-7.97	QP	300	214	
5	311.0867	50.06	-16.34	33.72	46.00	-12.28	QP	300	296	
6	344.3855	48.75	-14.17	34.58	46.00	-11.42	QP	300	360	

**Job No.:** SZAWW180905001-01      **Polarization:** Vertical  
**Standard:** FCC PART15 C\_3m      **Power Source:** DC 3.7V battery inside  
**Test item:** Radiation Test      **Temp.(C)/Hum.(%RH):** 24.3°C/55%RH  
**Test Mode:** Mode 2      **Distance:** 3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	40.2757	48.54	-13.43	35.11	40.00	-4.89	QP	300	0	
2	86.8068	54.95	-17.71	37.24	40.00	-2.76	QP	300	74	
3	92.1388	56.39	-16.40	39.99	43.50	-3.51	QP	300	114	
4	124.8966	56.36	-16.06	40.30	43.50	-3.20	QP	300	196	
5	159.2251	53.62	-16.91	36.71	43.50	-6.79	QP	300	256	
6	229.2931	50.93	-13.93	37.00	46.00	-9.00	QP	300	360	

## 5. Antenna Requirement

### 5.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard

### 5.2. Antenna Connected Construction

The antenna is a Inductive loop coil Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.





## APPENDIX I-- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement



Photo of Radiation Emission Test







## APPENDIX II -- EXTERNAL PHOTOGRAPH















### APPENDIX III -- INTERNAL PHOTOGRAPH







----- End of Report -----