



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: AMI Global LLC

Model: VAPOR-C & Cornell PILOT

Description: Smart Communication Gateway

Serial Number: NA

FCC ID: 2AQ9C-VAPOR-C18

To

FCC Part 1.1310

Date of Issue: February 14, 2019

On the behalf of the applicant:

**AMI Global LLC
6280 S. Valley View Blvd.
Suite 212
Las Vegas, NV 89118**

Attention of:

**Ori Peled, CTO
Ph: (702)478-9700
Email: opeled@amiglobal.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1870005**

**Poona Saber
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	September 20, 2018	Poona Saber	Original Document
2.0	January 15, 2019	Poona Saber	Revised calculation on page 4 Updated model & description
3.0	February 12, 2019	Poona Saber	Revised equation on page 4, revised model on page 1 & 3



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: VAPOR-C & Cornell PILOT

Description: Smart Communication Gateway

Firmware: N/A

Software: N/A

Serial Number: N/A

Additional Information: Device under test is a vibration/temperature monitoring which updates its data to the cloud using different communication modes- the 900 MHz radio with frequency range of 903.9-925.9. The antenna used with 900 MHz transceiver is permanently on the board and it has a 2 dBi gain.



Below is Calculation for SAR exclusion per KDB 447498.

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* $\leq$ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁶
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is $\leq$ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is $<$ 5 mm, a distance of 5 mm according to 5) in section 4.1 in KDB 447498 is applied to determine SAR test exclusion.

The Maximum output power per manufacturer declaration is -5.06 dBm.

$$\frac{0.3 \text{ mW}}{5 \text{ mm}} \cdot \sqrt{0.9139 \text{ GHz}} = 0.06$$

Since the above number is below 1-g SAR limit this device is excluded for SAR measurements

END OF TEST REPORT