

## FCC SAR TEST REPORT

For

**Product Name: Wireless digital flat panel detector**

**Brand Name: N/A**

**Model No.: Mars1717XU-VSI**

**Series Model: N/A**

**FCC ID: 2AQ9VMARS1717XU**

**Test Report Number:  
C180928E08-SF**

**Issued for**

**Shanghai United Imaging Healthcare Co., Ltd.  
2258 Chengbei Rd., Jiading District, Shanghai**

**Issued by**

**Compliance Certification Services Inc.**

**Kun shan Laboratory**

**No.10 Weiye Rd., Innovation park, Eco&Tec,  
Development Zone, Kunshan City, Jiangsu, China**

**TEL: 86-512-57355888**

**FAX: 86-512-57370818**



**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.

## Revision History

Revision	REPORT NO.	Date	Page Revised	Contents
Original	C180928E08-SF	November 12, 2018	N/A	N/A

**TABLE OF CONTENTS**

<b>1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION)</b>	<b>4</b>
<b>2. EUT DESCRIPTION</b>	<b>5</b>
2.1 MAXIMUM RF OUTPUT POWER WITH TEST CHANNEL	6
2.2 EUT ANTENNA LOCATIONS	8
2.3 STATEMENT OF COMPLIANCE	9
<b>3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC</b>	<b>10</b>
<b>4. TEST METHODOLOGY</b>	<b>10</b>
<b>5. TEST CONFIGURATION</b>	<b>10</b>
<b>6. DOSIMETRIC ASSESSMENT SETUP</b>	<b>11</b>
6.1 MEASUREMENT SYSTEM DIAGRAM	12
6.2 SYSTEM COMPONENTS	13
<b>7. EVALUATION PROCEDURES</b>	<b>16</b>
<b>8. MEASUREMENT UNCERTAINTY</b>	<b>20</b>
<b>9. EXPOSURE LIMIT</b>	<b>21</b>
<b>10. MEASUREMENT RESULTS</b>	<b>22</b>
10.1 TEST LIQUIDS CONFIRMATION	22
10.2 LIQUID MEASUREMENT RESULTS	23
10.3 SYSTEM PERFORMANCE CHECK	24
10.4 EUT TUNE-UP PROCEDURES AND TEST MODE	26
10.5 SAR TEST CONFIGURATIONS	32
10.6 ANTENNA LOCATION	33
10.7 BODY TEST EXCLUSION THRESHOLDS	34
10.8 SAR MEASUREMENT RESULTS	35
10.9 REPEATED SAR MEASUREMENT	37
10.10 SAR MULTI XMITER ASSESSMENT	38
<b>11. EQUIPMENT LIST &amp; CALIBRATION STATUS</b>	<b>40</b>
<b>12. FACILITIES</b>	<b>41</b>
<b>13. REFERENCES</b>	<b>41</b>
<b>14. LABORATORY ACCREDITATIONS AND LISTING</b>	<b>42</b>
<b>Appendix A: DUT and SAR Test setup</b>	<b>43</b>
<b>Appendix B: Plots of Performance Check</b>	<b>43</b>
<b>Appendix C: DASYS Calibration Certificate</b>	<b>50</b>
<b>Appendix D: Plots of SAR Test Result</b>	<b>50</b>

# 1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

<b>Product Name:</b>	Wireless digital flat panel detector
<b>Brand Name:</b>	N/A
<b>Model Name.:</b>	Mars1717XU-VSI
<b>Series Model:</b>	N/A
<b>Device Category:</b>	PORTABLE DEVICES
<b>Exposure Category:</b>	GENERAL POPULATION/UNCONTROLLED EXPOSURE
<b>Date of Test:</b>	November 7, 2018 & November 8, 2018
<b>Applicant:</b>	<b>Shanghai United Imaging Healthcare Co., Ltd.</b> 2258 Chengbei Rd., Jiading District, Shanghai
<b>Manufacturer:</b>	<b>iRay Technology Co., Ltd.</b> RM202, Building 7 No. 590, Ruiqing RD. Zhangjiang East, Pudong 201201 Shanghai, China
<b>Application Type:</b>	Certification

### APPLICABLE STANDARDS AND TEST PROCEDURES

STANDARDS AND TEST PROCEDURES	TEST RESULT
KDB 865664 D01	No non-compliance noted

### Deviation from Applicable Standard

None


The device was tested by Compliance Certification Services Inc. in accordance with the measurement methods and procedures specified in KDB 865664 The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

**Approved by:**



Jeff.fang  
RF Manager  
Compliance Certification Services Inc.

**Tested by:**



Sam.ye  
Test Engineer  
Compliance Certification Services Inc.

## 2. EUT DESCRIPTION

<b>Product Name:</b>	Wireless digital flat panel detector			
<b>Brand Name:</b>	N/A			
<b>Model Name.:</b>	Mars1717XU-VSI			
<b>Series Model:</b>	N/A			
<b>Model Discrepancy:</b>	N/A			
<b>FCC ID:</b>	2AQ9VMARS1717XU			
<b>Software version:</b>	Core:1.3. Kernel:1.18. FPGA:1.6. MCU:1.0.			
<b>Hardware version:</b>	V2.			
<b>Device Category:</b>	Production unit			
<b>Frequency Range:</b>	IEEE 802.11b/g/n HT20:2412MHz to 2462 MHz IEEE 802.11n HT40:2422MHz to 2452 MHz IEEE 802.11 5.2GHz Band: 5180 MHz ~ 5220 MHz IEEE 802.11 5.8GHz Band: 5745 MHz ~ 5825 MHz			
<b>Modulation Technique:</b>	2.4GHz: IEEE802.11b mode: DSSS (1,2,5.5 and 11 Mbps) IEEE802.11g mode: OFDM (6,9,12,18,24,36,48 and 54 Mbps) IEEE802.11n HT20 mode: OFDM (MCS0~MCS15) IEEE802.11n HT40 mode: OFDM (MCS0~MCS15) 5GHz: IEEE802.11a mode: OFDM (6,9,12,18,24,36,48 and 54 Mbps) IEEE802.11n HT20 mode: OFDM (MCS0~MCS15) IEEE802.11n HT40 mode: OFDM (MCS0~MCS15) IEEE802.11ac VHT20 mode: OFDM (VHTMCS0~VHTMCS0) IEEE802.11ac VHT40 mode: OFDM (VHTMCS0~VHTMCS9)			
<b>Antenna Type:</b>	FPC			
<b>Antenna Specification:</b>		Gain(dBi)		
		2.4G	Band I	BandIV
	Antenna 1	5.0	7.1	6.7
	Antenna 2	4.6	4.6	6.1
	Directional gain	7.81	9.04	9.42
<b>Accessories:</b>	Input: 12V 2.5A Capacitance 1: 3.8V-2.2V 2100F 2.8Wh Capacitance 2: 3.8V-2.2V 2100F 2.8Wh Capacitance 1+ Capacitance 2: 7.6V-4.4V			
<b>Operating Mode:</b>	Maximum continuous output			

**2.1 MAXIMUM RF OUTPUT POWER WITH TEST CHANNEL**


2.4GHz:

Band / Mode	Channel	ANT1 Average Tune-up power(dBm)	ANT2 Average Tune-up power(dBm)
802.11b	1	12	14
	6	12	14
	11	12	14
802.11g	1	11.5	13
	6	11.5	13
	11	11.5	13
802.11n 20MHz	1	11.5	13.5
	6	11.5	13.5
	11	11.5	13.5
802.11n 40MHz	3	9	11.5
	6	9	11.5
	9	9	11.5

5GHz:

Band / Mode	Channel	ANT1 Average Tune-up power(dBm)	ANT2 Average Tune-up power(dBm)
802.11a	36	13	13
	40	13	13
	44	13	13
	149	13.5	13
	157	13.5	13
	165	13.5	13
802.11n 20MHz	36	11	10.5
	40	11	10.5
	44	11	10.5
	149	13	12
	157	13	12
	165	13	12
802.11n 40MHz	38	10.5	10.5
	151	11	11
	159	11	11
802.11ac 20MHz	36	11	10.5
	40	11	10.5
	44	11	10.5
	149	13	12
	157	13	12
	165	13	12
802.11ac 40MHz	38	10.5	10.5
	151	11	11
	159	11	11

2.2 EUT ANTENNA LOCATIONS



Area Scan For SAR Testing

Antenna \ Area Scan	Scan 1	Scan 2	Scan 3	Scan 4
Antenna 1	Yes	Yes	Yes	Yes
Antenna 2	Yes	Yes	Yes	Yes

Note:802.11a/b/g does not support MIMO.



### 2.3 STATEMENT OF COMPLIANCE

The maximum results of Specific Absorption Rate (SAR) found during testing for **iRay Technology company Limited, Mars1717XU-VSI**, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary	
		Body 1g SAR (W/kg)	Head 1g SAR (W/kg)
DTS	2.4GHz WLAN	0.08	0.07
NII	5.2GHz WLAN	0.10	0.08
NII	5.8GHz WLAN	0.14	0.11
Highest Simultaneous Transmission SAR		Body 1g SAR (W/kg)	Head 1g SAR (W/kg)
DTS+DTS		0.16	0.13
NII+NII		0.28	0.21

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1999, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.

### 3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/Kg for an uncontrolled environment and 8.0 W/Kg for an occupational/controlled environment as recommended by the FCC 47 CFR Part 2 ( 2.1093).

### 4. TEST METHODOLOGY

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 ( 2.1093)
- ANSI/IEEE C95.1-1999
- IEEE 1528-2013
- KDB 447498 D01v06 General RF Exposure Guidance
- KDB 865664 D01v01r04 Measurement 100 MHz to 6 GHz
- KDB 865664 D02 v01r02 RF Exposure Reporting
- KDB 248227 D01v02r02 802 11 Wi-Fi SAR

### 5. TEST CONFIGURATION

During WLAN SAR testing EUT is configured with the WLAN continuous TX tool, and the transmission duty factor was monitored on the spectrum analyzer with zero-span setting For WLAN SAR testing, WLAN engineering test software installed on the EUT can provide continuous transmitting RF signal.

Duty cycle Form

Band	Mode	Duty cycle(100%)
2.4GHz	802.11b	100
	802.11g	100
	802.11n 20MHz	100
	802.11n 40MHz	100
5GHz	802.11a	100
	802.11n 20MHz	100
	802.11n 40MHz	100
	802.11ac 20MHz	100
	802.11ac 40MHz	100

## 6. DOSIMETRIC ASSESSMENT SETUP

These measurements were performed with the automated near-field scanning system DASY 5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m), which positions the probes with a positional repeatability of better than  $\pm 0.02$  mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the E-field PROBE EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in [7] with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure described in [8] and found to be better than  $\pm 0.25$  dB. IEEE1528 and CENELEC EN 62209.


The following table gives the recipes for tissue simulating liquids.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

### Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2

## 6.1 MEASUREMENT SYSTEM DIAGRAM



The DASYS system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASYS software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.

## 6.2 SYSTEM COMPONENTS



The DASYS measurement server is based on a PC/104 CPU board with a 400MHz intel ULV celeron, 128MB chip-disk and 128 MB RAM. The necessary circuits for communication with either the DAE4(or DAE3) electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASYS I/O-board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.



The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.

### Data Acquisition Electronics (DAE)



The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200M $\Omega$ ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

### EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements



**Construction:** Symmetrical design with triangular core  
Built-in shielding against static charges  
PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

**Calibration:** Basic Broad Band Calibration in air: 10-3000 MHz.  
Conversion Factors (CF) for HSL 900 and HSL 1800  
CF-Calibration for other liquids and frequencies upon request.

**Frequency:** 10 MHz to > 6 GHz; Linearity:  $\pm 0.2$  dB (30 MHz to 3 GHz)

**Directivity:**  $\pm 0.3$  dB in HSL (rotation around probe axis)  
 $\pm 0.5$  dB in HSL (rotation normal to probe axis)

**Dynamic Range:** 10  $\mu$ W/g to > 100 mW/g; Linearity:  $\pm 0.2$  dB  
(noise: typically < 1  $\mu$ W/g)

**Dimensions:** Overall length: 337 mm (Tip: 9 mm)  
Tip diameter: 2.5 mm (Body: 10 mm)  
Distance from probe tip to dipole centers:  
1 mm

**Application:** High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



Interior of probe

### SAM Twin Phantom

**Construction:**

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC 50360 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.



**Shell Thickness:**  $2 \pm 0.2$  mm

**Filling Volume:** Approx. 25 liters

**Dimensions:** Height: 850mm; Length: 1000mm; Width: 750mm

### SAM Phantom (ELI4 v4.0)

**Description Construction:**

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5.5 and higher and is compatible with all SPEAG dosimetric probes and dipoles



**Shell Thickness:**  $2.0 \pm 0.2$  mm (sagging: <1%)

**Filling Volume:** Approx. 25 liters

**Dimensions:** Major ellipse axis: 600 mm

**Minor axis:** 400 mm 500mm

**Device Holder for SAM Twin Phantom**

**Construction:** In combination with the Twin SAM Phantom, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).



**System Validation Kits for SAM Twin Phantom**

**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 900, 1800, 2450, 5800 MHz

**ReTune loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:**

- D835V2: dipole length: 161 mm; overall height: 340 mm
- D1800V2: dipole length: 72.5 mm; overall height: 300 mm
- D1900V2: dipole length: 67.7 mm; overall height: 300 mm
- D2450V2: dipole length: 51.5 mm; overall height: 290 mm
- D5GHzV2: dipole length: 20.6 mm; overall height: 300mm



**System Validation Kits for ELI4 phantom**

**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 900, 1800, 2450, 5800 MHz

**ReTune loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:**

- D835V2: dipole length: 161 mm; overall height: 340 mm
- D1800V2: dipole length: 72.5 mm; overall height: 300 mm
- D1900V2: dipole length: 67.7 mm; overall height: 300 mm
- D2450V2: dipole length: 51.5 mm; overall height: 290 mm
- D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm



## 7. EVALUATION PROCEDURES

### DATA EVALUATION

The DASY 5 post processing software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	$dcp_i$
Device parameters:	- Frequency	$f$
	- Crest factor	$cf$
Media parameters:	- Conductivity	$\sigma$
	- Density	$\rho$

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY 5 components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	$V_i$	= Compensated signal of channel i (i = x, y, z)
	$U_i$	= Input signal of channel i (i = x, y, z)
	$cf$	= Crest factor of exciting field (DASY 5 parameter)
	$dcp_i$	= Diode compression point (DASY 5 parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes:

$$H_i = \sqrt{V_i} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$$

with	$V_i$	= Compensated signal of channel i (i = x, y, z)
	$Norm_i$	= Sensor sensitivity of channel i (i = x, y, z) $\mu V/(V/m)^2$ for E0field Probes
	$ConvF$	= Sensitivity enhancement in solution
	$a_{ij}$	= Sensor sensitivity factors for H-field probes
	$f$	= Carrier frequency (GHz)
	$E_i$	= Electric field strength of channel i in V/m
	$H_i$	= Magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):



$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with  $SAR$  = local specific absorption rate in mW/g  
 $E_{tot}$  = total field strength in V/m  
 $\sigma$  = conductivity in [mho/m] or [Siemens/m]  
 $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with  $P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>  
 $E_{tot}$  = total electric field strength in V/m  
 $H_{tot}$  = total magnetic field strength in A/m

## **SAR EVALUATION PROCEDURES**

The procedure for assessing the peak spatial-average SAR value consists of the following steps:

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY 5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures 5 x 5 x 7 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

- **Power Drift measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY 5 software stop the measurements if this limit is exceeded.

- **Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.

## SPATIAL PEAK SAR EVALUATION

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1529 standard. It can be conducted for 1 g and 10 g.

The DASY 5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

### Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.

Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 5x5x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

### Boundary effect

For measurements in the immediate vicinity of a phantom surface, the field coupling effects between the probe and the boundary influence the probe characteristics. Boundary effect errors of different dosimetric probe types have been analyzed by measurements and using a numerical probe model. As expected, both methods showed an enhanced sensitivity in the immediate vicinity of the boundary. The effect strongly depends on the probe dimensions and disappears with increasing distance from the boundary. The sensitivity can be approximately given as:

$$S \approx S_o + S_b \exp\left(-\frac{z}{a}\right) \cos\left(\pi \frac{z}{\lambda}\right)$$

Since the decay of the boundary effect dominates for small probes ( $a \ll \lambda$ ), the cos-term can be omitted. Factors  $S_b$  (parameter Alpha in the DASY 5 software) and  $a$  (parameter Delta in the DASY 5 software) are assessed during probe calibration and used for numerical compensation of the boundary effect. Several simulations and measurements have confirmed that the compensation is valid for different field and boundary configurations.

This simple compensation procedure can largely reduce the probe uncertainty near boundaries. It works well as long as:

- the boundary curvature is small
- the probe axis is angled less than 30° to the boundary normal
- the distance between probe and boundary is larger than 25% of the probe diameter
- the probe is symmetric (all sensors have the same offset from the probe tip)

Since all of these requirements are fulfilled in a DASY 5 system, the correction of the probe boundary effect in the vicinity of the phantom surface is performed in a fully automated manner via the measurement data extraction during post processing.

## 8. MEASUREMENT UNCERTAINTY

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04, when the highest measured 1-g SAR within a frequency band is  $< 1.5$  W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

## 9. EXPOSURE LIMIT

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

**Note:** **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

**Population/Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Occupational/Controlled Environments** are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

**NOTE**  
**GENERAL POPULATION/UNCONTROLLED EXPOSURE**  
**PARTIAL BODY LIMIT**  
**1.6 W/kg**

## 10. MEASUREMENT RESULTS

### 10.1 TEST LIQUIDS CONFIRMATION

#### SIMULATED TISSUE LIQUID PARAMETER CONFIRMATION

The dielectric parameters were checked prior to assessment using the SPEAG DAK3.5 dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

#### IEEE SCC-34/SC-2 P1528 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528

Target Frequency (MHz)	Head		Body	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ kg/m}^3$ )

**10.2 LIQUID MEASUREMENT RESULTS**

The following table show the measuring results for simulating liquid:


Liquid Type	Liquid Temp. (°C)	Parameters	Target	Measured	Deviation (%)	Limited (%)	Measured Date
Body2450	21.5	Permittivity( $\epsilon$ )	52.70	51.66	-1.97	$\pm 5$	2018/11/7
		Conductivity( $\sigma$ )	1.95	1.91	-2.00	$\pm 5$	
Head2450	21.5	Permittivity( $\epsilon$ )	39.20	38.78	-1.08	$\pm 5$	2018/11/7
		Conductivity( $\sigma$ )	1.80	1.80	0.11	$\pm 5$	
Body5200	21.5	Permittivity( $\epsilon$ )	49.03	48.85	-0.37	$\pm 5$	2018/11/8
		Conductivity( $\sigma$ )	5.35	5.34	-0.27	$\pm 5$	
Body5800	21.5	Permittivity( $\epsilon$ )	48.20	47.53	-1.39	$\pm 5$	2018/11/8
		Conductivity( $\sigma$ )	6.00	6.25	4.12	$\pm 5$	
Head5200	21.5	Permittivity( $\epsilon$ )	36.00	35.92	-0.21	$\pm 5$	2018/11/8
		Conductivity( $\sigma$ )	4.66	4.55	-2.40	$\pm 5$	
Head5800	21.5	Permittivity( $\epsilon$ )	35.30	34.47	-2.35	$\pm 5$	2018/11/8
		Conductivity( $\sigma$ )	5.27	5.21	-1.21	$\pm 5$	

### 10.3 SYSTEM PERFORMANCE CHECK

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications of  $\pm 10\%$ . The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

#### SYSTEM PERFORMANCE CHECK MEASUREMENT CONDITIONS

- The measurements were performed in the flat section of the SAM twin phantom filled with head and body simulating liquid of the following parameters.
- The DASY5 system with an E-field probe EX3DV4 SN: 3798 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 cm from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration ( $dx=5\text{ mm}$ ,  $dy=5\text{ mm}$ ,  $dz=5\text{ mm}$ ).
- Distance between probe sensors and phantom surface was set to 2 mm.
- The dipole less than 3G input power was  $250\text{mW}\pm 3\%$ .
- The dipole above than 3G input power was  $100\text{mW}\pm 3\%$ .
- The results are normalized to 1 W input power.



Note: For SAR testing, the liquid depth is 15cm shown above



**SYSTEM PERFORMANCE CHECK RESULTS**

Liquid Type	Ambient Temp. (°C)	Liquid Temp. (°C)	Input Power (W)	Measured SAR <sub>1g</sub> (W/Kg)	1W Target SAR <sub>1g</sub> (W/Kg)	1W Normalized SAR <sub>1g</sub> (W/Kg)	Deviation (%)	Limited (%)	Date
Body2450	22	21.5	0.25	12.90	51.50	51.60	0.19	± 10	2018/11/7
Head2450	22	21.5	0.25	12.70	51.70	50.80	-1.74	± 10	2018/11/7
Body5200	22	21.5	0.1	7.61	74.50	76.10	2.15	± 10	2018/11/8
Body5800	22	21.5	0.1	7.93	77.20	79.30	2.72	± 10	2018/11/8
Head5200	22	21.5	0.1	7.77	77.90	77.70	-0.26	± 10	2018/11/8
Head5800	22	21.5	0.1	7.56	78.60	75.60	-3.82	± 10	2018/11/8

**10.4 EUT TUNE-UP PROCEDURES AND TEST MODE****Conducted output power(dBm):****General Note:**

- 1 Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- 2 Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
  - 1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
  - 2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- 3 For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.

**WLAN 2.4G**

Mode	Channel	Frequency (MHZ)	Ant1 Target power(dBm)	Tune up tolerance (dBm)	Maximum Tune up power (dBm)	Ant1 Average power (dBm)
802.11 b	1	2412	11	±1	12	11.58
	6	2437	11	±1	12	11.56
	11	2462	11	±1	12	11.99
802.11 g	1	2412	10.5	±1	11.5	10.70
	6	2437	10.5	±1	11.5	11.05
	11	2462	10.5	±1	11.5	10.75
802.11 n 20MHz	1	2412	10.5	±1	11.5	11.02
	6	2437	10.5	±1	11.5	10.56
	11	2462	10.5	±1	11.5	10.95
802.11 n 40MHz	3	2422	8	±1	9	8.43
	6	2437	8	±1	9	8.63
	9	2452	8	±1	9	8.10

Mode	Channel	Frequency (MHZ)	Ant2 Target power(dBm)	Tune up tolerance (dBm)	Maximum Tune up power (dBm)	Ant2 Average power (dBm)
802.11 b	1	2412	13	±1	14	13.26
	6	2437	13	±1	14	13.31
	11	2462	13	±1	14	13.42
802.11 g	1	2412	12	±1	13	12.10
	6	2437	12	±1	13	12.29
	11	2462	12	±1	13	11.97
802.11 n 20MHz	1	2412	12.5	±1	13.5	13.22
	6	2437	12.5	±1	13.5	13.04
	11	2462	12.5	±1	13.5	13.20
802.11 n 40MHz	3	2422	10.5	±1	11.5	10.83
	6	2437	10.5	±1	11.5	11.04
	9	2452	10.5	±1	11.5	10.57

**MIMO:**

Mode	Channel	Frequency	ANT1+2 Average power(dBm)
802.11 n 20M	1	2412	15.27
	6	2437	14.98
	11	2462	15.23
802.11 n 40M	3	2422	12.80
	6	2437	13.01
	9	2452	12.52

**Remark:**

For 2.4G, 802.11n20/n40 modes, the EUT can transmit at both ANT1 and ANT2 simultaneously. When two chains transmit simultaneously in 802.11n20/n40 modes, the power of each chain will not beyond the power of 802.11 b mode.

**5GHz****U-NII-1**

Mode	Channel	Frequency (MHZ)	Ant1 Target power(dBm)	Tune up tolerance (dBm)	Maximum Tune up power (dBm)	Ant1 Average power (dBm)
802.11 a	36	5180	12	±1	13	12.70
	40	5200	12	±1	13	12.51
	44	5220	12	±1	13	12.53
802.11 n 20MHz	36	5180	10	±1	11	10.35
	40	5200	10	±1	11	10.63
	44	5220	10	±1	11	10.82
802.11 n 40MHz	38	5190	9.5	±1	10.5	10.40
802.11 ac 20MHz	36	5180	10	±1	11	10.33
	40	5200	10	±1	11	10.92
	44	5220	10	±1	11	10.82
802.11 ac 40MHz	38	5190	9.5	±1	10.5	10.25

Mode	Channel	Frequency (MHZ)	Ant2 Target power(dBm)	Tune up tolerance (dBm)	Maximum Tune up power (dBm)	Ant2 Average power (dBm)
802.11 a	36	5180	12	±1	13	12.30
	40	5200	12	±1	13	12.37
	44	5220	12	±1	13	12.70
802.11 n 20MHz	36	5180	9.5	±1	10.5	9.50
	40	5200	9.5	±1	10.5	9.61
	44	5220	9.5	±1	10.5	10.12
802.11 n 40MHz	38	5190	9.5	±1	10.5	10.07
802.11 ac 20MHz	36	5180	9.5	±1	10.5	9.69
	40	5200	9.5	±1	10.5	9.68
	44	5220	9.5	±1	10.5	10.04
802.11 ac 40MHz	38	5190	9.5	±1	10.5	10.15

**MIMO:**

Mode	Channel	Frequency	ANT1+2 Average power(dBm)
802.11 n 20MHz	36	5180	12.96
	40	5200	13.16
	44	5220	13.49
802.11 n 40MHz	38	5190	13.25
802.11 ac 20MHz	36	5180	13.03
	40	5200	13.35
	44	5220	13.46
802.11 ac 40MHz	38	5190	13.21

**Remark:**

For 5G, 802.11n20/n40/ac20/ac40 modes, the EUT can transmit at both ANT1 and ANT2 simultaneously. When two chains transmit simultaneously in 802.11n20/n40/ac20/ac40 modes, the power of each chain will not beyond the power of 802.11 a mode.

**U-NII-3**

Mode	Channel	Frequency (MHZ)	Ant1 Target power(dBm)	Tune up tolerance (dBm)	Maximum Tune up power (dBm)	Ant1 Average power (dBm)
802.11 a	149	5745	12.5	±1	13.5	12.93
	157	5785	12.5	±1	13.5	13.29
	165	5825	12.5	±1	13.5	12.10
802.11 n 20MHz	149	5745	12	±1	13	12.50
	157	5785	12	±1	13	12.76
	165	5825	12	±1	13	12.89
802.11 n 40MHz	151	5755	10	±1	11	10.81
	159	5795	10	±1	11	10.69
802.11 ac 20MHz	149	5745	12	±1	13	12.11
	157	5785	12	±1	13	12.47
	165	5825	12	±1	13	12.52
802.11 ac 40MHz	151	5755	10	±1	11	10.75
	159	5795	10	±1	11	10.87

Mode	Channel	Frequency (MHZ)	Ant2 Target power(dBm)	Tune up tolerance (dBm)	Maximum Tune up power (dBm)	Ant2 Average power (dBm)
802.11 a	149	5745	12	±1	13	12.57
	157	5785	12	±1	13	12.51
	165	5825	12	±1	13	12.06
802.11 n 20MHz	149	5745	11	±1	12	11.05
	157	5785	11	±1	12	11.50
	165	5825	11	±1	12	11.05
802.11 n 40MHz	151	5755	10	±1	11	10.22
	159	5795	10	±1	11	10.30
802.11 ac 20MHz	149	5745	11	±1	12	11.20
	157	5785	11	±1	12	10.80
	165	5825	11	±1	12	11.33
802.11 ac 40MHz	151	5755	10	±1	11	10.05
	159	5795	10	±1	11	10.18

**MIMO:**

Mode	Channel	Frequency	ANT1+2 Average power(dBm)
802.11 n 20MHz	149	5745	14.85
	157	5785	15.19
	165	5825	15.08
802.11 n 40MHz	151	5755	13.54
	159	5795	13.51
802.11 ac 20MHz	149	5745	14.69
	157	5785	14.73
	165	5825	14.98
802.11 ac 40MHz	151	5755	13.42
	159	5795	13.55

**Remark:**

For 5G, 802.11n20/n40/ac20/ac40 modes, the EUT can transmit at both ANT1 and ANT2 simultaneously. When two chains transmit simultaneously in 802.11n20/n40/ac20/ac40 modes, the power of each chain will not beyond the power of 802.11 a mode.

## 10.5 SAR TEST CONFIGURATIONS

### Generic device

For a device that can not be categorized as any of the other specific device types, it shall be considered to be a generic device; i.e. represented by a closed box incorporating at least one internal RF transmitter and antenna.

The SAR evaluation shall be performed for all surfaces of the DUT that are accessible during intended use, as indicated in Figure . The separation distance in testing shall correspond to the intended use distance as specified in the user instructions provided by the manufacturer.

If the intended use is not specified, all surfaces of the DUT shall be tested with the separation of  $\leq 5\text{mm}$ .





Figure – Test positions for a generic device



10.6 ANTENNA LOCATION



Device dimensions for Tablet mode (H x W): 460x 460 mm

Antennas	Wireless Interface
WLAN Antenna	WLAN 2.4GHz WLAN 5.2GHz WLAN 5.8GHz

**Test Mode**

IEEE 802.11	Data transmission mode(802.11a/b)
-------------	-----------------------------------

## 10.7 BODY TEST EXCLUSION THRESHOLDS

The following SAR test exclusion Thresholds based on KDB 447498 D01 General RF Exposure Guidance v06 4.3.1

Exposure Position	Wireless Interface	WLAN	WLAN
		802.11 b	802.11 a
	Maximum power	14	13.5
	Maximum rated power(mW)	25.12	22.39
Front	Antenna to user (mm)	5	5
	SAR exclusion threshold	9.58	6.23
	SAR testing required?	<b>Yes</b>	<b>Yes</b>
Rear	Antenna to user (mm)	-	-
	SAR exclusion threshold	-	-
	SAR testing required?	<b>No (Remark)</b>	<b>No (Remark)</b>
Right	Antenna to user (mm)	-	-
	SAR exclusion threshold	-	-
	SAR testing required?	<b>No (Remark)</b>	<b>No (Remark)</b>
Left	Antenna to user (mm)	-	-
	SAR exclusion threshold	-	-
	SAR testing required?	<b>No (Remark)</b>	<b>No (Remark)</b>
Top	Antenna to user (mm)	-	-
	SAR exclusion threshold	-	-
	SAR testing required?	<b>No (Remark)</b>	<b>No (Remark)</b>
Bottom	Antenna to user (mm)	-	-
	SAR exclusion threshold	-	-
	SAR testing required?	<b>No (Remark)</b>	<b>No (Remark)</b>

### Remark:

In fact, there would be only front side contact with human body.

### Note:

- Maximum power is the source-based time-average power and represents the maximum RF output power among production units
- Per KDB 447498 D01v06, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
- Per KDB 447498 D01v06, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is < 5mm, 5mm is used to determine SAR exclusion threshold
- Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:  

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]}{1} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$
 Power and distance are rounded to the nearest mW and mm before calculation  
 The result is rounded to one decimal place for comparison  
 For < 50 mm distance, we just calculate mW of the exclusion threshold value (3.0) to do compare.  
 This formula is  $[3.0] / [\sqrt{f(\text{GHz})}] \cdot [(\text{min. test separation distance, mm})] = \text{exclusion threshold of mW.}$
- Per KDB 447498 D01v06, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following  
 a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · ( f(MHz)/150)] mW, at 100 MHz to 1500 MHz  
 b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

## 10.8 SAR MEASUREMENT RESULTS

**Note:**

1. Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - b. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)\* Duty Cycle scaling factor \* Tune-up scaling factor
2. Per KDB 447498 D01, for each exposure position, if the highest output channel reported SAR ≤0.8W/kg, other channels SAR testing is not necessary.
3. Per KDB 447498 D01, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
  - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

### 2.4GHz Standalone SAR Results for Test Records

**Body:**

Band	Mode	Test Position	Dist. (mm)	Freq. (MHZ)	Ant	max Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Duty Cycle Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
WLAN 2.4Ghz	802.11b	Front	0	2462	Ant1	11.99	12	1.002	0.02	1.000	0.076	0.076
WLAN 2.4Ghz	802.11b	Front	0	2462	Ant2	13.42	14	1.143	0.07	1.000	0.073	0.083

**Head:**

Band	Mode	Test Position	Dist. (mm)	Freq. (MHZ)	Ant	max Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Duty Cycle Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
WLAN 2.4Ghz	802.11b	Front	0	2462	Ant1	11.99	12	1.002	0.07	1.000	0.061	0.061
WLAN 2.4Ghz	802.11b	Front	0	2462	Ant2	13.42	14	1.143	0.01	1.000	0.060	0.069

Remark: SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. So 2.4 GHz OFDM mode is not require.

**5GHz Standalone SAR Results for Test Records**

**Body:**

Band	Mode	Test Position	Dist. (mm)	Freq. (MHZ)	Ant	max Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Duty Cycle Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
WLAN 5Ghz	802.11a	Front	0	5180	Ant1	12.70	13	1.072	0.04	1.000	0.075	0.080
WLAN 5Ghz	802.11a	Front	0	5785	Ant1	13.29	13.5	1.050	0.13	1.000	0.134	0.141
WLAN 5Ghz	802.11a	Front	0	5220	Ant2	12.70	13	1.072	0.11	1.000	0.090	0.096
WLAN 5Ghz	802.11a	Front	0	5745	Ant2	12.57	13	1.104	-0.08	1.000	0.121	0.134

**Head:**

Band	Mode	Test Position	Dist. (mm)	Freq. (MHZ)	Ant	max Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Duty Cycle Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
WLAN 5Ghz	802.11a	Front	0	5180	Ant1	12.70	13	1.072	0.16	1.000	0.059	0.063
WLAN 5Ghz	802.11a	Front	0	5785	Ant1	13.29	13.5	1.050	0.08	1.000	0.105	0.110
WLAN 5Ghz	802.11a	Front	0	5220	Ant2	12.70	13	1.072	-0.04	1.000	0.071	0.076
WLAN 5Ghz	802.11a	Front	0	5745	Ant2	12.57	13	1.104	-0.09	1.000	0.094	0.104

## 10.9 REPEATED SAR MEASUREMENT

**Note:**

1. Per KDB 865664 D01v01, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8\text{W/Kg}$
2. Per KDB 865664 D01v01, if the ratio of largest to smallest SAR for the original and first repeated measurement is  $\leq 1.2$  and the measured SAR  $< 1.45\text{W/Kg}$ , only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated measured SAR.

Band	Mode	Test Position	Freq (MHZ)	Original Measured SAR1g (W/kg)	1st Repeated SAR1g (W/kg)	Ratio	Original Measured SAR1g (W/kg)	2nd Repeated SAR1g (W/kg)	Ratio
--	--	--	--	--	--	--	--	--	--

### 10.10 SAR MULTI XMITER ASSESSMENT

1. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
  - 1) Scalar SAR summation < 1.6W/kg.
  - 2) SPLSR =  $(SAR_1 + SAR_2)^{1.5} / R_i$  (min. separation distance, mm), and the peak separation distance is determined from the square root of  $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$ , where  $(x_1, y_1, z_1)$  and  $(x_2, y_2, z_2)$  are the coordinates of the extrapolated peak SAR locations in the zoom scan  
If  $SPLSR \leq 0.04$ , simultaneously transmission SAR is compliant
  - 3) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg
2. According to KDB 447498 D01 simultaneous SAR testing can be excluded under the following conditions:  
The sum of the SAR for all simultaneously transmitting antennas is within the SAR limit.  
If the sum of the SAR for all simultaneously transmitting antennas exceeds the SAR limit testing can still be excluded if the SAR to Peak Location Ratio (SPLSR) between any pair of simultaneously transmitting antennas is  $\leq 0.04$

**$SPLSR = (SAR_1 + SAR_2)^{1.5} / R_i$**

Where:

**SAR<sub>1</sub>** is the highest measured or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

**SAR<sub>2</sub>** is the highest measured or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

**R<sub>i</sub>** is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured, for both antennas in the pair, it is determined by the actual x, y and z coordinates in the 1-g SAR for each SAR peak location, based on the extrapolated and interpolated result in the zoom scan measurement, using the formula of  $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$

**Sum of SAR for worst case standalone measurements (Wi-Fi 2.4 GHz)**

**Body**

SUM $\Sigma$ SAR1g 2.4G					
Position	Distance [mm]	Standalone SAR(1g) [W/kg]		SUM SAR(1g)[W/kg]	
		Ant1 2.4G①	Ant2 2.4G②	①+②	SPLSR (Yes/No)
Front	0	0.076	0.083	0.159	No

**Conclusion:**

When the  $\Sigma$  1-g SAR is less than 1.6 W/kg simultaneous transmission testing is not required

**Head**

SUM $\Sigma$ SAR1g 2.4G					
Position	Distance [mm]	Standalone SAR(1g) [W/kg]		SUM SAR(1g)[W/kg]	
		Ant1 2.4G①	Ant2 2.4G②	①+②	SPLSR (Yes/No)
Front	0	0.061	0.069	0.130	No

**Conclusion:**

When the  $\Sigma$  1-g SAR is less than 1.6 W/kg simultaneous transmission testing is not required

**Sum of SAR for worst case standalone measurements (Wi-Fi 5 GHz)**

**Body**

SUM $\Sigma$ SAR1g 5G					
Position	Distance [mm]	Standalone SAR(1g) [W/kg]		SUM SAR(1g)[W/kg]	
		Ant1 5G①	Ant2 5G②	①+②	SPLSR (Yes/No)
Front	0	0.141	0.134	0.275	No

**Conclusion:**

When the  $\Sigma$  1-g SAR is less than 1.6 W/kg simultaneous transmission testing is not required

**Head**

SUM $\Sigma$ SAR1g 5G					
Position	Distance [mm]	Standalone SAR(1g) [W/kg]		SUM SAR(1g)[W/kg]	
		Ant1 5G①	Ant2 5G②	①+②	SPLSR (Yes/No)
Front	0	0.110	0.104	0.214	No

**Conclusion:**

When the  $\Sigma$  1-g SAR is less than 1.6 W/kg simultaneous transmission testing is not required

## 11. EQUIPMENT LIST & CALIBRATION STATUS

Name of Equipment	Manufacturer	Type/Model	Serial Number	Last Calibration	Calibration Due
P C	HP	Core(rm)3.16G	CZCO48171H	N/A	N/A
Signal Generator	Agilent	E8257C	US37101915	02/26/2018	02/25/2019
S-Parameter Network Analyzer	Agilent	E5071B	MY42301382	02/26/2018	02/25/2019
Power meter	Anritsu	ML2495A	1445010	04/26/2018	04/25/2019
Power sensor	Anritsu	MA2411B	1339220	04/26/2018	04/25/2019
E-field PROBE	SPEAG	EX3DV4	3798	07/27/2018	07/26/2019
DAE	SPEAG	DAE4	1245	07/17/2018	07/16/2019
DIPOLE 2450MHZ ANTENNA	SPEAG	D2450V2	817	05/29/2018	05/28/2019
DIPOLE 5GHZ ANTENNA	SPEAG	D5GHzV2	1095	05/22/2018	05/21/2019
Electro Thermometer	DTM	DTM3000	3030	12/26/2017	12/25/2018
Amplifier	Mini-circuits	ZVE-8G	110405	N/A	N/A
Amplifier	Mini-circuits	ZHL-42	QA1331003	N/A	N/A
3db ATTENUATOR	MINI	MCL BW-S3W5	0533	N/A	N/A
DUMMY PROBE	SPEAG	DP_2	SPDP2001AA	N/A	N/A
Dual Directional Coupler	Woken	20W couple	DOM2BHW1A1	N/A	N/A
SAM PHANTOM (ELI4 v4.0)	SPEAG	QDOVA001BB	1102	N/A	N/A
Twin SAM Phantom	SPEAG	QD000P40CD	1609	N/A	N/A
ROBOT	SPEAG	TX60	F10/5E6AA1/A101	N/A	N/A
ROBOT KRC	SPEAG	CS8C	F10/5E6AA1/C101	N/A	N/A
LIQUID CALIBRATION KIT	ANTENNESSA	41/05 OCP9	00425167	N/A	N/A



## 12. FACILITIES

All measurement facilities used to collect the measurement data are located at

☒ No.10, Weiye Rd., Innovation Park, Eco & Tec. Development Part, Kunshan City, Jiangsu Province, China.

## 13. REFERENCES

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz – 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard Kuhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992. Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10

## 14. LABORATORY ACCREDITATIONS AND LISTING

FCC –Designation Number: CN1172.

Compliance Certification Services Inc. Kun shan Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Designation Number: CN1172.

**APPENDIX A: DUT AND SAR TEST SETUP****APPENDIX B: PLOTS OF PERFORMANCE CHECK**

The plots are showing as followings.

Test Laboratory: Compliance Certification Services Inc.

Date: 11/7/2018

**System Performance Check-Body D2450**

**DUT: Dipole 2450 MHz ; Type: D2450V2; Serial: 817**

Communication System: UID 0, CW; Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450 \text{ MHz}$ ;  $\sigma = 1.911 \text{ S/m}$ ;  $\epsilon_r = 51.662$ ;  $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.22, 7.22, 7.22); Calibrated: 7/27/2018;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/17/2018
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check at Frequencies above 1 GHz/Pin=250 mW, dist=10mm (EX-Probe)/Area Scan (9x10x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 18.3 W/kg


**System Performance Check at Frequencies above 1 GHz/Pin=250 mW, dist=10mm (EX-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 101.9 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 25.9 W/kg

**SAR(1 g) = 12.9 W/kg; SAR(10 g) = 6 W/kg**

Maximum value of SAR (measured) = 19.5 W/kg



0 dB = 19.5 W/kg = 12.90 dBW/kg

Test Laboratory: Compliance Certification Services Inc.

Date: 11/8/2018

**System Performance Check-Body D5200**

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095**

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.34$  S/m;  $\epsilon_r = 48.853$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(4.46, 4.46, 4.46); Calibrated: 7/27/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/17/2018
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5200**

**MHz 20/Area Scan (10x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 16.2 W/kg

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5200**

**MHz 20/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 62.78 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 32.6 W/kg

**SAR(1 g) = 7.61 W/kg; SAR(10 g) = 2.25 W/kg**

Maximum value of SAR (measured) = 19.4 W/kg



0 dB = 19.4 W/kg = 12.88 dBW/kg

Test Laboratory: Compliance Certification Services Inc.

Date: 11/8/2018

**System Performance Check-Body D5800**

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095**

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.247$  S/m;  $\epsilon_r = 47.529$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(4.18, 4.18, 4.18); Calibrated: 7/27/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/17/2018
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5800**

**MHz/Area Scan (9x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 16.7 W/kg

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5800**

**MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 69.04 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 40.0 W/kg

**SAR(1 g) = 7.93 W/kg; SAR(10 g) = 2.32 W/kg**

Maximum value of SAR (measured) = 20.6 W/kg



0 dB = 20.6 W/kg = 13.14 dBW/kg

Test Laboratory: Compliance Certification Services Inc.

Date: 11/7/2018

**System Performance Check-Head D2450**

**DUT: Dipole 2450 MHz ; Type: D2450V2; Serial: 817**

Communication System: UID 0, CW; Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450 \text{ MHz}$ ;  $\sigma = 1.802 \text{ S/m}$ ;  $\epsilon_r = 38.777$ ;  $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.2, 7.2, 7.2); Calibrated: 7/27/2018;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/17/2018
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check at Frequencies above 1 GHz/Pin=250 mW, dist=10mm (EX-Probe)/Area Scan (9x10x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 17.3 W/kg


**System Performance Check at Frequencies above 1 GHz/Pin=250 mW, dist=10mm (EX-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 102.0 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 24.6 W/kg

**SAR(1 g) = 12.7 W/kg; SAR(10 g) = 5.68 W/kg**

Maximum value of SAR (measured) = 18.5 W/kg



0 dB = 18.5 W/kg = 12.67 dBW/kg

Test Laboratory: Compliance Certification Services Inc.

Date: 11/8/2018

**System Performance Check-Head D5200**

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095**

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5200$  MHz;  $\sigma = 4.548$  S/m;  $\epsilon_r = 35.923$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(5.02, 5.02, 5.02); Calibrated: 7/27/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/17/2018
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5200**

**MHz 20/Area Scan (10x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 13.2 W/kg

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5200**

**MHz 20/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 59.18 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 28.2 W/kg

**SAR(1 g) = 7.77 W/kg; SAR(10 g) = 2.19 W/kg**

Maximum value of SAR (measured) = 15.8 W/kg



0 dB = 15.8 W/kg = 11.99 dBW/kg



Test Laboratory: Compliance Certification Services Inc.

Date: 11/8/2018

**System Performance Check-Head D5800**

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095**

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5800$  MHz;  $\sigma = 5.206$  S/m;  $\epsilon_r = 34.469$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(4.69, 4.69, 4.69); Calibrated: 7/27/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/17/2018
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5800**

**MHz/Area Scan (9x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 13.3 W/kg

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5800**

**MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 65.18 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 34.0 W/kg

**SAR(1 g) = 7.56 W/kg; SAR(10 g) = 2.22 W/kg**

Maximum value of SAR (measured) = 16.4 W/kg



0 dB = 16.4 W/kg = 12.15 dBW/kg

**APPENDIX C: DASY CALIBRATION CERTIFICATE**

The DASY Calibration Certificates are showing in the file named Appendix C DASY Calibration Certificate.

**APPENDIX D: PLOTS OF SAR TEST RESULT**

The plots are showing in the file named Appendix D: Plots of SAR Test Result.

**END REPORT**