

## RF Exposure Requirements

---

Product Description: Sensory Time

Model No.: CC1036, CC1037, CC1038, CC5013, CC5015, CC5016, CC5017, CC5018, CC5019, CC5020, CC5021, CC5022, CC5023, C5025, CC5026, CC5027, CC5028, CC5029, CC5030

FCC ID: 2AQAOCWA02

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

-  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation

- The result is rounded to one decimal place for comparison

### Calculation Result:

Tx frequency range: 2402-2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: -8.585dBm

Tune-Up output power: -8dBm

RF channel transmit frequency: 2480MHz

Result: 0.1

Limit: 3.0

The exclusion thresholds is  $0.1 < 3$ , so the transmitter complies with the RF exposure requirements and the SAR is not required.