Transmitter Manual

Model:R48

Before you start using it, Please make sure to read the instruction manual

carefully.Following and respecting the instructions in your manual will

prevent damage to your instrument and loss of your statutory rights arising

from defects due to incorrect use.

Please take particular note of the safety advice!

Please keep this instruction manual for future reference.

- 1. Temperature range: +70°C to 40°C
- 2. Humidity range:20%-99%
- **3.** Lowe battery indicator
- 4. 3 Channels
- 5. RF distance: 100 meters
- **6.** Functions:

7.1 One button: TX, press it once to send the signal one time.

7.2 When put the battery into it, it will test the temperature and humidity and sent the data one time.

Keep this instrument and the batteries out of reach of children. Batteries contain harmful acids and may be hazardous if swallowed. If a battery is swallowed, this can lead to serious internal burns and death within two hours. If you suspect a battery could have been swallowed or otherwise caught in the body, seek medical help immediately.

FCC Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.