

Power Density Based on

20 separation distance (cm)

2480	Frequency (MHz)
-4.62	Power to Antenna (dBm)
0	Antenna gain (dBi)

FCC

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

0.0001
Power Density (mW/cm²)

Canada	FCC	Limit (mW/cm ²)
0.547	1	Limit (mW/cm ²)
0.547	1.000	Margin
0.000	0.0001	MPE Ratio

(General Population)

BLE Mode

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Device FCC ID 2AQHSF0410003
Date 1-Apr-19
Prepared By Kyle Fujimoto

Canada

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ⁻²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}

Note: f is frequency in MHz.
*Based on nerve stimulation (NS).
** Based on specific absorption rate (SAR).

Power Density Based on

20 separation distance (cm)

1900	Frequency (MHz)
29.8	Power to Antenna (dBm)
2.32	Antenna gain (dBi)

FCC

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

0.324

Power Density (mW/cm²)

Canada	FCC	Limit (mW/cm ²)
0.456	1	Limit (mW/cm ²)
0.132	0.676	Margin
0.711	0.324	MPE Ratio

(General Population)

**SARA-U201 Module
GSM 1900 Mode**

Device FCC ID 2AQHSF0410003
Date 1-Apr-19
Prepared By Kyle Fujimoto

Canada

Note: The GSM 1900 Mode is the Worst Case Mode

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ⁻²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}

Note: f is frequency in MHz.
*Based on nerve stimulation (NS).
** Based on specific absorption rate (SAR).

MPE Ratio of simultaneous operation based on highest power density compared to the **ICES** limits

Device FCC ID 2AQHSF0410003
Date 1-Apr-19
Prepared By Kyle Fujimoto

e.i.r.p			
-4.62	0.0001	Ratio 1	BLE
32.12	0.324	Ratio 2	GSM 1900 Mode

0.3241 Total Ratio Must be <=1

0.6759 Remaining

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 , according to calculated/estimated, numerically modeled, or measured field strengths or power density.

447498 D01