

裁切线	辅助线
压痕线	牙刀
V槽线	画线
半穿刀	

<input checked="" type="checkbox"/> 外表面视图	<input type="checkbox"/> 内表面视图
---	--------------------------------

UGREEN

3-in-1 Wireless Charger
Model: CD278 | P/N: 90326

EN

DE

FR

ES

PT

RU

JP

CN

AR

NL

SE

PL

TR

PT

LED Indicator Status

Working Status	LED Indicator Status	Description
Flower icon	Green light on	Power on
Flower icon	Green light off	Power off
Flower icon	Red light on	Overheating
Flower icon	Red light off	Overheating cleared

IT

State of Charge	Indicator LED	Description
Accumulator	Green	Charging
Accumulator	Red	Overheating
Accumulator	Red	Overheating cleared

<p>NL</p> <p>Specs</p> <table border="1"> <tr> <th>Item</th> <th>Specification</th> </tr> <tr> <td>Material</td> <td>ABS</td> </tr> <tr> <td>Color</td> <td>Black</td> </tr> <tr> <td>Weight</td> <td>~100g</td> </tr> <tr> <td>Dimensions</td> <td>~80x120x10mm</td> </tr> </table>	Item	Specification	Material	ABS	Color	Black	Weight	~100g	Dimensions	~80x120x10mm	<p>Specifications</p> <p>Input: 5V/2A, 9V/1.67A, 12V/1A</p> <p>Output: 5V/1A, 9V/0.67A, 12V/0.5A</p> <p>Charging Power: 15W</p> <p>Charging Time: ~2h</p>	<p>CE Statement</p> <p>CE Declaration of Conformity</p> <p>CE Marking: CE</p>	<p>FC Statement</p> <p>FCC Declaration of Conformity</p> <p>FCC Marking: FCC</p>	<p>Warranty Information</p> <p>1 Year</p>
Item	Specification													
Material	ABS													
Color	Black													
Weight	~100g													
Dimensions	~80x120x10mm													

- 备注:
- 材质: 70G书写纸
 - 印刷颜色: 单黑+1专 ■ PANTONE 3415C
 - 展开尺寸: 400x240mm
 - 成品尺寸: 80x120mm
 - 成型工艺: 风琴折
 - 尺寸公差: ±1mm
 - 所有成品及辅料符合欧盟包装指令94/62/EC, 美国TPCH, 欧盟REACH
 - 印刷油墨 (成品) 矿物油含量需满足MOSH(C15-C36)小于0.1%; MOAH (1-7芳香环) 小于0.1%; MOAH (3-7芳香环) 小于0.0001%

SELECT	Dim	TOL.	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL	SCALE	UGREEN 绿联 深圳市绿联科技股份有限公司			
0~6	0.05	0.05	0.10							0.20	1:1	SHEET 1/1	物料名称: CD278 90326 说明书			
6~30	0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20	UNIT mm	产品名称		料号	产品工程师	核准	
30~120	0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25		张泽民		陈雨露			
120~300	0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30							
300~450	0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50							
450~600	0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80							
DRAFT TOLERANCE					±0.20*		CRITICAL DIM. MARK				*					