



版本	变更描述	变更日期	包装结构	包装平面
A01	初始发行	2022/12/13	/	曾李同

### UGREEN

#### Magnetic Wireless Car Charger

Model: CD345 | P/N: 15120

#### Product Overview

#### Before Setup

#### Dashboard

#### STEP 1

#### STEP 2

#### STEP 3

#### STEP 4

#### STEP 5

#### Remove The Mount

#### Product Overview

#### Air Vent

#### STEP 1

#### STEP 2

#### STEP 3

#### STEP 4

#### STEP 5

#### Specifications

Product Name	Magnetic Wireless Car Charger
Input	5VDC/2.1A (5V/2.1A) or 5VDC/2.0A
Output	5.0V/1.0A
Output for iOS device	5.0V/1.0A
Frequency Range	150kHz-200kHz
Field Strength	≤ 6.76µT/A/m (30Hz)

#### Package Contents

- 1 x Magnetic Wireless Car Charger
- 1 x Suction Cup Car Phone Mount
- 1 x Dashboard Pad Mount (CN)
- 1 x Air Vent Car Phone Mount
- 1 x USB-C Charging Cable
- 1 x User Manual
- 1 x Cleaning Kit

#### FCC Statement

The equipment complies with FCC radiation exposure limits for both the uncontrolled environment. This equipment must not be co-located or operated in proximity to sensitive information systems.

#### Important WEEE Information

Disposing of this product correctly will help save valuable resources and protect the environment. Please contact your local authority for further details of your nearest recycling centre.

- 备注:
1. 材质: 70g书写纸
  2. 印刷颜色: 1C+1专 ■ PANTONE 3415
  3. 成型尺寸: 70x105mm
  4. 展开尺寸: 630x210mm
  5. 尺寸公差: ±1 mm
  6. 印刷偏位: <=0.5 mm
  7. 套印偏位: <=0.35 mm
  8. 成型工艺: 风琴折
  9. 所有成品及辅料符合欧盟包装指令94/62/EC, 美国TPCH, 欧盟REACH
  10. 印刷油墨 (成品) 矿物油含量需满足MOSH(C15-C36)小于0.1%; MOAH (1-7芳香环) 小于0.1%; MOAH (3-7芳香环) 小于0.0001%

SELECT	Dim	TOL.	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL	SCALE 1:1	UGREEN 绿联 深圳市绿联科技股份有限公司			
0~6			0.05	0.05	0.10						0.20	SHEET 1/1	物料名称: CD345 15120 说明书			
6~30			0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20		UNIT mm	产品名称	料号	产品工程师
30~120			0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25	UNIT mm		车载磁吸无线充电器	/	张泽民
120~300			0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30					
300~450			0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50					
450~600			0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80					
DRAFT TOLERANCE			± 0.20*			CRITICAL DIM. MARK										