

FCC TEST REPORT

Client Name : Ugreen Group Limited

Address : UGREEN Building, Longcheng Industrial Park,
Longguanxi Road, Longhua, ShenZhen China 518000

Product Name : 10000mAh Magnetic Wireless Power Bank

Date : Oct. 04, 2021

Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information	4
1.1. Client Information	4
1.2. Description of Device (EUT)	4
1.3. Auxiliary Equipment Used During Test	5
1.4. Test Equipment List	5
1.5. Measurement Uncertainty	5
1.6. Description of Test Facility	6
2. Measurement and Result	7
2.1. Requirements	7
2.2. Test Setup	8
2.3. Test Procedure	8
2.4. Test Result	9
APPENDIX I -- TEST SETUP PHOTOGRAPH	12

TEST REPORT

Applicant : Ugreen Group Limited
Manufacturer : Ugreen Group Limited
Product Name : 10000mAh Magnetic Wireless Power Bank
Model No. : PB195, 40826

Trade Mark : **UGREEN**
Rating(s) : USB-C(IN) Input: 5.0V \equiv 3.0A, 9.0V \equiv 2.22A, 12.0V \equiv 1.5A
USB-C(OUT1)Output:5.0V \equiv 3.0A, 9.0V \equiv 2.22A, 12.0V \equiv 1.5A
USB-A(OUT2)Output:5.0V \equiv 3.0A, 9.0V \equiv 2.0A, 12.0V \equiv 1.5A,
4.5V \equiv 5.0A, 5.0V \equiv 4.5A
Total Output: 5.0V \equiv 2.4A Max
Magnetic Wireless Output: 10W Max

Test Standard(s) : **FCC Part 1.1310, 1.1307(b)**

Test Method(s) : **KDB680106 D01 RF Exposure Wireless Charging Apps v03
November 2019 TCB Workshop**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 1.1307 & KDB680106 D01, November 2019 TCB Workshop requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt Jun. 18, 2021

Date of Test Jun. 18~Sept. 27, 2021

Prepared By



(Ella Liang)

Approved & Authorized Signer



(Kingkong Jin)

1. General Information

1.1. Client Information

Applicant	:	Ugreen Group Limited
Address	:	UGREEN Building, Longcheng Industrial Park, Longguanxi Road, Longhua, ShenZhen China 518000
Manufacturer	:	Ugreen Group Limited
Address	:	UGREEN Building, Longcheng Industrial Park, Longguanxi Road, Longhua, ShenZhen China 518000
Factory	:	Shenzhen Blue Times Technology Co., Ltd.
Address	:	7/F, B block, Taixinglong Industrial Zone, Nan Bu Gang, Zhongwu Village, Xixiang Street, Bao'an District, Shenzhen City, Guangdong Province, China.

1.2. Description of Device (EUT)

Product Name	:	10000mAh Magnetic Wireless Power Bank	
Model No.	:	PB195, 40826 (Note: All samples are the same except the model number, so we prepare "PB195" for test only.)	
Trade Mark	:	UGREEN	
Test Power Supply	:	AC 120V, 60Hz for adapter/ AC 240V, 60Hz for adapter	
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)	
Product Description	:	Operation Frequency:	111-205KHz
		Modulation Type:	FSK
		Antenna Type:	Inductive loop coil Antenna
		Antenna Gain(Peak):	0 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.			

1.3. Auxiliary Equipment Used During Test

Adapter	:	M/N: HCE452 Input: 100-240V~ 50/60Hz, 1.5A Output : 5V---3A, 9V---3A, 12V---3A, 15V---3A,
Wireless charging load	:	Manufacturer: Gopod Group Holding Limited. M/N: DTE324EM Power: 5W/7.5W/10W/15W Last Cal.: Oct. 30, 2020 Cal. Interval: 1 Year

1.4. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Magnetic field meter	NARDA	ELT-400	423623	Dec. 24, 2018	3 Year
2	E-Field Probe	Narda	EF0391	Q15221	Nov.17, 2020	3 Year
3	H-Field Probe	Narda	HF3061	Q15835	Nov.17, 2020	3 Year

1.5. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.6. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 30, 2020.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, September 30, 2020.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China. 518102

2. Measurement and Result

2.1. Requirements

According to the item 5.b) of KDB 680106 D01v03:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

- 1) Power transfer frequency is less than 1 MHz
- 2) Output power from each primary coil is less than or equal to 15 watts.
- 3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils
- 4) Client device is inserted in or placed directly in contact with the transmitter
- 5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion)
- 6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Limits For Maximum Permissible Exposure (MPE)


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

2.2. Test Setup



Note:

The measured probe with 5cm radius measurement head.

The test separation distance is measured from the edge of the probe head to the edge of the device: 0cm, 2cm, 4cm, 6cm, 8cm, 10cm.

2.3. Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at required test distance (0cm, 2cm, 4cm, 6cm, 8cm, 10cm) which is from the edge of the probe to the edge of the device.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each point (A, B, C, D, E) were completed. (A is the right, B is the back, C is the left, D is the front, and E is the top side.)
- 4) The EUT was measured according to the dictates of TCB Workshop November 2019 and KDB 680106 D01 v03r01.

Remark;

The EUT's test position A, B, C, D and E is valid for the H field measurements.

2.4. Test Result

2.4.1. Equipment Approval Considerations item 5.b of KDB 680106 D01 v03.

1) Power transfer frequency is less than 1 MHz

- The device operate in the frequency range 111-205KHz.

2) Output power from each primary coil is less than 15 watts

- The maximum output power of the primary coil is 10W.

3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils

- The transfer system including a charging system with only single primary coils is to detect and allow only between individual pairs of coils.

4) Client device is inserted in or placed directly in contact with the transmitter

- Client device is placed directly in contact with the transmitter.

5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion)

- The EUT is a portable exposure conditions

6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

- Conducted the measurement with the required distance and the test results please refer to the section 2.4.2.



2.4.2. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

Temperature:	22.5°C	Relative Humidity:	49 %
Pressure:	1012 hPa	Test Voltage:	AC 120V, 60Hz for adapter

H-Field Strength at 0 cm

Power Level	Frequency Range (KHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
100%	111-205	0.49	0.67	0.56	0.38	0.37	0.815	1.63

H-Field Strength at 2 cm

Power Level	Frequency Range (KHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
100%	111-205	0.48	0.66	0.55	0.36	0.35	0.815	1.63

H-Field Strength at 4 cm

Power Level	Frequency Range (KHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
100%	111-205	0.46	0.64	0.53	0.32	0.31	0.815	1.63

H-Field Strength at 6 cm

Power Level	Frequency Range (KHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
100%	111-205	0.44	0.63	0.51	0.30	0.29	0.815	1.63

H-Field Strength at 8 cm

Power Level	Frequency Range (KHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
100%	111-205	0.43	0.61	0.50	0.28	0.27	0.815	1.63

H-Field Strength at 10 cm

Power Level	Frequency Range (KHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
100%	111-205	0.42	0.59	0.48	0.25	0.25	0.815	1.63

Note:

(1) Position E is Top surface.


(2) All the situation (full load, half load and empty load) has been tested, only the worst situation (full load 10W) was recorded in the report.

(3) All Position A, B, C, D, E have been performed testing. Since testing side A, B, C, D are similar, so we only display testing photos with Position A (Right side) & Position E (Top surface) in the report, see below photos.


APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of MPE Measurement


Position A (right side)-0cm




Position A (right side)-2cm




Position A (right side)-4cm



Position A (right side)-6cm




Position A (right side)-8cm



Position A (right side)-10cm



Position E (Top surface)-0cm



Position E (Top surface)-2cm



Position E (Top surface)-4cm




Position E (Top surface)-6cm



Position E (Top surface)-8cm



Position E (Top surface)-10cm



----- End of Report -----