


ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-194-RWD-046
AGR No. : A193A-184
Applicant : BROS & COMPANY INC.
Address : A-402, InnoValley, 253, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea
Manufacturer : SHENZHEN ARBITER TECHNOLOGY CO., LTD
Address : Bldg A, Meisheng Industrial Park, Chongqing Rd., Fuyong, Bao'an District, Shenzhen, China
Type of Equipment : Wireless Charging Mouse
FCC ID. : 2AQISPOUT-01401-01
Model Name : POUT-01401-01
Multiple Model Name: POUT-01401-02, POUT-01401-03
Serial number : N/A
Total page of Report : 36 pages (including this page)
Date of Incoming : March 18, 2019
Date of issue : April 22, 2019

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*
 This test report only contains the result of a single test of the sample supplied for the examination.
 It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by: 

 Ha-Ram, Lee / Assistant Manager
 ONETECH Corp.

Approved by: 

 Jae-Ho Lee / Chief Engineer
 ONETECH Corp.

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	5
2. TEST SUMMARY	6
2.1 TEST ITEMS AND RESULTS	6
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS	6
2.3 RELATED SUBMITTAL(S) / GRANT(S)	6
2.4 PURPOSE OF THE TEST	6
2.5 TEST METHODOLOGY	6
2.6 TEST FACILITY	7
3. GENERAL INFORMATION	8
3.1 PRODUCT DESCRIPTION	8
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT	8
4. EUT MODIFICATIONS	8
5. SYSTEM TEST CONFIGURATION	9
5.1 JUSTIFICATION	9
5.2 PERIPHERAL EQUIPMENT	9
5.3 MODE OF OPERATION DURING THE TEST	10
5.4 CONFIGURATION OF TEST SYSTEM	10
5.5 ANTENNA REQUIREMENT	10
6. PRELIMINARY TEST	11
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS	11
6.2 GENERAL RADIATED EMISSIONS TESTS	11
7. MINIMUM 20 DB BANDWIDTH	12
7.1 OPERATING ENVIRONMENT	12
7.2 TEST SET-UP	12
7.3 TEST EQUIPMENT USED	12
7.4 TEST DATA	13
8. HOPPING FREQUENCY SEPARATION	15
8.1 OPERATING ENVIRONMENT	15
8.2 TEST SET-UP	15
8.3 TEST EQUIPMENT USED	15
8.4 TEST DATA	16

9. NUMBER OF HOPPING CHANNELS	17
9.1 OPERATING ENVIRONMENT	17
9.2 TEST SET-UP	17
9.3 TEST EQUIPMENT USED	17
9.4 TEST DATA	18
10. TIME OF OCCUPANCY	21
10.1 OPERATING ENVIRONMENT	21
10.2 TEST SET-UP	21
10.3 TEST EQUIPMENT USED	21
10.4 TEST DATA	22
11. MAXIMUM PEAK OUTPUT POWER	24
11.1 OPERATING ENVIRONMENT	24
11.2 TEST SET-UP	24
11.3 TEST EQUIPMENT USED	24
11.4 TEST DATA	25
12. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND.....	27
12.1 OPERATING ENVIRONMENT	27
12.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	27
12.3 TEST SET-UP FOR RADIATED MEASUREMENT	27
12.4 TEST EQUIPMENT USED	27
12.5 TEST DATA FOR CONDUCTED EMISSION	28
12.6 TEST DATA FOR TRANSMITTING MODE RADIATED EMISSION.....	33
<i>12.6.1 Radiated Emission which fall in the Restricted Band.....</i>	<i>33</i>
<i>12.6.2 Spurious & Harmonic Radiated Emission above 1 GHz.....</i>	<i>34</i>

Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
OT-194-RWD-046	April 22, 2019	Initial Issue	All

1. VERIFICATION OF COMPLIANCE

APPLICANT : BROS & COMPANY INC.
 ADDRESS : A-402, InnoValley, 253, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea
 CONTACT PERSON : KIYEOL PARK / CEO
 TELEPHONE NO : +82-31-286-8646
 FCC ID : 2AQISPOUT-01401-01
 MODEL NAME : POUT-01401-01
 SERIAL NUMBER : N/A
 DATE : April 22, 2019

EQUIPMENT CLASS	<i>DSS – PART 15 SPREAD SPECTRUM TRANSMITTER</i>
KIND OF EQUIPMENT	Wireless Charging Mouse
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	None
FINAL TEST WAS CONDUCTED ON	3 m Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (1)	Carrier Frequency Separation	Met the Limit / PASS
15.247 (a) (1) (iii)	Minimum Number of Hopping Channels	Met the Limit / PASS
15.247 (a) (1) (iii)	Average Time of Occupancy	Met the Limit / PASS
15.247 (b) (1)	Maximum Peak Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.209	Radiated Emission Limits, General Requirement	Met the Limit / PASS
15.207	Conducted Limits	N/A
15.203	Antenna Requirement	Met requirement / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-4112/ C-14617/ G-10666 / T-1842

IC (Industry Canada) – Registration No. Site# 3736A-3

-. Site Accreditation:

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The BROS & COMPANY INC., Model POUT-01401-01 (referred to as the EUT in this report) is a Wireless Charging Mouse. The product specification described herein was obtained from product data sheet or user’s manual.

Device Type	Wireless Charging Mouse
Operating Frequency	2 402.75 MHz ~ 2 480.75 MHz
RF Output Power	-14.08 dBm
Number of Channel	16 Channels
Modulation Type	GFSK
Antenna Type	PCB Antenna
Antenna Gain	2.75 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	16 MHz
Rated Supply Voltage	DC 3.7 V

3.2 Alternative type(s)/model(s); also covered by this test report.

-. The following lists consist of the added model and their differences.

Model Name	Differences	Tested
POUT-01401-01	Basic Model	<input checked="" type="checkbox"/>
POUT-01401-02	This model is identical to the basic model except the uninstal of USB charging function and DPI button.	<input type="checkbox"/>
POUT-01401-03	This model is identical to the basic model except the uninstal of USB charging function.	<input type="checkbox"/>

Note: 1. Applicant consigns only basic model to test. Therefore, this test report just guarantees the units, which have been tested.

2. The Applicant/manufacturer is responsible for the compliance of all variants

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	N/A	N/A	-
USB Dongle	SHENZHEN ARBITER TECHNOLOGY CO., LTD	N/A	-

5.2 Peripheral equipment

- None

5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting and receiving mode is programmed. The EUT was set at Low Channel (2 402.75 MHz), Middle Channel (2 441.75MHz), and High Channel (2 480.75 MHz). To get a maximum radiated emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is “XY” axis, but the worst data was recorded in this test report.

5.4 Configuration of Test System

Radiated Emission Test: The EUT was tested in a Charging & Transmitting mode. Preliminary radiated emissions test was conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The transmitter antenna of the EUT is a Printed PCB Antenna, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

As this product is only using DC power, AC conducted emission test has not been performed.

6.2 General Radiated Emissions Tests

During Preliminary Tests, the following operating modes were investigated

Operation Mode	The Worse operating condition (Please check one only)
Charging & Transmitting mode.	X


7. MINIMUM 20 dB BANDWIDTH

7.1 Operating environment

Temperature : 23 °C
 Relative humidity : 49 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 10 kHz, and peak detection was used. The 20 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 20 dB.



7.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV30	Rohde & Schwarz	Signal Analyzer	101200	Aug. 23, 2018 (1Y)


All test equipment used is calibrated on a regular basis.


7.4 Test data

-. Test Date : March 18, 2019


CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.75	1 948.10
Middle	2 441.75	2 008.00
High	2 480.75	2 023.00

Tested by: Seion Lee / Assistant Manager





Middle Channel



High Channel


8. HOPPING FREQUENCY SEPARATION

8.1 Operating environment

Temperature : 23 °C
 Relative humidity : 49 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 5 MHz. The analyzer is set to peak hold then a pseudo-random hopping sequence of the transmitter is captured. The mark delta function was used to measure the frequency separation between two adjacent hopping channels.



8.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV30	Rohde & Schwarz	Signal Analyzer	101200	Aug. 23, 2018 (1Y)

All test equipment used is calibrated on a regular basis.


8.4 Test data

- Test Date : March 18, 2019

- Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
2 000.00	1 338.67	Separated by a minimum of 25 kHz

Tested by: Sieon Lee / Assistant Manager




9. NUMBER OF HOPPING CHANNELS

9.1 Operating environment

Temperature : 23 °C
 Relative humidity : 49 % R.H.

9.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to frequency band of operation and the resolution bandwidth is set to 100 kHz. The analyzer is set to peak hold and then complete pseudo-random hopping sequence of the transmitter is captured.



9.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV30	Rohde & Schwarz	Signal Analyzer	101200	Aug. 23, 2018 (1Y)

All test equipment used is calibrated on a regular basis.


9.4 Test data


-. Test Date : March 18, 2019
 -. Test Result : Pass

Measured value (Number)	Limit (Number)	Margin (Number)
16	Minimum of 15	1




Tested by: Sieon Lee / Assistant Manager






Number of hopping channel: 6



Number of hopping channel: 6




10. TIME OF OCCUPANCY

10.1 Operating environment

Temperature : 23 °C
 Relative humidity : 49 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The transmitter is set to operate in its normal frequency hopping mode. The center frequency of the spectrum analyzer is set to one of hopping channels near the center of the operating band and span is set to zero Hz. The sweep time is set to display one complete pulse. The mark delta function is used to measure the duration of the pulses.



10.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV30	Rohde & Schwarz	Signal Analyzer	101200	Aug. 23, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

10.4 Test data

-. Test Date : March 18, 2019

Frequency (MHz)	Pulse Time (ms)	Hops per second with channels	Period Time (s)	Total Dwell Time (ms)	Limit (ms)	Test Result
2 441	0.120	8.13	6.4	6.24	400	PASS

Total dwell time is calculated as following.


Period Time = 0.4 * 16 [channel]

Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.



Tested by: Seon Lee / Assistant Manager




11. MAXIMUM PEAK OUTPUT POWER

11.1 Operating environment

Temperature : 23 °C
 Relative humidity : 49 % R.H

11.2 Test set-up

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The EUT was operating in transmit mode at the appropriate center frequency.



11.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV30	Rohde & Schwarz	Signal Analyzer	101200	Aug. 23, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

11.4 Test data


-. Test Date : March 18, 2019


-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.75	-14.24	21.00	35.24
MIDDLE	2 441.75	-14.16	21.00	35.16
HIGH	2 480.75	-14.08	21.00	35.08


Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Tested by: Sieon Lee / Assistant Manager





Middle Channel



High Channel


12. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND

12.1 Operating environment

Temperature : 24 °C
 Relative humidity : 51 % R.H

12.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution and video bandwidth is set to 100 kHz, and peak detection was used.



12.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m, open-field test site. The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.


The frequency spectrum from 30 kHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 ms in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

12.4 Test equipment used


	Model Number	Manufacturer	Description	Serial Number	Last Cal. (Interval)
<input type="checkbox"/>	ESCI	Rohde & Schwarz	EMI Test Receiver	101012	Oct. 22, 2018 (1Y)
<input checked="" type="checkbox"/>	ESR	Rohde & Schwarz	EMI Test Receiver	101470	Oct. 22, 2018 (1Y)
<input type="checkbox"/>	FSP	Rohde & Schwarz	Spectrum Analyzer	100017	Aug. 23, 2018 (1Y)
<input checked="" type="checkbox"/>	310N	Sonoma Instrument	AMPLIFIER	312544	Mar. 18, 2019 (1Y)
<input checked="" type="checkbox"/>	FSV30	Rohde & Schwarz	Signal Analyzer	101200	Aug. 23, 2018 (1Y)
<input checked="" type="checkbox"/>	SCU18	Rohde & Schwarz	Pre-Amplifier	102266	Aug. 24, 2018 (1Y)
<input checked="" type="checkbox"/>	MA-4000XPET	Innco Systems GmbH	Antenna Master	MA4000/509	N/A
<input type="checkbox"/>	HD100	HD GmbH	Position Controller	N/A	N/A
<input checked="" type="checkbox"/>	DT3000-3t	Innco Systems GmbH	Turn Table	N/A	N/A
<input type="checkbox"/>	FMZB 1513	Schwarzbeck	LOOP ANTENNA	1513-235	May. 13, 2018 (2Y)
<input checked="" type="checkbox"/>	VULB9163	Schwarzbeck	TRILOG Broadband Antenna	9163-255	Jun 05, 2018 (2Y)
<input checked="" type="checkbox"/>	BBHA9120D	Schwarzbeck	Horn Antenna	BBHA9120D295	Aug. 16, 2017 (2Y)
<input checked="" type="checkbox"/>	BBHA9170	Schwarzbeck	Horn Antenna	BBHA91700179	Jul. 28, 2017 (2Y)
<input checked="" type="checkbox"/>	SCU40A	Rohde & Schwarz	Pre-Amplifier	100436	May. 15, 2018 (1Y)

All test equipment used is calibrated on a regular basis.


12.5 Test data for conducted emission




Low Channel




Middle Channel







Low Channel




Low Channel




Middle Channel



Middle Channel



High Channel



High Channel

12.6 Test data for Transmitting Mode radiated emission

12.6.1 Radiated Emission which fall in the Restricted Band

12.6.1.1 Test data

- . Test Date : March 29, 2019
- . Resolution bandwidth : 1 MHz for Peak and Average Mode
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Detector : Peak Mode(Peak), Average Mode(RMS)
- . Measurement distance : 3 m
- . Operating Condition : Highest Output Power Transmitting Mode (Low Channel and High Channel)
- . Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
2 387.88	49.45	Peak	H	27.60	11.40	34.29	54.16	74.00	19.84
2 337.93	31.19	Average	H				35.90	54.00	18.10
2 387.96	43.93	Peak	V				48.64	74.00	25.36
2 349.68	30.82	Average	V				35.53	54.00	18.47
Test Data for High Channel									
2 483.51	57.16	Peak	H	27.80	11.40	34.46	61.90	74.00	12.10
2 483.82	31.16	Average	H				35.90	54.00	18.10
2 494.80	43.74	Peak	V				48.48	74.00	25.52
2 491.27	30.53	Average	V				35.27	54.00	18.73

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical



Tested by: Sieon Lee / Assistant Manager

12.6.2 Spurious & Harmonic Radiated Emission above 1 GHz

12.6.2.1 Test data

- Test Date : March 29, 2019
- Resolution bandwidth : 1 MHz for Peak and Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Detector : Peak Mode(Peak), Average Mode(RMS)
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Operating Condition : Highest Output Power Transmitting Mode
- Result : PASSED

Frequency (GHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
4 805.50	50.46	Peak	H	31.00	16.10	35.23	62.33	74.00	11.67
	31.37	Average	H				43.24	54.00	10.76
	45.43	Peak	V				57.30	74.00	16.70
	30.79	Average	V				42.66	54.00	11.34
Test Data for Middle Channel									
4 883.50	49.30	Peak	H	31.10	16.10	35.27	61.23	74.00	12.77
	31.41	Average	H				43.34	54.00	10.66
	45.02	Peak	V				56.95	74.00	17.05
	31.00	Average	V				42.93	54.00	11.07
Test Data for High Channel									
4 961.50	49.53	Peak	H	31.20	16.10	35.28	61.55	74.00	12.45
	31.45	Average	H				43.47	54.00	10.53
	44.64	Peak	V				56.66	74.00	17.34
	31.06	Average	V				43.08	54.00	10.92

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical, "*" Frequency fall in restricted band



Tested by: Sieon Lee / Assistant Manager


12.6.3 Spurious Radiated Emission

12.6.3.1 Test Data for 30 MHz ~ 1 GHz (Transmitting Mode)

Humidity Level : 51 % R.H. Temperature: 24 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247
 Result : PASSED

EUT : Wireless Charging Mouse Date: March 29, 2019

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
---- Horizontal ----										
1	82.380	34.0	8.4	2.0	33.0	11.4	40.0	28.6	100	359
2	184.230	33.1	10.2	3.1	33.0	13.4	43.5	30.1	300	341
3	784.652	33.2	21.1	6.5	33.1	27.7	46.0	18.3	100	359
---- Vertical ----										
4	50.370	30.0	14.1	1.7	33.1	12.7	40.0	27.3	100	0
5	402.480	34.1	15.9	4.6	33.1	21.5	46.0	24.5	100	329
6	756.523	34.0	20.7	6.4	33.2	27.9	46.0	18.1	100	146

Tested by: Sieon Lee / Assistant Manager

12.6.3.2 Test Data for Below 30 MHz

- . Test Date : March 29, 2019
- . Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- . Frequency range : 9 kHz ~ 30 MHz
- . Measurement distance : 3 m
- . Operating Condition : Highest Output Power Transmitting Mode
- . Result : PASSED

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Amp Gain	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Emissions observed were 20dB below the limit and thus not reported								

12.6.3.3 Test Data for above 1 GHz

- . Test Date : March 29, 2019
- . Resolution bandwidth : 1 MHz for Peak and Average Mode
- . Frequency range : 1 GHz ~ 26.5 GHz
- . Measurement distance : 3 m
- . Operating Condition : Highest Output Power Transmitting Mode
- . Result : PASSED

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Amp Gain	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Emissions observed were 20dB below the limit and thus not reported								



Tested by: Sieon Lee / Assistant Manager