

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AQKA-E206W-SPS

### EUT Specification

<b>EUT</b>	<b>Hunting Camera</b>
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others: BLE: 2.402GHz~2.480GHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	BLE: 1.35dBm (0.0014W) WIFI 2.4G: 19.45dBm (0.0881W)
<b>Antenna gain (Max)</b>	BLE: 0.84dBi WiFi 2.4G: 2.44dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	<b>F/300</b>	<b>6</b>
1500-100000	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	<b>F/1500</b>	<b>6</b>
1500-100000	--	--	<b>1</b>	<b>30</b>

**Friis transmission formula:  $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$**

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

**Max Measurement Result**

Operating Mode	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits
	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
BLE	1.35	1.35 ±1	2.35	0.84	0.0004	1
WiFi 2.4G	19.45	19.45 ±1	20.45	2.44	0.0387	1

**The WLAN 2.4G and BLE can transmit simultaneously:**

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

=  $S_{WiFi2.4} / S_{limit-2.4} + S_{BLE} / S_{limit-BLE}$

= 0.0387/1 + 0.0004/1

= 0.0391

< 1.0