

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AQKA-E9W

EUT Specification

EUT	Hunting camera
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz / 2.422GHz ~ 2.452GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others: 2.402GHz~2.480GHz 2.4G
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	Wifi 2.4G:16.08dBm (0.0406W) BT 4.2 BLE:1.126dBm (0.0013W)
Antenna gain (Max)	2.2 dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $Pd=(Pout \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd = Power density in mW/cm^2

$Pout$ =output power to antenna in Mw

G = gain of antenna in linear scale

$\pi=3.1416$

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

WIFI 2.4GHz :

Channel Frequency (MHz)	Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
2412	14.28	14.28±1	15.28	2.2	0.0111	1
2437	13.88	14.28±1	14.88	2.2	0.0102	1
2462	15.13	15.13±1	16.13	2.2	0.0135	1
2412	12.83	12.83±1	13.83	2.2	0.0080	1
2437	14.71	14.71±1	15.71	2.2	0.0123	1
2462	15.97	15.97±1	16.97	2.2	0.0164	1
2412	13.3	13.3±1	14.3	2.2	0.0089	1
2437	14.89	14.89±1	15.89	2.2	0.0128	1
2462	16.08	16.08±1	17.08	2.2	0.0169	1
2422	12.78	12.78±1	13.78	2.2	0.0079	1
2437	15.24	15.24±1	16.24	2.2	0.0139	1
2452	14.92	14.92±1	15.92	2.2	0.0129	1

Note: WIFI 2.4G cannot support simultaneous transmission.

BT

Channel Frequency (MHz)	Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
2402	-1.26	-1.26±1	-0.26	2.2	0.0003	1
2440	-1.141	-1.141±1	-0.141	2.2	0.0003	1
2480	1.126	1.126±1	2.126	2.2	0.0005	1

Note: BT cannot support simultaneous transmission.