



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China


Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No. : CQASZ20200901113E-02
Applicant: AKSys Co.,Ltd.
Address of Applicant: A706, Ace Cheonggye Tower, 53 Seonggogae-ro, Uiwang-si, Gyeonggi-do, Korea
Equipment Under Test (EUT):
EUT Name: WIRELESS CONTROLLER
Mode No.: Gamepad S5i, topp Gaming Medusa
Test Model No.: Gamepad S5i
Brand Name: SHAKS, topp Gaming
FCC ID: 2AQKJ-S5I
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2020-09-26
Date of Test: 2020-09-26 to 2020-10-12
Date of Issue: 2020-10-12
Test Result : PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Tested By: 

(Martin Lee)

Reviewed By: 

(Sheek Luo)

Approved By: 

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200901113E-02	Rev.01	Initial report	2020-10-12

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	AKSys Co.,Ltd.
Address of Applicant:	A706, Ace Cheonggye Tower, 53 Seonggogae-ro, Uiwang-si, Gyeonggi-do, Korea
Manufacturer:	AKSys Co.,Ltd.
Address of Manufacturer:	A706, Ace Cheonggye Tower, 53 Seonggogae-ro, Uiwang-si, Gyeonggi-do, Korea
Factory:	Dongguan Zhonghe electronic technology co., LTD
Address of Factory:	6th floor, building B, No.2, Lilian road, Tangxia town, Dongguan, Guangdong

3.2 General Description of EUT

Product Name:	WIRELESS CONTROLLER
Model No.:	Gamepad S5i, topp Gaming Medusa
Trade Mark:	SHAKS, topp Gaming
Hardware Version:	V1.0
Software Version:	300006
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.1
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	Blue test3 (manufacturer declare)
Antenna Type:	Ceramic antenna
Antenna Gain:	0dBi
EUT Power Supply:	lithium battery:DC3.7V, 400mAh, Charge by DC5.0V

Note:

Model No.: Gamepad S5i, topp Gaming Medusa

Only the model Gamepad S5i was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

For BLE

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	5.84	5.0±1	6.0	3.981
Middle(2440MHz)	8.08	7.5±1	8.5	7.079
Highest(2480MHz)	8.41	7.5±1	8.5	7.079

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	5.84	5.0±1	6.0	3.981	0.618	3.0
Middle (2440MHz)	8.08	7.5±1	8.5	7.079	0.623	
Highest (2480MHz)	8.41	7.5±1	8.5	7.079	0.791	

Conclusion: the calculated value ≤ 3.0 , SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20200901113E-01.