

# EMC Test Report

**Project Number: 4175716**

**Report Number: 4175716EMC01**

**Revision Level: 1**

**Client: Wistron NeWeb Corporation**

**Equipment Under Test: LTE CAT-M1 Device**

**Model: IMS2**


**FCC ID: NKRIMS2**

**FCC Rule Parts: Part 2, Part 27, Part 24E**

**Report issued on: 05 September 2017**

**Test Result: Compliant**

Tested by:

  
\_\_\_\_\_  
Jeremy Pickens, Senior EMC Engineer

Reviewed by:

  
\_\_\_\_\_  
David Schramm, Operations Manager

*Remarks: This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.*

*This document is issued by the Company under its General Conditions of Service accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.*

*Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.*

## Table of Contents

<b>1</b>	<b>SUMMARY OF TEST RESULTS</b> .....	<b>4</b>
1.1	MODIFICATIONS REQUIRED TO COMPLIANCE.....	4
<b>2</b>	<b>GENERAL INFORMATION</b> .....	<b>5</b>
2.1	CLIENT INFORMATION.....	5
2.2	TEST LABORATORY.....	5
2.3	GENERAL INFORMATION OF EUT.....	5
2.4	OPERATING MODES AND CONDITIONS.....	5
<b>3</b>	<b>RF OUTPUT POWER</b> .....	<b>6</b>
3.1	TEST RESULT.....	6
3.2	TEST METHOD.....	6
3.3	TEST SITE.....	6
3.4	TEST EQUIPMENT.....	6
3.5	TEST DATA.....	7
<b>4</b>	<b>PEAK TO AVERAGE RATIO</b> .....	<b>8</b>
4.1	TEST RESULT.....	8
4.2	TEST METHOD.....	8
4.3	TEST SITE.....	8
4.4	TEST EQUIPMENT.....	8
4.5	TEST DATA.....	9
<b>5</b>	<b>OCCUPIED BANDWIDTH</b> .....	<b>12</b>
5.1	TEST RESULT.....	12
5.2	TEST METHOD.....	12
5.3	TEST SITE.....	12
5.4	TEST EQUIPMENT.....	12
5.5	TEST DATA.....	13
<b>6</b>	<b>BAND EDGE AND CONDUCTED SPURIOUS EMISSIONS</b> .....	<b>15</b>
6.1	TEST RESULT.....	15
6.2	TEST METHOD.....	15
6.3	TEST SITE.....	15
6.4	TEST EQUIPMENT.....	15
6.5	TEST DATA - BAND EDGE.....	16
6.6	TEST DATA - CONDUCTED SPURIOUS EMISSIONS.....	18
<b>7</b>	<b>EFFECTIVE RADIATED POWER</b> .....	<b>21</b>
7.2	TEST SITE.....	21
7.3	TEST EQUIPMENT.....	21
7.4	TEST DATA.....	21
<b>8</b>	<b>RADIATED SPURIOUS EMISSIONS</b> .....	<b>22</b>
8.1	TEST RESULT.....	22
8.2	TEST METHOD.....	22
8.3	TEST SITE.....	22
8.4	TEST EQUIPMENT.....	23
8.5	TEST DATA.....	24
<b>9</b>	<b>FREQUENCY STABILITY</b> .....	<b>45</b>
9.1	TEST RESULT.....	45



9.2 TEST METHOD..... 45

9.3 TEST SITE..... 45

9.4 TEST EQUIPMENT..... 45

9.5 TEST DATA..... 46

**10 REVISION HISTORY..... 49**

## 1 Summary of Test Results

Reference Sections	Test Description	Test Limit	Test Condition	Test Result
2.1046	Conducted Output Power	N/A	Conducted	Compliant
24.232(d) 27.50(d)(5)	Peak-to-Average Ratio	<13 dB		Compliant
2.1049	Occupied Bandwidth	N/A		Reported
2.1051 24.238(a) 27.53(h) 27.53(g)	Band Edge / Conducted Spurious Emissions	< 43 +10log <sub>10</sub> (P <sub>[Watts]</sub> ) at band edge and for all out of band emissions		Compliant
27.50(c)(10)	Effective Radiated Power	< 3 Watts max ERP	Radiated	Compliant
24.232(c)	Effective Isotropic Radiated Power	< 2 Watts max EIRP		Compliant
27.50(d)(4)	Effective Isotropic Radiated Power	< 1 Watt max EIRP		Compliant
2.1053 24.238(a) 27.53(h) 27.53(g)	Radiated Spurious Emissions	< 43 +10log <sub>10</sub> (P <sub>[Watts]</sub> ) at band edge and for all out of band emissions		Compliant
2.1055 24.238(a) 27.5(c) 27.5(h) 27.54	Frequency Stability	<2.5 ppm		Compliant

### 1.1 Modifications Required to Compliance

None

## 2 General Information

### 2.1 Client Information

Name: Wistron NeWeb Corporation  
Address: 3322 Route 22 West, Building 10, Suite 1007  
City, State, Zip, Country: Branchburg, NJ 08876, USA

### 2.2 Test Laboratory

Name: SGS North America, Inc.  
Address: 620 Old Peachtree Road NW, Suite 100  
City, State, Zip, Country: Suwanee, GA 30024, USA

### 2.3 General Information of EUT

Type of Product: Wireless Modem Module  
Model Number: IMS2  
Serial Number: 11  
IMEI: 353180080000345

Rated Voltage: 3.3 – 4.2 Vdc,  
Test Voltage: 3.8 Vdc,

Tx Frequency Range: 1850 - 1910 MHz (LTE Band 2)  
1710 – 1755 MHz (LTE Band 4)  
699 – 716MHz (LTE Band 12)

FCC Classification: PCS Licensed Transmitter PCB  
Type: Pre Production

Sample Received Date: 07 July 2017  
Dates of testing: 20 – 25 July 2017

### 2.4 Operating Modes and Conditions

The EUT was exercised by sending test commands to place the device into constant transmit mode. Low, middle, and high channels were investigated for each frequency band of operation.

### 3 RF Output Power

#### 3.1 Test Result

Test Description	Basic Standards	Test Result
RF Output Power	2.1046, 27.50(c)(10), 24.232(c), 27.50(d)(4)	Compliant

#### 3.2 Test Method

The EUT was configured for transmission at maximum power using test commands. Average power measurements were taken using a spectrum analyzer.

##### Limits:

Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

For the 1850-1910MHz band, mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

#### 3.3 Test Site

SGS EMC Laboratory, Suwanee, GA

##### Environmental Conditions

Temperature: 24.5 °C

Relative Humidity: 51.0%

Atmospheric Pressure: 98.2 kPa

#### 3.4 Test Equipment

Test End Date: 20-Jul-2017

Tester: JOP

Equipment	Model	Manufacturer	Asset Number	Cal Due Date
SIGNAL ANALYZER	FSV30	ROHDE & SCHWARZ	B085749	8-Oct-2017
ATTENUATOR, 10DB	10DB	ROHDE & SCHWARZ	B095591	27-Jul-2017
RF CABLE	SF102	HUBER & SUHNER	B079822	27-Jul-2017

- Unless otherwise noted, equipment is on a 1 year calibration cycle.
- Based on manufacturer's specifications, the FSV is on a 2 year calibration cycle.

### 3.5 Test Data

Note: All quantities of resource blocks were measured (1 through 6). There was no appreciable difference in the test results. Results for 6 RBs are reported.

Band	UpLink Channel	UL Frequency (MHz)	BW (MHz)	Measured Power (dBm)	Cable Loss (dB)	Conducted Power (dBm)
2	18607	1850.7	1.4	15.2	11.9	22.76
2	18900	1880	1.4	15.4	11.9	22.96
2	19193	1909.3	1.4	15.5	11.9	23.06
4	19957	1710.7	1.4	15.4	11.8	22.86
4	20175	1732.5	1.4	15.3	11.8	22.76
4	20393	1754.3	1.4	15.4	11.8	22.86
12	23017	699.7	1.4	16.2	11.1	22.96
12	23095	707.5	1.4	16.2	11.1	22.96
12	23173	715.3	1.4	16.2	11.1	22.96

## 4 Peak to Average Ratio

### 4.1 Test Result

Test Description	Basic Standards	Test Result
Peak to Average Ratio	24.232(d) 27.50(d)(5)	Compliant

### 4.2 Test Method

KDB document 971168 D01 Power Meas License Digital Systems v02r02 was used to determine peak-to-average ratio. For the LTE measurements, Clause 5.7.1 was used which defined the measurement method using the CCDF function of the spectrum analyzer. Measurements were recorded at the mid channels and the worst-case setting was determined to be 1RB (center), and QPSK modulation.

### 4.3 Test Site

SGS EMC Laboratory, Suwanee, GA

Environmental Conditions

Temperature: 24.5 °C

Relative Humidity: 51.0%

Atmospheric Pressure: 98.2 kPa

### 4.4 Test Equipment

Test End Date: 20-Jul-2017

Tester: JOP

Equipment	Model	Manufacturer	Asset Number	Cal Due Date
SIGNAL ANALYZER	FSV30	ROHDE & SCHWARZ	B085749	8-Oct-2017
ATTENUATOR, 10DB	10DB	ROHDE & SCHWARZ	B095591	27-Jul-2017
RF CABLE	SF102	HUBER & SUHNER	B079822	27-Jul-2017


- Unless otherwise noted, equipment is on a 1 year calibration cycle.
- Based on manufacturer's specifications, the FSV is on a 2 year calibration cycle.



### 4.5 Test Data

Note: All quantities of resource blocks were measured (1 through 6). There was no appreciable difference in the test results. Results for 6 RBs are reported.


**LTE Band 2, ULCH: 18900 (1880MHz)**  
**ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)**



Date: 20.JUL.2017 13:53:29

Note: Mean power does not include the losses associated with the attenuator and cable (11.1dB)


**LTE Band 4, ULCH: 20175 (1732.5MHz)**  
**ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)**



Date: 20.JUL.2017 15:02:02

Note: Mean power does not include the losses associated with the attenuator and cable (11.1dB)

**LTE Band 12, ULCH: 23095 (707.5MHz)**  
**ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)**



Date: 20.JUL.2017 15:11:51

Note: Mean power does not include the losses associated with the attenuator and cable (10.7dB)

## 5 Occupied Bandwidth

### 5.1 Test Result

Test Description	Basic Standards	Test Result
Occupied Bandwidth	2.1049	Reported

### 5.2 Test Method

The occupied bandwidth is the frequency bandwidth such that below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power by a given emission. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted.

The output power of the EUT was set to maximum value by test commands. The occupied bandwidth was measured using spectrum analyzer's occupied bandwidth measurement.

The bandwidth of 99% power can be read on spectrum analyzer.

The measurement was conducted at the center channel of each band. All resource blocks were explored. Worst-case results are reported.

### 5.3 Test Site

SGS EMC Laboratory, Suwanee, GA

#### Environmental Conditions

Temperature: 24.5 °C  
 Relative Humidity: 51.0%  
 Atmospheric Pressure: 98.2 kPa

### 5.4 Test Equipment

Test End Date: 20-Jul-2017

Tester: JOP

Equipment	Model	Manufacturer	Asset Number	Cal Due Date
SIGNAL ANALYZER	FSV30	ROHDE & SCHWARZ	B085749	8-Oct-2017
ATTENUATOR, 10DB	10DB	ROHDE & SCHWARZ	B095591	27-Jul-2017
RF CABLE	SF102	HUBER & SUHNER	B079822	27-Jul-2017


- Unless otherwise noted, equipment is on a 1 year calibration cycle.
- Based on manufacturer's specifications, the FSV is on a 2 year calibration cycle.

### 5.5 Test Data

Note: All quantities of resource blocks were measured (1 through 6). There was no appreciable difference in the test results. Results for 6 RBs are reported.

#### LTE Band 2


**Occupied Bandwidth: :@ULCH: 18900, BW: 1.4 MHz**  
**ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)**



Date: 20.JUL.2017 15:50:05


#### LTE Band 4

**Occupied Bandwidth: :@ULCH: 20175, BW: 1.4 MHz ,**  
**ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)**



Date: 20.JUL.2017 15:52:54

**LTE Band 12**  
**Occupied Bandwidth: :@ULCH: 23095, BW: 1.4 MHz ,**  
**ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)**



Date: 20.JUL.2017 15:44:59

## 6 Band Edge and Conducted Spurious Emissions

### 6.1 Test Result

Test Description	Basic Standards	Test Result
Conducted spurious emissions and Band Edge	2.1051 24.238(a) 27.53(h) 27.53(g)	Compliant

### 6.2 Test Method

The levels of the carrier and the various conducted spurious and harmonics frequencies are measured by means of a calibrated spectrum analyzer. The emissions spectrum emanating from the EUT transmit antenna port is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB. Compliance is based on the use of a spectrum analyzer employing a resolution bandwidth of 1 MHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of a least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emissions bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

### 6.3 Test Site

SGS EMC Laboratory, Suwanee, GA

#### Environmental Conditions

Temperature: 24.5 °C  
 Relative Humidity: 51.0%  
 Atmospheric Pressure: 98.2 kPa

### 6.4 Test Equipment

Test End Date: 20-Jul-2017

Tester: JOP


Equipment	Model	Manufacturer	Asset Number	Cal Due Date
SIGNAL ANALYZER	FSV30	ROHDE & SCHWARZ	B085749	8-Oct-2017
ATTENUATOR, 10DB	10DB	ROHDE & SCHWARZ	B095591	27-Jul-2017
RF CABLE	SF102	HUBER & SUHNER	B079822	27-Jul-2017

Unless otherwise noted, equipment is on a 1 year calibration cycle.

Based on manufacturer's specifications, the FSV is on a 2 year calibration cycle.

### 6.5 Test Data - Band Edge

Note: All quantities of resource blocks were measured (1 through 6). There was no appreciable difference in the test results. Results for 6 RBs are reported.







LTE Band 12, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)


Low Channel (23017)

High Channel (23173)




### 6.6 Test Data - Conducted Spurious Emissions


LTE Band 2, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)  
 Low Channel (18607)



Mid Channel (18900)




High Channel (19193)




LTE Band 4, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)


Low Channel (19957)



Mid Channel (20175)




High Channel (20393)




LTE Band 12, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)


Low Channel (23017)



Mid Channel (23095)



High Channel (23173)



## 7 Effective Radiated Power

### 7.1.1 Test Result

Test Description	Basic Standards	Test Result
Effective Radiated Power	27.50(c)(10)	Compliant
Effective Isotropic Radiated Power	24.232(c)	Compliant
Effective Isotropic Radiated Power	27.50(d)(4)	Compliant

### 7.1.2 Test Method

Because the IMS2 is provided with a coaxial port but no antenna, ERP/EIRP measurements were taken by using the maximum tune-up limits and defining the maximum gain antenna that may be used while maintaining compliance with the applicable ERP/EIRP and RF Exposure limits.

### 7.2 Test Site

SGS EMC Laboratory, Suwanee, GA

### 7.3 Test Equipment

None

### 7.4 Test Data

Band of Operation		Conducted Power dBm	Antenna Gain	Cable Loss	Average EIRP		Distance (R) cm	Power Density $EIRP_{Avg}/(4\pi R^2)$ mW/cm <sup>2</sup>	FCC mW/cm <sup>2</sup>	% of Limit	Verdict
Type	MHz				dBm	mW					
LTE Band 2	1850-1910	25.7	7.0	0.0	32.7	1862	20	0.370	1.00	37%	Pass
LTE Band 4	1710-1755	25.7	4.0	0.0	29.7	933	20	0.186	1.00	19%	Pass
LTE Band 12	699-716	25.7	7.0	0.0	32.7	1862	20	0.370	0.47	79%	Pass

Note: Antenna gain was determined as maximum gain while still meeting the EIRP limits and RF exposure requirements at 20cm.

## 8 Radiated Spurious Emissions

### 8.1 Test Result

Test Description	Basic Standards	Test Result
Radiated Spurious Emissions	2.1053 24.238(a) 27.53(h) 27.53(g) ANSI/TIA-603-D-2010	Compliant

### 8.2 Test Method

The levels are measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB. Compliance is based on the use of a spectrum analyzer employing a resolution bandwidth of 1 MHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of a least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emissions bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

The EUT was manipulated through each of its three orthogonal axes with the measurement oriented in both vertical and horizontal polarizations.

A radio link was established between EUT and Radio Communications Tester. The output power of the EUT was set to maximum value by using the maximum power setting on the Radio Communications Tester.

The measurements were performed at the low, middle, and high channels.

### 8.3 Test Site

SGS 10m Chamber, Suwanee, GA (validated to ANS C63.4: 2014 below and above 1GHz)

#### Environmental Conditions

Temperature: 27.7 C  
 Relative Humidity: 38.3 %  
 Atmospheric Pressure: 98.03 kpa

## 8.4 Test Equipment

Test End Date: 1-Aug-2017

Tester: ASF

Equipment	Model	Manufacturer	Asset Number	Cal Due Date
EMI TEST RECEIVER	ESU40	ROHDE & SCHWARZ	B079629	25-Apr-2018
RF CABLE	SUCOFLEX 100	HUBER & SUHNER	B108523	24-Jul-2018
LOW NOISE AMPLIFIER	TS-PR18	ROHDE & SCHWARZ	B094463	22-Feb-2018
NETWORK ANALYZER	ZVL	ROHDE & SCHWARZ	B079799	6-Mar-2018
RF CABLE	SF106	HUBER & SUHNER	B079659	25-Jul-2018
RF CABLE	SF106	HUBER & SUHNER	B079713	24-Jul-2018
RF CABLE	SF106	HUBER & SUHNER	17014	24-Jul-2018
ANTENNA, BILOG	JB6	SUNOL	B079690	10-Nov-2017
RF CABLE	SF106	HUBER & SUHNER	B079712	24-Jul-2018
ANTENNA, DRG HORN (MEDIUM)	3117	ETS LINDGREN	B079699	16-May-2018
LOW NOISE AMPLIFIER	NSP1840-HG	MITEQ	B087572	28-Jul-2018
RF CABLE	SF102	HUBER & SUHNER	B079822	27-Jul-2018
RF CABLE	SF102	HUBER & SUHNER	B079823	26-Jul-2018
HORN(SMALL)	LB-180400-20-C-KF	A-INFO	15007	21-Mar-2018


- Unless otherwise noted, equipment is on a 1 year calibration cycle.

### 8.5 Test Data


LTE Band 2, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Low Channel (18607)

Vertical Data (30-1000MHz)




Horizontal Data (30-1000MHz)






LTE Band 2, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Low Channel (18607)  
 Vertical Data (1-18GHz)




Horizontal Data (1-18GHz)




LTE Band 2, QPSK modulation, 1.4MHz  
ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Low Channel (18607)  
Vertical Data (18-20GHz)




Horizontal Data (18-20GHz)




LTE Band 2, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Mid Channel (18900)  
 Vertical Data (30-1000MHz)




Horizontal Data (30-1000MHz)




LTE Band 2, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Mid Channel (18900)  
 Vertical Data (1-18GHz)




Horizontal Data (1-18GHz)




LTE Band 2, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Mid Channel (18900)  
 Vertical Data (18-20GHz)




Horizontal Data (18-20GHz)




LTE Band 2, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

High Channel (19193)  
 Vertical Data (30-1000MHz)




Horizontal Data (30-1000MHz)




LTE Band 2, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

High Channel (19193)  
 Vertical Data (1-18GHz)



Horizontal Data (1-18GHz)




LTE Band 2, QPSK modulation, 1.4MHz


High Channel (19193)

ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Vertical Data (18-20GHz)




Horizontal Data (18-20GHz)






LTE Band 4, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Low Channel (19957)  
 Vertical Data (30-1000MHz)




Horizontal Data (30-1000MHz)




LTE Band 4, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Low Channel (19957)  
 Vertical Data (1-18GHz)




Horizontal Data (1-18G Hz)




LTE Band 4, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Mid Channel (20175)  
 Vertical Data (30-1000MHz)




Horizontal Data (30-1000MHz)




LTE Band 4, QPSK modulation, 1.4MHz  
ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Mid Channel (20175)  
Vertical Data (1-18GHz)




Horizontal Data (1-18GHz)




LTE Band 4, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

High Channel (20393)  
 Vertical Data (30-1000MHz)




Horizontal Data (30-1000MHz)




LTE Band 4, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

High Channel (20393)  
 Vertical Data (1-18GHz)




Horizontal Data (1-18GHz)




LTE Band 12, QPSK modulation, 1.4MHz  
ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

### Low Channel (23017) Vertical Data (30-1000MHz)




### Horizontal Data (30-1000MHz)




LTE Band 12, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Low Channel (23017)  
 Vertical Data (1-18GHz)




Horizontal Data (1-18GHz)






LTE Band 12, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Mid Channel (23095)  
 Vertical Data (30-1000MHz)




Horizontal Data (30-1000MHz)




LTE Band 12, QPSK modulation, 1.4MHz  
 UL Power: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

Mid Channel (23095)  
 Vertical Data (1-18GHz)




Horizontal Data (1-18GHz)




LTE Band 12, QPSK modulation, 1.4MHz  
ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

High Channel (23173)  
Vertical Data (30-1000MHz)




Horizontal Data (30-1000MHz)




LTE Band 12, QPSK modulation, 1.4MHz  
 ULPower: 23dBm; UL\_MOD\_RB: QPSK, 6 (RB\_Pos:0)

High Channel (23173)  
 Vertical Data (1-18GHz)



Horizontal Data (1-18GHz)



## 9 Frequency Stability

### 9.1 Test Result

Test Description	Basic Standards	Test Result
Frequency Stability	2.1055 24.238(a) 27.5(c) 27.5(h) 27.54	Compliant

### 9.2 Test Method

The EUT was placed inside the Environmental Chamber and was left inside chamber to stabilize to set temperature for minimum of thirty minutes before any measurements were made. The EUT was tested at the middle channel of Bands 2, 4, and 12.

### 9.3 Test Site

SGS EMC Laboratory, Suwanee, GA

### 9.4 Test Equipment

Test End Date: 24-Jul-2017

Tester: JOP


Equipment	Model	Manufacturer	Asset Number	Cal Due Date
SIGNAL ANALYZER	FSV30	ROHDE & SCHWARZ	B085749	8-Oct-2017
ATTENUATOR, 10DB	10DB	ROHDE & SCHWARZ	B095591	27-Jul-2017
RF CABLE	SF102	HUBER & SUHNER	B079822	27-Jul-2017
MULTIMETER	87V	FLUKE	B079675	29-Jul-2017
ENVIRONMENTAL TEST CHAMBER	T2RC	TENNEY ENVIRONMENTAL	B094877	CNR

- Unless otherwise noted, equipment is on a 1 year calibration cycle.
- Based on manufacturer's specifications, the FSV is on a 2 year calibration cycle.

### 9.5 Test Data


Band 2, Channel 18900

Voltage %	Power V <sub>DC</sub>	Temp °C	Frequency Hz	Freq Dev	Freq Dev ppm	Deviation %
100%	3.80	+20 (Ref)	1,880,000,702	+702	+0.37	+0.000037
100%	3.80	-30	1,880,000,659	+659	+0.35	+0.000035
100%	3.80	-20	1,880,000,738	+738	+0.39	+0.000039
100%	3.80	-10	1,880,000,810	+810	+0.43	+0.000043
100%	3.80	0	1,880,000,630	+630	+0.33	+0.000033
100%	3.80	+10	1,880,000,731	+731	+0.39	+0.000039
100%	3.80	+20	1,880,000,702	+702	+0.37	+0.000037
100%	3.80	+30	1,880,000,926	+926	+0.49	+0.000049
100%	3.80	+40	1,880,001,042	+1042	+0.55	+0.000055
100%	3.80	+50	1,880,000,707	+707	+0.38	+0.000038
100%	3.80	+55	1,880,001,049	+1049	+0.56	+0.000056
115%	4.37	+20	1,880,000,709	+709	+0.38	+0.000038
85%	3.23	+20	1,880,000,702	+702	+0.37	+0.000037




Band 4, Channel 20175

Voltage %	Power V <sub>DC</sub>	Temp °C	Frequency Hz	Freq Dev	Freq Dev ppm	Deviation %
100%	3.80	+20 (Ref)	1,732,500,659	+659	+0.38	+0.000038
100%	3.80	-30	1,732,500,579	+579	+0.33	+0.000033
100%	3.80	-20	1,732,500,637	+637	+0.37	+0.000037
100%	3.80	-10	1,732,500,774	+774	+0.45	+0.000045
100%	3.80	0	1,732,500,586	+586	+0.34	+0.000034
100%	3.80	+10	1,732,500,687	+687	+0.40	+0.000040
100%	3.80	+20	1,732,500,659	+659	+0.38	+0.000038
100%	3.80	+30	1,732,500,847	+847	+0.49	+0.000049
100%	3.80	+40	1,732,500,848	+848	+0.49	+0.000049
100%	3.80	+50	1,732,500,962	+962	+0.56	+0.000056
100%	3.80	+55	1,732,500,984	+984	+0.57	+0.000057
115%	4.37	+20	1,732,500,651	+651	+0.38	+0.000038
85%	3.23	+20	1,732,500,659	+659	+0.38	+0.000038



Band 12, Channel 23095

Voltage %	Power V <sub>DC</sub>	Temp °C	Frequency Hz	Freq Dev	Freq Dev ppm	Deviation %
100%	3.80	+20 (Ref)	707,500,268	+268	+0.38	+0.000038
100%	3.80	-30	707,500,268	+268	+0.38	+0.000038
100%	3.80	-20	707,500,261	+261	+0.37	+0.000037
100%	3.80	-10	707,500,318	+318	+0.45	+0.000045
100%	3.80	0	707,500,246	+246	+0.35	+0.000035
100%	3.80	+10	707,500,282	+282	+0.40	+0.000040
100%	3.80	+20	707,500,268	+268	+0.38	+0.000038
100%	3.80	+30	707,500,340	+340	+0.48	+0.000048
100%	3.80	+40	707,500,369	+369	+0.52	+0.000052
100%	3.80	+50	707,500,398	+398	+0.56	+0.000056
100%	3.80	+55	707,500,391	+391	+0.55	+0.000055
115%	4.37	+20	707,500,268	+268	+0.38	+0.000038
85%	3.23	+20	707,500,268	+268	+0.38	+0.000038





## 10 Revision History

Revision Level	Description of changes	Revision Date
0	Initial release	24 August 2017
1	- Updated ERP/EIRP table using maximum tune-up limits in lieu of measured conducted power.	05 September 2017