

RADIO TEST REPORT

Type of assessment:

MPE Exemption report

Manufacturer:

Thales DIS USA, Inc

Equipment description:

RFID Module

Hardware Version Identification Number (HVIN):

PR-01737

HMNs:

PV70-02-02-00-01	PV75-02-02-07-01
PV70-02-02-01-01	PV75-02-02-08-01
PV70-02-02-05-01	PV75-02-05-00-01
PV70-03-02-00-01	PV75-03-02-00-01
PV75-02-02-00-01	PV75-03-02-07-01
PV75-02-02-00-02	PV70-02-02-00-02
PV70-02-02-06-01	

FCC Identifier:

FCC ID: 2AQL3PR01737

ISED certification number:

IC: 22832-PR01737

Specification:

- ◆ FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ FCC KDB 447498 D01 General RF Exposure Guidance v06
- ◆ ISED Canada RSS-102 Issue 5 Amendment 1, (February 2021)

Declaration of RF exposure compliance for exemption from routine evaluation limits


RSS-102 Annex C - Attestation:

I attest that the radiocommunication apparatus meets the exemption from the routine evaluation limits in Section 2.5 of RSS-102 standard; that the Technical Brief was prepared, and the information contained therein is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed; and that the device meets the SAR and/or RF field strength limits of RSS-102.

Date of issue: **August 31, 2022**

Andrey Adelberg, Senior EMC/RF Specialist

Prepared by



Signature



Lab locations

Company name	Nemko Canada Inc.			
Facilities	<i>Ottawa site:</i> 303 River Road Ottawa, Ontario Canada K1V 1H2 Tel: +1 613 737 9680 Fax: +1 613 737 9691	<i>Montréal site:</i> 292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8 Tel: +1 514 694 2684 Fax: +1 514 694 3528	<i>Cambridge site:</i> 1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2 Tel: +1 519 650 4811	<i>Almonte site:</i> 1500 Peter Robinson Road West Carleton, Ontario Canada K0A 1L0 Tel: +1 613 256-9117
	Test site identifier	Organization	Ottawa/Almonte	Montreal
	FCC:	CA2040	CA2041	CA0101
	ISED:	2040A-4	2040G-5	24676
Website	www.nemko.com			

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

Section 1 Evaluation summary

1.1 MPE exemption for standalone transmission

1.1.1 References, definitions and limits

FCC §2.1091(c)

- (1) Mobile devices that operate in the Commercial Mobile Radio Services pursuant to part 20 of this chapter; the Cellular Radiotelephone Service pursuant to part 22 of this chapter; the Personal Communications Services pursuant to part 24 of this chapter; the Satellite Communications Services pursuant to part 25 of this chapter; the Miscellaneous Wireless Communications Services pursuant to part 27 of this chapter; the Upper Microwave Flexible Use Service pursuant to part 30 of this chapter; the Maritime Services (ship earth station devices only) pursuant to part 80 of this chapter; the Specialized Mobile Radio Service, and the 3650 MHz Wireless Broadband Service pursuant to part 90 of this chapter; the 76–81 GHz Band Radar Service pursuant to part 95 of this chapter; and the Citizens Broadband Radio Service pursuant to part 96 of this chapter are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if:
 - (i) They operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or
 - (ii) They operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.
- (2) Unlicensed personal communications service devices, unlicensed millimeter-wave devices, and unlicensed NII devices authorized under §§15.255(f), 15.257(g), 15.319(i), and 15.407(f) of this chapter are also subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if their ERP is 3 watts or more or if they meet the definition of a portable device as specified in §2.1093(b) requiring evaluation under the provisions of that section.
- (3) All other mobile and unlicensed transmitting devices are categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, except as specified in §§1.1307(c) and 1.1307(d) of this chapter.

RSS-102, Section 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $0.0131 f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

1.1.2 EUT technical information

Operational frequency	13.56 MHz
Antenna type	Internal
Number of antennas	1
Maximum field strength	67.80 dBµV/m

1.1.3 MPE exemption calculation

Fundamental transmit (prediction) frequency: 13.56 MHz
Maximum measured field strength at 3 m: 67.8 dB μ V/m
Duty cycle: 100 %
Maximum calculated average field strength: 67.8 dB μ V/m

	<u>ISED limit</u>	<u>FCC limit</u>
MPE exemption limit:	<u>1.000000</u> W	<u>1.500000</u> W
Average EIRP at prediction frequency:	<u>0.002</u> mW <u>0.000</u> W	<u>0.002</u> mW <u>0.000</u> W
Margin of Compliance:	<u>57.43</u> dB	<u>59.19</u> dB

1.1.4 Verdict

The calculation of EIRP is below the exemption limit; therefore, the product is passing the RF Exposure exemption requirements.

End of the test report