



**CTC**  **advanced**  
member of RWTÜV group



Bundesnetzagentur

BNetzA-CAB-02/21-102



**DAkkS**  
Deutsche  
Akrediterungsstelle  
D-PL-12076-01-03

## **SAR Test exclusion documentation according to FCC KDB 447498, RSS-102**

**Report identification number: 1-6689/18-01-01 Exclusion (FCC\_IC)**

**contains the module with the following certification numbers**

FCC ID	2AQME-MYUB-PLUG
IC number	24130-MYUBPLUG
HVIN (Hardware Version Identification Number)	MYUB-PLUG; MYUB-ROLL/1000; MYUB-ROLL/1250; MYUB-ROLL/1500
PMN (Product Marketing Name)	MYUB-PLUG; MYUB-ROLL/1000; MYUB-ROLL/1250; MYUB-ROLL/1500
FVIN (Firmware Version Identification Number)	Test Firmware v1.2.1 with BLE stack V. 4.2
HMN (Host Marketing Name)	-/-

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

**Document authorised:**

Mihail Dorongovskij  
Lab Manager  
Radio Communications & EMC

**EUT technologies:**

Technologies:	Max. declared PEAK EIRP:	Max. Declared AVG EIRP
Bluetooth LE	4.3 dBm	4.3 dBm

\*) Max. Peak EIRP measured including measurement uncertainty.

**SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)**

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances  $\leq$  50mm

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{seperation}} / f^{0.5}$$

where

$\text{Threshold}_{1\text{-g};10\text{-g}}$  is 3 for 1-g; 7.5 for 10-g

$d_{\text{seperation}}$  is the min. test separation distance; 5mm is used if the distance is less

$f$  is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	d <sub>seperation</sub> [mm]	Threshold <sub>1-g</sub>	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
				[dBm]	[mW]	
2440,00	5	3	9,60	4,30	2,69	yes

**SAR test exclusion according to RSS-102 Issue 5 Section 2.5.1/Table 1**

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	d <sub>seperation</sub> [mm]	tissue volume	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
				[dBm]	[mW]	
2440,00	5	1 g	4,00	4,30	2,69	yes