



FCC TEST REPORT

FCC ID: 2AQMU-6182-1DC

On Behalf of

HUACAI KEYI INDUSTRY COMMERCE CO.,LTD.

THE REMOTE CONTROL OF FOLDING SELFIE 4

CHANNEL FOLDABLE DRONE

Model No.: 6182-1DC, HC655, HC656, HC657, HC658,

HC659, HC660, HC661, HC662, HC631

Prepared for : HUACAI KEYI INDUSTRY COMMERCE CO.,LTD.
Address : The North of the Middle Section of Guangyi Road, Chenghai
Shantou, Guangdong Province, China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District,
518103, Shenzhen, Guangdong, China

Report Number : T1881083 01
Date of Receipt : July 11, 2018
Date of Test : July 11, 2018 - September 10, 2018
Date of Report : September 10, 2018
Version Number : REV0

TABLE OF CONTENTS

Description	Page
1. Summary of Standards And Results.....	6
1.1. Description of Standards and Results	6
2. General Information	7
2.1. Description of Device (EUT).....	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators.....	8
2.5. Test Mode Description.....	8
2.6. Test Conditions	9
2.7. Test Facility	9
2.8. Measurement Uncertainty	9
2.9. Test Equipment List.....	10
3. Power Line Conducted Emission Test.....	11
3.1. Block Diagram of Test Setup.....	11
3.2. Test Limits	11
3.3. Configuration of EUT on Test	12
3.4. Operating Condition of EUT	12
3.5. Test Procedure	12
3.6. Test Results.....	13
4. Radiated Emission Test.....	14
4.1. Block Diagram of Test Setup.....	14
4.2. Test Limit.....	15
4.3. Configuration of EUT on Test	16
4.4. Operating Condition of EUT	16
4.5. Test Procedure	16
4.6. Test Results.....	17
5. Band Edge Test.....	23
5.1. Block Diagram of Test Setup.....	23
5.2. Test Limit.....	23
5.3. Configuration of EUT on Test	24
5.4. Operating Condition of EUT	24
5.5. Test Procedure	24
5.6. Test Results.....	26
6. Occupied bandwidth Test	28
6.1. Block Diagram of Test Setup.....	28
6.2. Test Limit.....	28
6.3. Test Procedure	28
6.4. Test Results.....	28
7. Antenna Requirement	30

7.1. Standard Requirement.....	30
7.2. Antenna Connected Construction	30
7.3. Results.....	30
8. Photograph	31
8.1. Photos of Radiated Emission Test (In Semi Anechoic Chamber)	31
9. Photos of The EUT	32

TEST REPORT DECLARATION


Applicant : HUACAI KEYI INDUSTRY COMMERCE CO.,LTD.
 Address : The North of the Middle Section of Guangyi Road, Chenghai
 Shantou, Guangdong Province, China
 Manufacturer : HUACAI KEYI INDUSTRY COMMERCE CO.,LTD.
 Address : The North of the Middle Section of Guangyi Road, Chenghai
 Shantou, Guangdong Province, China
 EUT Description : THE REMOTE CONTROL OF FOLDING SELFIE 4 CHANNEL
 FOLDABLE DRONE
 (A) Model No. : 6182-1DC, HC655, HC656, HC657, HC658,
 HC659, HC660, HC661, HC662, HC631
 (B) Trademark : N/A


Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.249: 2018, ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part15 requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Reak Yang 
 Project Engineer

Approved by (name + signature).....: Simple Guan 
 Project Manager

Date of issue..... : September 10, 2018

Revision History

Revision	Issue Date	Revisions	Revised By
00	September 10, 2018	Initial released Issue	Simple Guan

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

EMISSION			
Description of Test Item	Test Requirement	Standard Paragraph	Results
Power Line Conducted Emission Test	FCC Part 15:2018	Section 15.207	N/A
Spurious Emission Test	FCC Part 15:2018	Section 15.249&15.209	P
Occupied bandwidth	FCC Part 15:2018	Section 15.215	P
Band edge Requirement	FCC Part 15:2018	Section 15.249	P
Antenna Requirement	FCC Part 15:2018	Section 15.203	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.			

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description	: THE REMOTE CONTROL OF FOLDING SELFIE 4 CHANNEL FOLDABLE DRONE
Model Number	: 6182-1DC, HC655, HC656, HC657, HC658, HC659, HC660, HC661, HC662, HC631
Diff	: There is no difference between all the models, except the model number, this report performs the model 6182-1DC.
Trademark	: N/A
Test Voltage	: 3*DC 1.5V AA battery
Operation frequency	: 2415-2470MHz
Channel No.	: 56
Channel Separation	: 1MHz
Modulation type	: GFSK
Antenna Type	: Internal Antenna, max gain 0dBi.
Software version	: V1.0
Hardware version	: JR-HC655T
Sample Type	: Prototype production


2.2. Accessories of Device (EUT)

Accessory 1 : /

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or DOC
1	N/A	N/A	N/A	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Test mode:

Mode	Channel	Frequency (MHz)
GFSK	CH1	2415
GFSK	CH31	2445
GFSK	CH56	2470

Note:

1. The test was used to control EUT work in Continuous TX mode, and select test channel, wireless mode
2. The EUT has been tested as an independent unit. And Continual Transmitting in maximum power.
3. New battery is used during all tests.
4. For the relevant Conducted Measurement, the temporary antenna connector is used during the measurement. Antenna Connector Impedance: 50Ω , Cable Loss: 1.0 dB

2.6. Test Conditions

Temperature range	21-25°C
Humidity range	40-75%
Pressure range	86-106kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd.

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District,
518103, Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission
Registration Number: 293961

July 25, 2017 Certificated by IC
Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)


Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77 dB (Distance: 3m Polarize: V)
	3.80 dB (Distance: 3m Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.16 dB (Distance: 3m Polarize: V)
	4.13 dB (Distance: 3m Polarize: H)
Uncertainty for radio frequency	5.8×10^{-8}
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
3m Semi-Anechoic	ETS-LINDGREN	N/A	SEL0017	2017.09.22	1 Year
Spectrum analyzer	Agilent	E4407B	MY46185649	2017.09.22	1 Year
Receiver	R&S	ESCI	1166.5950K03-10 11	2017.09.22	1 Year
Receiver	R&S	ESCI	101202	2017.09.22	1 Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2016.09.30	2 Year
Horn Antenna	EMCO	3115	640201028-06	2016.09.30	2 Year
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	2016.09.30	2 Year
Cable	Resenberger	N/A	No.1	2017.09.22	1 Year
Cable	SCHWARZBECK	N/A	No.2	2017.09.22	1 Year
Cable	SCHWARZBECK	N/A	No.3	2017.09.22	1 Year
Pre-amplifier	Schwarzbeck	BBV9743	9743-019	2017.09.22	1 Year
Pre-amplifier	R&S	AFS33-18002	SEL0080	2017.09.22	1 Year
Temperature	Terchy	MHQ	120	2017.09.22	1 Year
20db Attenuator	ICPROBING	IATS1	82347	2017.09.22	1 Year
18-40 Horn Antenna	18-40G antenna	Sas-574	571	2018-3-15	3 Year

3. POWER LINE CONDUCTED EMISSION TEST

3.1. Block Diagram of Test Setup



3.2. Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

- Notes:
1. Emission level=Read level + LISN factor-Preamp factor + Cable loss
 2. * Decreasing linearly with logarithm of frequency.
 3. The lower limit shall apply at the transition frequencies.

3.3. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4. Operating Condition of EUT

- (1) Setup the EUT as shown as Section 3.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in test mode taking the test.

3.5. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#2). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on conducted Emission test.
- (2) The frequency range from 150kHz to 30MHz is checked, the bandwidth of test receiver (R&S TEST RECEIVER ESCI) is set at 9kHz.
- (3) The frequency range from 30MHz to 1000MHz was pre-scanned with a Peak detector and all final readings of measurement from Test Receiver are Quasi-Peak and Average values.
- (4) The test results are reported on Section 3.6.


3.6. Test Results

EUT	THE REMOTE CONTROL OF : FOLDING SELFIE 4 CHANNEL FOLDABLE DRONE	Test Date	: N/A
M/N	: 6182-1DC	Temperature	: N/A
Test Engineer	: N/A	Humidity	: N/A
Test Mode	: N/A		
Test Results	: N/A		
Note: 1. Not applicable for equipment operated with battery power supply.			


4. RADIATED EMISSION TEST

4.1. Block Diagram of Test Setup


In Semi Anechoic Chamber (3m) Test Setup Diagram for 9KHz~30MHz



In Semi Anechoic Chamber (3m) Test Setup Diagram for 30MHz~1000MHz



In Semi Anechoic Chamber (3m) Test Setup Diagram for Above 1GHz



4.2. Test Limit

Frequency MHz	Distance (Meters)	Field Strengths Limits	
		uV/m	dB uV/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	----
1.705 ~ 30	30	30	29.5
30 ~ 88	3	100(3nW)	40
88 ~ 216	3	150(6.8nW)	43.5
216 ~ 960	3	200(12nW)	46
Above 960	3	500(75nW)	54
Carrier frequency	3	50000(avg)	113.97(peak) 93.97(avg)

Notes:

1. Emission level = Read level + Antenna Factor - Preamp Factor + Cable Loss
2. The smaller limit shall apply at the cross point between two frequency bands.
3. Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
4. For frequencies above 1000 MHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

4.3. Configuration of EUT on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner that tends to maximize its emission characteristics in normal application.

4.4. Operating Condition of EUT

- (1) Setup the EUT as shown as Section 4.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in test mode taking the test.

4.5. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1GHz and 150 cm above the ground plane inside a semi-anechoic chamber for above 1GHz. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10: 2013 on Radiated Emission test.
- (2) For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- (3) Test antenna was located 4m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP

- (5) The frequency range from 9KHz to 150KHz is checked, the bandwidth of test receiver (R&S TEST RECEIVER ESCI) is set at 200Hz.
The frequency range from 150KHz to 30MHz is checked, the bandwidth of test receiver (R&S TEST RECEIVER ESCI) is set at 9KHz.
The frequency range from 30MHz to 1000MHz is checked, the bandwidth of test receiver (R&S TEST RECEIVER ESCI) is set at 120kHz.
The frequency range from above 1GHz is checked, the bandwidth of Signal Analyzer (Signal Analyzer N9020A) is set at 1MHz.
- (6) The frequency range from 30MHz to 1000MHz was pre-scanned with a peak detector and all final readings of measurement from Test Receiver are Quasi-Peak values, the frequency range from 1GHz to 6GHz was pre-scanned with a peak detector and all final readings of measurement from Spectrum Analyzer are peak and average values checked, all measurement distance is 3m in 3m semi anechoic chamber.
- (7) Test for all x, y, z axes is performed and only the worst case of X axes was recorded in the test report.
- (8) The test results are reported on Section 4.6.

4.6. Test Results


Frequency Range : 9KHz~30MHz	
EUT : THE REMOTE CONTROL OF FOLDING SELFIE 4 CHANNEL FOLDABLE DRONE	Test Date : 2018.07.18
M/N : 6182-1DC	Temperature : 23.9°C
Test Engineer : Reak Yang	Humidity : 56%
Test Mode : TX CH1	
Test Results : PASS	
Note: 1. Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.	

Frequency Range : 30MHz~1000MHz	
EUT : THE REMOTE CONTROL OF FOLDING SELFIE 4 CHANNEL FOLDABLE DRONE	Test Date : 2018.07.18
M/N : 6182-1DC	Temperature : 23.9°C
Test Engineer : Reak Yang	Humidity : 56%
Test Mode : TX CH1	
Test Results : PASS	
Note: 1. The test results are listed in next pages. 2. This mode is worst case mode, and this report only reflected the worst mode. 3. If the limits for the measurement with the quasi-peak detector are met when using a	

receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the quasi-peak detector need not be carried out.

Vertical:

Radiated Emission Measurement




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree	Comment
1		39.0245	9.00	14.20	23.20	40.00	-16.80			peak
2		61.9951	8.61	12.55	21.16	40.00	-18.84			peak
3		107.8877	8.44	11.32	19.76	43.50	-23.74			peak
4		155.9101	8.87	14.57	23.44	43.50	-20.06			peak
5		443.2943	10.17	16.73	26.90	46.00	-19.10			peak
6	*	766.0571	10.03	21.78	31.81	46.00	-14.19			peak

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Horizontal:

Radiated Emission Measurement



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree	Comment
1	37.2855	9.10	13.82	22.92	40.00	-17.08	peak			
2	66.9669	7.51	11.50	19.01	40.00	-20.99	peak			
3	159.7844	8.36	14.58	22.94	43.50	-20.56	peak			
4	375.9385	9.48	15.31	24.79	46.00	-21.21	peak			
5	631.6884	10.18	19.85	30.03	46.00	-15.97	peak			
6 *	909.6667	10.12	23.25	33.37	46.00	-12.63	peak			

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


Frequency Range : 1GHz~25GHz								
EUT : THE REMOTE CONTROL OF FOLDING SELFIE 4 CHANNEL FOLDABLE DRONE						Test Date : 2018.07.18		
M/N : 6182-1DC						Temperature : 23.9°C		
Test Engineer : Reak Yang						Humidity : 56%		
Test Mode : TX 2415MHz								
Test Results : PASS								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2415	H	76.62	-3.38	73.24	113.97	-40.73	Peak
2	2415	H	72.30	-3.38	68.92	93.97	-25.05	Avg
3	4830	H	42.31	3.23	45.54	74	-28.46	Peak
4	4830	H	--	3.23	--	54	--	Avg
5	7245	H	38.94	10.57	49.51	74	-24.49	Peak
6	7245	H	--	10.57	--	54	--	Avg
1	2415	V	71.40	-3.38	68.02	113.97	-45.95	Peak
2	2415	V	68.00	-3.38	64.62	93.97	-29.35	Avg
3	4830	V	43.22	3.23	46.45	74	-27.55	Peak
4	4830	V	--	3.23	--	54	--	Avg
5	7245	V	39.08	10.57	49.65	74	-24.35	Peak
6	7245	V	--	10.57	--	54	--	Avg
Note:	<p>1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.</p> <p>2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.</p> <p>3. Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK.</p> <p>4. Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: Avg.</p> <p>5. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.</p>							

Frequency Range : 1GHz~25GHz								
EUT : THE REMOTE CONTROL OF FOLDING SELFIE 4 CHANNEL FOLDABLE DRONE						Test Date : 2018.07.18		
M/N : 6182-1DC						Temperature : 23.9°C		
Test Engineer : Reak Yang						Humidity : 56%		
Test Mode : TX 2445MHz								
Test Results : PASS								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2445	H	72.75	-3.38	69.37	113.97	-44.60	Peak
2	2445	H	68.97	-3.38	65.59	93.97	-28.38	Avg
3	4890	H	41.66	3.23	44.89	74	-29.11	Peak
4	4890	H	--	3.23	--	54	--	Avg
5	7335	H	38.24	10.57	48.81	74	-25.19	Peak
6	7335	H	--	10.57	--	54	--	Avg
1	2445	V	69.39	-3.38	66.01	113.97	-47.96	Peak
2	2445	V	65.18	-3.38	61.80	93.97	-32.17	Avg
3	4890	V	44.68	3.23	47.91	74	-26.09	Peak
4	4890	V	--	3.23	--	54	--	Avg
5	7335	V	37.60	10.57	48.17	74	-25.83	Peak
6	7335	V	--	10.57	--	54	--	Avg
Note:	<p>1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.</p> <p>2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.</p> <p>3. Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK.</p> <p>4. Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: Avg.</p> <p>5. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.</p>							

Frequency Range : 1GHz~25GHz								
EUT : THE REMOTE CONTROL OF FOLDING SELFIE 4 CHANNEL FOLDABLE DRONE						Test Date : 2018.07.18		
M/N : 6182-1DC						Temperature : 23.9°C		
Test Engineer : Reak Yang						Humidity : 56%		
Test Mode : TX 2470MHz								
Test Results : PASS								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2470	H	77.16	-3.38	73.78	113.97	-40.19	Peak
2	2470	H	74.02	-3.38	70.64	93.97	-23.33	Avg
3	4940	H	42.17	3.23	45.40	74	-28.60	Peak
4	4940	H	--	3.23	--	54	--	Avg
5	7410	H	39.39	10.57	49.96	74	-24.04	Peak
6	7410	H	--	10.57	--	54	--	Avg
1	2470	V	72.78	-3.38	69.40	113.97	-44.57	Peak
2	2470	V	66.88	-3.38	63.50	93.97	-30.47	Avg
3	4940	V	44.64	3.23	47.87	74	-26.13	Peak
4	4940	V	--	3.23	--	54	--	Avg
5	7410	V	39.31	10.57	49.88	74	-24.12	Peak
6	7410	V	--	10.57	--	54	--	Avg
Note:	<p>1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.</p> <p>2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.</p> <p>3. Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK.</p> <p>4. Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: Avg.</p> <p>5. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.</p>							

5. BAND EDGE TEST

5.1. Block Diagram of Test Setup



5.2. Test Limit

Please refer section 15.249 and section 15.205.

249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in section 15.209, whichever is the lesser attenuation.

249(e) As show in section 15.35(b), for frequencies above 1000MHz, the above field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak filed strength shall not exceed 2500 millivolts/meter at 3meters along the antenna azimuth.

5.3. Configuration of EUT on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner that tends to maximize its emission characteristics in normal application.

5.4. Operating Condition of EUT

- (1) Setup the EUT as shown as Section 5.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in test mode taking the test.

5.5. Test Procedure

- (1) The EUT was placed on a non-metallic table, 150 cm above the ground plane inside a semi-anechoic chamber. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10: 2013 on Radiated Emission test.
- (2) For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- (3) Test antenna was located 4m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions


- (5) The frequency range from above 1GHz is checked, the bandwidth of Signal Analyzer (Signal Analyzer N9020A) is set at 1MHz.
- (6) The frequency range from 1GHz to 6GHz was pre-scanned with a peak detector and all final readings of measurement from Spectrum Analyzer are peak and average values checked, all measurement distance is 3m in 3m semi anechoic chamber.
- (7) Test for all x, y, z axes is performed and only the worst case of X axes was recorded in the test report.
- (8) The test results are reported on Section 5.6.

5.6. Test Results

Polarization: Vertical

Test Mode: GFSK-Low

Radiated Emission Measurement




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2390.000	44.31	8.42	52.73	74.00	-21.27	peak		
2	*	2414.991	60.74	8.41	69.15	74.00	-4.85	peak		

Polarization: Horizontal

Test Mode: GFSK-Low

Radiated Emission Measurement




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2390.000	43.91	8.42	52.33	74.00	-21.67	peak		
2	*	2414.991	64.84	8.41	73.25	74.00	-0.75	peak		

Polarization: Vertical

Test Mode: GFSK-High

Radiated Emission Measurement

File :6182-1DC Data :#20 Date: 2018/9/10 Time: 9:11:51




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2469.820	61.22	8.43	69.65	74.00	-4.35			peak
2		2483.500	43.53	8.44	51.97	74.00	-22.03			peak

Polarization: Horizontal

Test Mode: GFSK-High

Radiated Emission Measurement

File :6182-1DC Data :#21 Date: 2018/9/10 Time: 9:13:35




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2469.919	65.88	8.43	74.31	74.00	0.31			peak
2		2483.500	43.59	8.44	52.03	74.00	-21.97			peak

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

6. OCCUPIED BANDWIDTH TEST

6.1. Block Diagram of Test Setup



6.2. Test Limit

Please refer section 15.249 and section 15.205.

6.3. Test Procedure


- (1) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- (2) The test receiver RBW set 10KHz, VBW set 30KHz, Sweep time set auto.

6.4. Test Results


Mode	Frequency MHz	20dB Bandwidth (KHz)	99% Bandwidth (KHz)	Limit (kHz)
GFSK	2415	51.77	96.490	/
GFSK	2445	53.33	96.674	/
GFSK	2470	54.95	89.907	/

Note: 1. The test results are listed in next pages.


Frequency: 2415MHz



Frequency: 2445MHz



Frequency: 2470MHz



7. ANTENNA REQUIREMENT

7.1. Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

7.2. Antenna Connected Construction


The directional gains of antenna used for transmitting is 0dBi, and the antenna is fixed antenna no consideration of replacement. Please see EUT photo for details.

7.3. Results

The EUT antenna is Internal Antenna. It complies with the standard requirement.

8. PHOTOGRAPH

8.1.Photos of Radiated Emission Test





9. PHOTOS OF THE EUT














----END OF REPORT----