

# FCC RF Exposure

EUT Description: **14.1 INCH NEO Notebook**

Model No.: **WWNEO14C4BK64-P**

FCC ID: **2AQOO-N14AC464P**

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,

Where:

Result =  $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm <sup>2</sup> )	SAR Test Exclusion
EDR	1.259	1±1(2)	1.585	5	0.499	3.0	Pass
2.4GWIFI	8.43	7.5±1(8.5)	7.079	5	2.222	3.0	Pass
5.2GWIFI	7.49	6.5±1(7.5)	5.623	5	2.562	3.0	Pass

Note:

PK Output power = conducted power.

Conducted power see the test report **HK2011123502-1E/2E/3E**,

BT antenna gain = 1.72dBi

2.4GWIFI antenna gain = 1.64dBi

5.2GWIFI antenna gain = 1.64dBi

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 2.222 which is  $\leq 3$ , SAR testing is not required.

Note: Exclusion Thresholds Results =  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance = 5mm

Note: the device could not transmit simultaneously in BT/2.4G WIFI/5.2G WIFI.