


FCC RF EXPOSURE REPORT

FCC ID: 2AQPW-SB485

Project No. : 2106T118
Equipment : Ultra Bright LCD Display with LED Backlight
Brand Name : Seura
Test Model : UB4-85
Series Model : N/A
Applicant : Innolux Corporation
Address : No. 160, Kesyue Rd. Jhunan Science Park, Miaoli County, Taiwan 350
Manufacturer : Innolux Corporation
Address : No. 160, Kesyue Rd. Jhunan Science Park, Miaoli County, Taiwan 350
Factory : Keewin Display Co., Ltd.
Address : No.17 Chengpu Road, Suzhou Jiangsu Province, 215400, China
Date of Receipt : Jun. 29, 2021
Date of Test : Jun. 29, 2021 ~ Jul. 26, 2021
Issued Date : Aug. 04, 2021
Report Version : R00
Test Sample : Engineering Sample No.: DG20210629327
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.


Prepared by : Nick Chen


Approved by : Ethan Ma



TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China

Tel: +86-769-8318-3000

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Aug. 04, 2021

1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China
BTL's Test Firm Registration Number for FCC: 357015
BTL's Designation Number for FCC: CN1240

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

Ant.	Manufacturer	P/N	Antenna Type	Connector	Gain (dBi)
1	SHENZHEN ZHONGTIAN XUN Communication Technology Co., Ltd.	61005-00244	Internal	N/A	2.99

Note:

The antenna gain is provided by the manufacturer.

3. TEST RESULTS

For BT:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.99	1.9907	9.79	9.5280	0.00378	1	Complies

For LE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.99	1.9907	2.76	1.8880	0.00075	1	Complies

Note: The calculated distance is 20 cm.
Output power including tune up tolerance.

End of Test Report