

Page 28 of 48

#### 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

#### **10.1 MEASUREMENT PROCEDURE**

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of AVGPSD in the KDB 558074 item 10.3 was used in this testing.

#### 10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 8.2.

#### **10.3 MEASUREMENT EQUIPMENT USED**

Refer To Section 6.

The results spowfil this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 40°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.




Page 29 of 48

#### **10.4 LIMITS AND MEASUREMENT RESULT**


| Mode            | Channel | PSD [dBm/20kHz] | Limit[dBm/3kHz]                       | Verdict |
|-----------------|---------|-----------------|---------------------------------------|---------|
| K 12 Compliance | LCH     | -1.548          | 8                                     | PASS    |
| 11b             | MCH     | -1.445          | 8                                     | PASS    |
|                 | HCH     | -1.081          | 8                                     | PASS    |
| 海河 河            | LCH     | -2.268          | 8 (Market 1970)                       | PASS    |
| 11g             | MCH     | -2.309          | 8                                     | PASS    |
|                 | HCH     | -0.879          | 8                                     | PASS    |
|                 | LCH     | -2.766          | 8 16 200                              | PASS    |
| 11nHT20         | MCH     | -2.832          | 8                                     | PASS    |
|                 | HCH     | -2.328          | 8                                     | PASS    |
| 60              | LCH     | -6.587          | 8                                     | PASS    |
| 11NHT40         | MCH     | -6.526          | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | PASS    |
|                 | HCH     | -6.450          | 8                                     | PASS    |




**Test Graph** 



















Page 32 of 48

#### 11. RADIATED EMISSION


#### 11.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.




#### 11.2. TEST SETUP


# Radiated Emission Test-Setup Frequency Below 30MHz



# RADIATED EMISSION TEST SETUP 30MHz-1000MHz



# RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 34 of 48

#### 11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

| . ,                  |                                   |  |  |  |  |  |
|----------------------|-----------------------------------|--|--|--|--|--|
| Frequencies<br>(MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters)  |  |  |  |  |
| 0.009~0.490          | 2400/F(KHz)                       | 300  |  |  |  |  |
| 0.490~1.705          | 24000/F(KHz)                      | 30   |  |  |  |  |
| 1.705~30.0           | 30                                | 30   |  |  |  |  |
| 30~88                | 100                               | 3  |  |  |  |  |
| 88~216               | 150                               | 3  |  |  |  |  |
| 216~960              | 200                               | The state of the s |  |  |  |  |
| Above 960            | 500                               | 3  |  |  |  |  |

Note: All modes were tested For restricted band radiated emission,

the test records reported below are the worst result compared to other modes



Page 35 of 48


#### 11.4. TEST RESULT

#### **RADIATED EMISSION BELOW 30MHZ**

No emission found between lowest internal used/generated frequencies to 30MHz.

#### **RADIATED EMISSION BELOW 1GHZ**

RADIATED EMISSION TEST- (30MHZ-1GHZ) -HORIZONTAL




| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna<br>Height | Table<br>Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|-------------------|-----------------|---------|
|     | •  | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB     |          | cm                | degree          |         |
| 1   |    | 49.3999  | 13.73   | 11.28  | 25.01       | 40.00  | -14.99 | peak     |                   |                 |         |
| 2   |    | 149.6332 | 13.74   | 12.85  | 26.59       | 43.50  | -16.91 | peak     |                   |                 |         |
| 3   |    | 298.3666 | 19.48   | 15.13  | 34.61       | 46.00  | -11.39 | peak     |                   |                 |         |
| 4   |    | 479.4332 | 12.92   | 20.91  | 33.83       | 46.00  | -12.17 | peak     |                   |                 |         |
| 5   |    | 749.4166 | 10.74   | 26.61  | 37.35       | 46.00  | -8.65  | peak     |                   |                 |         |
| 6   | *  | 949.8832 | 8.18    | 30.00  | 38.18       | 46.00  | -7.82  | peak     |                   |                 |         |

**RESULT: PASS** 



# RADIATED EMISSION TEST- (30MHZ-1GHZ) -VERTICAL



| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over  | Detector | Antenna<br>Height | Table<br>Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|-------|----------|-------------------|-----------------|---------|
|     |    | MHz      | dBuV    | dB/m   | dBuV/m      | dBuV/m | dB    |          | cm                | degree          |         |
| 1   | *  | 49.3999  | 27.28   | 8.28   | 35.56       | 40.00  | -4.44 | peak     |                   |                 |         |
| 2   | ļ  | 149.6332 | 23.75   | 15.26  | 39.01       | 43.50  | -4.49 | peak     |                   |                 |         |
| 3   |    | 249.8667 | 23.10   | 13.89  | 36.99       | 46.00  | -9.01 | peak     |                   |                 |         |
| 4   |    | 650.7999 | 12.34   | 23.87  | 36.21       | 46.00  | -9.79 | peak     |                   |                 |         |
| 5   |    | 849.6499 | 11.21   | 27.31  | 38.52       | 46.00  | -7.48 | peak     |                   |                 |         |
| 6   |    | 949.8832 | 7.01    | 30.00  | 37.01       | 46.00  | -8.99 | peak     |                   |                 |         |

#### **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Margin= Result -Limit.

- 2. The "Factor" value can be calculated automatically by software of measurement system.
- 3. All test modes had been pre-tested. The 802.11b at low channel is the worst case and recorded in the report.

Page 37 of 48

#### **RADIATED EMISSION ABOVE 1GHZ**

| Frequency       | <b>Emission Level</b> | Limits        | Margin | Detector       | 0.0000000000000000000000000000000000000 |  |
|-----------------|-----------------------|---------------|--------|----------------|---|--|
| (MHz)           | (dBµV/m)              | (dBµV/m)      | (dB)   | Туре           | Comment                                 |  |
| The Colonic Con | CO M                  | TX 11b 2412Ml | -lz    |                |   |  |
| 4824            | 52.45                 | 74            | -21.55 | Pk             | Horizonta                               |  |
| 4824            | 38.83                 | 54            | -15.17 | AV             | Horizonta                               |  |
| 7236            | 49.69                 | 74            | -24.31 | pk             | Horizonta                               |  |
| 7236            | 38.24                 | 54            | -15.76 | AV             | Horizonta                               |  |
| 4824            | 49.90                 | 74            | -24.10 | Pk             | Vertical                                |  |
| 4824            | 39.60                 | 54            | -14.40 | ⊚ <b>AV</b> √  | Vertical                                |  |
| 7236            | 49.36                 | 74            | -24.64 | Pk             | Vertical                                |  |
| 7236            | 37.12                 | 54            | -16.88 | AV             | Vertical                                |  |
| 3               |                       | TX 11b 2437Ml | -lz    | The Compliance | F (Global Complies                      |  |
| 4874            | 52.56                 | 74 1          | -21.44 | Pk             | Horizonta                               |  |
| 4874            | 38.75                 | 54            | -15.25 | AV             | Horizonta                               |  |
| 7311            | 49.73                 | 74            | -24.27 | Pk Pk          | Horizonta                               |  |
| 7311            | 38.36                 | 54            | -15.64 | AV             | Horizonta                               |  |
| 4874            | 50.03                 | 74            | -23.97 | Pk             | Vertical                                |  |
| 4874            | 39.16                 | 54            | -14.84 | AV             | Vertical                                |  |
| 7311            | 49.17                 | 74            | -24.83 | Pk             | Vertical                                |  |
| 7311            | 37.15                 | 54            | -16.85 | AV             | Vertical                                |  |
| 一位              | The Sandiance         | TX 11b 2462M  | 1z     |                | 100                                     |  |
| 4924            | 52.59                 | 74            | -21.41 | Pk             | Horizonta                               |  |
| 4924            | 39.03                 | 54            | -14.97 | AV             | Horizonta                               |  |
| 7386            | 49.74                 | 74            | -24.26 | Pk             | Horizonta                               |  |
| 7386            | 38.20                 | 54            | -15.80 | AV             | Horizonta                               |  |
| 4924            | 49.85                 | 74            | -24.15 | Pk             | Vertical                                |  |
| 4924            | 39.28                 | 54            | -14.72 | AV             | Vertical                                |  |
| 7386            | 49.27                 | 74            | -24.73 | Pk             | Vertical                                |  |
| 7386            | 37.23                 | 54            | -16.77 | AV             | Vertical                                |  |

RESULT: PASS Note:

1. Margin = Emission Level - Limit

2.1GHz-25GHz(All test modes had been pre-tested. The 802.11b mode is the worst case and recorded in the report. No recording in the test report at least have 20dB margin).



Page 38 of 48

#### 12. BAND EDGE EMISSION

#### 12.1. MEASUREMENT PROCEDURE

1)Radiated restricted band edge measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting

- 2)Conducted Emissions at the bang edge
  - a)The transmitter output was connected to the spectrum analyzer
  - b)Set RBW=100kHz,VBW=300kHz
  - c)Suitable frequency span including 100kHz bandwidth from band edge

#### 12.2. TEST SET-UP

Radiated same as 11.2

Conducted set up

EUT Spectrum analyzer cable



Page 39 of 48

# 12.3. RADIATED TEST RESULT

| Frequency | Emission Level | Limits   | Margin  | Detector     | Comment              |  |
|-----------|----------------|----------|---------|--------------|----------------------|--|
| (MHz)     | (dBµV/m)       | (dBµV/m) | (dB)    | Туре         |                      |  |
| B A TOOLS | 40             | TX 11b   | 2412MHz |              |                      |  |
| 2399.9    | 52.57          | 74       | -21.43  | pk           | Horizontal           |  |
| 2399.9    | 38.72          | 54       | -15.28  | AV           | Horizontal           |  |
| 2400      | 49.82          | 74       | -24.18  | pk           | Horizontal           |  |
| 2400      | 38.36          | 54       | -15.64  | AV           | Horizontal           |  |
| 2399.9    | 49.70          | 74       | -24.30  | pk , b       | Vertical<br>Vertical |  |
| 2399.9    | 39.59          | 54       | -14.41  | AV           |                      |  |
| 2400      | 49.19          | 74       | -24.81  | pk           | Vertical             |  |
| 2400      | 37.26          | 54       | -16.74  | AV           | Vertical             |  |
|           |                | TX 11b   | 2462MHz | The Kingdone | F of Global Company  |  |
| 2483.5    | 52.14          | 74       | -21.86  | pk           | Horizontal           |  |
| 2483.5    | 38.82          | 54       | -15.18  | AV           | Horizontal           |  |
| 2483.6    | 49.91          | 74       | -24.09  | pk           | Horizontal           |  |
| 2483.6    | 38.20          | 54       | -15.80  | AV           | Horizontal           |  |
| 2483.5    | 49.80          | 74       | -24.20  | pk           | Vertical             |  |
| 2483.5    | 39.59          | 54       | -14.41  | AV           | Vertical             |  |
| 2483.6    | 49.25          | 74       | -24.75  | pk           | Vertical             |  |
| 2483.6    | 37.24          | 54       | -16.76  | AV           | Vertical             |  |

**RESULT: PASS** 


Note: Scan with 11b,11g,11n, the worst case is 11b Mode


Margin= Emission Level -Limit.




#### 12.4. CONDUCTED TEST RESULT


# **Test Graph**













# 13. FCC LINE CONDUCTED EMISSION TEST


# 13.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| F             | Maximum RF  | Line Voltage   |
|---------------|-------------|----------------|
| Frequency     | Q.P.( dBuV) | Average( dBuV) |
| 150kHz~500kHz | 66-56       | 56-46          |
| 500kHz~5MHz   | 56          | 46             |
| 5MHz~30MHz    | 060         | 50             |

#### Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

# 13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Page 43 of 48

# 13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received charging voltage by adapter which received 120V/60Hzpower by a LISN..
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.



Page 44 of 48

#### 13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

The results spowfil this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 40°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



# 13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

#### LINE CONDUCTED EMISSION TEST LINE 1-L




| No. | No. Freq. |       | Reading_Level<br>(dBuV) |       | Correct<br>Factor | Measurement<br>(dBuV) |    |       |       |       | Margin<br>(dB) P/ |        | Comment |  |
|-----|-----------|-------|-------------------------|-------|-------------------|-----------------------|----|-------|-------|-------|-------------------|--------|---------|--|
|     | (MHz)     | Peak  | QP                      | AVG   | dB                | Peak                  | QP | AVG   | QP    | AVG   | QP                | AVG    |         |  |
| 1   | 0.1740    | 35.61 |                         | 26.59 | 10.19             | 45.80                 |    | 36.78 | 64.76 | 54.76 | -18.96            | -17.98 | Р       |  |
| 2   | 0.2660    | 35.75 |                         | 20.86 | 10.28             | 46.03                 |    | 31.14 | 61.24 | 51.24 | -15.21            | -20.10 | Р       |  |
| 3   | 0.3540    | 33.52 |                         | 23.59 | 10.31             | 43.83                 |    | 33.90 | 58.87 | 48.87 | -15.04            | -14.97 | Р       |  |
| 4   | 0.6180    | 34.45 |                         | 22.86 | 10.32             | 44.77                 |    | 33.18 | 56.00 | 46.00 | -11.23            | -12.82 | Р       |  |
| 5   | 1.6580    | 35.60 |                         | 19.11 | 10.33             | 45.93                 |    | 29.44 | 56.00 | 46.00 | -10.07            | -16.56 | Р       |  |
| 6   | 2.8220    | 33.81 |                         | 16.29 | 10.51             | 44.32                 |    | 26.80 | 56.00 | 46.00 | -11.68            | -19.20 | Р       |  |

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



# Line Conducted Emission Test Line 2-N



| No. | No. Freq. |       | Reading_Level<br>(dBuV) |       | - 1 1 |       |    |       | nit<br>uV) |       |        | P/F    | Comment |  |
|-----|-----------|-------|-------------------------|-------|-------|-------|----|-------|------------|-------|--------|--------|---------|--|
|     | (MHz)     | Peak  | QP                      | AVG   | dB    | Peak  | QP | AVG   | QP         | AVG   | QP     | AVG    |         |  |
| 1   | 0.1740    | 36.50 |                         | 26.58 | 10.19 | 46.69 |    | 36.77 | 64.76      | 54.76 | -18.07 | -17.99 | Р       |  |
| 2   | 0.2660    | 36.42 |                         | 26.32 | 10.28 | 46.70 |    | 36.60 | 61.24      | 51.24 | -14.54 | -14.64 | Р       |  |
| 3   | 0.3540    | 34.19 |                         | 25.14 | 10.31 | 44.50 |    | 35.45 | 58.87      | 48.87 | -14.37 | -13.42 | Р       |  |
| 4   | 1.6780    | 36.53 |                         | 19.21 | 10.32 | 46.85 |    | 29.53 | 56.00      | 46.00 | -9.15  | -16.47 | Р       |  |
| 5   | 1.7500    | 37.22 |                         | 23.01 | 10.30 | 47.52 |    | 33.31 | 56.00      | 46.00 | -8.48  | -12.69 | Р       |  |
| 6   | 2.7139    | 31.21 |                         | 16.48 | 10.48 | 41.69 |    | 26.96 | 56.00      | 46.00 | -14.31 | -19.04 | Р       |  |

The results spowth this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.




# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

LINE CONDUCTED EMISSION TEST SETUP



RADIATED EMISSION TEST SETUP




The results shown in this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true of the confirmed at a true of true of the confirmed at a true of the confirmed at a

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F. , Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



# RADIATED EMISSION ABOVE 1G TEST SETUP



**END OF REPORT-**

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc-gett.com.

Attestation of Global Compliance

AGC 8

Fax: +86-755 2600 8484 Tel: +86-755 2908 1955 E-mail: agc@agc-cert.com **@** 400 089 2118 Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China