

# FCC Part 15C Measurement and Test Report

For

**HANGZHOU ZENO-VIDEOPARK IMPORT & EXPORT CO.,  
LTD.**

**FCC ID: 2AQR4-IPC**

<b>FCC Rule(s):</b>	<u>FCC Part 15C</u>
<b>Product Description:</b>	<u>IPC/Wi-Fi IPC</u>
<b>Tested Model:</b>	<u>GAR2200N-I2WS</u>
<b>Report No.:</b>	<u>BST0084998A01RF</u>
<b>Tested Date:</b>	<u>July 22~25, 2018</u>
<b>Issued Date:</b>	<u>July 25,2018</u>
<b>Tested By:</b>	<u>Lisa. Li / Engineer</u> <i>Lisa . Li</i>
<b>Reviewed By:</b>	<u>Messi.Wang/ EMC Manager</u> <i>Messi Wang</i>
<b>Approved &amp; Authorized By:</b>	<u>Mike mo / PSQ Manager</u> <i>Mike mo</i>
<b>Prepared By:</b>	

**BSL Testing Co.,LTD.**  
NO. 24, ZH Park, Nantou, Shenzhen, 518000 China  
Tel: 400-882-9628 Fax: 86- 755-26508703

**TABLE OF CONTENTS**

**1. GENERAL INFORMATION..... 3**

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... 3

1.2 TEST STANDARDS..... 4

1.3 TEST METHODOLOGY..... 4

1.4 TEST FACILITY..... 4

1.5 EUT SETUP AND TEST MODE..... 5

1.6 MEASUREMENT UNCERTAINTY..... 5

1.7 TEST EQUIPMENT LIST AND DETAILS..... 6

**2. SUMMARY OF TEST RESULTS..... 7**

**3. RF EXPOSURE..... 8**

3.1 STANDARD APPLICABLE..... 8

3.2 TEST RESULT..... 8

**4. ANTENNA REQUIREMENT..... 9**

4.1 STANDARD APPLICABLE..... 9

4.2 EVALUATION INFORMATION..... 9

**5. POWER SPECTRAL DENSITY..... 10**

5.1 STANDARD APPLICABLE..... 10

5.2 TEST PROCEDURE..... 10

5.3 ENVIRONMENTAL CONDITIONS..... 10

5.4 SUMMARY OF TEST RESULTS/PLOTS..... 11

**6. 6DB BANDWIDTH..... 18**

6.1 STANDARD APPLICABLE..... 18

6.2 TEST PROCEDURE..... 18

6.3 ENVIRONMENTAL CONDITIONS..... 18

6.4 SUMMARY OF TEST RESULTS/PLOTS..... 18

**7. RF OUTPUT POWER..... 25**

7.1 STANDARD APPLICABLE..... 25

7.2 TEST PROCEDURE..... 25

7.3 ENVIRONMENTAL CONDITIONS..... 25

7.4 SUMMARY OF TEST RESULTS/PLOTS..... 26

**8. FIELD STRENGTH OF SPURIOUS EMISSIONS..... 27**

8.1 STANDARD APPLICABLE..... 27

8.2 TEST PROCEDURE..... 27

8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION..... 28

8.4 ENVIRONMENTAL CONDITIONS..... 28

8.5 SUMMARY OF TEST RESULTS/PLOTS..... 28

**9. OUT OF BAND EMISSIONS..... 38**

9.1 STANDARD APPLICABLE..... 38

9.2 TEST PROCEDURE..... 38

9.3 ENVIRONMENTAL CONDITIONS..... 39

9.4 SUMMARY OF TEST RESULTS/PLOTS..... 39

**10. CONDUCTED EMISSIONS..... 44**

10.1 TEST PROCEDURE..... 44

10.2 BASIC TEST SETUP BLOCK DIAGRAM..... 44

10.3 ENVIRONMENTAL CONDITIONS..... 44

10.4 TEST RECEIVER SETUP..... 45

10.5 SUMMARY OF TEST RESULTS/PLOTS..... 45

10.6 CONDUCTED EMISSIONS TEST DATA..... 45

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: HANGZHOU ZENO-VIDEOPARK IMPORT & EXPORT CO., LTD.  
 Address of applicant: 19th floor, Building 3, IT Park, No. 1217, Wenyi West Road, Yuhang District, Hangzhou, Zhejiang P.R. China

Manufacturer: HANGZHOU ZENO TECHNOLOGY CO.,LTD  
 Address of manufacturer: 16-21F, Bldg. 3, IT Park, No.1217 Wenyi Road, Yuhang District, HangZhou, China

General Description of EUT	
Product Name:	IPC/Wi-Fi IPC
Trade Name:	N/A
Model No.:	GAR2200N-I2WS, GAR2200 Series
Rated Voltage:	DC 12V from adapter
Adapter information:	Model: CS-1201000 Input: AC100-240V, 0.35mA, 50/60Hz Output: DC12V, 1000mA
<p><i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model GAR2200N-I2WS, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	18.68dBm (Conducted)
Type of Modulation:	DSSS, OFDM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Type of Antenna:	RP-SMA Antenna
Antenna Gain:	0dBi
Lowest Internal Frequency	24MHz



## 1.2 Test Standards

The following report is prepared on behalf of the HANGZHOU ZENO-VIDEOPARK IMPORT & EXPORT CO., LTD. in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v04 for digital transmission systems shall be performed also.

## 1.4 Test Facility

BSL Testing Co.,LTD.  
NO. 24, ZH Park, Nantou, Shenzhen, 518000 China  
Designation Number : CN1217  
Test Firm Registration Number: 866035  
Tel: 86- 755-26508703  
Fax: 86- 755-26508703

### 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest

possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz
TM4	802.11n-HT40	2422MHz, 2437MHz, 2452MHz

Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.

Accessories Equipment List and Details			
Description	Manufacturer	Model No.	Serial Number

Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E23	EB12648265
USB	ESR	Shielded	Without Core

### 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Power Spectral Density	Conducted	±1.8dB
Conducted Spurious Emission	Conducted	±2.17dB

Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

**1.7  
Test  
Equip  
ment  
List  
and  
Detail  
s**

Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
Communication Tester	Rohde & Schwarz	CMW500	100358	2017-10-21	2018-10-20
Spectrum Analyzer	R&S	FSP40	100550	2017-10-21	2018-10-20
Test Receiver	R&S	ESCI7	US4714010 2	2017-10-21	2018-10-20
Signal Generator	HP	83630B	3844A0102 8	2017-10-22	2018-10-21
Test Receiver	R&S	ESPI-3	100180	2017-10-21	2018-10-20
Amplifier	Agilent	8449B	4035A0011 6	2017-10-22	2018-10-21
Amplifier	HP	8447E	2945A0277 0	2017-10-22	2018-10-21
Signal Generator	IFR	2023A	202307/242	2017-10-22	2018-10-21
Broadband Antenna	SCHAFFNER	2774	2774	2017-10-17	2018-10-16
Biconical and log periodic antennas	ELECTRO-METRICS	EM-6917B-1	171	2017-10-17	2018-10-16
Horn Antenna	R&S	HF906	100253	2017-10-17	2018-10-16
Horn Antenna	EM	EM-6961	6462	2017-10-17	2018-10-16
LISN	R&S	ESH3-Z5	100196	2017-10-17	2018-10-16
LISN	COM-POWER	LI-115	02027	2017-10-17	2018-10-16
3m Semi-Anechoic Chamber	Chengyu Electron	9 (L)*6 (W)* 6 (H)	BSL086	2017-10-21	2018-10-20
Horn Antenna	A-INFOMW	LB-180400K F	BSL088	2017-10-21	2018-10-20



## 2. SUMMARY OF TEST RESULTS

---

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§ 2.1093	RF Exposure	PASS
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	PASS
§15.205	Restricted Band of Operation	PASS
§ 15.207(a)	Conducted Emission	PASS
§ 15.247(e)	Power Spectral Density	PASS
§ 15.247(a)(2)	6 dB Bandwidth	PASS
§ 15.247(b)(3)	RF Output Power	PASS
§ 15.209(a)	Radiated Emission	PASS
§ 15.247(d)	Band Edge (Out of Band Emissions)	PASS

Note: PASS: applicable, N/A: not applicable.

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has a RP-SMA Antenna, fulfill the requirement of this section.

## 5. Power Spectral Density

---

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Procedure

According to the KDB 558074 D01 v04, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

### 5.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

**5.4 Summary of Test Results/Plots**


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-17.34	8
	2437	-17.96	8
	2462	-17.54	8
802.11g	2412	-20.63	8
	2437	-21.36	8
	2462	-20.77	8
802.11n HT20	2412	-21.67	8
	2437	-22.46	8
	2462	-22.19	8
802.11n HT40	2422	-24.95	8
	2437	-25.28	8
	2452	-25.87	8

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel



802.11g-Middle Channel




802.11g-High Channel







802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



## 6. 6dB Bandwidth

### 6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.3 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

### 6.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b	2412	9.2400	$\geq 500$
	2437	9.5200	$\geq 500$
	2462	9.4800	$\geq 500$
802.11g	2412	16.5600	$\geq 500$
	2437	16.5600	$\geq 500$
	2462	16.5600	$\geq 500$
802.11n-HT20	2412	17.7000	$\geq 500$
	2437	17.7000	$\geq 500$
	2462	17.7000	$\geq 500$
802.11n-HT40	2422	36.4000	$\geq 500$
	2437	36.4000	$\geq 500$
	2452	36.4000	$\geq 500$

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel



802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel







802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



## 7. RF Output Power

---

### 7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Procedure

According to the KDB-558074 D01 v04, 9.2.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times$  span / RBW. (This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98$  %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

### 7.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

**7.4 Summary of Test Results/Plots**

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b _ 11Mbps	2412	18.68	73.79	1000
	2437	17.87	61.24	1000
	2462	17.91	61.80	1000
802.11g_54Mbps	2412	17.84	60.81	1000
	2437	16.57	45.39	1000
	2462	17.52	56.49	1000
802.11n HT20_MCS7	2412	17.22	52.72	1000
	2437	17.65	58.21	1000
	2462	16.63	46.03	1000
802.11n HT40_MCS7	2422	17.28	53.46	1000
	2437	16.92	49.20	1000
	2452	16.84	48.31	1000

Please refer to the following test plots:

## 8. Field Strength of Spurious Emissions

---

### 8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz  
RBW=10KHz,  
VBW =30KHz  
Sweep time= Auto  
Trace = max hold  
Detector function = peak  
AV

Frequency :30MHz-1GHz  
RBW=120KHz,  
VBW=300KHz  
Sweep time= Auto  
Trace = max hold  
Detector function = peak, QP

Frequency :Above 1GHz  
RBW=1MHz,  
VBW=3MHz(Peak), 10Hz(AV)  
Sweep time= Auto  
Trace = max hold  
Detector function = peak,

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of  $-6\text{dB}\mu\text{V}$  means the emission is  $6\text{dB}\mu\text{V}$  below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

### 8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

### 8.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note:


1. Worst-case radiated emission below 1GHz is 802.11b (CH Low) mode.
2. Worst-case radiated emission above 1GHz is 802.11g (CH Low, Middle, High) mode.

#### Plot of Radiated Emissions Test Data (30MHz to 1GHz)

Operating Condition: 802.11b Transmitting Low Channel-2412MHz


Test Specification: Horizontal





No.	Mk.	Freq.	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	42.1542	31.64	40.00	-8.36	QP		
2		49.1865	27.80	40.00	-12.20	QP		
3		110.1816	27.14	43.50	-16.36	QP		
4		195.8220	26.20	43.50	-17.30	QP		
5		326.7395	31.59	46.00	-14.41	QP		
6		586.8437	35.05	46.00	-10.95	QP		

Test Specification: Vertical



No.	Mk.	Freq.	Measure- ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	52.0251	32.27	40.00	-7.73	QP		
2		100.5806	29.12	43.50	-14.38	QP		
3		143.3257	28.33	43.50	-15.17	QP		
4		231.7178	28.38	46.00	-17.62	QP		
5		356.6757	30.84	46.00	-15.16	QP		
6		595.1326	34.22	46.00	-11.78	QP		

*Spurious Emissions Above 1GHz*

Test Mode: 802.11g

Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low channel-2412MHz					
4824.000	54.62	74	-19.38	H	PK
4824.000	41.34	54	-12.66	H	AV
7236.000	51.52	74	-22.48	H	PK
7236.000	36.57	54	-17.43	H	AV
4824.000	54.92	74	-19.08	V	PK
4824.000	42.52	54	-11.48	V	AV
7236.000	53.01	74	-20.99	V	PK
7236.000	38.24	54	-15.76	V	AV
Middle channel-2437MHz					
4874.000	54.24	74	-19.76	H	PK
4874.000	43.05	54	-10.95	H	AV
7311.000	55.65	74	-18.35	H	PK
7311.000	37.84	54	-16.16	H	AV
4874.000	52.52	74	-21.48	V	PK
4874.000	40.20	54	-13.8	V	AV
7311.000	54.45	74	-19.55	V	PK
7311.000	38.86	54	-15.14	V	AV
High channel-2462MHz					
4924.000	54.32	74	-19.68	H	PK
4924.000	36.24	54	-17.76	H	AV
7386.000	51.84	74	-22.16	H	PK
7386.000	37.95	54	-16.05	H	AV
4924.000	56.27	74	-17.73	V	PK
4924.000	41.24	54	-12.76	V	AV
7386.000	54.23	74	-19.77	V	PK
7386.000	38.85	54	-15.15	V	AV


Note:

1. Calculation of result is: Result (dBm) = Reading (dBm) + Correction Factor (dB).
2. Correction Factor (dB)=Ant. Factor + Cable Loss – Ampl. Gain.
3. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Spurious (Conducted)

802.11b-Lowest


Lowest




Middle




### Highest




### Spurious (Conducted) 802.11g-Lowest Lowest




Middle



Highest




Spurious (Conducted)  
802.11n-HT20-Lowest  
Lowest




Middle






Highest




Spurious (Conducted)  
 802.11n-HT40-Lowest


Lowest



Middle



Highest



## 9. Out of Band Emissions

### 9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074D01 v04, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product

outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the

marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply

with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement

KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v04, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW ≥ 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1.

Report

the three highest emissions relative to the limit.

### 9.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 9.4 Summary of Test Results/Plots


802.11b- Bandedge (Radiated)

Note: we are pre-scan all modes, the worst data is 802.11b mode.


Channel	Freq.(MHz)	Level(dBuV)	Limit(dBuV)	Margin(dB)	Detector
	2400	54.35	74	-19.65	Peak
LOW	2400	36.24	54	-17.76	Average

	2483.5	54.52	74	-19.48	Peak
HIGH	2483.5	34.96	54	-19.04	Average


Bandedge (Conducted)  
 802.11b-Lowest  
 Lowest




Highest



802.11g-Lowest




Highest




802.11n-HT20-Lowest

Lowest




Highest




802.11n-HT40-Lowest





Highest



## 10. Conducted Emissions

---


### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram



### 10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

#### 10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth.....	9 kHz
Quasi-Peak Adapter Mode.....	Normal

#### 10.5 Summary of Test Results/Plots


According to the data in section 10.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device.

#### 10.6 Conducted Emissions Test Data

Note: we are pre-scan all modes, the worst data is 802.11n HT20(Low) mode.


**Plot of Conducted Emissions Test Data: 802.11n HT20(Low)**

Test Specification: Neutral



No.	Mk.	Freq. MHz	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1711	43.95	64.90	-20.95	QP	
2		0.1711	29.89	54.90	-25.01	AVG	
3	*	0.5655	44.50	56.00	-11.50	QP	
4		0.5655	32.83	46.00	-13.17	AVG	
5		0.8900	36.61	56.00	-19.39	QP	
6		0.8900	26.35	46.00	-19.65	AVG	
7		2.5219	37.26	56.00	-18.74	QP	
8		2.5219	22.40	46.00	-23.60	AVG	
9		7.0697	43.70	60.00	-16.30	QP	
10		7.0697	29.52	50.00	-20.48	AVG	
11		25.8580	36.81	60.00	-23.19	QP	
12		25.8580	26.34	50.00	-23.66	AVG	

Test Specification: Live



No.	Mk.	Freq.	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dBuV	dB		
1		0.2977	47.12	60.30	-13.18	QP	
2		0.2977	35.59	50.30	-14.71	AVG	
3		0.6380	39.26	56.00	-16.74	QP	
4		0.6380	25.80	46.00	-20.20	AVG	
5		0.9020	38.62	56.00	-17.38	QP	
6		0.9020	28.99	46.00	-17.01	AVG	
7	*	2.1018	46.84	56.00	-9.16	QP	
8		2.1018	31.93	46.00	-14.07	AVG	
9		5.5979	38.54	60.00	-21.46	QP	
10		5.5979	26.23	50.00	-23.77	AVG	
11		26.9980	43.26	60.00	-16.74	QP	
12		26.9980	33.17	50.00	-16.83	AVG	

\*\*\*\*\* END OF REPORT \*\*\*\*\*