

5G NR N78


MEASUREMENT 1

Hight Band SAR (Channel 650000):


Date: 06/18/2024

| | |
|---|---|
| Frequency (MHz) | 3750.000000 |
| Relative permittivity (real part) | 39.113793 |
| Relative permittivity (imaginary part) | 12.607061 |
| Conductivity (S/m) | 1.337526 |
| Variation (%) | -4.980000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 4.85 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Left head</u> |
| Device Position | <u>Cheek</u> |
| Band | <u>NR N78</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=-56.00, Y=-53.00 SAR Peak: 0.38 W/kg

SAR 10g (W/Kg)


0.150219

SAR 1g (W/Kg)


0.177376



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.3755 | 0.2648 | 0.1692 | 0.1088 | 0.0711 |



Hot spot position



MEASUREMENT 2

Hight Band SAR (Channel 650000):


Date: 06/18/2024

| | |
|---|---|
| Frequency (MHz) | 3750.000000 |
| Relative permittivity (real part) | 53.342133 |
| Relative permittivity (imaginary part) | 14.329440 |
| Conductivity (S/m) | 1.491983 |
| Variation (%) | 1.820000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 5.01 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |


| | |
|------------------------|-------------------------|
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(10mm)</u> |

| | |
|-------------|---------------|
| Band | <u>NR N78</u> |
|-------------|---------------|

SURFACE SAR




VOLUME SAR




Maximum location: X=8.00, Y=-38.00 SAR Peak: 1.07 W/kg


| | |
|-----------------------|----------|
| SAR 10g (W/Kg) | 0.374037 |
| SAR 1g (W/Kg) | 0.555230 |



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 1.0654 | 0.7197 | 0.4321 | 0.2592 | 0.1581 |



Hot spot position



MEASUREMENT 3

Hight Band SAR (Channel 650000):


Date: 06/18/2024

| | |
|--|---|
| Frequency (MHz) | 3750.000000 |
| Relative permittivity (real part) | 53.342133 |
| Relative permittivity (imaginary part) | 14.329440 |
| Conductivity (S/m) | 1.491983 |
| Variation (%) | 1.820000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 5.01 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |


| | |
|-----------------|--------------------------------|
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(hotspot 10mm)</u> |

| | |
|------|---------------|
| Band | <u>NR N78</u> |
|------|---------------|

SURFACE SAR




VOLUME SAR




Maximum location: X=6.00, Y=-32.00 SAR Peak: 1.07 W/kg


| | |
|-----------------------|----------|
| SAR 10g (W/Kg) | 0.373822 |
| SAR 1g (W/Kg) | 0.554586 |



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 1.0661 | 0.7195 | 0.4316 | 0.2587 | 0.1576 |



Hot spot position



WLAN 2.4G


MEASUREMENT 1

Lower Band SAR (Channel 1):


Date: 09/23/2024

| | |
|--|---|
| Frequency (MHz) | 2412.000000 |
| Relative permittivity (real part) | 37.851613 |
| Relative permittivity (imaginary part) | 13.546980 |
| Conductivity (S/m) | 1.814111 |
| Variation (%) | -1.900000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 4.58 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Left head</u> |
| Device Position | <u>Cheek</u> |
| Band | <u>IEEE 802.11n ISM</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=-10.00, Y=11.00 SAR Peak: 0.52 W/kg

SAR 10g (W/Kg)


0.213235

SAR 1g (W/Kg)


0.177533



| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
| SAR (W/Kg) | 0.5168 | 0.2908 | 0.1329 | 0.0600 | 0.0299 |



Hot spot position



MEASUREMENT 2


Lower Band SAR (Channel 1):

Date: 09/23/2024


| | |
|--|---|
| Frequency (MHz) | 2412.00000 |
| Relative permittivity (real part) | 54.630667 |
| Relative permittivity (imaginary part) | 14.318444 |
| Conductivity (S/m) | 1.982536 |
| Variation (%) | 4.110000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 4.70 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |

| | |
|-----------------|-------------------------|
| Phantom | Validation plane |
| Device Position | Body back(10mm) |
| Band | <u>IEEE 802.11n ISM</u> |

SURFACE SAR




VOLUME SAR




Maximum location: X=-9.00, Y=19.00 SAR Peak: 0.23 W/kg


| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.087086 |
| SAR 1g (W/Kg) | 0.149186 |



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.2272 | 0.1559 | 0.0960 | 0.0595 | 0.0377 |



Hot spot position



MEASUREMENT 3


Lower Band SAR (Channel 1):

Date: 09/23/2024


| | |
|--|---|
| Frequency (MHz) | 2412.000000 |
| Relative permittivity (real part) | 54.630667 |
| Relative permittivity (imaginary part) | 14.318444 |
| Conductivity (S/m) | 1.982536 |
| Variation (%) | 4.110000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 4.70 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |

| | |
|-----------------|-----------------------------------|
| Phantom | Validation plane |
| Device Position | Body back(10mm) |
| Band | <u>IEEE 802.11n ISM (hotspot)</u> |

SURFACE SAR




VOLUME SAR




Maximum location: X=-15.00, Y=48.00 SAR Peak: 0.28 W/kg


| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.081527 |
| SAR 1g (W/Kg) | 0.149042 |



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.2739 | 0.1599 | 0.0775 | 0.0375 | 0.0197 |



Hot spot position



WLAN 5.2G


MEASUREMENT 1

SAR (Channel 42):


Date: 09/27/2024

| | |
|--|---|
| Frequency (MHz) | 5210.000000 |
| Relative permittivity (real part) | 39.072785 |
| Relative permittivity (imaginary part) | 12.607042 |
| Conductivity (S/m) | 1.377820 |
| Variation (%) | -4.560000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 4.85 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Left head</u> |
| Device Position | <u>Cheek</u> |
| Band | <u>IEEE 802.11ac HT80 ISM</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=-65.00, Y=-56.00 SAR Peak: 1.08 W/kg

SAR 10g (W/Kg)


0.394868

SAR 1g (W/Kg)


0.535962



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 1.0832 | 0.7647 | 0.4868 | 0.3081 | 0.1951 |



Hot spot position




MEASUREMENT 2

SAR (Channel 42):


Date: 09/27/2024

| | |
|--|---|
| Frequency (MHz) | 5210.000000 |
| Relative permittivity (real part) | 53.336293 |
| Relative permittivity (imaginary part) | 14.232201 |
| Conductivity (S/m) | 1.490357 |
| Variation (%) | 3.500000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 5.01 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(10mm)</u> |
| Band | <u>IEEE 802.11ac HT80 ISM</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=9.00, Y=-9.00 SAR Peak: 1.10 W/kg

SAR 10g (W/Kg)


0.458909

SAR 1g (W/Kg)


0.285771



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 1.1007 | 0.7736 | 0.4897 | 0.3087 | 0.1952 |



Hot spot position




MEASUREMENT 3

SAR (Channel 42):


Date: 09/27/2024

| | |
|--|---|
| Frequency (MHz) | 5210.000000 |
| Relative permittivity (real part) | 53.336293 |
| Relative permittivity (imaginary part) | 14.232201 |
| Conductivity (S/m) | 1.490357 |
| Variation (%) | 3.500000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 5.01 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(10mm)</u> |
| Band | <u>IEEE 802.11ac HT80 ISM(hotspot)</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=-16.00, Y=-23.00 SAR Peak: 0.77 W/kg

SAR 10g (W/Kg)


0.103409

SAR 1g (W/Kg)


0.286219



| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 2.00 | 7.00 | 12.00 | 17.00 |
| SAR (W/Kg) | 0.7434 | 0.4238 | 0.0668 | 0.0114 | 0.0140 |



Hot spot position



WLAN 5.3G


MEASUREMENT 1

SAR (Channel 52):


Date: 09/28/2024

| | |
|--|---|
| Frequency (MHz) | 5260.000000 |
| Relative permittivity (real part) | 39.105208 |
| Relative permittivity (imaginary part) | 12.607628 |
| Conductivity (S/m) | 1.342108 |
| Variation (%) | -4.290000 |
| Crest Factor | 8.3 |
| Probe Conversion factor | 4.85 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Left head</u> |
| Device Position | <u>Cheek</u> |
| Band | <u>IEEE 802.11a ISM</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=-26.00, Y=-17.00 SAR Peak: 0.55 W/kg

SAR 10g (W/Kg)


0.438330

SAR 1g (W/Kg)


0.360015



| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
| SAR (W/Kg) | 0.5564 | 0.3621 | 0.2121 | 0.1212 | 0.0743 |



Hot spot position



MEASUREMENT 2


SAR (Channel 52):

Date: 09/28/2024


| | |
|--|---|
| Frequency (MHz) | 5260.000000 |
| Relative permittivity (real part) | 53.341337 |
| Relative permittivity (imaginary part) | 14.232400 |
| Conductivity (S/m) | 1.491736 |
| Variation (%) | 3.020000 |
| Crest Factor | 8.3 |
| Probe Conversion factor | 5.01 |
| E-Field Probe: | SSE2 (SN 25/22 EPG0375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |

| | |
|-----------------|-------------------------|
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(10mm)</u> |
| Band | <u>IEEE 802.11a ISM</u> |

SURFACE SAR




VOLUME SAR




Maximum location: X=14.00, Y=-25.00 SAR Peak: 0.43 W/kg


| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.133387 |
| SAR 1g (W/Kg) | 0.243472 |



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.4314 | 0.2803 | 0.1598 | 0.0915 | 0.0543 |



Hot spot position



MEASUREMENT 3


SAR (Channel 52):

Date: 09/28/2024


| | |
|--|---|
| Frequency (MHz) | 5260.000000 |
| Relative permittivity (real part) | 53.341337 |
| Relative permittivity (imaginary part) | 14.232400 |
| Conductivity (S/m) | 1.491736 |
| Variation (%) | 3.020000 |
| Crest Factor | 8.3 |
| Probe Conversion factor | 5.01 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |

| | |
|-----------------|----------------------------------|
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(10mm)</u> |
| Band | <u>IEEE 802.11a ISM(hotspot)</u> |

SURFACE SAR




VOLUME SAR




Maximum location: X=-16.00, Y=-46.00 SAR Peak: 0.94 W/kg


| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.117976 |
| SAR 1g (W/Kg) | 0.242744 |



| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 2.00 | 7.00 | 12.00 | 17.00 |
| SAR (W/Kg) | 0.8925 | 0.5412 | 0.1151 | 0.0199 | 0.0126 |



Hot spot position



WLAN 5.6G


MEASUREMENT 1

SAR (Channel 140):


Date: 09/28/2024

| | |
|--|---|
| Frequency (MHz) | 5700.000000 |
| Relative permittivity (real part) | 40.387760 |
| Relative permittivity (imaginary part) | 18.129852 |
| Conductivity (S/m) | 0.884923 |
| Variation (%) | -1.930000 |
| Crest Factor: | 1.0 |
| Probe Conversion factor | 1.80 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Left head</u> |
| Device Position | <u>Cheek</u> |
| Band | <u>IEEE 802.11a ISM</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=8.00, Y=-32.00 SAR Peak: 0.61 W/kg

SAR 10g (W/Kg)


0.587152

SAR 1g (W/Kg)


0.461235



| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
| SAR (W/Kg) | 0.6138 | 0.4111 | 0.2437 | 0.1439 | 0.0861 |



Hot spot position



MEASUREMENT 2


SAR (Channel 140):

Date: 09/28/2024


| | |
|--|---|
| Frequency (MHz) | 5700.000000 |
| Relative permittivity (real part) | 55.212927 |
| Relative permittivity (imaginary part) | 21.368266 |
| Conductivity (S/m) | 0.971230 |
| Variation (%) | 0.760000 |
| Crest Factor: | 1.0 |
| Probe Conversion factor | 1.86 |
| E-Field Probe: | SSE2 (SN 25/22 EPG0375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |

| | |
|-----------------|-------------------------|
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(10mm)</u> |
| Band | <u>IEEE 802.11a ISM</u> |

SURFACE SAR




VOLUME SAR




Maximum location: X=-2.00, Y=1.00 SAR Peak: 0.17 W/kg


| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.192914 |
| SAR 1g (W/Kg) | 0.260070 |



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.4300 | 0.3357 | 0.2419 | 0.1707 | 0.1169 |



Hot spot position



MEASUREMENT 3


SAR (Channel 140):

Date: 09/28/2024


| | |
|--|---|
| Frequency (MHz) | 5700.000000 |
| Relative permittivity (real part) | 55.212927 |
| Relative permittivity (imaginary part) | 21.368266 |
| Conductivity (S/m) | 0.971230 |
| Variation (%) | 0.760000 |
| Crest Factor: | 1.0 |
| Probe Conversion factor | 1.86 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |

| | |
|-----------------|----------------------------------|
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(10mm)</u> |
| Band | <u>IEEE 802.11a ISM(hotspot)</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=-24.00, Y=-24.00 SAR Peak: 0.58 W/kg

SAR 10g (W/Kg)


0.087702

SAR 1g (W/Kg)


0.260140



| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 2.00 | 7.00 | 12.00 | 17.00 |
| SAR (W/Kg) | 0.5506 | 0.3426 | 0.0832 | 0.0198 | 0.0146 |



Hot spot position



WLAN 5.8G


MEASUREMENT 1

SAR (Channel 149)


Date: 09/28/2024

| | |
|--|---|
| Frequency (MHz) | 5745.000000 |
| Relative permittivity (real part) | 41.422883 |
| Relative permittivity (imaginary part) | 18.129634 |
| Conductivity (S/m) | 0.867241 |
| Variation (%) | 1.650000 |
| Crest Factor: | 8.3 |
| Probe Conversion factor | 5.50 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Left head</u> |
| Device Position | <u>Cheek</u> |
| Band | <u>IEEE 802.11ac HT20 ISM</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=-49.00, Y=-39.00 SAR Peak: 0.75 W/kg

SAR 10g (W/Kg)


0.384282

SAR 1g (W/Kg)


0.497701



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.9139 | 0.6546 | 0.4255 | 0.2757 | 0.1792 |



Hot spot position



MEASUREMENT 2


SAR (Channel 149):

Date: 09/28/2024


| | |
|--|---|
| Frequency (MHz) | 5745.000000 |
| Relative permittivity (real part) | 55.242927 |
| Relative permittivity (imaginary part) | 21.378266 |
| Conductivity (S/m) | 0.941230 |
| Variation (%) | -3.260000 |
| Crest Factor: | 8.3 |
| Probe Conversion factor | 5.65 |
| E-Field Probe: | SSE2 (SN 25/22 EPG0375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |

| | |
|-----------------|-------------------------------|
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(10mm)</u> |
| Band | <u>IEEE 802.11ac HT20 ISM</u> |

SURFACE SAR




VOLUME SAR




Maximum location: X=0.00, Y=-15.00 SAR Peak: 0.95 W/kg


| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.559375 |
| SAR 1g (W/Kg) | 0.407121 |



| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.9547 | 0.3493 | 0.2145 | 0.2163 | 0.1300 |



Hot spot position



MEASUREMENT 3


SAR (Channel 149):

Date: 09/28/2024


| | |
|--|---|
| Frequency (MHz) | 5745.000000 |
| Relative permittivity (real part) | 55.242927 |
| Relative permittivity (imaginary part) | 21.378266 |
| Conductivity (S/m) | 0.941230 |
| Variation (%) | -3.260000 |
| Crest Factor: | 8.3 |
| Probe Conversion factor | 5.65 |
| E-Field Probe: | SSE2 (SN 25/22 EPG0375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |

| | |
|-----------------|---|
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(10mm)</u> |
| Band | <u>IEEE 802.11ac HT20 ISM (hotspot)</u> |

SURFACE SAR




VOLUME SAR




Maximum location: X=-9.00, Y=-33.00 SAR Peak: 0.42 W/kg


| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.064116 |
| SAR 1g (W/Kg) | 0.406795 |



| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 2.00 | 7.00 | 12.00 | 17.00 |
| SAR (W/Kg) | 0.4011 | 0.2424 | 0.0522 | 0.0118 | 0.0127 |



Hot spot position



BT


MEASUREMENT 1

Lower Band SAR (Channel 0):


Date: 09/23/2024

| | |
|--|---|
| Frequency (MHz) | 2402.000000 |
| Relative permittivity (real part) | 37.821613 |
| Relative permittivity (imaginary part) | 13.546980 |
| Conductivity (S/m) | 1.834111 |
| Variation (%) | -1.750000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 2.31 |
| E-Field Probe: | SSE2 (SN 25/22 EPGO375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Left head</u> |
| Device Position | <u>Cheek</u> |
| Band | <u>8DPSK</u> |

SURFACE SAR



VOLUME SAR




Maximum location: X=-15.00, Y=18.00 SAR Peak: 0.39 W/kg

SAR 10g (W/Kg)


0.051521

SAR 1g (W/Kg)


0.030887



| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
| SAR (W/Kg) | 0.3797 | 0.2828 | 0.1881 | 0.1180 | 0.0677 |



Hot spot position



MEASUREMENT 2

Lower Band SAR (Channel 0):


Date: 09/23/2024

| | |
|--|---|
| Frequency (MHz) | 2402.000000 |
| Relative permittivity (real part) | 37.821613 |
| Relative permittivity (imaginary part) | 13.546980 |
| Conductivity (S/m) | 1.834111 |
| Variation (%) | -2.500000 |
| Crest Factor | 1.0 |
| Probe Conversion factor | 2.31 |
| E-Field Probe: | SSE2 (SN 25/22 EPG0375) |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |


| | |
|-----------------|------------------|
| Phantom | Validation plane |
| Device Position | Body back(10mm) |

| | |
|------|--------------|
| Band | 8DPSK |
|------|--------------|

SURFACE SAR




VOLUME SAR




Maximum location: X=23.00, Y=-14.00 SAR Peak: 0.03 W/kg

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.014035 |
|----------------|----------|


| | |
|---------------|----------|
| SAR 1g (W/Kg) | 0.019918 |
|---------------|----------|




| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
| SAR (W/Kg) | 0.0313 | 0.0204 | 0.0125 | 0.0090 | 0.0082 |



Hot spot position



Appendix A: EUT Photos



Liquid depth



The Body Liquid of 835MHz (15.4cm)



The Body Liquid of 1800MHz (15.2 cm)



The Body Liquid of 1900MHz (16.4 cm)



The Body Liquid of 2450MHz (15.3cm)



The Body Liquid of 2600MHz (16.5cm)



The Body Liquid of 3500MHz (15.4cm)



The Body Liquid of 3700MHz (15.2 cm)




The Body Liquid of 5000-6000MHz (16.5cm)



The Head Liquid of 1900MHz (15.5cm)




The Head Liquid of 2450MHz (15.6cm)




The Head Liquid of 835MHz (15.3cm)



The Head Liquid of 1800MHz (15.2cm)




The Head Liquid of 2600MHz (15.1cm)



The Head Liquid of 3500MHz (15.3cm)




The Head Liquid of 3700MHz (15.6cm)



The Body Liquid of 5000-6000MHz (15.8cm)


Appendix B: Test Setup Photos




Right Cheek



Right Tilted




Left Cheek




Left Tilted




Body worn – Front (10mm)




Body worn – Back (10mm)



Hotspot Front (10mm)




Hotspot Back (10mm)




Hotspot Top (10mm)



Hotspot Right (0mm)



Hotspot Bottom (0mm)



Hotspot Left (0mm)

Appendix C: Probe Calibration Certificate

COMOSAR E-FIELD Probe



COMOSAR E-Field Probe Calibration Report

Ref : ACR.180.7.22.BES.B

SHENZHEN TONGCE TESTING LAB

2101 & 2201, ZHENCHANG FACTORY RENSHAN INDUSTRIAL ZONE, FUHAI SUBDISTRICT, BAO'AN DISTRICT SHENZHEN, GUANGDONG, 518103, PEOPLE'S REPUBLIC OF CHINA

MVG COMOSAR DOSIMETRIC E-FIELD PROBE

SERIAL NO.: SN 25/22 EPG0375

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon

29280 PLOUZANE - FRANCE

Calibration date: 06/29/2024



Accreditations #2-6789
Scope available on www.cofrac.fr

The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.180.7.22 BES B

| | <i>Name</i> | <i>Function</i> | <i>Date</i> | <i>Signature</i> |
|-----------------------------------|----------------|-------------------------|-------------|------------------|
| <i>Prepared by :</i> | Jérôme Le Gall | Measurement Responsible | 6/30/2024 | |
| <i>Checked & approved by:</i> | Jérôme Luc | Technical Manager | 6/30/2024 | |
| <i>Authorized by:</i> | Yann Toutain | Laboratory Director | 7/05/2024 | |

| | |
|-----------------------|--|
| <i>Distribution :</i> | <i>Customer Name</i> Shenzhen Tongce Testing Lab |
|-----------------------|--|

| <i>Issue</i> | <i>Name</i> | <i>Date</i> | <i>Modifications</i> |
|--------------|----------------|-------------|----------------------|
| A | Jérôme Le Gall | 6/30/2024 | Initial release |
| | | | |
| | | | |



TABLE OF CONTENTS

| | | |
|-----|---------------------------------------|----|
| 1 | Device Under Test | 4 |
| 2 | Product Description | 4 |
| 2.1 | General Information | 4 |
| 3 | Measurement Method | 4 |
| 3.1 | Linearity | 4 |
| 3.2 | Sensitivity | 4 |
| 3.3 | Lower Detection Limit | 5 |
| 3.4 | Isotropy | 5 |
| 3.1 | Boundary Effect | 5 |
| 4 | Measurement Uncertainty | 6 |
| 5 | Calibration Measurement Results | 6 |
| 5.1 | Sensitivity in air | 6 |
| 5.2 | Linearity | 7 |
| 5.3 | Sensitivity in liquid | 8 |
| 5.4 | Isotropy | 9 |
| 6 | List of Equipment | 10 |



1 DEVICE UNDER TEST

| Device Under Test | |
|--|---|
| Device Type | COMOSAR DOSIMETRIC E FIELD PROBE |
| Manufacturer | MVG |
| Model | SSE2 |
| Serial Number | SN 25/22 EPGO375 |
| Product Condition (new / used) | New |
| Frequency Range of Probe | 0.15 GHz-6GHz |
| Resistance of Three Dipoles at Connector | Dipole 1: R1=0.197 MΩ Dipole 2: R2=0.230 MΩ Dipole 3: R3=0.208 MΩ |

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Probe

| | |
|--|--------|
| Probe Length | 330 mm |
| Length of Individual Dipoles | 2 mm |
| Maximum external diameter | 8 mm |
| Probe Tip External Diameter | 2.5 mm |
| Distance between dipoles / probe extremity | 1 mm |

3 MEASUREMENT METHOD

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

Page: 4/11

Template_ACR.DDD.N.YY.MVGB.ISSUE_COMOSAR Probe vK

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.1 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \Delta SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-\alpha \cdot (d_{be} + d_{step})})}{\delta/2} \text{ for } (d_{be} + d_{step}) < 10 \text{ mm}$$

- where
- $SAR_{uncertainty}$ is the uncertainty in percent of the probe boundary effect
- d_{be} is the distance between the surface and the closest *zoom-scan* measurement point, in millimetre
- Δ_{step} is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
- δ is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14$ mm at 3 GHz;
- ΔSAR_{be} in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.

The measured worst case boundary effect SAR uncertainty[%] for scanning distances larger than 4mm is 1.0% Limit ,2%).



4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

| Uncertainty analysis of the probe calibration in waveguide | | | | | |
|--|-----------------------|--------------------------|---------|----|--------------------------|
| ERROR SOURCES | Uncertainty value (%) | Probability Distribution | Divisor | ci | Standard Uncertainty (%) |
| Expanded uncertainty 95 % confidence level k = 2 | | | | | 14 % |

5 CALIBRATION MEASUREMENT RESULTS

| Calibration Parameters | |
|------------------------|-------------|
| Liquid Temperature | 20 +/- 1 °C |
| Lab Temperature | 20 +/- 1 °C |
| Lab Humidity | 30-70 % |

5.1 SENSITIVITY IN AIR

| Normx dipole 1 (µV/(V/m) ²) | Normy dipole 2 (µV/(V/m) ²) | Normz dipole 3 (µV/(V/m) ²) |
|---|---|---|
| 0.64 | 0.53 | 0.44 |

| DCP dipole 1 (mV) | DCP dipole 2 (mV) | DCP dipole 3 (mV) |
|-------------------|-------------------|-------------------|
| 106 | 108 | 109 |

Calibration curves $e_i=f(V)$ (i=1,2,3) allow to obtain E-field value using the formula:


$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$



COMOSAR E-FIELD PROBE CALIBRATION REPORT


Ref: ACR.180.7.22.BES.B

Calibration curves



5.2 LINEARITY

Linearity



Linearity: +/-1.94% (+/-0.09dB)



5.3 SENSITIVITY IN LIQUID


| Liquid | Frequency (MHz +/- 100MHz) | ConvF |
|--------|----------------------------------|-------|
| HL750 | 750 | 1.71 |
| BL750 | 750 | 1.78 |
| HL900 | 900 | 1.91 |
| BL900 | 900 | 1.96 |
| HL1800 | 1800 | 2.08 |
| BL1800 | 1800 | 2.16 |
| HL2000 | 2000 | 2.03 |
| BL2000 | 2000 | 2.10 |
| HL2450 | 2450 | 2.31 |
| BL2450 | 2450 | 2.37 |
| HL2600 | 2600 | 2.16 |
| BL2600 | 2600 | 2.23 |
| HL3500 | 3500 | 2.21 |
| BL3500 | 3500 | 2.28 |
| HL3700 | 3700 | 3.45 |
| BL3700 | 3700 | 3.15 |
| HL4600 | 4600 | 3.30 |
| BL4600 | 4600 | 3.70 |
| HL5200 | 5200 | 2.01 |
| BL5200 | 5200 | 2.08 |
| HL5600 | 5600 | 2.07 |
| BL5600 | 5600 | 2.12 |
| HL5800 | 5800 | 2.06 |
| BL5800 | 5800 | 2.13 |

LOWER DETECTION LIMIT: 7mW/kg



5.4 ISOTROPY

HL1800 MHz





6 LIST OF EQUIPMENT

| Equipment Summary Sheet | | | | |
|------------------------------------|----------------------|-------------------------|---|---|
| Equipment Description | Manufacturer / Model | Identification No. | Current Calibration Date | Next Calibration Date |
| CALIPROBE Test Bench | Version 2 | NA | Validated. No cal required. | Validated. No cal required. |
| Network Analyzer | Rohde & Schwarz ZVM | 100203 | 08/2021 | 08/2024 |
| Network Analyzer | Agilent 8753ES | MY40003210 | 10/2023 | 10/2026 |
| Network Analyzer – Calibration kit | HP 85033D | 3423A08186 | 06/2021 | 06/2027 |
| Multimeter | Keithley 2000 | 1160271 | 02/2023 | 02/2026 |
| Signal Generator | Rohde & Schwarz SMB | 106589 | 03/2022 | 03/2025 |
| Amplifier | MVG | MODU-023-C-0002 | Characterized prior to test. No cal required. | Characterized prior to test. No cal required. |
| Power Meter | NI-USB 5680 | 170100013 | 06/2024 | 06/2027 |
| Power Meter | Rohde & Schwarz NRVD | 832839-056 | 11/2023 | 11/2026 |
| Directional Coupler | Krytar 158020 | 131467 | Characterized prior to test. No cal required. | Characterized prior to test. No cal required. |
| Waveguide | MVG | SN 32/16 WG4_1 | Validated. No cal required. | Validated. No cal required. |
| Liquid transition | MVG | SN 32/16 WGLIQ_0G900_1 | Validated. No cal required. | Validated. No cal required. |
| Waveguide | MVG | SN 32/16 WG6_1 | Validated. No cal required. | Validated. No cal required. |
| Liquid transition | MVG | SN 32/16 WGLIQ_1G500_1 | Validated. No cal required. | Validated. No cal required. |
| Waveguide | MVG | SN 32/16 WG8_1 | Validated. No cal required. | Validated. No cal required. |
| Liquid transition | MVG | SN 32/16 WGLIQ_1G800B_1 | Validated. No cal required. | Validated. No cal required. |
| Liquid transition | MVG | SN 32/16 WGLIQ_1G800H_1 | Validated. No cal required. | Validated. No cal required. |
| Waveguide | MVG | SN 32/16 WG10_1 | Validated. No cal required. | Validated. No cal required. |
| Liquid transition | MVG | SN 32/16 WGLIQ_3G500_1 | Validated. No cal required. | Validated. No cal required. |
| Waveguide | MVG | SN 32/16 WG12_1 | Validated. No cal required. | Validated. No cal required. |

Page: 10/11

Template_ACR.DDD.N.YY.MVGB.ISSUE.COMOSAR.Probe.vX

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.180.7.22 BES B

| | | | | |
|----------------------------------|--------------|---------------------------|--------------------------------|--------------------------------|
| Liquid transition | MVG | SN 32/16 WGLIQ_5G000_1 | Validated. No cal required. | Validated. No cal required. |
| Temperature / Humidity Sensor | Testo 184 H1 | 44225320 | 06/2024 | 06/2027 |



Dielectric Probe Calibration Report

Ref : ACR.138.4.33.SATU.A

SHENZHEN TONGCE TESTING LAB
2101&2201, ZHENCHANG FACTORY, RENSHAN
INDUSTRIAL ZONE, FUHAI SUBDISTRICT, BAOAN
DISTRICT, SHENZHEN, GUANGDONG, 518103,
PEOPLES REPUBLIC OF CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE

FREQUENCY: 0.3-6 GHZ
SERIAL NO.: SN 19/15 OCPG 71

Calibrated at MVG US
2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 06/05/2024

Summary:

This document presents the method and results from an accredited Dielectric Probe calibration performed in MVG USA using the LIMESAR test bench. All calibration results are traceable to national metrology institutions.



SAR DIELECTRIC PROBE CALIBRATION REPORT

Ref: ACR.138.433..SATUA

| | Name | Function | Date | Signature |
|---------------|---------------|-----------------|------------|----------------------|
| Prepared by : | Jérôme LUC | Product Manager | 06/05/2024 | <i>JL</i> |
| Checked by : | Jérôme LUC | Product Manager | 06/05/2024 | <i>JL</i> |
| Approved by : | Kim RUTKOWSKI | Quality Manager | 06/05/2024 | <i>Kim Rutkowski</i> |

| | Customer Name |
|----------------|-----------------------------|
| Distribution : | SHENZHEN TONGCE TESTING LAB |

| Issue | Date | Modifications |
|-------|------------|-----------------|
| A | 06/05/2024 | Initial release |
| | | |
| | | |



TABLE OF CONTENTS

| | | |
|-----|---|---|
| 1 | Introduction..... | 4 |
| 2 | Device Under Test | 4 |
| 3 | Product Description | 4 |
| 3.1 | General Information | 4 |
| 4 | Measurement Method | 5 |
| 4.1 | Liquid Permittivity Measurements | 5 |
| 5 | Measurement Uncertainty | 5 |
| 5.1 | Dielectric Permittivity Measurement | 5 |
| 6 | Calibration Measurement Results | 6 |
| 6.1 | Liquid Permittivity Measurement | 6 |
| 7 | List of Equipment | 7 |



1 INTRODUCTION

This document contains a summary of the suggested methods and requirements set forth by the IEEE 1528 and CEI/IEC 62209 standards for liquid permittivity measurements and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

| Device Under Test | |
|--------------------------------|--------------------------|
| Device Type | LIMESAR DIELECTRIC PROBE |
| Manufacturer | MVG |
| Model | SCLMP |
| Serial Number | SN 19/15 OCPG 71 |
| Product Condition (new / used) | Used |

A yearly calibration interval is recommended.

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's Dielectric Probes are built in accordance to the IEEE 1528 and CEI/IEC 62209 standards. The product is designed for use with the LIMESAR test bench only.



Figure 1 – MVG LIMESAR Dielectric Probe



4 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209-1 & 2 standards outline techniques for dielectric property measurements. The LIMESAR test bench employs one of the methods outlined in the standards, using a contact probe or open-ended coaxial transmission-line probe and vector network analyzer. The standards recommend the measurement of two reference materials that have well established and stable dielectric properties to validate the system, one for the calibration and one for checking the calibration. The LIMESAR test bench uses De-ionized water as the reference for the calibration and either DMS or Methanol as the reference for checking the calibration. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 LIQUID PERMITTIVITY MEASUREMENTS

The permittivity of a liquid with well established dielectric properties was measured and the measurement results compared to the values provided in the fore mentioned standards.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 DIELECTRIC PERMITTIVITY MEASUREMENT

The following uncertainties apply to the Dielectric Permittivity measurement:

| Uncertainty analysis of Permittivity Measurement | | | | | |
|--|--------------------------|--------------------------|------------|----|-----------------------------|
| ERROR SOURCES | Uncertainty value (+/-%) | Probability Distribution | Divisor | ci | Standard Uncertainty (+/-%) |
| Repeatability (n repeats, mid-band) | 4.00% | N | 1 | 1 | 4.000% |
| Deviation from reference liquid | 5.00% | R | $\sqrt{3}$ | 1 | 2.887% |
| Network analyser-drift, linearity | 2.00% | R | $\sqrt{3}$ | 1 | 1.155% |
| Test-port cable variations | 0.00% | U | $\sqrt{2}$ | 1 | 0.000% |
| Combined standard uncertainty | | | | | 5.066% |
| Expanded uncertainty (confidence level of 95%, k = 2) | | | | | 10.0% |

| Uncertainty analysis of Conductivity Measurement | | | | | |
|--|--------------------------|--------------------------|------------|----|-----------------------------|
| ERROR SOURCES | Uncertainty value (+/-%) | Probability Distribution | Divisor | ci | Standard Uncertainty (+/-%) |
| Repeatability (n repeats, mid-band) | 3.50% | N | 1 | 1 | 3.500% |
| Deviation from reference liquid | 3.00% | R | $\sqrt{3}$ | 1 | 1.732% |
| Network analyser-drift, linearity | 2.00% | R | $\sqrt{3}$ | 1 | 1.155% |
| Test-port cable variations | 0.00% | U | $\sqrt{2}$ | 1 | 0.000% |
| Combined standard uncertainty | | | | | 4.072% |
| Expanded uncertainty (confidence level of 95%, k = 2) | | | | | 8.1% |



SAR DIELECTRIC PROBE CALIBRATION REPORT

Ref: ACR.138.4.33..SATU.A


6 CALIBRATION MEASUREMENT RESULTS

Measurement Condition

| | |
|--------------------|---------|
| Software | LIMESAR |
| Liquid Temperature | 21°C |
| Lab Temperature | 21°C |
| Lab Humidity | 44% |

6.1 LIQUID PERMITTIVITY MEASUREMENT

A liquid of known characteristics (methanol at 20°C) is measured with the probe and the results (complex permittivity $\epsilon' + j\epsilon''$) are compared with the well-known theoretical values for this liquid.





7 LIST OF EQUIPMENT

| Equipment Summary Sheet | | | | |
|---------------------------------|----------------------|--------------------|-----------------------------|-----------------------------|
| Equipment Description | Manufacturer / Model | Identification No. | Current Calibration Date | Next Calibration Date |
| LIMESAR Test Bench | Version 3 | NA | Validated. No cal required. | Validated. No cal required. |
| Network Analyzer | Rhode & Schwarz ZVA | SN100132 | 02/2024 | 02/2027 |
| Methanol CAS 67-56-1 | Alpha Aesar | Lot D13W011 | Validated. No cal required. | Validated. No cal required. |
| Temperature and Humidity Sensor | Control Company | 11-661-9 | 09/2023 | 09/2024 |

Appendix D: Dipole Calibration Report

SID 750



SAR Reference Dipole Calibration Report

Ref : ACR.156.3.15.SATU.A

SHENZHEN TONGCE TESTING LAB
2101&2201, ZHENCHANG FACTORY, RENSHAN
INDUSTRIAL ZONE, FUHAI SUBDISTRICT, BAOAN
DISTRICT, SHENZHEN, GUANGDONG, 518103,
PEOPLES REPUBLIC OF CHINA

COMOSAR REFERENCE DIPOLE
FREQUENCY: 750 MHZ
SERIAL NO.: SN 16/15 DIP 0G750-368

Calibrated at MVG US
2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 06/05/2024

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.3.15.SATU.A

| | <i>Name</i> | <i>Function</i> | <i>Date</i> | <i>Signature</i> |
|----------------------|---------------|-----------------|-------------|----------------------|
| <i>Prepared by :</i> | Jérôme LUC | Product Manager | 06/05/2024 | <i>[Signature]</i> |
| <i>Checked by :</i> | Jérôme LUC | Product Manager | 06/05/2024 | <i>[Signature]</i> |
| <i>Approved by :</i> | Kim RUTKOWSKI | Quality Manager | 06/05/2024 | <i>Kim Rutkowski</i> |

| | <i>Customer Name</i> |
|-----------------------|-----------------------------|
| <i>Distribution :</i> | SHENZHEN TONGCE TESTING LAB |

| <i>Issue</i> | <i>Date</i> | <i>Modifications</i> |
|--------------|-------------|----------------------|
| A | 06/05/2024 | Initial release |
| | | |
| | | |
| | | |



TABLE OF CONTENTS

| | | |
|-----|--|----|
| 1 | Introduction..... | 4 |
| 2 | Device Under Test | 4 |
| 3 | Product Description | 4 |
| 3.1 | General Information | 4 |
| 4 | Measurement Method | 5 |
| 4.1 | Return Loss Requirements | 5 |
| 4.2 | Mechanical Requirements | 5 |
| 5 | Measurement Uncertainty..... | 5 |
| 5.1 | Return Loss | 5 |
| 5.2 | Dimension Measurement | 5 |
| 5.3 | Validation Measurement | 5 |
| 6 | Calibration Measurement Results..... | 6 |
| 6.1 | Return Loss and Impedance In Head Liquid | 6 |
| 6.2 | Return Loss and Impedance In Body Liquid | 6 |
| 6.3 | Mechanical Dimensions | 6 |
| 7 | Validation measurement | 7 |
| 7.1 | Head Liquid Measurement | 7 |
| 7.2 | SAR Measurement Result With Head Liquid | 8 |
| 7.3 | Body Liquid Measurement | 9 |
| 7.4 | SAR Measurement Result With Body Liquid | 10 |
| 8 | List of Equipment | 11 |



1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

| Device Under Test | |
|--------------------------------|----------------------------------|
| Device Type | COMOSAR 750 MHz REFERENCE DIPOLE |
| Manufacturer | MVG |
| Model | SID750 |
| Serial Number | SN 16/15 DIP 0G750-368 |
| Product Condition (new / used) | Used |

A yearly calibration interval is recommended.

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

| Frequency band | Expanded Uncertainty on Return Loss |
|----------------|-------------------------------------|
| 400-6000MHz | 0.1 dB |

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

| Length (mm) | Expanded Uncertainty on Length |
|-------------|--------------------------------|
| 3 - 300 | 0.05 mm |

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

| Scan Volume | Expanded Uncertainty |
|-------------|----------------------|
| 1 g | 20.3 % |