



Conforms to  
UL Std. 1993  
Certified to  
CSA Std. C22.2 No. 1993  
Model: BLB-A19-RGBW  
100-132Vac, 50/60Hz ,0.15A ,8W  
FCC ID: 2AQSN-A19-RGBW  
IC: 10733A-A19RGBW

Font requirements: Silk-screen

1. ETL logo shall be at least 8mm high. "US" shall be at least 2mm high, "Intertek" shall be at least 3mm high, control number shall be at least 2mm high. Other letters shall be at least 1.6mm high.



Conforms to  
UL Std. 1993  
Certified to  
CSA Std. C22.2 No. 1993  
Model: I-WFRGBWBLB  
100-132Vac, 50/60Hz ,0.15A ,8W  
FCC ID: 2AQSN-A19-RGBW  
IC: 10733A-A19RGBW

Font requirements: Silk-screen

1. ETL logo shall be at least 8mm high. "US" shall be at least 2mm high, "Intertek" shall be at least 3mm high, control number shall be at least 2mm high. Other letters shall be at least 1.6mm high.



Conforms to  
UL Std. 1993  
Certified to  
CSA Std. C22.2 No. 1993  
Model: I-K4WFRGBWBLB  
100-132Vac, 50/60Hz ,0.15A ,8W  
FCC ID: 2AQSN-A19-RGBW  
IC: 10733A-A19RGBW

Font requirements: Silk-screen

1. ETL logo shall be at least 8mm high. "US" shall be at least 2mm high, "Intertek" shall be at least 3mm high, control number shall be at least 2mm high. Other letters shall be at least 1.6mm high.