

RF EXPOSURE EVALUATION

EUT Specification

EUT	LED Strip Light Controller
Model Number	Y4305A
FCC ID	2AQSN-Y4305A
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Antenna gain (Max)	1.2dBi
Max. output power	802.11b: 14.15dBm 802.11g: 13.29dBm 802.11n(HT20): 11.74dBm
Input Rating	AC120V/60Hz for adapter
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Applicable Standard:

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J. Section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m Normally can be maintained between the user and the device.

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where P_d = Power density in mW/cm², P_{out} =output power to antenna in Mw G = gain of antenna in linear scale, $P_i=3.1416$ R = distance between observation point and center of the radiator in cm P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.


Measurement Result

Max power Result:

Operation Mode	Channel Number	Channel Frequency (MHz)	Peak Output Power(dBm)	Limit (dBm)	Verdict
802.11b	1	2412	14.15	30	PASS
	6	2437	13.72	30	PASS
	11	2462	13.64	30	PASS
802.11g	1	2412	13.29	30	PASS
	6	2437	12.78	30	PASS
	11	2462	12.11	30	PASS
802.11n (HT20)	1	2412	11.74	30	PASS
	6	2437	10.98	30	PASS
	11	2462	9.75	30	PASS

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	1	14±1	15	31.623	1.2	1.318	0.008293	1
	6	14±1	15	31.623	1.2	1.318	0.008293	1
	11	14±1	15	31.623	1.2	1.318	0.008293	1
802.11g	1	13±1	14	25.119	1.2	1.318	0.006588	1
	6	13±1	14	25.119	1.2	1.318	0.006588	1
	11	12±1	13	19.953	1.2	1.318	0.005233	1
802.11n (HT20)	1	12±1	13	19.953	1.2	1.318	0.005233	1
	6	11±1	12	15.849	1.2	1.318	0.004157	1
	11	10±1	11	12.589	1.2	1.318	0.003302	1

signature:



Print: Lisa Wang

Title: Manager

Date: 2018-12-28