

RF Report On



**Add value.
Inspire trust.**

FCC Testing of the Octasic Portable MIMO System in accordance with
FCC CFR 47 Part 2, and [FCC CFR 47 Part 22H](#)

COMMERCIAL-IN-CONFIDENCE

FCC: 2AQSOCBRSYS4450

PREPARED BY

Handwritten signature of Jose Martinez.

Jose Martinez

APPROVED BY

Handwritten signature of Scott Drysdale.

Scott Drysdale

DATED

Nov. 11, 21

11-Nov-21

Page 1 of 57

Report Issued:
11/11/2021

Report File #:
TR-7169009211M-
CBRSYS4450- UTMS_Band
5_FCC-Issue -04





Contents

1	SECTION 1: REPORT INFORMATION	3
1.1	Report Details	4
1.2	Brief Summary of Results	5
1.3	Product Information	6
1.3.1	Technical Description	6
1.3.1.1	The Transmission in the Band 5	6
1.3.2	Configuration Description	7
1.4	Declaration of Build Status	8
1.5	General Test Setup	10
1.6	Test Conditions	11
1.7	Deviation From The Standard	11
1.8	Modification Record	11
1.9	TEST FACILITY	11
2	SECTION 2: TEST DETAILS	12
2.1	Maximum Peak Output Power and Peak to Average Ratio - Conducted	13
2.1.1	Specification Reference	13
2.1.2	Date of Test and Modification State	13
2.1.3	Test Equipment Used	13
2.1.4	Environmental Conditions	13
2.1.6	Test Results	14
2.1.6.1	Bottom Channel – 871.6MHz	14
2.1.6.1.1	Worst Case – Port 2B	15
2.1.6.2	Bottom Channel – 877.4MHz	17
2.1.6.2.1	Worst Case – Port 2B	18
2.1.6.3	Middle Channel: 882.6MHz	20
2.1.6.3.1	Worst Case – Port 2B	21
2.1.6.4	Top Channel: 887.4MHz	23
2.1.6.4.1	Worst Case – Port 1A	24
2.2	Occupied Bandwidth	26
2.2.1	Specification Reference	26
2.2.2	Date of Test and Modification State	26
2.2.3	Test Equipment Used	26
2.2.4	Environmental Conditions	26
2.2.6	Test Results	26
2.2.6.1	Bottom/Top Channel – 871.6 MHz	27
2.2.6.1.1	Worst Case – Port 2B	27
2.2.6.1	Bottom/Top Channel – 877.4 MHz	28
2.2.6.1.1	Worst Case – Port 2B	28
2.2.6.2	Middle Channel: 882.6 MHz	29
2.2.6.2.1	Worst Case – Port 1B	29
2.2.6.1	Top Channel – 887.4 MHz	30
2.2.6.1.1	Worst Case – Port 1A	30
2.3	Band Edge	31
2.3.1	Specification Reference	31
2.3.2	Date of Test and Modification State	31
2.3.3	Test Equipment Used	31
2.3.4	Environmental Conditions	31
2.3.6	Test Results	32
2.3.6.1	Bottom Channel – 871.6 MHz	32
2.3.6.1.1	Worst Case – Port 2B	32
2.3.6.1	Bottom/Top Channel: 877.4MHz	34
2.3.6.1.1	Worst Case – Port 2B	34



2.3.6.2	Bottom/Top Channel: 882.6MHz	36
2.3.6.2.1	Worst Case – Port 2B	36
2.3.6.3	Bottom/Top Channel: 887.4MHz	38
2.3.6.3.1	Worst Case – Port 1A	38
2.4	Transceiver Spurious Emissions	40
2.4.1	Specification Reference.....	40
2.4.2	Date of Test and Modification State	40
2.4.3	Test Equipment Used	40
2.4.4	Environmental Conditions.....	40
2.4.6	Test Results	41
2.4.6.1.1	Worst Case – Port 1A	41
2.5	Frequency Stability	45
2.5.1	Specification Reference.....	45
2.5.2	Date of Test and Modification State	45
2.5.3	Test Equipment Used	45
2.5.4	Environmental Conditions.....	45
2.5.6	Test Results	45
2.5.6.1.1	Worst Case – Port 1A	45
2.6	Field Strength	46
2.6.1	Specification Reference.....	46
2.6.2	Date of Test and Modification State	46
2.6.3	Test Equipment Used	46
2.6.4	Environmental Conditions.....	46
2.6.6	Test Results	47
3	SECTION 3: TEST EQUIPMENT USED	52
3.1	Test Equipment Used	53
3.2	Measurement Uncertainty	54
4	ACCREDITATION, DISCLAIMERS AND COPYRIGHT.....	55
4.1	Accreditation, Disclaimers and Copyright.....	56



SECTION 1: REPORT INFORMATION



1.1 REPORT DETAILS

Manufacturer	Octasic inc.
Manufacturer Description	CBRSYS4450
Address	2901 Rachel St. East, Suite 30. Montreal, QC, H1W 4A4
Product Name	Portable MIMO System
Product Number	CBRSYS4450
Serial Number(s)	F-01150
Hardware Version(s)	Version 1
Software Version(s)	BSP CBRBTS-BSP-02.07.03.02-B454
Test Specification/Issue/Date	FCC CFR 47 Part 2: August 16, 2021 FCC CFR 47 Part 22: September 1, 2021
Max Antenna Gain	5dBi
Start of Test	June 22, 2021
Finish of Test	November 11, 2021
Name of Test Personnel(s)	Jose Martinez
Related Document(s)	KDB 971168 D01 v02r02: April 2018 KDB 662911 D01 v02r01: October 2013
Test report revision history	<p>2021-09-15. Issue 000. Initial release.</p> <p>2021-09-29. Issue 001. FCC Label updated</p> <p>2021-01-04. Issue 002. ISED Clause updated</p> <p>2021-10-19. Issue 03. Modifications:</p> <ul style="list-style-type: none"> • Removed RSS-132 • Section 2.1. Power table arranged properly • Section 2.3.5. Update RBW method section <p>2021-11-11. Issue 04. Modifications:</p> <ul style="list-style-type: none"> • Section 2.1, 2.2 and 2.3. Added measurements of new carriers.



1.2 BRIEF SUMMARY OF RESULTS

A summary of results for each configuration, in accordance with FCC CFR 47 Part 2 and [FCC CFR 47 Part 22H](#) is shown below.

Table 1 –Test Summary

Section	FCC CFR 47 Part 2	FCC CFR 47 Part 22	Test Description	Result
2.1	§2.1046	§22.913(a)(1)(i)	Maximum Peak Output Power	Pass
2.1	§2.1049	§ 22.917	Occupied Bandwidth	Pass
2.2	§2.1051	§22.917 (a)	Band Edge	Pass
2.3	§2.1051	§22.357	Transceiver Spurious Emissions	Pass
2.4	§2.1055	§22.355	Frequency Stability	Pass
2.3	-	§22.983	Filed Strength Limit	Pass



1.3 PRODUCT INFORMATION

1.3.1 Technical Description

The EUT, hereafter referred as the Equipment Under Test (EUT) is a MIMO Station unit CBRSYS4450 of Octasic Inc operating in the Block A (869MHz – 880MHz) and Block B (880MHz – 890MHz) and according to [22.905](#) for cellular service.

1.3.1.1 The Transmission in the Band 5

The channel configuration is as follows:

Channels	Frequency (MHz)	Target Power (dBm)	Power Measured (dBm)
Bottom/Top	871.6	30	29.55 <Note 1>
Bottom/Top	877.4	30	29.82 <Note 2>
Bottom/Top	882.6	30	29.69 <Note 3>
Bottom/Top	887.4	30	29.97 <Note 4>
Note 1. See Table 3 in Section 2.1.6.1 Note 2. See Table 4 in Section 2.1.6.2 Note 3. See Table 5 in Section 2.1.6.3. Note 4. See Table 5 in Section 2.1.6.4.			

A full technical description can be found in the Manufacturer's documentation guide and datasheet CBRSYS4450-User_Guide.pdf and CBRSYS4450-Datasheet.pdf, respectively.



1.3.2 Configuration Description

The EUT supports single mode operation having four transmitting ports (see Figure 3)

TX test cases: Maximum Conducted Output Power, Spurious Emissions at Antenna Terminals (± 1 MHz) and Conducted Spurious Emissions, measurements were performed on the four RF Port. The test limits shown are representative of the worst case. All testing was performed with the EUT transmitting at maximum RF power unless as designated setting by client, otherwise stated.

The EUT was powered via a 120V/60Hz power AC/DC Adapter.

Channel Configurations:

Table 2 – Channel Configuration

UTMS Band	No. Of Carriers	Modulation	Carrier Bandwidth	Carrier Frequency Configuration (MHz)		
				Bottom/ B_R FBW (MHz)	Middle/ M_{RFBW} (MHz)	Top/ T_{RFBW} (MHz)
5	1	QPSK	5 MHz	871.6	882.6	887.4



1.4 DECLARATION OF BUILD STATUS

MAIN EUT	
MANUFACTURING DESCRIPTION	CBRSYS4450
MANUFACTURER	Octasic inc.
TYPE	Portable Transportable Amplification Unit (TAU)
PART NUMBER(S)	CBRSYS4450
SERIAL NUMBER(S)	F-01150
HARDWARE VERSION(S)	Version 1
SOFTWARE VERSIONS(S)	CBRBTS-BSP-02.07
TRANSMITTER OPERATING RANGE (Band 5)	871.6MHz – 887.4MHz
RECEIVER OPERATING RANGE(MHz)	663 to 2690
EMISSION DESIGNATOR(S): (i.e. G1D, GXW)	194M
Country of Origin	Bangalore, India
MODULATION TYPES: (i.e. GMSK, QPSK)	QPSK
HIGHEST INTERNALLY GENERATED FREQUENCY	2.7GHz
OUTPUT POWER (W or dBm)	30dBm
FCC ID:	2AQSOCBRSYS4450
TECHNICAL DESCRIPTION (a brief description of the intended use and operation)	The CBRSYS4450 is a base station solution build for the particular needs of application like search and Rescue (SRR), Network in Box (NiB) and Disaster Recovery. It integrates four transceiver cellular base station (BTS) with all necessary RF, GPS and Wi-Fi antennas. The control is through an easy-to-use Android app on a smartphone or table for convenient on-the-go operation

Equipment Under Test (EUT)



Figure 3. Top view of CBRSYS4450

1.5 GENERAL TEST SETUP




Figure 2. Block Diagram of Conducted Measurement Setup.



1.6 TEST CONDITIONS

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated as described in the Test Method for each Test.

The EUT was powered using the AC/DC adapter.

1.7 DEVIATION FROM THE STANDARD

No deviations from the applicable test standards or test plan were made during testing.

1.8 MODIFICATION RECORD

No modifications were made to the EUT during testing.

1.9 TEST FACILITY

FCC Measurement Facility Registration Number: CA4810

Under our group A2LA Accreditation, TÜV SÜD conducted the following tests at Kanata, Test Laboratory.

Test Name	Name of Test Specialist(s)
Maximum Peak Output Power and Peak to Average Ratio - Conducted	Jose Martinez
Occupied Bandwidth	Jose Martinez
Band Edge	Jose Martinez
Transmitter Spurious Emissions	Jose Martinez
Frequency Stability	Jose Martinez
Field Strength of Spurious Emissions - Radiated	Jose Martinez



SECTION 2: TEST DETAILS



2.1 MAXIMUM PEAK OUTPUT POWER AND PEAK TO AVERAGE RATIO - CONDUCTED

2.1.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1046
FCC CFR 47 Part 22H, [§22.913\(a\)\(1\)\(i\)](#)

2.1.2 Date of Test and Modification State

11 November 2021 -Modification State 0

2.1.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.4 Environmental Conditions

Ambient Temperature	25.1°C
Relative Humidity	20.4%

2.1.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01, clause 5.2.1 and summed in accordance with FCC KDB 662911 D01. The attenuation value used throughout this report is 30dB ± 0.6dB.

Measurements were performed with a Spectrum Analyser using the Band Power measurement function. The detector was set to RMS with an RBW of at least 1 % of the carrier bandwidth and a VBW of at least 3 times the RBW. The integration bandwidth was configured to be wider than the total bandwidth of the carrier or combinations of carriers, (multi-carrier). Using a sweep time of auto, measurements were performed over 200 samples, with the average measurement recorded.

Due to Average measurements being recorded, an additional Peak to Average power ratio (PAPR) measurement was made. This was achieved using the CCDF function of the Spectrum Analyser with the RBW being set to a value wider than the largest signal being measured – in this case – 20MHz.

The EUT was configured to transmit on maximum power on the configurations defined in the tables below.

The peak to average ratio measurement was performed at the conducted ports of the EUT. The spectrum analyzer's Complementary Cumulative Distribution Function (CCDF) was used, and 0.1% probability value recorded.

The RMS Power and Peak to Average Ratio were measured and recorded with the results being compared with the limits.

Measurements presented are the worst-case of measurements conducted in the four ports: TX1A, TX1B, Tx2A and Tx2B, respectively.



2.1.6 Test Results

2.1.6.1 Bottom Channel – 871.6MHz

Maximum Target Output Power: 30 dBm


Table 3 – Max Peak Output Power – Bottom Channel

Antenna	Output Power/PAPR					Result <Note 4>
	PAPR	Conducted Average Power		ERP <Note 2>	Limit <Note 3>	
	(@ 0.1%)	(dBm)	(mW)	(dBm)	(W)	
TX1A	6.22	29.43	877.00	26.54	500	Pass
TX1B	6.24	29.5	891.25	26.78		
TX2A	6.08	29.47	885.12	26.68		
TX2B	6.16	29.55 <Note 1>	901.57	26.62		
Total		35.51	3554.94	-		
Note 1. See worst-case TX1B in Graph 1 Note 2. ERP =EIRP -2.15 dB as per 412172 D01 Note 3 As per §22.913(a)(1)(i)						



2.1.6.1.1 Worst Case – Port 2B

Carrier Power Modulation QPSK - Carrier Bandwidth 5.0 MHz – Channel Position: 871.6 MHz




Graph 1: Output Power – Port 2B – Bottom Channel

Calculation: $30\text{dB} - 0.45\text{ dBm} = 29.55\text{ dBm}$.



PAPR - Carrier Bandwidth 5.0 MHz – Channel Position: 871.6 MHz





2.1.6.2 Bottom Channel – 877.4MHz

Maximum Target Output Power: 30 dBm

Table 4 – Max Peak Output Power – Bottom Channel


Antenna	Output Power/PAPR					Result
	PAPR	Conducted Average Power		ERP <Note 2>	Limit <Note 3>	
	(@ 0.1%)	(dBm)	(mW)	(dBm)	(W)	
TX1A	6.20	29.53	897.43	26.85	500	Pass
TX1B	6.12	29.79	952.80	27.24		
TX2A	6.14	29.45	881.05	26.63		
TX2B	6.03	29.82 <Note 1>	959.40	27.17		
Total		35.67	3690.67	-		

Note 1. See worst-case TX1B in Graph 1
 Note 2. ERP =EIRP -2.15 dB as per [412172 D01](#)
 Note 3 As per [§22.913\(a\)\(1\)\(i\)](#)



2.1.6.2.1 Worst Case – Port 2B

Carrier Power Modulation QPSK - Carrier Bandwidth 5.0 MHz – Channel Position: 877.4 MHz




Graph 2: Output Power – Port 2B – Bottom Channel

Calculation: $30\text{dB} - 0.18\text{dBm} = 29.82\text{ dBm}$.



PAPR - Carrier Bandwidth 5.0 MHz – Channel Position: 877.4 MHz





2.1.6.3 Middle Channel: 882.6MHz

Maximum Target Output Power: 30 dBm

Table 5 – Max Peak Output Power – Middle Channel


Antenna	Output Power/PAPR					Result <Note 4>
	PAPR	Conducted Average Power		ERP <Note 2>	Limit <Note 3>	
	(@ 0.1%)	(dBm)	(mW)	(dBm)	(W)	
TX1A	6.16	29.66	924.70	34.66	500	Pass
TX1B	6.16	29.67	926.83	34.67		
TX2A	6.04	29.56	903.65	34.56		
TX2B	6.06	29.69 <Note 1>	931.11	34.69		
Total		35.67	3686.29	-		

Note 1. See worst-case TX1B in Graph 2
 Note 2. ERP =EIRP -2.15 dB as per [412172 D01](#)
 Note 3 As per [§22.913\(a\)\(1\)\(i\)](#)



2.1.6.3.1 Worst Case – Port 2B

Carrier Power - Modulation QPSK - Carrier Bandwidth 5.0 MHz – Channel Position:
882.6MHz




Graph 3: Output Power – Port 2B – Middle Channel

Calculation: $30.0\text{dB} - 0.31\text{ dBm} = 29.69\text{ dBm}$.



PAPR - Carrier Bandwidth 5.0 MHz – Channel Position: 882.6MHz





2.1.6.4 Top Channel: 887.4MHz

Maximum Target Output Power: 30 dBm


Table 6 – Max Peak Output Power – Top Channel

Antenna	Output Power/PAPR					Result <Note 4>
	PAPR	Conducted Average Power		ERP <Note 2>	Limit <Note 3>	
	(@ 0.1%)	(dBm)	(mW)	(dBm)	(W)	
TX1A	6.01	29.97 <Note 1>	993.12	34.97	500	Pass
TX1B	6.21	29.57	905.73	34.57		
TX2A	6.05	29.57	905.73	34.57		
TX2B	6.17	29.56	903.65	34.56		
Total		35.69	3708.23	-		
<p>Note 1. See worst-case TX1B in Graph 3</p> <p>Note 2. ERP =EIRP -2.15 dB as per 412172 D01</p> <p>Note 3 As per §22.913(a)(1)(i)</p> <p>Note 4 The power was reduced to comply with Clause 22.917 (a)</p>						



2.1.6.4.1 Worst Case – Port 1A

Carrier Power - Modulation QPSK - Carrier Bandwidth 5.0 MHz – Channel Position: 887.4MHz




Graph 4: Output Power – Port 2B – Top Channel

Calculation. $30\text{dB} - .03\text{ dBm} = 29.97\text{ dBm}$.



PAPR - Carrier Bandwidth 5.0 MHz – Channel Position: 887.4MHz





2.2 OCCUPIED BANDWIDTH

2.2.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1049
FCC CFR 47 Part 27, [Clause § 22.917](#)

2.2.2 Date of Test and Modification State

11 November 2021 - Modification State 0

2.2.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.2.4 Environmental Conditions

Ambient Temperature	22.1°C
Relative Humidity	16.4%

2.2.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01.

2.2.6 Test Results

Maximum Output Power: Bottom- Middle- and Top- channels was 30 dBm; respectively. The worst-case scenario of all channels is provided below.




2.2.6.1 Bottom/Top Channel – 871.6 MHz

2.2.6.1.1 Worst Case – Port 2B

Modulation	Carrier Bandwidth	Result (MHz)	
		Channel Bandwidth	-26 dB Bandwidth
QPSK	4.2 MHz	4.2	4.7

Bandwidth 5.0MHz – Modulation: QPSK – Channel B: 871.6 MHz






2.2.6.1 Bottom/Top Channel – 877.4 MHz

2.2.6.1.1 Worst Case – Port 2B

Modulation	Carrier Bandwidth	Result (MHz)	
		Channel Bandwidth	-26 dB Bandwidth
QPSK	5.0 MHz	4.2	4.7

Bandwidth 5.0MHz – Modulation: QPSK – Channel B: 871.6 MHz






2.2.6.2 Middle Channel: 882.6 MHz

2.2.6.2.1 Worst Case – Port 1B

Modulation	Carrier Bandwidth	Result (MHz)	
		Channel Bandwidth	
		Occupied Bandwidth	-26 dB Bandwidth
QPSK	5.0 MHz	4.2	4.7

Bandwidth 5.0MHz – Modulation: QPSK – Channel Middle: 882.6 MHz






2.2.6.1 Top Channel – 887.4 MHz

2.2.6.1.1 Worst Case – Port 1A

Modulation	Carrier Bandwidth	Result (MHz)	
		Channel Bandwidth	
		Occupied Bandwidth	-26 dB Bandwidth
QPSK	5.0 MHz	4.5	4.8

Bandwidth 5.0MHz – Modulation: QPSK – Channel Top: 887.4 MHz





2.3 BAND EDGE

2.3.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1051
FCC CFR 47 Part 22, [Clause 22.917 \(a\)](#)

2.3.2 Date of Test and Modification State

11 November 2021 - Modification State 0

2.3.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.3.4 Environmental Conditions

Ambient Temperature	24.1°C
Relative Humidity	25.4%

2.3.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01, clause 6. The EUT was connected to a Spectrum Analyser via an attenuator. The path loss between the EUT and the Spectrum Analyser was measured using a Network Analyser. The measured path loss was entered as a Reference Level Offset in the Spectrum Analyser. The Spectrum Analyser RBW was adjusted to be at least 1% of the measured 26dB Bandwidth. Using an RMS detector, the frequency spectrum up to 1MHz away from the Band Edge was Investigated.

The Spectrum Analyser RBW was adjusted to be at least 1% of the measured 26dB Bandwidth. Using an RMS detector, the frequency spectrum up to 1MHz from the band edge was investigated. The worst-case path loss in the measured ranges was entered as a reference level offset. Over the measured ranges, the RBW was set to 10kHz, however the band power function of the SA was used with an integration of 50kHz bandwidth. All measurement results are specified as average with an RMS detector being used in conjunction with a trace setting of Max Hold or clear write if representative. Measurements were performed in configurations of the EUT as reported below.

The EUT has one transmit port, testing was performed on this port with a test limit of $43+10 \times \log_{10}(P) + 10 \times \log_{10}(4) = -19$ dBm.



2.3.6 Test Results

Maximum Output Power: Bottom 30 dBm; Middle 30 dBm and Top 30 dBm. The band edges of middle channels were determined and only the worst scenario is provided.


2.3.6.1 Bottom Channel – 871.6 MHz

2.3.6.1.1 Worst Case – Port 2B

Maximum Target output Power: 30dBm


Modulation	Carrier Bandwidth	Band Edge (MHz)	Channel Position B:	Band Power 100kHz	Band Power 50kHz
			871.6		
QPSK	5.0 MHz	869 –880	Bottom	-23.17	-26.54
			Top	-46.20	-49.07

Modulation QPSK – Bottom – Carrier Bandwidth 5.0 MHz - Channel Position: 871.6 MHz (Band Power 50kHz and 100kHz)





Modulation QPSK – Top – Carrier Bandwidth 5.0 MHz - Channel Position: 871.6 MHz (Band Power 50kHz and 100kHz)






2.3.6.1 Bottom/Top Channel: 877.4MHz

Maximum Target output Power: 30 dBm

2.3.6.1.1 Worst Case – Port 2B


Modulation	Carrier Bandwidth	Band Edge (MHz)	Channel Position B:	Band Power 100kHz	Band Power 50kHz	Band Power 30kHz
			877.4			
QPSK	5.0 MHz	869 –880	Bottom	-46.04	-48.77	-50.70
			Top	-25.33	-29.01	-31.45

Modulation QPSK – Bottom - Carrier Bandwidth 4.2.0 MHz - Channel Position: 877.4MHz (Band Power 30kHz, 50kHz and 100kHz)





Modulation QPSK – Top- Carrier Bandwidth 5.0 MHz - Channel Position: 887.4MHz (Band Power 30kHz, 50kHz and 100kHz)






2.3.6.2 Bottom/Top Channel: 882.6MHz

Maximum Target output Power: 30 dBm

2.3.6.2.1 Worst Case – Port 2B


Modulation	Carrier Bandwidth	Band Edge (MHz)	Channel Position B:	Band Power 100kHz	Band Power 50kHz
			882.6		
QPSK	5.0 MHz	880 –890	Bottom	-22.71	-26.11
			Top	-41.89	-44.88

Modulation QPSK – Bottom – Carrier Bandwidth 5.0 MHz - Channel Position: 882.6 MHz (Band Power 50kHz and 100kHz)





Modulation QPSK – Top – Carrier Bandwidth 5.0 MHz - Channel Position: 882.6 MHz (Band Power 50kHz and 100kHz)






2.3.6.3 Bottom/Top Channel: 887.4MHz

Maximum Target output Power: 30 dBm

2.3.6.3.1 Worst Case – Port 1A


Modulation	Carrier Bandwidth	Band Edge (MHz)	Channel Position B:	Band Power 100kHz	Band Power 50kHz
			QPSK	5.0 MHz	880 –890
			Bottom	-39.96	-43.03
			Top	-23.02	-26.45

Modulation QPSK – Bottom – Carrier Bandwidth 5.0 MHz - Channel Position: 887.4 MHz (Band Power 50kHz and 100kHz)





Modulation QPSK – Top – Carrier Bandwidth 5.0 MHz - Channel Position: 887.4 MHz (Band Power 50kHz and 100kHz)





2.4 TRANSCEIVER SPURIOUS EMISSIONS

2.4.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1051
FCC CFR 47 Part 22, [Clause §22.357](#)

2.4.2 Date of Test and Modification State

11 November 2021- Modification State 0

2.4.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.4.4 Environmental Conditions

Ambient Temperature	25.1°C
Relative Humidity	16.4%

2.4.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01.

All measurements were made in accordance with FCC KDB 971168 D01 Clause 6. The EUT was connected to a Spectrum Analyser via an attenuator and switching box. Prior to testing, a Network Analyser was used to calibrate the path loss between the EUT and the Spectrum Analyser. The worst-case path loss in the measured ranges was entered as a reference level offset. Over the measured ranges, the RBW was set to 1MHz with a VBW of 3MHz. All measurement results are specified as average with an RMS detector being used in conjunction with a trace setting of Max Hold. Measurements were performed in configurations of the EUT as reported below. Testing was performed on this port with a test limit of $43+10\log_{10}(P) +10\text{Log}_{10}(4) = -19$ dBm.




2.4.6 Test Results

Range Frequency	Limit (dBm)	Result
9kHz to 1GHz	-19	Pass
1GHz to 5G	-19	Pass
5G to 26GHz	-19	Pass
26GHz to 40GHz	-19	Pass <Note 1>
Note 1. The device was scanned up to 40Ghz with no emission (peak values less than 6Bd from the limit)		


2.4.6.1.1 Worst Case – Port 1A

Modulation QPSK - Carrier Bandwidth 5.0 MHz – Range 9kHz to 500MHz






Modulation QPSK - Carrier Bandwidth 5.0 MHz – Range 500MHz to 5GHz: 871.6 MHz




Modulation QPSK - Carrier Bandwidth 5.0 MHz – Range 500MHz to 5GHz: 877.4MHz






Modulation QPSK - Carrier Bandwidth 5.0 MHz – Range 500MHz to 5GHz: 882.6 MHz






Modulation QPSK - Carrier Bandwidth 5.0 MHz – Range 500MHz to 1GHz: 887.4 MHz



Modulation QPSK - Carrier Bandwidth 5.0 MHz – Range 5GHz to 26GHz





2.5 FREQUENCY STABILITY

2.5.1 Specification Reference

FCC CFR 47 Part 2, Clause 2.1055
 FCC CFR 47 Part 27, [Clause 22.355](#)

2.5.2 Date of Test and Modification State

22 June 2021 - Modification State 0

2.5.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.5.4 Environmental Conditions

Ambient Temperature 26.7°C
 Relative Humidity 32.2%

2.5.5 Test Method

All measurements were made in accordance with FCC KDB 971168 D01.

2.5.6 Test Results

Maximum Target Output Power 30dBm

2.5.6.1.1 Worst Case – Port 1A

Temperature	Voltage (AC)	Frequency Error (Hz)	Limit ppm <Note 2>	Error/Freq ppm	Result
-30°C	115	Note 1	±1.5	N/A	<Note 1>
-20°C	115	87.24	±1.5	0.10	Pass
-10°C	115	34.21	±1.5	0.04	Pass
0°C	115	31.0	±1.5	0.03	Pass
+10°C	115	20.50	±1.5	0.02	Pass
+20°C	115	22.7	±1.5	0.03	Pass
+20°C	90	21.22	±1.5	0.02	Pass
+20°C	132	13.17	±1.5	0.01	Pass
+30°C	115	16.34	±1.5	0.02	Pass
+40°C	115	18.30	±1.5	0.02	Pass
+55°C	115	4.62	±1.5	0.005	Pass
Note 1. EUT stop the operation and no transmission was recorded: Pass The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation Note 2. Frequency Range 821 to 896 of Table C-1 in §22.355					



2.6 FIELD STRENGTH

2.6.1 Specification Reference

FCC CFR 47 Part 2.1053
FCC CFR 47 Part 90, Clause [§ 22.983](#)

2.6.2 Date of Test and Modification State

June 22, 2021 – Modification State 0
June 23, 2021 – Modification State 0
July 5th, 2021 – Modification State 0

2.6.3 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.6.4 Environmental Conditions

Ambient Temperature	23.1°C
Relative Humidity	13.4%

2.6.5 Test Method

All measurements were made in accordance with:

- 971168 D01 Power Meas License Digital Systems v03r01 Clause 5.6
- 971168 D01 Power Meas License Digital Systems v03r01 Clause 7

From Clause 5:6, the field strength of the EUT can be calculated by:

$$\text{EIRP} = P_{\text{meas}} + A_{\text{gain}} = 30 \text{ dBm} + 5\text{dBi} = 35\text{dBm} \text{ (or } 127.23 \text{ dB}\mu\text{V/m at 3m)}$$

Measurements were performed in configurations of the EUT as reported below. Testing was performed with RF on (Port TX1A) with a test limit of FCC 15 Subpart B Class B of 40 dB μ V/m, which is more restricted than -19 dBm or 76.23 dB μ V/m at 3m.




2.6.6 Test Results

A summary of the test result is depicted in the table below.

Range Frequency	Test Limit (dB μ V/m)	Limit <Note 1> dB μ V/m	Result
9kHz to 150kHz	40.0	76.23	Pass <Note 2>
150kHz to 30MHz	40.0	76.23	Pass
30MHz to 1GHz	33.06	76.23	Pass
1GHz to 10GHz	53.96	76.23	Pass
10GHz to 18GHz	53.96	76.23	Pass
18GHz to 40GHz	53.96	76.23	Pass <Note 3>
Note 1. As per CFR 47 27.55(a)(1) Note 2. No significant emission (> 20dB margin below the limit) was recorded according to FCC 15 Subpart B. Note 3. The device was scanned up to 40Ghz with no emission (peak values less than 6Bd from the limit)			



Spurious Radiation
Spurious Radiation Emission – 150kHz to 30MHz



Note 1. The spurious emissions comply with the limit of 76.23 dB μ V/m at 3m.


Frequency (MHz)	Detector	Raw Reading	Cable 27 - 10m LMR4 00 Factor	Loop - EM687 2 100k to 30M Factor	Pream p-LNA14 50 Factor	Level	FCC Part 15.209 Generic Limits (51.7 dB/decade factor used) Limit	FCC Part 15.209 Generic Limits (51.7 dB/decade factor used) Margin
0.7642	PEAK	31.4	0	-2.3	-31	-1.9	93.3	95.2
1.6872	PEAK	28.5	0.1	-7.4	-31.1	-9.9	86.4	96.3
1.1427	PEAK	28.7	0.1	-4.5	-31	-6.7	89.8	96.5
1.5378	PEAK	28	0.1	-6.6	-31	-9.5	87.2	96.7



Spurious Radiation Emission –30MHz to 1GHz

"TÜV SÜD, by release of this raw data, does not imply that the tested product has demonstrated compliance to any standard. The raw data provided may not be complete and may require additional processing. If raw data provided includes engineering data, testing may not have been done according to a standard test method. "

Emi CC test:RE_30-1000 MHz 10m - FCC- Class B Number:122 Execution date: 6/22/2021 1:42:24 PM	
Limit	FCC Part 15 Subpart B
Class	Class : B
Test Plan Number	7169009211
Configuration Information	Mode: Operating: Band:891.5MHz (30dBm)
Results	Pass
Model	CBRSYS4450
Tested by	KP and SM
Comments	Port activated: TX1A



Red=Vertical, Blue=Horizontal

Finals

Quasi-Peak Detector (6)

Frequency (MHz)	S R	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m) (dB)	Azimuth (°) (dB)	Polarization (dB)	Correction (dB)
135.8700672	1	32.42	33.06	-0.64	1.00	117.75	Vertical	-9.37
166.2925738	1	29.15	33.06	-3.91	1.11	175.25	Vertical	-10.68
187.5651795	1	27.54	33.06	-5.52	1.06	119.75	Vertical	-11.92
749.9822821	1	22.16	35.56	-13.40	1.84	220.75	Vertical	3.69
135.8608141	2	28.49	33.06	-4.57	4.00	112.75	Horizontal	-9.37
192.6622692	2	26.30	33.06	-6.76	3.40	127.25	Horizontal	-11.80

Note 1. The spurious emissions comply with the limit of 76.23 dBµV/m at 3m.


Note 2. Operating at 887.4MHz, thus emission excluded from FCC limit.



Spurious Radiation Emission –1GHz to 10GHz

"TÜV SÜD, by release of this raw data, does not imply that the tested product has demonstrated compliance to any standard. The raw data provided may not be complete and may require additional processing. If raw data provided includes engineering data, testing may not have been done according to a standard test method. "

Emi CC test:RE_1-10 GHz 3m - MIMO- FCC Class B Number:129 Execution date: 6/22/2021 3:15:43 PM	
Limit	FCC Part 15 Subpart B
Class	Class: B
Test Plan Number	7169009211
Configuration Information	Mode: Operating
Results	Pass
Model	CBRSYS4450
Tested by	KP and SM
Comments	Port activated: TX1A



Red=Vertical, Blue=Horizontal

Finals

AVG (4)								
Frequency (MHz)	SR	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m) (dB)	Azimuth (°) (dB)	Polarization (dB)	Correction (dB)
2405.726603	1	28.27	53.96	-25.69	3.69	9.50	Vertical	-5.79
6492.401603	1	33.47	53.96	-20.49	2.08	343.00	Vertical	1.37
2403.416346	2	28.38	53.96	-25.58	1.00	356.75	Horizontal	-5.81
6513.693269	2	33.56	53.96	-20.40	2.42	2.25	Horizontal	1.35

Note 1. The spurious emissions comply with the limit of 76.23 dBµV/m at 3m.


Note 2. 2.4GHz peak correspond to the computer WIFI communication.



Spurious Radiation Emission –10GHz to 18GHz

"TÜV SÜD, by release of this raw data, does not imply that the tested product has demonstrated compliance to any standard. The raw data provided may not be complete and may require additional processing. If raw data provided includes engineering data, testing may not have been done according to a standard test method. "

Emi CC test:RE_10-18 GHz 3m - MIMO - FCC Class B Number:135 Execution date: 6/23/2021 8:42:04 AM	
Limit	FCC Part 15 Subpart B
Class	Class: B
Test Plan Number	7169009211
Configuration Information	Operation: Band:891.5MHz (30dBm)
Results	Pass
Model	CBRSYS4450
Tested by	KP and SM
Comments	Port activated: TX1A



Red=Vertical, Blue=Horizontal

Finals

AVG Detector (4)

Frequency (MHz)	S R	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m) (dB)	Azimuth (°) (dB)	Polarization (dB)	Correction (dB)
16750.52277	2	41.61	53.96	-12.35	1.00	10.50	Horizontal	14.25
16753.59519	1	41.97	53.96	-11.99	4.00	271.50	Vertical	14.29
17898.35513	2	41.39	53.96	-12.57	3.86	16.75	Horizontal	14.87
17916.38559	1	41.10	53.96	-12.86	1.00	0.00	Vertical	14.82

Note 1. The spurious emissions comply with the limit of 76.23 dBµV/m at 3m.



SECTION 3: TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

List of absolute measurements and other principal items of test equipment.

Instrument	Manufacturer	Type No.	Serial No.	Calibration Period (months)	Calibration Due
Bilog Antenna	TESEQ	CBL 6111D	SSG013965	2021-05-04	2022-05-04
Horn Antenna 3MCH 00003	ETS	3117	LAVE04211	2021-03-30	2022-03-30
EMI Receiver	Rohde & Schwarz	ESU26	SSG013729	2021-03-31	2022-03-31
EMI Receiver	Rohde & Schwarz	ESU40	SSG013672	2020-10-29	2021-10-29
Coaxial Cable	Huber & Suhner	106A	SSG012455	2021-01-05	2022-01-05
Coaxial Cable	Huber & Suhner	106A	SSG012711	2021-01-05	2022-01-05
Coaxial Cable	Huber & Suhner	104PEA	SSG012041	2021-01-05	2022-01-05
Coaxial Cable	Huber & Suhner	ST18/Nm/Nm/36	SSG012785	2021-01-06	2022-01-06
Coaxial Cable	Micro-Coax	UFA 210B-1-1500-504504	SSG012376	2021-01-06	2022-01-06
Pre-Amplifier	Hp	8447D	LAVE04346	2020-09-10	2021-09-10
Pre-Amplifier	BNR	LNA	SSG012360	2020-11-16	2021-11-16
Power Supply	Hewlett Packard	6216A	SSG013063	not required	not required
N/A: No applicable O/P Mon – Output monitored with Calibrated Equipment					



3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:

Test Discipline	Frequency / Parameter	MU
Conducted Maximum Peak Output Power	30 MHz to 20 GHz Amplitude	± 0.1 dB
Conducted Emissions	30 MHz to 20 GHz Amplitude	± 2.3 dB
Frequency Stability	30 MHz to 2 GHz	± 5.0 Hz
Occupied Bandwidth	Up to 20 MHz Bandwidth	± 1.1 Hz
Band Edge	30 MHz to 20 GHz Amplitude	± 2.3 dB



SECTION 5

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



Testing Laboratory
Certificate #2955.19

This report relates only to the actual item/items tested.

This report does not imply product endorsement by any government, accreditation agency, or TÜV SÜD Canada Inc.

Opinions or interpretations expressed in this report, if any, are outside the scope of TÜV SÜD Canada Inc. accreditations. Any opinions expressed do not necessarily reflect the opinions of TÜV SÜD Canada Inc., unless otherwise stated.

This report relates only to the actual item/items tested.

© 2021 TÜV SÜD