

FCC RF EXPOSURE REPORT

Applicant	:	Globe Electric Company Inc
Address of Applicant	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8
Manufacturer	:	Zhejiang Bernal Electric Co., Ltd.
Address of Manufacturer	:	No.188, Punan Fifth Road, Economic Development Zone, Yueqing , Zhejiang, China.
Equipment under Test	:	Wireless push button
Model No.	:	WLTX-313-A*
FCC ID		2AQUQ313A
Test Standard(s)	:,	KDB447498 D01 General RF Exposure Guidance v06
Report No.	1	DDT-RE24012618-2E02
Issue Date	:	2024/03/06
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd.
Address of Laboratory		Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808



Table of Contents

	Test report declares	
1.	General Information	
1.1.	Description of equipment	!
1.2.	Assess laboratory	
2.	RF Exposure evaluation for FCC	(

Test Report Declare

Report No.: DDT-RE24012618-2E02

Applicant	:	Globe Electric Company Inc	
Address of Applicant	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8	
Equipment under Test	:	Wireless push button	
Model No.	:	WLTX-313-A*	
Manufacturer	:	Zhejiang Bernal Electric Co., Ltd.	
Address of Manufacturer	.0	No.188, Punan Fifth Road, Economic Development Zone, Yueqing, Zhejiang, China.	

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-RE24012618-2E02		× dr
Date of Receipt:	2024/01/26	Date of Test:	2024/01/26 ~ 2024/03/06
Pre	epared By:		Approved By:
To you	inson fliang		Damon Mu
Johnson	Huang/Fngineer		Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

TRF No.: RT-4-E-02-025 FCC RF Exposure Report 315 MHz Ver.1.1

Revision History

Report No.: DDT-RE24012618-2E02

Rev.	Revisions	Issue Date	Revised By
	Initial issue	2024/03/06	(6)

TRF No.: RT-4-E-02-025 FCC RF Exposure Report 315 MHz Ver.1.1

1. General Information

1.1. Description of equipment

EUT Name	:	Wireless push button
Model Number	:	WLTX-313-A*
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	DC 3V by electro-magnetic induction
Operation Frequency	:	315 MHz
Modulation	1	оок
Antenna Gain):	Spring antenna, maximum PK gain: 1 dBi

Report No.: DDT-RE24012618-2E02

1.2. Assess laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No.17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China 523808

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

TRF No.: RT-4-E-02-025 FCC RF Exposure Report 315 MHz Ver.1.1

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

Report No.: DDT-RE24012618-2E02

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Estimation Result

Worse case is as below: [315 MHz, -5.9 dBm, (0.2570 mW) output power]

PK Output Power=89.30dBuV/m@3m-95.2=-5.9dBm

Please refer to the test report "DDT-RE24012618-2E01"

 $(0.2570/5) \cdot [\sqrt{0.315}(GHz)] = 0.0288 < 3.0 \text{ for } 1-g \text{ SAR}$

Then SAR evaluation is not required.

END OF REPORT