FCC ID: 2AQUQGB24034

RF Exposure Evaluation

Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1-Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm²) | Averaging time (minutes) | | |
|---|-------------------------------------|-------------------------------|---------------------------|--------------------------|--|--|
| (A) Limits for Occupational/Controlled Exposures | | | | | | |
| 0.3–3.0 | 614 | 1.63 | 1.63 *(100) | | | |
| 3.0–30 | 1842/f | 4.89/f | 4.89/f *(900/f²) | | | |
| 30–300 | 61.4 | 0.163 1.0 | | 6 | | |
| 300–1500 | - | - | f/300 | 6 | | |
| 1500-100,000 | - | - | 5 | 6 | | |
| (B) Limits for General Population/Uncontrolled Exposure | | | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 | | |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 | | |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 | | |
| 300–1500 | - | - f/1500 | | 30 | | |
| 1500-100,000 | - | - | 1.0 | 30 | | |

Note: f = frequency in MHz

Evaluation Method

Transmission formula: $P_d = (Pout^*G)/(4^*pi^*R^2)$

Where

Pd = power density in mW/cm2, Pout = output power to antenna in mW, G = gain of antenna in linear scale;

Pi = 3.1416, R = distance between observation point and center of the radiator in cm

Conducted Power Results & Manufacturing tolerance

| Specification | Operating Mode | Conducted Peak Output Power (dBm) | Target (dBm) | Tolerance ±(dB) |
|---------------|----------------|-----------------------------------|--------------|-----------------|
| 2.4GWIFI | 802.11b | 19.51 | 19 | 1 |
| | 802.11g | 16.83 | 16 | 1 |
| | 802.11n(HT20) | 13.65 | 13 | 1 |
| | 802.11n(HT40) | 13.58 | 13 | 1 |
| BLE | GFSK | 5.14 | 5 | 1 |

Evaluation Results

| Spec. | Operating Mode | Antenna Distance (cm) | Conducted Output Power | | Gain of antenna in linear | Power Densit y (mW | Limit (mW | Result |
|----------|-------------------|-----------------------------|---------------------------|-------|---------------------------|--------------------------|--------------------|--------|
| | | | dBm | mW | scale | /cm ²) | /cm ²) | |
| 2.4GWIFI | 802.11b | 20 | 20 | 100 | 1.26 | 0.025 | 1 | PASS |
| | 802.11g | 20 | 17 | 56.23 | 1.26 | 0.013 | 1 | PASS |
| | 802.11n(HT20) | 20 | 14 | 25.12 | 1.26 | 0.006 | 1 | PASS |
| | 802.11n(HT40) | 20 | 14 | 25.12 | 1.26 | 0.006 | 1 | PASS |
| BLE | GFSK | 20 | 6 | 3.98 | 1.26 | 0.0010 | 1 | PASS |

Remark:

- 1. Output power including tune up tolerance;
- 2. The maximum 2.4G antenna gain is 1dBi
- 3. The exposure safety distance is 20cm.

Simulation Transmission

EUT can only work in 2.4GWIFI+BLE mode

The formula of calculated the Simulation Transmission MPE is:

CPD1/LPD1+CPD2/LPD2+.....etc.<1

CPD=Calculation Maximum Power Denisty

| Mode | Calculate | Limit | Result |
|-------------------|-----------|-------|--------|
| 2.4GWIFI+BLE mode | 0.026 | 1 | Pass |

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE complicance per KDB 447498 v06.