RF Exposure Evaluation

Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0	614	1.63	*(100)	6			
3.0–30	1842/f	4.89/f	*(900/f ²)	6			
30–300	61.4	0.163	1.0	6			
300-1500	-	-	f/300	6			
1500-100,000	-100,000		5	6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f ²)	30			
30–300	27.5	0.073	0.2	30			
300-1500	-	-	f/1500	30			
1500-100,000	_	-	1.0	30			

Note: f = frequency in MHz

Evaluation Method

Transmission formula: $P_d = (Pout*G)/(4*pi*R^2)$

Where

Pd = power density in mW/cm2, Pout = output power to antenna in mW, G = gain of antenna in linear scale; Pi = 3.1416, R = distance between observation point and center of the radiator in cm

Conducted Power Results & Manufacturing tolerance

Specification	Operating Mode	Conducted Peak Output Power (dBm)	Target (dBm)	Tolerance ±(dB)	
2.4GWIFI	802.11b	8.94	8	1	
	802.11g	14.93	14	1	
	802.11n(HT20)	14.36	13.5	1	
	802.11n(HT40)	14.02	13.5	1	
BLE	GFSK	2.36	1.5	1	

Evaluation Results

Spec.	Operating Mode	Antenna Distance (cm)	Conducted Output Power		Gain of antenna in linear	Power Density (mW	Limit (mW	Result
			dBm	mW	scale	/cm ²)	/cm ²)	
2.4GWIFI	802.11b	20	9	7.94	2.88	0.005	1	PASS
	802.11g	20	15	31.62	2.88	0.018	1	PASS
	802.11n(HT20)	20	14.5	28.18	2.88	0.016	1	PASS
	802.11n(HT40)	20	14.5	28.18	2.88	0.016	1	PASS
BLE	GFSK	20	2.5	4.47	2.88	0.003	1	PASS

Remark:

1. Output power including tune up tolerance;

2. The maximum 2.4G antenna gain is 4.6dBi

3. The exposure safety distance is 20cm.

Simulation Transmission

EUT can only work in 2.4GWIFI+BLE mode The formula of calculated the Simulation Transmission MPE is: CPD1/LPD1+CPD2/LPD2+.....etc.<1 CPD=Calculation Maximum Power Denisty

Mode	Calculate	Limit	Result
2.4GWIFI+BLE mode	0.021	1	Pass

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE complicance per KDB 447498 v06.