## **RF Exposure Evaluation**

## Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1 Limite for Merimum	Demuiseihle Europeanne (MDE)
Table 1-Linnis for Maximum	Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	strength Magnetic field strength $(A/m)$ Power density $(mW/cm^2)$		Averaging time (minutes)			
	(A) Limits for Occupational/Controlled Exposures						
0.3–3.0	614	1.63	*(100)	6			
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6			
30–300	61.4	0.163	1.0	6			
300-1500	-	-	f/300	6			
1500-100,000	-	-	5	6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	.19/f *(180/f <sup>2</sup> )				
30–300	27.5	0.073 0.2		30			
300-1500	-	-	f/1500	30			
1500-100,000	-	-	1.0	30			

Note: f = frequency in MHz

### **Evaluation Method**

Transmission formula:  $P_d = (Pout*G)/(4*pi*R^2)$ 

Where

Pd = power density in mW/cm2, Pout = output power to antenna in mW, G = gain of antenna in linear scale; Pi = 3.1416, R = distance between observation point and center of the radiator in cm

### **Conducted Power Results & Manufacturing tolerance**

Specification	Operating Mode	Conducted Peak Output Power (dBm)	Target (dBm)	Tolerance ±(dB)
	802.11b	17.06	16.5	1
2.4GWIFI	802.11g	17.14	16.5	1
	802.11n(HT20)	15.71	15	1
BLE	GFSK	7.23	7	1

### **Evaluation Results**

Spec.	Operating Mode	Antenna Distance (cm)	Conducted Output Power		Gain of antenna in linear	Power Density (mW	Limit (mW /cm <sup>2</sup> )	Result
			dBm	mW	scale	<b>/cm</b> <sup>2</sup> )	$/cm^2$ ) /cm)	
	802.11b	20	17.5	56.23	2.88	0.032	1	PASS
2.4GWIFI	802.11g	20	17.5	56.23	2.88	0.032	1	PASS
	802.11n(HT20)	20	16	39.81	2.88	0.023	1	PASS
BLE	GFSK	20	8	6.31	2.88	0.002	1	PASS

Remark:

1. Output power including tune up tolerance;

2. The maximum 2.4G antenna gain is 4.6dBi

3. The exposure safety distance is 20cm.

### Simulation Transmission

EUT can only work in 2.4GWIFI+BLE mode The formula of calculated the Simulation Transmission MPE is: CPD1/LPD1+CPD2/LPD2+.....etc. <1 CPD=Calculation Maximum Power Denisty

Mode	Calculate	Limit	Result
2.4GWIFI+BLE mode	0.034	1	Pass

# Conclusion

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE complicance per KDB 447498 v06.