# **RF Exposure Evaluation**

#### Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1-Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)		
(A) Limits for Occupational/Controlled Exposures						
0.3–3.0	614	1.63 *(100)		6		
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6		
30–300	61.4	0.163	1.0	6		
300–1500	-	-	f/300	6		
1500-100,000	-	-	5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3-1.34	614	1.63	*(100)	30		
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30		
30–300	27.5	0.073	0.2	30		
300–1500	-	-	f/1500	30		
1500-100,000	-	-	1.0	30		

Note: f = frequency in MHz

#### **Evaluation Method**

Transmission formula:  $P_d = (Pout^*G)/(4^*pi^*R^2)$ 

Where

Pd = power density in mW/cm2, Pout = output power to antenna in mW, G = gain of antenna in linear scale;

Pi = 3.1416, R = distance between observation point and center of the radiator in cm

# **Conducted Power Results**

**WIFI** 

Mode	Channel	Frequency (MHz)	Conducted Output Power (dBm)
802.11b	1	2412	12.65
	6	2437	11.84
	11	2462	8.90
802.11g	1	2412	12.04
	6	2437	11.56
	11	2462	11.85
802.11n(HT20)	1	2412	12.23
	6	2437	11.49
	11	2462	11.82

# FCC ID: 2AQUQGE50068

# Manufacturing tolerance

#### WIFI

802.11b					
Channel	Channel 1	Channel 6	Channel 11		
Target (dBm)	10.8	10.8	10.8		
Tolerance ±(dB)	2	2	2		
802.11g					
Channel	Channel 1	Channel 6	Channel 11		
Target (dBm)	11	11	11		
Tolerance ±(dB)	2	2	2		
802.11n20					
Channel	Channel 1	Channel 6	Channel 11		
Target (dBm)	11	11	11		
Tolerance ±(dB)	2	2	2		

#### **Evaluation Results**

# WIFI

	Antenna	EIRP		Power		
Band/Mode	Distance	dBm	W	Density	Limit (mW/cm <sup>2</sup> )	Result
	(cm)	UDIII	VV	(mW/cm <sup>2</sup> )		
802.11b	20	14.8	0.030	0.006	1.0	Pass
802.11g	20	15	0.032	0.006	1.0	Pass
802.11n20	20	15	0.032	0.006	1.0	Pass

#### Remark:

- 1. Output power including tune up tolerance;
- 2. The maximum antenna gain is 2dBi
- 3. The exposure safety distance is 20cm.
- 4. EIRP = Conducted Output Power + Antenna Gain + Tolerance

#### Conclusion

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE complicance per KDB 447498 v06.