

RF Exposure Evaluation

Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1-Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

Evaluation Method

Transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm², P_{out} = output power to antenna in mW, G = gain of antenna in linear scale;

P_i = 3.1416, R = distance between observation point and center of the radiator in cm

Conducted Power Results

WIFI

Mode	Channel	Frequency (MHz)	Conducted Peak Output Power (dBm)
802.11b	1	2412	9.69
	6	2437	9.87
	11	2462	9.9
802.11g	1	2412	10.71
	6	2437	10.32
	11	2462	9.86
802.11n(HT20)	1	2412	10.21
	6	2437	10.12
	11	2462	9.46
802.11n(HT40)	3	2422	9.26
	6	2437	8.21
	9	2452	8.79

Manufacturing tolerance**WIFI**

802.11b			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	9.0	9.0	9.0
Tolerance \pm (dB)	1	1	1
802.11g			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	10	10	10
Tolerance \pm (dB)	1	1	1
802.11n20			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	9.5	9.5	9.5
Tolerance \pm (dB)	1	1	1
802.11n40			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	8.5	8.5	8.5
Tolerance \pm (dB)	1	1	1

Evaluation Results**WIFI**

Band/Mode	Antenna Distance (cm)	Conducted Output Power		Gain of antenna in linear scale	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
		dBm	mW				
802.11b	20	10	10.00	2.00	0.004	1.0	Pass
802.11g	20	11	12.59	2.00	0.005	1.0	Pass
802.11n20	20	10.5	11.22	2.00	0.004	1.0	Pass
802.11n40	20	9.5	8.91	2.00	0.004	1.0	Pass

Remark:

1. Output power including tune up tolerance;
2. The maximum antenna gain is 3dBi
3. The exposure safety distance is 20cm.

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE compliance per KDB 447498 v06.