RF Exposure Evaluation

Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1-Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)		
(A) Limits for Occupational/Controlled Exposures						
0.3–3.0	614	1.63	*(100)	6		
3.0–30	1842/f	4.89/f	*(900/f ²)	6		
30–300	61.4	0.163	1.0	6		
300–1500	-	-	f/300	6		
1500-100,000	-	-	5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3–1.34	614	614 1.63		30		
1.34–30	824/f	2.19/f	*(180/f ²)	30		
30–300	27.5	0.073	0.2	30		
300–1500	-	-	f/1500	30		
1500-100,000	-	-	1.0	30		

Note: f = frequency in MHz

Evaluation Method

Transmission formula: $P_d = (Pout^*G)/(4^*pi^*R^2)$

Where

Pd = power density in mW/cm2, Pout = output power to antenna in mW, G = gain of antenna in linear scale;

Pi = 3.1416, R = distance between observation point and center of the radiator in cm

Conducted Power Results & Manufacturing tolerance

Specification	Operating Mode	Conducted Peak Output Power (dBm)	Target (dBm)	Tolerance ±(dB)	
2.4GWIFI	802.11b	16.32	15.5	1	
	802.11g	14.19	13.5	1	
	802.11n(HT20)	13.67	13	1	
	802.11n(HT40)	13.28	12.5	1	
BLE	GFSK	5.19	4.5	1	

Evaluation Results

Spec.	Operating Mode	Antenna Distance (cm)	Conducted Output Power		Gain of antenna in linear	Power Density (mW	Limit (mW /cm²)	Result
			dBm	mW	scale	/cm ²)	/CIII)	
2.4GWIFI	802.11b	20	16.5	44.67	1.70	0.015	1	PASS
	802.11g	20	14.5	28.18	1.70	0.010	1	PASS
	802.11n(HT20)	20	14	25.12	1.70	0.008	1	PASS
	802.11n(HT40)	20	13.5	22.39	1.70	0.008	1	PASS
BLE	GFSK	20	5.5	3.55	1.70	0.001	1	PASS

Remark:

- 1. Output power including tune up tolerance;
- 2. The maximum 2.4G antenna gain is 2.3dBi
- 3. The exposure safety distance is 20cm.

Simulation Transmission

EUT can only work in 2.4GWIFI+Ble mode

The formula of calculated the Simulation Transmission MPE is:

CPD1/LPD1+CPD2/LPD2+.....etc.<1

CPD=Calculation Maximum Power Denisty

Mode	Calculate	Limit	Result
2.4GWIFI+Ble mode	0.016	1	Pass

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE complicance per KDB 447498 v06.