

# TEST REPORT

Reference No..... : WTX20X04017157W  
FCC ID ..... : 2AQUQGE50274  
Applicant ..... : Globe Electric Company Inc.  
Address ..... : 150 Oneida, Montreal, Quebec, Canada, H9R 1A8  
Manufacturer ..... : NINGBO HOMEMATE PRODUCTS CO.,LTD  
Address ..... : FLOOR 18, HOMEMATE PLAZA,ZHENHAI ,NINGBO,CHINA  
Product Name ..... : Wifi Sensor  
Test Model ..... : 50274  
Standards ..... : FCC Part 15.247  
Date of Receipt sample .... : Apr.08, 2020  
Date of Test..... : Apr.28, 2020 to Jun.04, 2020  
Date of Issue ..... : Jun.04, 2020  
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308

Fax.: +86-755-33663309


Tested by:

Reviewed By:

Approved & Authorized By:



Jason Su / Project Engineer



Lion Cai / RF Manager



Silin Chen / Manager

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION</b> .....	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	6
1.3 TEST METHODOLOGY.....	6
1.4 TEST FACILITY.....	6
1.5 EUT SETUP AND TEST MODE.....	7
1.6 MEASUREMENT UNCERTAINTY.....	8
1.7 TEST EQUIPMENT LIST AND DETAILS.....	9
<b>2. SUMMARY OF TEST RESULTS</b> .....	<b>11</b>
<b>3. RF EXPOSURE</b> .....	<b>12</b>
3.1 STANDARD APPLICABLE.....	12
3.2 TEST RESULT.....	12
<b>4. ANTENNA REQUIREMENT</b> .....	<b>13</b>
4.1 STANDARD APPLICABLE.....	13
4.2 EVALUATION INFORMATION.....	13
<b>5. POWER SPECTRAL DENSITY</b> .....	<b>14</b>
5.1 STANDARD APPLICABLE.....	14
5.2 TEST SETUP BLOCK DIAGRAM.....	14
5.3 TEST PROCEDURE.....	14
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	14
<b>6. DTS BANDWIDTH</b> .....	<b>19</b>
6.1 STANDARD APPLICABLE.....	19
6.2 TEST SETUP BLOCK DIAGRAM.....	19
6.3 TEST PROCEDURE.....	19
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	19
<b>7. RF OUTPUT POWER</b> .....	<b>24</b>
7.1 STANDARD APPLICABLE.....	24
7.2 TEST SETUP BLOCK DIAGRAM.....	24
7.3 TEST PROCEDURE.....	24
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	24
<b>8. FIELD STRENGTH OF SPURIOUS EMISSIONS</b> .....	<b>29</b>
8.1 STANDARD APPLICABLE.....	29
8.2 TEST PROCEDURE.....	29
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	31
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	31
<b>9. OUT OF BAND EMISSIONS</b> .....	<b>39</b>
9.1 STANDARD APPLICABLE.....	39
9.2 TEST PROCEDURE.....	39
9.3 SUMMARY OF TEST RESULTS/PLOTS.....	40
<b>10. CONDUCTED EMISSIONS</b> .....	<b>56</b>
10.1 TEST PROCEDURE.....	56
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	56
10.3 TEST RECEIVER SETUP.....	56
10.4 SUMMARY OF TEST RESULTS/PLOTS.....	56

**Report version**

Version No.	Date of issue	Description
Rev.00	Jun.04, 2020	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Globe Electric Company Inc.  
 Address of applicant: 150 Oneida, Montreal, Quebec, Canada, H9R 1A8

Manufacturer: NINGBO HOMEMATE PRODUCTS CO.,LTD  
 Address of manufacturer: FLOOR 18, HOMEMATE PLAZA,ZHENHAI ,NINGBO,CHINA

General Description of EUT	
Product Name:	Wifi Sensor
Trade Name:	GLOBE
Model No.:	50274
Adding Model(s):	/
Rated Voltage:	DC 3.0V
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n-HT20
RF Output Power:	11.98dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 72.2Mbps
Quantity of Channels:	11 for 802.11b/g/n-HT20
Channel Separation:	5MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	2.5dBi

## ➤ Center Frequency of Each of Channel:

802.11b/g/n(HT20)	
Channel	Frequency (MHz)
01	2412
02	2417
03	2422
04	2427
05	2432
06	2437
07	2442
08	2447
09	2452
10	2457
11	2462

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.247**: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

**558074 D01 15.247 Meas Guidance v05r02**: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

**ANSI C63.10-2013**: American National Standard for Testing Unlicensed Wireless Devices.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### **Address of the test laboratory**

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### **FCC – Registration No.: 125990**

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd., has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

## 1.5 EUT Setup and Test Mode

Use “SecureCRT.exe” and follow the instructions given by the manufacturer, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. Test use the customer default power level, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

<b>Test Mode List</b>		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz

<b>Test Conditions</b>	
Temperature:	22~25 °C
Relative Humidity:	50~56 %.
ATM Pressure:	1019 mbar

<b>EUT Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

<b>Accessories Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

<b>Auxiliary Equipment List and Details</b>			
Description	Manufacturer	Model	Serial Number
/	/	/	/

**1.6 Measurement Uncertainty**

<b>Measurement uncertainty</b>		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$



**1.7 Test Equipment List and Details**

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2020-04-28	2021-04-27
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2020-04-28	2021-04-27
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2020-04-28	2021-04-27
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2020-04-28	2021-04-27
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2020-04-28	2021-04-27
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2020-04-28	2021-04-27
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2020-04-28	2021-04-27
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2020-04-28	2021-04-27
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2020-04-28	2021-04-27
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2020-03-17	2021-03-16
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2020-03-17	2021-03-16
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2020-03-17	2021-03-16
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2020-03-17	2021-03-16
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16

<b>Software List</b>			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing

## 2. SUMMARY OF TEST RESULTS

---

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§2.1091	RF Exposure	Compliant
§15.203;15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	N/A
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to §1.1307 and §2.1091, the fixed transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has a PCB antenna, fulfill the requirement of this section.


## 5. Power Spectral Density

---

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Setup Block Diagram



### 5.3 Test Procedure




According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

### 5.4 Summary of Test Results/Plots


<b>Test Mode</b>	<b>Test Channel MHz</b>	<b>Power Spectral Density dBm/3kHz</b>	<b>Limit dBm/3kHz</b>
802.11b_11Mbps	2412	-23.55	8
	2437	-23.57	8
	2462	-23.20	8
802.11g_54Mbps	2412	-26.96	8
	2437	-26.53	8
	2462	-26.39	8
802.11n-HT20_MCS7	2412	-26.36	8
	2437	-25.67	8
	2462	-25.53	8

Please refer to the following test plots:

<p>802.11b-Low</p>	 <p>Ref 0 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -23.55 dBm VBW 10 kHz SWT 3.4 s 2.41160000 GHz</p> <p>Offset 1 dB</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 26.MAY.2020 14:46:44</p>
<p>802.11b-Middle</p>	 <p>Ref 0 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -23.57 dBm VBW 10 kHz SWT 3.4 s 2.436280000 GHz</p> <p>Offset 1 dB</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 26.MAY.2020 14:47:44</p>
<p>802.11b-High</p>	 <p>Ref 0 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -23.20 dBm VBW 10 kHz SWT 3.4 s 2.461280000 GHz</p> <p>Offset 1 dB</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 26.MAY.2020 14:49:51</p>




802.11g-Low




Date: 26.MAY.2020 14:50:22

802.11g-Middle




Date: 26.MAY.2020 14:51:11

802.11g-High




Date: 26.MAY.2020 14:52:17

802.11n-HT20-Low




Date: 26.MAY.2020 14:53:11

802.11n-HT20-Middle



Date: 26.MAY.2020 14:53:36

802.11n-HT20-High



Date: 26.MAY.2020 14:54:00


## 6. DTS Bandwidth

---

### 6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Setup Block Diagram



### 6.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


### 6.4 Summary of Test Results/Plots

<b>Test Mode</b>	<b>Test Channel MHz</b>	<b>6 dB Bandwidth MHz</b>	<b>Limit kHz</b>
802.11b_11Mbps	2412	9.12	$\geq 500$
	2437	9.00	$\geq 500$
	2462	9.06	$\geq 500$
802.11g_54Mbps	2412	16.32	$\geq 500$
	2437	16.26	$\geq 500$
	2462	16.38	$\geq 500$
802.11n-HT20_MCS7	2412	16.86	$\geq 500$
	2437	16.98	$\geq 500$
	2462	16.80	$\geq 500$

Please refer to the following test plots:




802.11g-Low




Date: 26.MAY.2020 15:37:25

802.11g-Middle




Date: 26.MAY.2020 15:38:43

802.11g-High




Date: 26.MAY.2020 15:39:53

802.11n-HT20-Low




Date: 26.MAY.2020 15:41:10

802.11n-HT20-Middle



Date: 26.MAY.2020 15:42:25

802.11n-HT20-High



Date: 26.MAY.2020 15:43:43


## 7. RF Output Power

---

### 7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Setup Block Diagram



### 7.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times$  span / RBW. (This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98$  %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.


### 7.4 Summary of Test Results/Plots



<b>Test Mode</b>	<b>Frequency MHz</b>	<b>Reading dBm</b>	<b>Output Power mW</b>	<b>Limit mW</b>
802.11b_11Mbps	2412	10.75	11.89	1000
	2437	10.93	12.39	1000
	2462	11.18	13.12	1000
802.11g_54Mbps	2412	11.96	15.70	1000
	2437	11.77	15.03	1000
	2462	11.80	15.14	1000
802.11n HT20_MCS7	2412	11.67	14.69	1000
	2437	11.62	14.52	1000
	2462	11.98	15.78	1000


Please refer to the following test plots:

802.11b-Low  
11Mbps




Date: 26.MAY.2020 14:29:06

802.11b-Middle  
11Mbps




Date: 26.MAY.2020 14:32:47

802.11b-High  
11Mbps




Date: 26.MAY.2020 14:33:41

802.11g-Low  
54Mbps




Date: 26.MAY.2020 14:36:01

802.11g-Middle  
54Mbps




Date: 26.MAY.2020 14:37:08

802.11g-High  
54Mbps




Date: 26.MAY.2020 14:37:29

802.11n-HT20-Low  
MCS7




Date: 26.MAY.2020 14:40:22

802.11n-HT20-Middle  
MCS7



Date: 26.MAY.2020 14:40:47

802.11n-HT20-High  
MCS7



Date: 26.MAY.2020 14:44:13

## 8. Field Strength of Spurious Emissions

### 8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.


The test setup for emission measurement below 30MHz..



The test setup for emission measurement from 30 MHz to 1 GHz..



The test setup for emission measurement above 1 GHz..



Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz,	RBW=120KHz,	RBW=1MHz,
VBW =30KHz	VBW=360KHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

### 8.4 Summary of Test Results/Plots

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported. All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.*

➤ Spurious Emissions Below 1GHz


802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	43.5057	34.83	-14.00	20.83	40.00	-19.17	-	-	peak
2	60.0691	40.37	-15.16	25.21	40.00	-14.79	-	-	peak
3	359.1860	32.29	-7.72	24.57	46.00	-21.43	-	-	peak




802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	51.8430	34.24	-14.16	20.08	40.00	-19.92	-	-	peak
2	86.5029	36.82	-17.78	19.04	40.00	-20.96	-	-	peak
3	321.0608	32.37	-8.38	23.99	46.00	-22.01	-	-	peak

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	50.4089	33.67	-13.75	19.92	40.00	-20.08	-	-	peak
2	109.0286	33.52	-14.79	18.73	43.50	-24.77	-	-	peak
3	304.6100	31.96	-7.95	24.01	46.00	-21.99	-	-	peak

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	51.4807	34.36	-14.06	20.30	40.00	-19.70	-	-	peak
2	110.1816	33.41	-14.79	18.62	43.50	-24.88	-	-	peak
3	407.5145	31.64	-7.87	23.77	46.00	-22.23	-	-	peak

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	64.8865	34.50	-16.11	18.39	40.00	-21.61	-	-	peak
2	98.4866	33.96	-15.22	18.74	43.50	-24.76	-	-	peak
3	368.1116	32.12	-7.86	24.26	46.00	-21.74	-	-	peak

802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	52.5753	34.68	-14.37	20.31	40.00	-19.69	-	-	peak
2	103.0800	35.31	-14.88	20.43	43.50	-23.07	-	-	peak
3	299.3158	31.98	-7.87	24.11	46.00	-21.89	-	-	peak

Remark: '-Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

- Spurious Emissions Above 1GHz
- Test Mode: 802.11b\_11Mbps (worst case)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	60.14	-3.86	56.28	74	-17.72	H	PK
4824.000	41.51	-3.86	37.65	54	-16.35	H	AV
7236.000	53.24	1.1	54.34	74	-19.66	H	PK
7236.000	40.91	1.1	42.01	54	-11.99	H	AV
4824.000	58.76	-3.86	54.9	74	-19.1	V	PK
4824.000	41.94	-3.86	38.08	54	-15.92	V	AV
7236.000	54.65	1.1	55.75	74	-18.25	V	PK
7236.000	39.18	1.1	40.28	54	-13.72	V	AV
Middle Channel-2437MHz							
4874.000	62	-3.74	58.26	74	-15.74	H	PK
4874.000	42.7	-3.74	38.96	54	-15.04	H	AV
7311.000	54.93	1.47	56.4	74	-17.6	H	PK
7311.000	40.47	1.47	41.94	54	-12.06	H	AV
4874.000	61.19	-3.74	57.45	74	-16.55	V	PK
4874.000	43.35	-3.74	39.61	54	-14.39	V	AV
7311.000	53.75	1.47	55.22	74	-18.78	V	PK
7311.000	38.98	1.47	40.45	54	-13.55	V	AV
High Channel-2462MHz							
4924.000	60.09	-3.63	56.46	74	-17.54	H	PK
4924.000	43.08	-3.63	39.45	54	-14.55	H	AV
7386.000	53.4	1.62	55.02	74	-18.98	H	PK
7386.000	39	1.62	40.62	54	-13.38	H	AV
4924.000	61.76	-3.63	58.13	74	-15.87	V	PK
4924.000	41.66	-3.63	38.03	54	-15.97	V	AV
7386.000	52.65	1.62	54.27	74	-19.73	V	PK
7386.000	40.35	1.62	41.97	54	-12.03	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the emissions in restricted frequency bands test method as follows:

#### A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement

KDB publication number: 913591 may be used for the radiated bandedge measurements.

#### B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW  $\geq$   $[3 \times \text{RBW}]$ .
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

**Table 9—RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

### 9.3 Summary of Test Results/Plots




➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	39.60	-9.66	29.94	54.00	-24.06	Average Detector
	2310.000	51.82	-9.66	42.16	74.00	-31.84	Peak Detector
2	2390.000	47.46	-9.50	37.96	54.00	-16.04	Average Detector
	2390.000	56.66	-9.50	47.16	74.00	-26.84	Peak Detector
3	2400.000	67.11	-9.48	57.63	Delta=36.99dBc		Average Detector
4	2414.421	104.07	-9.45	94.62		Average Detector	

802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.073	106.30	-9.36	96.94	/	/	Average Detector
	2459.938	110.96	-9.35	101.61	/	/	Peak Detector
2	2483.500	47.51	-9.31	38.20	54.00	-15.80	Average Detector
	2483.500	56.95	-9.31	47.64	74.00	-26.36	Peak Detector
3	2500.000	39.23	-9.28	29.95	54.00	-24.05	Average Detector
	2500.000	51.12	-9.28	41.84	74.00	-32.16	Peak Detector

802.11g_54Mbps			
Test Channel	Low	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	39.66	-9.66	30.00	54.00	-24.00	Average Detector
	2310.000	51.54	-9.66	41.88	74.00	-32.12	Peak Detector
2	2390.000	55.18	-9.50	45.68	54.00	-8.32	Average Detector
	2390.000	73.92	-9.50	64.42	74.00	-9.58	Peak Detector
3	2400.000	67.96	-9.48	58.48	Delta= 30.73 dBc		Average Detector
4	2414.353	98.66	-9.45	89.21			Average Detector

802.11g_54Mbps			
Test Channel	High	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.466	94.28	-9.35	84.93	/	/	Average Detector
	2467.299	106.13	-9.35	96.78	/	/	Peak Detector
2	2483.500	52.58	-9.31	43.27	54.00	-10.73	Average Detector
	2483.500	72.73	-9.31	63.42	74.00	-10.58	Peak Detector
3	2500.000	39.01	-9.28	29.73	54.00	-24.27	Average Detector
	2500.000	51.53	-9.28	42.25	74.00	-31.75	Peak Detector

802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	39.95	-9.66	30.29	54.00	-23.71	Average Detector
	2310.000	53.15	-9.66	43.49	74.00	-30.51	Peak Detector
2	2390.000	50.39	-9.50	40.89	54.00	-13.11	Average Detector
	2390.000	69.85	-9.50	60.35	74.00	-13.65	Peak Detector
3	2400.000	62.26	-9.48	52.78	Delta= 32.87 dBc		Average Detector
4	2419.513	95.09	-9.44	85.65			Average Detector

802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2459.368	95.94	-9.36	86.58	/	/	Average Detector
	2457.622	108.30	-9.36	98.94	/	/	Peak Detector
2	2483.500	48.06	-9.31	38.75	54.00	-15.25	Average Detector
	2483.500	68.06	-9.31	58.75	74.00	-15.25	Peak Detector
3	2500.000	39.19	-9.28	29.91	54.00	-24.09	Average Detector
	2500.000	51.39	-9.28	42.11	74.00	-31.89	Peak Detector


➤ Conducted test

802.11b\_11Mbps

Low




Date: 28.MAY.2020 16:39:41




Date: 28.MAY.2020 16:39:59

802.11b\_11Mbps

Middle



Date: 28.MAY.2020 16:40:55




Date: 28.MAY.2020 16:41:15




802.11b\_11Mbps

High




Date: 28.MAY.2020 16:42:14




Date: 28.MAY.2020 16:42:29

802.11g\_54Mbps

Low




Date: 28.MAY.2020 16:44:49




Date: 28.MAY.2020 16:45:36

802.11g\_54Mbps

Middle




Date: 28.MAY.2020 16:46:14




Date: 28.MAY.2020 16:46:33

802.11g\_54Mbps

High




Date: 28.MAY.2020 16:47:10




Date: 28.MAY.2020 16:47:27

802.11n-HT20\_MCS7

Low




Date: 28.MAY.2020 16:49:30




Date: 28.MAY.2020 16:49:51

802.11n-HT20\_MCS7

Middle




Date: 28.MAY.2020 16:50:23




Date: 28.MAY.2020 16:50:39

802.11n-HT20\_MCS7

High



Date: 28.MAY.2020 16:51:18



Date: 28.MAY.2020 16:51:33


## 10. Conducted Emissions

### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram



### 10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency .....	150 kHz
Stop Frequency .....	30 MHz
Sweep Speed .....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth .....	9 kHz
Quasi-Peak Adapter Mode .....	Normal

### 10.4 Summary of Test Results/Plots

Not applicable

\*\*\*\*\* END OF REPORT \*\*\*\*\*