



RF EXPOSURE EVALUATION

Product Name	:	Remote Switch
Model Name	:	ZW922-V2, ZEN34
Operating frequency	:	908.40MHz 908.42MHz 916.00MHz 912 MHz 920 MHz
Numbers of Channel	:	5 channels
Antenna Type	:	PCB Antenna
Antenna Gain	:	-15.59 dBi
Type of Modulation	:	2FSK for 908.40MHz 2FSK for 908.42MHz 2GFSK for 916.00MHz DSSS OQPSK LR for 912 MHz and 920 MHz
Power supply	:	Battery: CR2032*2 Voltage: 6.0V
Hardware Version	:	1.0
Software Version	:	1.0



Standard Requirement

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission’s guidelines. See KDB 447498 D01 General RF Exposure Guidance v06, section 4. 3. 1.

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \times \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g SAR extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is < 5 mm, a distance of 5mm is applied to determine SAR test exclusion. Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to quality for TCB approval.

RF Output power

Freq. (MHz)	Field strength(max)(dBuV/m)	EIRP (max) (dBm)
908.40	90.04	-5.16
908.42	89.91	-5.29
916.00	89.87	-5.33

Note: 1. $EIRP = E - 104.8 + 20 \log D$,
Where
E is the electric field strength in dBuV/m.
EIRP is the equivalent isotropically radiated power in dBm.
d is the specified measurement distance in m. where $D=3$, $EIRP = E - 95.2$.
 $ERP = EIRP - 2.15$.



Channel (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Distance(mm)	Calculation results	Limit
912	0.338	0.5 ± 1	1.412538	5	0.269791	3
920	0.381	0.5 ± 1	1.412538	5	0.270972	3
908.40	-5.16	-5.00 ± 1	0.398107	5	0.075887	3
908.42	-5.29	-5.00 ± 1	0.398107	5	0.075888	3
916.00	-5.33	-5.00 ± 1	0.398107	5	0.076204	3

According to KDB 447498, no stand-alone required for SRD antenna, and no simultaneous SAR measurement is required.

Signature

A handwritten signature in black ink, appearing to read 'Ronnie Liu', written in a cursive style.

Ronnie Liu

EMC Manager

Date: 2023-08-17