

RF Exposure Evaluation Report

Product Name	WC Subsystem Qi. 1.3 Gen.4 1-Coil
Model No.	240000-01-11
FCC ID	2AQWT2400000111

Applicant	acv GmbH
Address	Strassburger Allee 10-12, Erkelenz 41812 Germany

Date of Receipt	Jul. 01, 2022
Date of Declaration	Oct. 06, 2022
Report No.	2270026R-RFUSMPEV01-A
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Issued Date: Oct. 06, 2022
 Report No.: 2270026R-RFUSMPEV01-A



Product Name	WC Subsystem Qi. 1.3 Gen.4 1-Coil	
Applicant	acv GmbH	
Address	Strassburger Allee 10-12, Erkelenz 41812 Germany	
Manufacturer	Santek Overseas Corp.	
Model No.	240000-01-11	
FCC ID	2AQWT2400000111	
EUT Rated Voltage	DC 12V by battery	
EUT Test Voltage	DC 12V by battery	
Trade Name	Inbay	
Applicable Standard	KDB 447498 D01 v06	<input checked="" type="checkbox"/> For Field Strength Test
Test Result	Complied	

Documented By : Joanne Lin
 (Senior Project Specialist / Joanne Lin)

Tested By : Bill Lin
 (Senior Engineer / Bill Lin)

Approved By : Jack Hsu
 (Senior Engineer / Jack Hsu)

Revision History

Report No.	Version	Description	Issued Date
2270026R-RFUSMPEV01-A	V1.0	Initial issue of report.	Oct. 06, 2022

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	WC Subsystem Qi. 1.3 Gen.4 1-Coil
Trade Name	Inbay
Model No.	240000-01-11
FCC ID	2AQWT2400000111
Frequency Range	127.75 kHz \pm 1.2 kHz
Type of antenna	Coil

Antenna List

No.	Manufacturer	Part No.	Antenna Type
1	RUIKAI	YB.B.TXT.018	Coil

2. Test Facility

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual
Radiated Emission	Temperature (°C)	10~40 °C	22.2 °C
	Humidity (%RH)	10~90 %	54.3 %

USA : FCC Registration Number: TW0033

Canada : CAB Identifier Number: TW3023 / Company Number: 26930

Site Description : Accredited by TAF
Accredited Number: 3023

Test Laboratory : DEKRA Testing and Certification Co., Ltd
Address : No. 5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan
Performed Location : No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan,
R.O.C.
Phone Number : +886-3-275-7255
Fax Number : +886-3-327-8031
Email Address : info.tw@dekra.com
Website : <http://www.dekra.com.tw>

3. RF Exposure Evaluation

3.1. Test Equipment

Equipment	Manufacturer	Model No. / Serial No.	Specification	Cal. Date
X EM Field Meter	Wavecontrol	SMP2 / 18SN0746	1 Hz - 60 GHz	2021.06.17
X Isotropic EM Field Probe	Wavecontrol	WP400-3 / 18WP120014	1 Hz - 400 kHz	2021.06.17
X Isotropic EM Field Probe	Wavecontrol	WP400 / 18WP100392	1 Hz - 400 kHz	2021.06.17
X Isotropic EM Field Probe	Wavecontrol	WPF8 / 18WP040835	100 kHz - 8 GHz	2021.06.17

Note: All equipments are calibrated every three year.

3.2. Uncertainty

Uncertainties have been calculated according to the DEKRA internal document.

The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test Item	Uncertainty
E-Field Emissions	± 1.31 dB
H-Field Emissions	± 1.30 dB

3.3. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/F	4.89/F	*(900/F ²)	6
30-300	61.4	0.163	1	6
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/F	2.19/F	*(180/F ²)	30
300-1500	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100,000	--	--	1	30

Note:

1. RF Exposure evaluation should be conducted assuming a separation distance of 10 cm
2. The EUT is including four models for different marketing requirement.

3.4. Test Procedure

The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils per the FCC 's request. (reference KDB 680106 D01 RF Exposure Wireless Charging Apps v03r01)

The temperature and related humidity: 18°C and 62% RH.

3.5. Test Result of RF Exposure Evaluation for WPT

Items to be covered	Answer from applicant
Power transfer frequency is less than 1 MHz.	Operation frequency range is 127.75kHz.
Output power from each primary coil is less than or equal to 15 watts.	Output Power equal to 15W.
The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	Yes, allow coupling only between individual pairs of coils.
Client device is placed directly in contact with the transmitter.	Yes, meet the requirements.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes, meet the requirements.
The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	<p>*Electric Field Strength (V/m) @15cm =1.110 V/m (< 307 V/m) MPE Limit (614 V/m) *50% =307 V/m</p> <p>*Magnetic Field Strength (A/m) @15cm =0.030 A/m (< 0.815 A/m) MPE Limit (1.63 A/m) *50%= 0.815 A/m</p>

Product : WC Subsystem Qi. 1.3 Gen.4 1-Coil
 Test Item : RF Exposure Evaluation
 Test Site : HY-CB03
 Test Date : 2022/07/29

E-Field Emissions

Test Position	Frequency (MHz)	Measurement Level @15cm (V/m)	Limit (V/m)	50% Limit (V/m)	Result
Side 1	0.12800	0.810	614.0	307.0	PASS
Side 2	0.12800	1.110	614.0	307.0	PASS
Side 3	0.12800	0.820	614.0	307.0	PASS
Side 4	0.12800	0.960	614.0	307.0	PASS

Test Position	Frequency (MHz)	Measurement Level @20cm (V/m)	Limit (V/m)	50% Limit (V/m)	Result
Top	0.12800	1.130	614.0	307.0	PASS
Bottom	0.12800	0.480	614.0	307.0	PASS

H-Field Emissions

Test Position	Frequency (MHz)	Measurement Level @15cm (A/m)	Limit (A/m)	50% Limit (A/m)	Result
Side 1	0.12800	0.030	1.63	0.815	PASS
Side 2	0.12800	0.020	1.63	0.815	PASS
Side 3	0.12800	0.020	1.63	0.815	PASS
Side 4	0.12800	0.020	1.63	0.815	PASS

Test Position	Frequency (MHz)	Measurement Level @20cm (A/m)	Limit (A/m)	50% Limit (A/m)	Result
Top	0.12800	0.040	1.63	0.815	PASS
Bottom	0.12800	0.030	1.63	0.815	PASS