

# **SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch**

Application No..: GZEM1807003791CR

Page: 1 of 2 FCC ID: 2AQWXSH-T6700A

### **RF Exposure Compliance Requirement**

#### 1. Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm²)	Averaging Times   E   <sup>2</sup> , H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm²)	Averaging Times   E   <sup>2</sup> , H   <sup>2</sup> or S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			F/1500	30	
1500-100000			1.0	30	

Note: f=frequency in MHz; \*Plane-wave equivalent power density



## SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

Application No..: GZEM1807003791CR

Page: 2 of 2 FCC ID: 2AQWXSH-T6700A

#### 2. MPE Calculation Method

E (V/m)=(30\*P\*G)0.5/d Power Density: Pd(W/m2)=E2/377

E=Electric Field (V/m)

P=Peak RF output Power (W)

G=EUT Antenna numeric gain (numeric)

d= Separation distance between radiator and human body (m)

The formula can be changed to

Pd = (30\*P\*G)/(377\*d2)

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

#### 3. Calculated Result and Limit

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm2)	Limit of Power Density (S) (mW/cm2)	Test Result
2402	1.000	-5.457	0.285	0.00006	1	Complies
2441	1.000	-5.701	0.269	0.00005	1	Complies
2480	1.000	-5.905	0.257	0.00005	1	Complies