

# RF Exposure Evaluation Statement

Model No.: BW-BS9, BW-BS10, BW-BS11, BW-BS12, BW-BS13, BW-BS14, BW-BS15, BW-BS16, BW-BS17, BW-BS18, BW-BS19, BW-BS20

Product Name: Bluetooth selfie stick

FCC ID: 2AQXL-BW-BS10

## 1.1 RF Exposure Compliance Requirement

### 1.1.1 Standard Requirement

According to KDB 447498 D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 1.1.3 EUT RF Exposure

Operational Mode: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
2402MHz	1.27	$\pm 1$	2.27	1.69	0.52	3.0
2441MHz	1.27	$\pm 1$	2.27	1.69	0.53	
2480MHz	0.66	$\pm 1$	1.66	1.47	0.46	
Conclusion: the calculated value $\leq 3.0$ , SAR is exempted.						