

# TEST REPORT

Report No.: BCTC2203999847E

Applicant: SUPERSONIC GATE AND DOOR AUTOMATION  
CO.,LIMITED

Product Name: Wireless Keypad

Model/Type Ref.: 878max

Tested Date: 2022-03-09 to 2022-03-26

Issued Date: 2022-03-26

Shenzhen **BCTC** Testing Co., Ltd.



# FCC ID: 2AQXW878MAX

Product Name: Wireless Keypad  
Trademark: N/A  
Model/Type Ref.: 878max  
Prepared For: SUPERSONIC GATE AND DOOR AUTOMATION CO.,LIMITED  
Address: no.28 tianshan road changzhou city jiangsu province china  
Manufacturer: SUPERSONIC GATE AND DOOR AUTOMATION CO.,LIMITED  
Address: no.28 tianshan road changzhou city jiangsu province china  
Prepared By: Shenzhen BCTC Testing Co., Ltd.  
Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China  
Sample Received Date: 2022-03-09  
Sample tested Date: 2022-03-09 to 2022-03-26  
Issue Date: 2022-03-26  
Report No.: BCTC2203999847E  
Test Standards: FCC Part15.231  
ANSI C63.10-2013  
Test Results: PASS

Tested by:



Jeff.Fu/Project Handler

Approved by:



Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

## Table Of Content

Test Report Declaration	Page
1. Version .....	4
2. Test Summary .....	5
3. Measurement Uncertainty .....	6
4. Product Information And Test Setup .....	7
4.1 Product Information .....	7
4.2 Test Setup Configuration .....	7
4.3 Support Equipment .....	7
4.4 Channel List .....	8
4.5 Test Mode .....	8
5. Test Facility And Test Instrument Used .....	9
5.1 Test Facility .....	9
5.2 Test Instrument Used .....	9
6. Conducted Emissions .....	11
6.1 Block Diagram Of Test Setup .....	11
6.2 Limit .....	11
6.3 Test Procedure .....	11
6.4 EUT Operating Conditions .....	12
6.5 Test Result .....	12
7. Radiated Emissions .....	13
7.1 Block Diagram Of Test Setup .....	13
7.2 Limit .....	14
7.3 Test Procedure .....	15
7.4 EUT Operating Conditions .....	16
7.5 Test Result .....	17
8. Bandwidth Test .....	27
8.1 Block Diagram Of Test Setup .....	27
8.2 Limit .....	27
8.3 Test Procedure .....	27
8.4 EUT Operating Conditions .....	27
8.5 Test Result .....	28
9. Calculation Of Average Factor .....	31
10. Dwell Time .....	37
10.1 Block Diagram Of Test Setup .....	37
10.2 Limit .....	37
10.3 Test Procedure .....	37
10.4 Test Result .....	38
11. Antenna Requirement .....	41
11.1 Standard Requirement .....	41
11.2 EUT Antenna .....	41
12. EUT Photographs .....	42
13. EUT Test Setup Photographs .....	43

(Note: N/A Means Not Applicable)

**1. Version**

Report No.	Issue Date	Description	Approved
BCTC2203999847E	2022-03-26	Original	Valid

## 2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No	Results
1	Conducted Emission	§15.207	N/A
2	Fundamental & Radiated Spurious Emission Measurement	15.209, 15.231b	PASS
3	Occupy Bandwidth	15.231c	PASS
4	Dwell time	15.231a	PASS
5	Antenna Requirement	15.203	PASS

### 3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission(150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	U=0.59°C


## 4. Product Information And Test Setup

### 4.1 Product Information

Model/Type Ref.:	878max
Model differences:	N/A
Hardware Version:	N/A
Software Version:	N/A
Operation Frequency:	310 MHz, 315 MHz, 390 MHz
Type of Modulation:	ASK
Number Of Channel	3CH
Antenna installation:	PCB antenna
Antenna Gain:	0dBi
Ratings:	DC 3V from battery

### 4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.  
Radiated Spurious Emission



### 4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Wireless Keypad	N/A	878max	N/A	EUT

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

#### 4.4 Channel List

CH	Frequency (MHz)
1	310
2	315
3	390


#### 4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Final Test Mode	Description
Mode 1	TX Mode

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Fully-charged battery is used during the test





## 5. Test Facility And Test Instrument Used

### 5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.  
FCC Test Firm Registration Number: 712850  
IC Registered No.: 23583


### 5.2 Test Instrument Used

RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power Metter	Keysight	E4419	\	May 28, 2021	May 27, 2022
Power Sensor (AV)	Keysight	E9300A	\	May 28, 2021	May 27, 2022
Signal Analyzer20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 28, 2021	May 27, 2022
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	\	May 28, 2021	May 27, 2022

Radiated Emissions Test (966 Chamber)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	Jun. 06. 2020	Jun. 05, 2023
Receiver	R&S	ESR3	102075	May 28, 2021	May 27, 2022
Receiver	R&S	ESRP	101154	May 28, 2021	May 27, 2022
Amplifier	SKET	LAPA_01G18 G-45dB	\	May 28, 2021	May 27, 2022
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 28, 2021	May 27, 2022
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	Jun. 01, 2021	May 31, 2022
Horn Antenna	Schwarzbeck	BBHA9120D	1541	Jun. 02, 2021	Jun. 01, 2022
Horn Antenn(18GHz -40GHz)	Schwarzbeck	BBHA9170	00822	Jun. 15, 2021	Jun. 14, 2022
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35- HG	2034381	May 28, 2021	May 27, 2022
Loop Antenna(9kHz -30MHz)	Schwarzbeck	FMZB1519B	00014	Jun. 02, 2021	Jun. 01, 2022
RF cables1(9kHz- 30MHz)	Huber+Suhnar	9kHz-30MHz	B1702988-000 8	May 28, 2021	May 27, 2022
RF cables2(30MH z-1GHz)	Huber+Suhnar	30MHz-1GHz	1486150	May 28, 2021	May 27, 2022
RF cables3(1GHz -40GHz)	Huber+Suhnar	1GHz-40GHz	1607106	May 28, 2021	May 27, 2022
Power Metter	Keysight	E4419	\	May 28, 2021	May 27, 2022
Power Sensor (AV)	Keysight	E9300A	\	May 28, 2021	May 27, 2022
Signal Analyzer20kH z-26.5GHz	Keysight	N9020A	MY49100060	May 28, 2021	May 27, 2022
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	\	May 28, 2021	May 27, 2022
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

## 6. Conducted Emissions

### 6.1 Block Diagram Of Test Setup



### 6.2 Limit

FREQUENCY (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:

- \*Decreasing linearly with logarithm of frequency.
- The lower limit shall apply at the transition frequencies.

### 6.3 Test Procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

## 6.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

## 6.5 Test Result


N/A




## 7. Radiated Emissions

### 7.1 Block Diagram Of Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



### (C) Radiated Emission Test-Up Frequency Above 1GHz



## 7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength uV/m	Distance (m)	Field Strength Limit at 3m Distance	
			uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

## LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

## Notes:

(1)The limit for radiated test was performed according to FCC PART 15C.

(2)The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

## FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

### 7.3 Test Procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Spectrum Parameter	Setting
1-6GHz	RBW 1 MHz /VBW 1 MHz for Peak, RBW 1 MHz / VBW 10Hz for Average

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
  - d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
  - e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
  - f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Above 1GHz test procedure as below:
- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre( Above 18GHz the distance is 1 meter and table is 1.5 metre).
  - h. Test the EUT in the lowest channel, the middle channel ,the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

Above 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

## 7.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



## 7.5 Test Result

Below 30MHz

Temperature:	26℃	Relative Humidity:	24%
Pressure:	101 kPa	Test Voltage :	DC 3V
Test Mode :	Mode 1	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

**Note:**


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

**310 MHz**  
Between 30MHz – 1GHz

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode1	Remark:	N/A



Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

2. Measurement=Reading Level+ Correct Factor

3. Over= Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		51.6615	28.38	-15.03	13.35	40.00	-26.65	QP
2		55.0274	28.91	-15.38	13.53	40.00	-26.47	QP
3		199.9856	28.71	-16.30	12.41	43.50	-31.09	QP
4		250.3011	28.74	-15.14	13.60	46.00	-32.40	QP
5	*	309.9977	74.32	-13.33	60.99	95.32	-34.33	peak
6		434.0650	31.49	-10.33	21.16	46.00	-24.84	QP
7		620.7096	31.02	-6.64	24.38	75.32	-50.94	peak
8		932.2714	34.15	-1.25	32.90	46.00	-13.10	QP

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode1	Remark:	N/A



Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

2. Measurement = Reading Level + Correct Factor

3. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		51.8430	32.67	-15.05	17.62	40.00	-22.38	QP
2		56.5929	32.20	-15.55	16.65	40.00	-23.35	QP
3	*	309.9977	64.00	-13.33	50.67	95.32	-44.65	peak
4		375.9384	28.29	-11.64	16.65	46.00	-29.35	QP
5		390.7225	28.35	-11.30	17.05	46.00	-28.95	QP
6		434.0649	38.30	-10.33	27.97	46.00	-18.03	QP
7		620.7096	32.76	-6.64	26.12	75.32	-49.20	peak
8		932.2714	33.82	-1.25	32.57	46.00	-13.43	QP

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
310	60.99	-3.56	57.43	75.32	-17.89	Horizontal
620	24.38	-3.56	20.82	55.32	-34.50	Horizontal

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
310	50.67	-3.56	47.11	75.32	-28.21	Vertical
620	26.12	-3.56	22.56	55.32	-32.76	Vertical

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.


#### Radiated Spurious Emission ( 1GHz to 10<sup>th</sup> harmonics)

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit		Margin dB		Polarization
				PK	AV	PK	AV	
1240.08	51.18	-3.56	47.62	75.32	55.32	-24.14	-7.70	Vertical
1550.12	52.36	-3.56	48.8	74.00	54.00	-21.64	-5.20	Vertical
1860.07	51.49	-3.56	47.93	75.32	55.32	-23.83	-7.39	Vertical
2170.11	52.27	-3.56	48.71	75.32	55.32	-23.05	-6.61	Vertical
2480.05	50.63	-3.56	47.07	75.32	55.32	-24.69	-8.25	Vertical
2790.21	47.91	-3.56	44.35	74.00	54.00	-26.09	-9.65	Vertical
1240.08	47.25	-3.56	43.69	75.32	55.32	-28.07	-11.63	Horizontal
1550.12	47.73	-3.56	44.17	74.00	54.00	-26.27	-9.83	Horizontal
1860.07	49.45	-3.56	45.89	75.32	55.32	-25.87	-9.43	Horizontal
2170.11	49.37	-3.56	45.81	75.32	55.32	-25.95	-9.51	Horizontal
2480.05	47.89	-3.56	44.33	75.32	55.32	-27.43	-10.99	Horizontal
2790.21	48.05	-3.56	44.49	74.00	54.00	-25.95	-9.51	Horizontal

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.  
3. Pulse Desensitization Correction Factor  
Pulse Width (PW) = 71.6ms  
RBW = 1 MHz  
PW(71.6 ms) > 1/RBW (1us)  
Therefore PDCF is not needed  
4. Other harmonics emissions are lower than 20dB below the allowable limit.

**315 MHz**  
Between 30MHz – 1GHz

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode1	Remark:	N/A



Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

2. Measurement=Reading Level+ Correct Factor

3. Over= Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		51.6615	28.38	-15.03	13.35	40.00	-26.65	QP
2		55.0274	28.91	-15.38	13.53	40.00	-26.47	QP
3		199.9856	28.71	-16.30	12.41	43.50	-31.09	QP
4		250.3011	28.74	-15.14	13.60	46.00	-32.40	QP
5	*	315.4806	74.01	-13.18	60.83	95.62	-34.79	peak
6		434.0650	31.49	-10.33	21.16	46.00	-24.84	QP
7		631.6884	29.12	-6.70	22.42	75.62	-53.20	peak
8		945.4398	30.41	-1.15	29.26	46.00	-16.74	QP

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode1	Remark:	N/A



Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

2. Measurement = Reading Level + Correct Factor

3. Over = Measurement - Limit

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
	MHz	dBuV	dB	dBuV/m	dB/m	dB	
1	51.8430	32.67	-15.05	17.62	40.00	-22.38	QP
2	56.5929	32.20	-15.55	16.65	40.00	-23.35	QP
3	81.7832	30.44	-20.00	10.44	40.00	-29.56	QP
4	135.5062	27.82	-18.57	9.25	43.50	-34.25	QP
5 *	315.4806	63.82	-13.18	50.64	95.62	-44.98	peak
6	434.0650	38.30	-10.33	27.97	46.00	-18.03	QP
7	631.6884	31.59	-6.70	24.89	75.62	-50.37	peak
8	945.4398	32.35	-1.15	31.20	46.00	-14.80	QP

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
315	60.83	-3.06	57.77	75.62	-17.85	Horizontal
630	22.42	-3.06	19.36	55.62	-36.26	Horizontal

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
315	50.64	-3.06	47.58	75.62	-28.04	Vertical
630	24.89	-3.06	21.83	55.62	-33.79	Vertical

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.

#### Radiated Spurious Emission ( 1GHz to 10<sup>th</sup> harmonics)


Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit		Margin dB		Polarization
				PK	AV	PK	AV	
1260.03	51.48	-3.06	48.42	75.62	55.62	-24.14	-7.20	Vertical
1575.06	52.76	-3.06	49.70	74.00	54.00	-21.24	-4.30	Vertical
1890.11	51.59	-3.06	48.53	75.62	55.62	-24.03	-7.09	Vertical
2205.13	52.21	-3.06	49.15	74.00	54.00	-21.79	-4.85	Vertical
2520.17	50.68	-3.06	47.62	75.62	55.62	-24.94	-8.00	Vertical
2835.09	47.93	-3.06	44.87	74.00	54.00	-26.07	-9.13	Vertical
1260.03	47.55	-3.06	44.49	75.62	55.62	-28.07	-11.13	Horizontal
1575.06	47.74	-3.06	44.68	74.00	54.00	-26.26	-9.32	Horizontal
1890.11	49.4	-3.06	46.34	75.62	55.62	-26.22	-9.28	Horizontal
2205.13	49.32	-3.06	46.26	74.00	54.00	-24.68	-7.74	Horizontal
2520.17	47.83	-3.06	44.77	75.62	55.62	-27.79	-10.85	Horizontal
2835.09	48.09	-3.06	45.03	74.00	54.00	-25.91	-8.97	Horizontal

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.  
3. Pulse Desensitization Correction Factor  
Pulse Width (PW) = 71.6ms  
RBW = 1 MHz  
PW(71.6 ms) > 1/RBW (1us)  
Therefore PDCF is not needed  
4. Other harmonics emissions are lower than 20dB below the allowable limit.



**390 MHz**  
Between 30MHz – 1GHz

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode1	Remark:	N/A



Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.


2. Measurement=Reading Level+ Correct Factor

3. Over= Measurement-Limit

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		51.6615	28.38	-15.03	13.35	40.00	-26.65	QP
2		55.0274	28.91	-15.38	13.53	40.00	-26.47	QP
3		199.9856	28.71	-16.30	12.41	43.50	-31.09	QP
4		250.3011	28.74	-15.14	13.60	46.00	-32.40	QP
5	*	390.7225	78.37	-11.30	67.07	99.24	-32.17	peak
6		434.0650	29.49	-10.33	19.16	46.00	-26.84	QP
7		620.7096	26.02	-6.64	19.38	46.00	-26.62	QP
8	!	782.3452	46.41	-3.89	42.52	79.24	-36.72	peak



Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode1	Remark:	N/A



Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over= Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		51.8430	32.67	-15.05	17.62	40.00	-22.38	QP
2		56.5929	32.20	-15.55	16.65	40.00	-23.35	QP
3		325.5957	27.51	-12.90	14.61	46.00	-31.39	QP
4		375.9384	28.29	-11.64	16.65	46.00	-29.35	QP
5	*	390.7225	65.85	-11.30	54.55	99.24	-44.69	peak
6		434.0650	38.30	-10.33	27.97	46.00	-18.03	QP
7		782.3452	37.98	-3.89	34.09	79.24	-45.15	peak
8		952.0937	24.13	-1.10	23.03	46.00	-22.97	QP

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
390	67.07	-1.32	65.75	79.24	-13.49	Horizontal
780	42.52	-1.32	41.20	59.24	-18.04	Horizontal

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
390	54.55	-1.32	53.23	79.24	-26.01	Vertical
780	34.09	-1.32	32.77	59.24	-26.47	Vertical

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.


#### Radiated Spurious Emission ( 1GHz to 10<sup>th</sup> harmonics)

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit		Margin dB		Polarization
				PK	AV	PK	AV	
1170.03	51.58	-1.32	50.26	74.00	54.00	-22.42	-3.74	Vertical
1560.12	52.71	-1.32	51.39	74.00	54.00	-21.29	-2.61	Vertical
2340.14	51.89	-1.32	50.57	74.00	54.00	-22.11	-3.43	Vertical
2730.07	52.24	-1.32	50.92	74.00	54.00	-21.76	-3.08	Vertical
3120.11	50.38	-1.32	49.06	79.24	59.24	-28.86	-10.18	Vertical
3510.08	47.95	-1.32	46.63	79.24	59.24	-31.29	-12.61	Vertical
1170.03	47.15	-1.32	45.83	74.00	54.00	-26.85	-8.17	Horizontal
1560.12	47.76	-1.32	46.44	74.00	54.00	-26.24	-7.56	Horizontal
2340.14	49.74	-1.32	48.42	74.00	54.00	-24.26	-5.58	Horizontal
2730.07	49.39	-1.32	48.07	74.00	54.00	-24.61	-5.93	Horizontal
3120.11	47.03	-1.32	45.71	79.24	59.24	-32.21	-13.53	Horizontal
3510.08	48.11	-1.32	46.79	79.24	59.24	-31.13	-12.45	Horizontal

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.  
3. Pulse Desensitization Correction Factor  
Pulse Width (PW) = 72ms  
RBW = 1 MHz  
PW(72 ms) > 1/RBW (1us)  
Therefore PDCF is not needed  
4. Other harmonics emissions are lower than 20dB below the allowable limit.

## 8. Bandwidth Test

### 8.1 Block Diagram Of Test Setup



### 8.2 Limit

According to FCC 15.231(c) requirement:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating between 70 MHz to 900 MHz. Those devices operating above 900 MHz, the emission spurious shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

B.W (20dBc) Limit = 0.25% \* f(MHz) = 0.25% \* 310MHz = 0.7750MHz

B.W (20dBc) Limit = 0.25% \* f(MHz) = 0.25% \* 315MHz = 0.7875MHz

B.W (20dBc) Limit = 0.25% \* f(MHz) = 0.25% \* 390MHz = 0.9750MHz

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	1kHz
VB	≥RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 8.3 Test Procedure

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 1kHz, VBW≥ RBW, Sweep time = Auto.

### 8.4 EUT Operating Conditions


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## 8.5 Test Result

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 3V
Test Mode :	Mode 1		


☐

Frequency	20dB Bandwidth (kHz)	Limit (MHz)	Result
310MHz	16.04	0.7750	PASS

☐
☐

☐


Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 3V
Test Mode :	Mode 1		

Frequency	20dB Bandwidth (kHz)	Limit (MHz)	Result
315MHz	15.52	0.7875	PASS



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 3V
Test Mode :	Mode 1		

Frequency	20dB Bandwidth (kHz)	Limit (MHz)	Result
390 MHz	14.94	0.9750	PASS



## 9. Calculation Of Average Factor

The output field strengths of specification in accordance with the FCC rules specify measurements with an average detector. During the test, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The duty cycle is measured in 100 ms or the repetition cycle period, whichever is a shorter time frame. The duty cycle is measured by placing the spectrum analyzer to set zero span at 100kHz resolution bandwidth.

Averaging factor in dB =  $20\log(\text{duty cycle})$

Averaging factor in dB =  $20\log(\text{duty cycle})$

### 310 MHz

The duration of one cycle = 71.6 ms

The duty cycle is simply the on-time divided the duration of one cycle

Duty Cycle =  $(0.265\text{ms} \times 30 + 0.55\text{ms} \times 72) / 71.6\text{ms}$


=  $47.55\text{ ms} / 71.6\text{ ms}$

= 0.664

Therefore, the averaging factor is found by  $20\log 0.664 = -3.56\text{ dB}$


Test plot as follows:

Note: During the 100ms, the amount of pulse and on-time of pulse are the same for every pulse train.






### Pulse



### On-time





### 315 MHz

The duration of one cycle = 71.6 ms

The duty cycle is simply the on-time divided the duration of one cycle

Duty Cycle =  $(0.265\text{ms} \times 26 + 0.55\text{ms} \times 79) / 71.6\text{ms}$


= 50.34ms / 71.6 ms

= 0.703


Therefore, the averaging factor is found by  $20\log 0.703 = -3.06\text{ dB}$

Test plot as follows:


Note: During the 100ms, the amount of pulse and on-time of pulse are the same for every pulse train.



### Pulse



### On-time



### 390MHz

The duration of one cycle =72 ms

The duty cycle is simply the on-time divided the duration of one cycle

Duty Cycle =  $(0.26\text{ms} \times 17 + 0.565 \times 97) / 72\text{ms}$


=61.825 ms/72 ms

=0.859


Therefore, the averaging factor is found by  $20\log 0.859 = -1.32 \text{ dB}$

Test plot as follows:


Note: During the 100ms, the amount of pulse and on-time of pulse are the same for every pulse train.



### Pulse



### On-time



## 10. Dwell Time

### 10.1 Block Diagram Of Test Setup



### 10.2 Limit

According to FCC 15.231(a) requirement:

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

### 10.3 Test Procedure


- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

## 10.4 Test Result

### 310 MHz

Dwell time (second)	Limit (second)	Result
400 ms	<5s	Pass


Test plot as follows:



**315 MHz**

Dwell time (second)	Limit (second)	Result
220 ms	<5s	Pass


Test plot as follows:



**390 MHz**

Dwell time (second)	Limit (second)	Result
320 ms	<5s	Pass

Test plot as follows:






## 11. Antenna Requirement

### 11.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


### 11.2 EUT Antenna

The EUT antenna is the PCB antenna, The antenna gain is 0dBi, It comply with the standard requirement.



## 12. EUT Photographs

EUT Photo 1





EUT Photo 2



### 13. EUT Test Setup Photographs

#### Radiated Measurement Photos





## STATEMENT

- 1.The equipment lists are traceable to the national reference standards.
- 2.The test report can not be partially copied unless prior written approval is issued from our lab.
- 3.The test report is invalid without stamp of laboratory.
- 4.The test report is invalid without signature of person(s) testing and authorizing.
- 5.The test process and test result is only related to the Unit Under Test.
- 6.The quality system of our laboratory is in accordance with ISO/IEC17025.
- 7.If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

E-Mail: [bctc@bctc-lab.com.cn](mailto:bctc@bctc-lab.com.cn)

\*\*\*\*\* END \*\*\*\*\*