

## Appendix B - DAE & Probe Calibration Certificate

**Calibration Laboratory of  
 Schmid & Partner  
 Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Auden**

Certificate No: **DAE4-914\_Dec18**

### CALIBRATION CERTIFICATE

Object: **DAE4 - SD 000 D04 BK - SN: 914**

Calibration procedure(s): **QA CAL-06.v29  
 Calibration procedure for the data acquisition electronics (DAE)**

Calibration date: **December 11, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	SN: 0810278	03-Sep-18 (No:23488)	Sep-19
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Auto DAE Calibration Unit	SE UWS 053 AA 1001	04-Jan-18 (in house check)	In house check: Jan-19
Calibrator Box V2.1	SE UMS 006 AA 1002	04-Jan-18 (in house check)	In house check: Jan-19

Calibrated by:	Name <b>Eric Heinfeld</b>	Function Laboratory Technician	Signature 
Approved by:	Name <b>Sven Kühn</b>	Deputy Manager	

Issued: December 11, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Calibration Laboratory of  
 Schmid & Partner  
 Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

### Glossary

**DAE** data acquisition electronics  
**Connector angle** information used in DASY system to align probe sensor X to the robot coordinate system.

### Methods Applied and Interpretation of Parameters

- **DC Voltage Measurement:** Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- **Connector angle:** The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
  - **DC Voltage Measurement Linearity:** Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
  - **Common mode sensitivity:** Influence of a positive or negative common mode voltage on the differential measurement.
  - **Channel separation:** Influence of a voltage on the neighbor channels not subject to an input voltage.
  - **AD Converter Values with inputs shorted:** Values on the internal AD converter corresponding to zero input voltage
  - **Input Offset Measurement:** Output voltage and statistical results over a large number of zero voltage measurements.
  - **Input Offset Current:** Typical value for information; Maximum channel input offset current, not considering the input resistance.
  - **Input resistance:** Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
  - **Low Battery Alarm Voltage:** Typical value for information. Below this voltage, a battery alarm signal is generated.
  - **Power consumption:** Typical value for information. Supply currents in various operating modes.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

### DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 $\mu$ V, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	405.118 $\pm$ 0.02% (k=2)	404.309 $\pm$ 0.02% (k=2)	403.887 $\pm$ 0.02% (k=2)
Low Range	3.99249 $\pm$ 1.50% (k=2)	3.98909 $\pm$ 1.50% (k=2)	3.99066 $\pm$ 1.50% (k=2)

### Connector Angle

Connector Angle to be used in DASY system	64.0 $^{\circ}$ $\pm$ 1 $^{\circ}$
---	------------------------------------

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Appendix (Additional assessments outside the scope of SCS0108)**
**1. DC Voltage Linearity**

High Range	Reading ( $\mu\text{V}$ )	Difference ( $\mu\text{V}$ )	Error (%)
Channel X + Input	199998.58	2.11	0.00
Channel X + Input	19998.57	-2.75	-0.01
Channel X - Input	-20000.73	1.25	-0.01
Channel Y + Input	199998.17	2.01	0.00
Channel Y + Input	19997.28	-3.97	-0.02
Channel Y - Input	-20001.99	-0.10	0.00
Channel Z + Input	199997.18	0.68	0.00
Channel Z + Input	19998.61	-2.66	-0.01
Channel Z - Input	-20002.03	-0.10	0.00

Low Range	Reading ( $\mu\text{V}$ )	Difference ( $\mu\text{V}$ )	Error (%)
Channel X + Input	2001.17	0.30	0.02
Channel X + Input	200.57	-0.58	-0.29
Channel X - Input	-199.13	-0.34	0.17
Channel Y + Input	2000.87	-0.05	-0.00
Channel Y + Input	200.49	-0.62	-0.31
Channel Y - Input	-199.14	-0.42	0.21
Channel Z + Input	2000.66	-0.18	-0.01
Channel Z + Input	200.17	-0.94	-0.47
Channel Z - Input	-200.12	-1.35	0.68

**2. Common mode sensitivity**

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading ( $\mu\text{V}$ )	Low Range Average Reading ( $\mu\text{V}$ )
Channel X	200	-12.83	-14.43
	-200	15.19	13.34
Channel Y	200	-5.26	-5.22
	-200	4.18	4.10
Channel Z	200	5.91	5.36
	-200	-7.27	-7.63

**3. Channel separation**

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X ( $\mu\text{V}$ )	Channel Y ( $\mu\text{V}$ )	Channel Z ( $\mu\text{V}$ )
Channel X	200	-	3.18	-4.63
Channel Y	200	7.77	-	2.34
Channel Z	200	9.02	5.71	-

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

#### 4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	16113	12727
Channel Y	16145	15429
Channel Z	16017	14873

#### 5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10M $\Omega$

	Average ( $\mu$ V)	min. Offset ( $\mu$ V)	max. Offset ( $\mu$ V)	Std. Deviation ( $\mu$ V)
Channel X	0.17	-0.89	1.03	0.39
Channel Y	1.31	-0.62	2.92	0.71
Channel Z	0.01	-1.10	1.53	0.60

#### 6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

#### 7. Input Resistance (Typical values for information)

	Zeroing (kOhm)	Measuring (MOhm)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

#### 8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)
Supply (+ Vcc)	+7.9
Supply (- Vcc)	-7.6

#### 9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-8	-9

**Calibration Laboratory of  
 Schmid & Partner  
 Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Auden**

Certificate No: **EX3-3801\_Jun18**

## CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3801**

Calibration procedure(s): **QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v4, QA CAL-23.v5,  
 QA CAL-25.v6  
 Calibration procedure for dosimetric E-field probes**

Calibration date: **June 26, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-18 (No. 217-02682)	Apr-19
Reference Probe ES3DV2	SN: 3013	30-Dec-17 (No. ES3-3013_Dec17)	Dec-18
DAE4	SN: 660	21-Dec-17 (No. DAE4-660_Dec17)	Dec-18
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293674	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by: **Claudio Leubler** (Name), **Laboratory Technician** (Function), [Signature]

Approved by: **Katja Pokovic** (Name), **Technical Manager** (Function), [Signature]

Issued: June 27, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization $\varphi$	$\varphi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Methods Applied and Interpretation of Parameters:**

- NORM<sub>x,y,z</sub>:** Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR:** PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle:** The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4 – SN:3801

June 26, 2018

# Probe EX3DV4

## SN:3801

Manufactured: April 5, 2011  
Calibrated: June 26, 2018

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



EX3DV4--SN:3801

June 26, 2018

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3801

### Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	0.53	0.57	0.52	$\pm 10.1\%$
DCP (mV) <sup>B</sup>	101.8	101.3	96.8	

### Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc <sup>E</sup> (k=2)
0	CW	X	0.0	0.0	1.0	0.00	166.4	$\pm 3.0\%$
		Y	0.0	0.0	1.0		173.4	
		Z	0.0	0.0	1.0		164.7	

Note: For details on UID parameters see Appendix.

### Sensor Model Parameters

	C1 fF	C2 fF	$\alpha$ V <sup>-1</sup>	T1 ms.V <sup>-2</sup>	T2 ms.V <sup>-1</sup>	T3 ms	T4 V <sup>-2</sup>	T5 V <sup>-1</sup>	T6
X	43.02	327.9	36.76	18.19	0.894	5.085	0.000	0.523	1.011
Y	48.75	365.0	35.77	24.10	0.825	5.100	0.855	0.468	1.008
Z	43.58	332.6	36.84	15.47	0.783	5.090	0.000	0.516	1.010

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X, Y, Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter; uncertainty not required.

<sup>E</sup> Uncertainty is determined using the  $\text{max. deviation}$  from linear response applying rectangular distribution and is expressed for the square of the field value.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3801

### Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>E</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth (mm) <sup>H</sup>	Unc (k=2)
150	52.3	0.76	11.05	11.05	11.05	0.00	1.00	± 13.3 %
450	43.5	0.87	9.90	9.90	9.90	0.15	1.30	± 13.3 %
750	41.9	0.89	9.50	9.50	9.50	0.43	0.96	± 12.0 %
835	41.5	0.90	9.08	9.08	9.08	0.51	0.85	± 12.0 %
900	41.5	0.97	8.95	8.95	8.95	0.51	0.87	± 12.0 %
1450	40.5	1.20	8.17	8.17	8.17	0.33	0.80	± 12.0 %
1750	40.1	1.37	8.10	8.10	8.10	0.39	0.84	± 12.0 %
1900	40.0	1.40	7.78	7.78	7.78	0.36	0.84	± 12.0 %
2100	39.8	1.49	7.90	7.90	7.90	0.35	0.80	± 12.0 %
2450	39.2	1.80	7.08	7.08	7.08	0.35	0.86	± 12.0 %
2600	39.0	1.96	6.94	6.94	6.94	0.40	0.86	± 12.0 %
3500	37.9	2.91	6.88	6.88	6.88	0.25	1.20	± 13.1 %
5200	36.0	4.66	4.93	4.93	4.93	0.40	1.80	± 13.1 %
5300	35.9	4.76	4.70	4.70	4.70	0.40	1.80	± 13.1 %
5500	35.6	4.96	4.82	4.82	4.82	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.69	4.69	4.69	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.61	4.61	4.61	0.40	1.80	± 13.1 %

<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>E</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3801

### Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth (mm) <sup>G</sup>	Unc (k=2)
150	61.9	0.80	10.74	10.74	10.74	0.00	1.00	± 13.3 %
450	56.7	0.94	10.16	10.16	10.16	0.09	1.25	± 13.3 %
750	55.5	0.96	9.19	9.19	9.19	0.49	0.83	± 12.0 %
835	55.2	0.97	9.04	9.04	9.04	0.53	0.80	± 12.0 %
900	55.0	1.05	9.01	9.01	9.01	0.44	0.89	± 12.0 %
1450	54.0	1.30	7.93	7.93	7.93	0.33	0.80	± 12.0 %
1750	53.4	1.49	7.68	7.68	7.68	0.49	0.82	± 12.0 %
1900	53.3	1.52	7.37	7.37	7.37	0.38	0.86	± 12.0 %
2100	53.2	1.62	7.79	7.79	7.79	0.42	0.80	± 12.0 %
2450	52.7	1.95	7.19	7.19	7.19	0.41	0.84	± 12.0 %
2600	52.5	2.16	7.01	7.01	7.01	0.30	0.99	± 12.0 %
3500	51.3	3.31	6.90	6.90	6.90	0.25	1.25	± 13.1 %
5200	49.0	5.30	4.23	4.23	4.23	0.50	1.90	± 13.1 %
5300	48.9	5.42	4.09	4.09	4.09	0.50	1.90	± 13.1 %
5500	48.6	5.65	3.94	3.94	3.94	0.50	1.90	± 13.1 %
5600	48.5	5.77	3.80	3.80	3.80	0.50	1.90	± 13.1 %
5800	48.2	6.00	3.95	3.95	3.95	0.50	1.90	± 13.1 %

<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\alpha$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\alpha$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

## Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$



Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

## Dynamic Range f(SAR<sub>head</sub>) (TEM cell , f<sub>eval</sub>= 1900 MHz)



Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801



June 26, 2018

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi$ ,  $\vartheta$ ), f = 900 MHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3801

### Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	126.3
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



EX3DV4- SN:3801

June 26, 2018

**Appendix: Modulation Calibration Parameters**

UID	Communication System Name		A dB	B dB/μV	C	D dB	VR mV	Max Unc <sup>E</sup> (k=2)
0	CW	X	0.00	0.00	1.00	0.00	166.4	± 3.0 %
		Y	0.00	0.00	1.00		173.4	
		Z	0.00	0.00	1.00		164.7	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	3.37	69.78	12.74	10.00	20.0	± 9.6 %
		Y	6.44	76.86	15.76		20.0	
		Z	3.21	69.39	12.43		20.0	
10011-CAB	UMTS-FDD (WCDMA)	X	0.83	64.38	12.95	0.00	150.0	± 9.6 %
		Y	0.99	67.13	14.98		150.0	
		Z	0.83	64.35	12.93		150.0	
10012-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	1.10	62.97	14.26	0.41	150.0	± 9.6 %
		Y	1.20	64.42	15.48		150.0	
		Z	1.09	62.83	14.21		150.0	
10013-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	4.80	66.58	16.95	1.46	150.0	± 9.6 %
		Y	4.93	66.87	17.23		150.0	
		Z	4.79	66.54	16.94		150.0	
10021-DAC	GSM-FDD (TDMA, GMSK)	X	100.00	116.48	28.92	9.39	50.0	± 9.6 %
		Y	100.00	116.87	29.39		50.0	
		Z	100.00	116.44	28.77		50.0	
10023-DAC	GPRS-FDD (TDMA, GMSK, TN 0)	X	100.00	116.20	28.84	9.57	50.0	± 9.6 %
		Y	100.00	116.71	29.35		50.0	
		Z	100.00	116.08	28.65		50.0	
10024-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	100.00	113.53	26.55	6.56	60.0	± 9.6 %
		Y	100.00	114.45	27.34		60.0	
		Z	100.00	114.34	26.74		60.0	
10025-DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	X	4.69	72.18	26.92	12.57	50.0	± 9.6 %
		Y	15.97	110.85	44.06		50.0	
		Z	4.44	71.01	26.44		50.0	
10026-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	X	11.01	95.24	33.64	9.56	60.0	± 9.6 %
		Y	27.30	117.67	41.25		60.0	
		Z	9.87	93.32	33.15		60.0	
10027-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	100.00	112.38	25.28	4.80	80.0	± 9.6 %
		Y	100.00	114.07	26.45		80.0	
		Z	100.00	113.67	25.65		80.0	
10028-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	100.00	111.82	24.34	3.55	100.0	± 9.6 %
		Y	100.00	114.73	26.07		100.0	
		Z	100.00	113.39	24.82		100.0	
10029-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	X	6.96	84.53	28.40	7.80	80.0	± 9.6 %
		Y	12.11	97.00	33.17		80.0	
		Z	6.28	82.79	27.89		80.0	
10030-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	X	100.00	111.17	25.02	5.30	70.0	± 9.6 %
		Y	100.00	112.86	26.19		70.0	
		Z	100.00	112.10	25.26		70.0	
10031-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	X	100.00	105.29	20.26	1.88	100.0	± 9.6 %
		Y	100.00	113.55	24.19		100.0	
		Z	100.00	105.78	20.26		100.0	

Certificate No: EX3-3801\_Jun18

Page 12 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	100.00	101.22	17.75	1.17	100.0	± 9.6 %	
		Y	100.00	116.20	24.29			100.0	
		Z	100.00	100.56	17.31			100.0	
10033-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	X	18.92	99.43	26.35	5.30	70.0	± 9.6 %	
		Y	100.00	126.11	33.82			70.0	
		Z	20.67	102.09	27.36			70.0	
10034-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	X	3.06	75.57	16.71	1.88	100.0	± 9.6 %	
		Y	9.98	92.25	23.17			100.0	
		Z	2.90	75.55	16.88			100.0	
10035-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	X	1.83	70.29	14.26	1.17	100.0	± 9.6 %	
		Y	4.00	80.96	19.27			100.0	
		Z	1.74	70.11	14.32			100.0	
10036-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	X	30.39	106.85	28.45	5.30	70.0	± 9.6 %	
		Y	100.00	126.44	33.98			70.0	
		Z	35.81	110.82	29.76			70.0	
10037-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	X	2.84	74.70	16.36	1.88	100.0	± 9.6 %	
		Y	8.90	90.73	22.69			100.0	
		Z	2.69	74.65	16.52			100.0	
10038-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	X	1.85	70.62	14.50	1.17	100.0	± 9.6 %	
		Y	4.14	81.72	19.65			100.0	
		Z	1.75	70.43	14.57			100.0	
10039-CAB	CDMA2000 (1xRTT, RC1)	X	1.12	65.78	11.74	0.00	150.0	± 9.6 %	
		Y	1.72	71.14	15.18			150.0	
		Z	1.13	65.83	11.81			150.0	
10042-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	X	100.00	111.21	25.70	7.78	50.0	± 9.6 %	
		Y	100.00	112.25	26.50			50.0	
		Z	100.00	111.42	25.65			50.0	
10044-CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	X	0.04	119.18	11.18	0.00	150.0	± 9.6 %	
		Y	0.01	110.75	9.59			150.0	
		Z	0.04	119.30	10.88			150.0	
10048-CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	X	100.00	116.95	30.57	13.80	25.0	± 9.6 %	
		Y	100.00	118.90	31.58			25.0	
		Z	100.00	115.50	29.86			25.0	
10049-CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	X	100.00	116.02	29.07	10.79	40.0	± 9.6 %	
		Y	100.00	116.75	29.64			40.0	
		Z	100.00	115.45	28.70			40.0	
10056-CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	X	26.45	101.81	27.79	9.03	50.0	± 9.6 %	
		Y	95.09	123.36	33.94			50.0	
		Z	35.26	107.00	29.30			50.0	
10058-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	X	5.27	78.98	25.36	6.55	100.0	± 9.6 %	
		Y	7.85	87.34	28.81			100.0	
		Z	4.82	77.53	24.91			100.0	
10059-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	X	1.16	64.21	14.95	0.61	110.0	± 9.6 %	
		Y	1.31	66.27	16.46			110.0	
		Z	1.14	63.97	14.87			110.0	
10060-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	X	8.60	97.03	24.51	1.30	110.0	± 9.6 %	
		Y	100.00	133.40	34.07			110.0	
		Z	7.00	95.42	24.31			110.0	

Certificate No: EX3-3801\_Jun18

Page 13 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10061-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	X	3.49	81.85	22.13	2.04	110.0	± 9.6 %
		Y	10.88	100.68	28.62		110.0	
		Z	3.06	80.49	21.85		110.0	
10062-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	X	4.56	66.41	16.26	0.49	100.0	± 9.6 %
		Y	4.69	66.72	16.55		100.0	
		Z	4.56	66.38	16.26		100.0	
10063-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	X	4.58	66.53	16.38	0.72	100.0	± 9.6 %
		Y	4.72	66.85	16.68		100.0	
		Z	4.58	66.50	16.38		100.0	
10064-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	X	4.86	66.80	16.63	0.86	100.0	± 9.6 %
		Y	5.01	67.14	16.92		100.0	
		Z	4.86	66.78	16.63		100.0	
10065-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	X	4.75	66.74	16.76	1.21	100.0	± 9.6 %
		Y	4.90	67.11	17.07		100.0	
		Z	4.75	66.71	16.76		100.0	
10066-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	X	4.77	66.80	16.95	1.46	100.0	± 9.6 %
		Y	4.93	67.18	17.28		100.0	
		Z	4.77	66.76	16.95		100.0	
10067-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	X	5.09	67.08	17.46	2.04	100.0	± 9.6 %
		Y	5.24	67.39	17.76		100.0	
		Z	5.08	67.03	17.46		100.0	
10068-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	X	5.14	67.13	17.70	2.55	100.0	± 9.6 %
		Y	5.32	67.54	18.04		100.0	
		Z	5.13	67.08	17.69		100.0	
10069-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	X	5.22	67.17	17.91	2.67	100.0	± 9.6 %
		Y	5.40	67.53	18.24		100.0	
		Z	5.22	67.11	17.90		100.0	
10071-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	X	4.91	66.72	17.29	1.99	100.0	± 9.6 %
		Y	5.04	67.03	17.58		100.0	
		Z	4.90	66.67	17.29		100.0	
10072-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	X	4.90	67.07	17.53	2.30	100.0	± 9.6 %
		Y	5.05	67.46	17.86		100.0	
		Z	4.89	67.01	17.52		100.0	
10073-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	X	4.99	67.32	17.91	2.83	100.0	± 9.6 %
		Y	5.14	67.73	18.26		100.0	
		Z	4.97	67.24	17.90		100.0	
10074-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	X	5.00	67.29	18.10	3.30	100.0	± 9.6 %
		Y	5.15	67.70	18.46		100.0	
		Z	4.97	67.19	18.08		100.0	
10075-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	X	5.05	67.46	18.45	3.82	90.0	± 9.6 %
		Y	5.22	67.96	18.86		90.0	
		Z	5.02	67.34	18.42		90.0	
10076-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	X	5.08	67.31	18.60	4.15	90.0	± 9.6 %
		Y	5.23	67.75	18.99		90.0	
		Z	5.05	67.18	18.57		90.0	
10077-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	X	5.11	67.39	18.71	4.30	90.0	± 9.6 %
		Y	5.26	67.83	19.09		90.0	
		Z	5.08	67.25	18.67		90.0	

Certificate No: EX3-3801\_Jun18

Page 14 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10081-CAB	CDMA2000 (1xRTT, RC3)	X	0.58	62.15	9.26	0.00	150.0	± 9.6 %
		Y	0.79	65.29	12.01		150.0	
		Z	0.59	62.18	9.31		150.0	
10082-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	X	0.89	60.00	5.00	4.77	80.0	± 9.6 %
		Y	1.06	60.10	5.42		80.0	
		Z	0.82	60.00	4.83		80.0	
10090-DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	X	100.00	113.61	26.61	6.56	60.0	± 9.6 %
		Y	100.00	114.52	27.40		60.0	
		Z	100.00	114.43	26.80		60.0	
10097-CAB	UMTS-FDD (HSDPA)	X	1.61	65.84	14.20	0.00	150.0	± 9.6 %
		Y	1.79	67.45	15.49		150.0	
		Z	1.61	65.80	14.19		150.0	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	1.57	65.77	14.15	0.00	150.0	± 9.6 %
		Y	1.75	67.41	15.45		150.0	
		Z	1.57	65.73	14.14		150.0	
10099-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	X	11.08	95.35	33.68	9.56	60.0	± 9.6 %
		Y	27.49	117.79	41.28		60.0	
		Z	9.94	93.45	33.20		60.0	
10100-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	2.79	68.48	15.57	0.00	150.0	± 9.6 %
		Y	3.10	70.20	16.56		150.0	
		Z	2.79	68.46	15.56		150.0	
10101-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	3.04	66.54	15.23	0.00	150.0	± 9.6 %
		Y	3.21	67.43	15.84		150.0	
		Z	3.04	66.53	15.23		150.0	
10102-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	3.15	66.58	15.37	0.00	150.0	± 9.6 %
		Y	3.32	67.39	15.93		150.0	
		Z	3.15	66.57	15.36		150.0	
10103-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.94	77.02	20.93	3.98	65.0	± 9.6 %
		Y	8.30	79.59	21.98		65.0	
		Z	6.60	76.51	20.82		65.0	
10104-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	6.60	74.37	20.62	3.98	65.0	± 9.6 %
		Y	7.74	76.89	21.76		65.0	
		Z	6.34	73.90	20.51		65.0	
10105-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	6.43	73.76	20.67	3.98	65.0	± 9.6 %
		Y	7.21	75.46	21.47		65.0	
		Z	6.12	73.09	20.46		65.0	
10108-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	2.42	67.75	15.36	0.00	150.0	± 9.6 %
		Y	2.70	69.42	16.38		150.0	
		Z	2.42	67.73	15.35		150.0	
10109-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	2.68	66.30	15.02	0.00	150.0	± 9.6 %
		Y	2.87	67.25	15.73		150.0	
		Z	2.69	66.28	15.02		150.0	
10110-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	1.93	66.75	14.78	0.00	150.0	± 9.6 %
		Y	2.19	68.51	15.97		150.0	
		Z	1.93	66.73	14.77		150.0	
10111-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	2.36	66.83	15.03	0.00	150.0	± 9.6 %
		Y	2.58	67.98	15.96		150.0	
		Z	2.36	66.80	15.03		150.0	

Certificate No: EX3-3801\_Jun18

Page 15 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10112-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	2.81	66.38	15.13	0.00	150.0	± 9.6 %
		Y	2.99	67.24	15.78		150.0	
		Z	2.82	66.36	15.13		150.0	
10113-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	2.51	67.07	15.23	0.00	150.0	± 9.6 %
		Y	2.73	68.12	16.09		150.0	
		Z	2.52	67.04	15.23		150.0	
10114-CAC	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	4.99	66.82	16.16	0.00	150.0	± 9.6 %
		Y	5.10	67.13	16.38		150.0	
		Z	5.00	66.82	16.16		150.0	
10115-CAC	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	X	5.25	66.91	16.21	0.00	150.0	± 9.6 %
		Y	5.40	67.27	16.46		150.0	
		Z	5.26	66.91	16.22		150.0	
10116-CAC	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	X	5.07	66.99	16.17	0.00	150.0	± 9.6 %
		Y	5.20	67.33	16.40		150.0	
		Z	5.08	66.99	16.17		150.0	
10117-CAC	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	4.96	66.69	16.10	0.00	150.0	± 9.6 %
		Y	5.07	67.00	16.33		150.0	
		Z	4.96	66.68	16.10		150.0	
10118-CAC	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	X	5.33	67.12	16.33	0.00	150.0	± 9.6 %
		Y	5.48	67.48	16.57		150.0	
		Z	5.34	67.12	16.33		150.0	
10119-CAC	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	X	5.06	66.96	16.16	0.00	150.0	± 9.6 %
		Y	5.17	67.27	16.38		150.0	
		Z	5.07	66.96	16.16		150.0	
10140-CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	3.18	66.58	15.28	0.00	150.0	± 9.6 %
		Y	3.35	67.40	15.85		150.0	
		Z	3.18	66.57	15.28		150.0	
10141-CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	3.31	66.74	15.49	0.00	150.0	± 9.6 %
		Y	3.48	67.49	16.02		150.0	
		Z	3.31	66.73	15.48		150.0	
10142-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	1.67	66.36	14.09	0.00	150.0	± 9.6 %
		Y	1.96	68.43	15.60		150.0	
		Z	1.68	66.34	14.10		150.0	
10143-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	2.13	66.92	14.26	0.00	150.0	± 9.6 %
		Y	2.43	68.64	15.63		150.0	
		Z	2.14	66.91	14.27		150.0	
10144-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	1.95	64.98	12.78	0.00	150.0	± 9.6 %
		Y	2.21	66.44	14.07		150.0	
		Z	1.96	64.98	12.81		150.0	
10145-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	0.89	61.84	8.95	0.00	150.0	± 9.6 %
		Y	1.18	64.72	11.53		150.0	
		Z	0.90	61.92	9.05		150.0	
10146-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	1.50	63.67	9.83	0.00	150.0	± 9.6 %
		Y	2.10	66.97	12.06		150.0	
		Z	1.48	63.51	9.75		150.0	
10147-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	1.66	64.83	10.55	0.00	150.0	± 9.6 %
		Y	2.53	69.23	13.24		150.0	
		Z	1.63	64.59	10.43		150.0	

Certificate No: EX3-3801\_Jun18

Page 16 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10149-CAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	2.69	66.35	15.07	0.00	150.0	± 9.6 %
		Y	2.88	67.31	15.77		150.0	
		Z	2.70	66.34	15.06		150.0	
10150-CAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	2.82	66.43	15.17	0.00	150.0	± 9.6 %
		Y	3.00	67.30	15.82		150.0	
		Z	2.82	66.41	15.17		150.0	
10151-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	7.29	79.43	21.93	3.98	65.0	± 9.6 %
		Y	9.32	83.12	23.40		65.0	
		Z	6.94	78.98	21.87		65.0	
10152-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	6.14	74.36	20.27	3.98	65.0	± 9.6 %
		Y	7.37	77.20	21.60		65.0	
		Z	5.87	73.88	20.17		65.0	
10153-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	6.57	75.50	21.13	3.98	65.0	± 9.6 %
		Y	7.80	78.18	22.37		65.0	
		Z	6.29	74.99	21.02		65.0	
10154-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	1.96	67.07	14.99	0.00	150.0	± 9.6 %
		Y	2.23	68.90	16.22		150.0	
		Z	1.97	67.05	14.99		150.0	
10155-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	2.36	66.85	15.05	0.00	150.0	± 9.6 %
		Y	2.58	68.00	15.98		150.0	
		Z	2.37	66.82	15.05		150.0	
10156-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	1.49	66.02	13.56	0.00	150.0	± 9.6 %
		Y	1.80	68.47	15.37		150.0	
		Z	1.50	66.01	13.58		150.0	
10157-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	1.74	65.03	12.45	0.00	150.0	± 9.6 %
		Y	2.04	66.94	14.07		150.0	
		Z	1.75	65.04	12.50		150.0	
10158-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	2.52	67.13	15.27	0.00	150.0	± 9.6 %
		Y	2.73	68.18	16.14		150.0	
		Z	2.52	67.10	15.27		150.0	
10159-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	1.82	65.36	12.68	0.00	150.0	± 9.6 %
		Y	2.15	67.39	14.35		150.0	
		Z	1.83	65.38	12.73		150.0	
10160-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	2.49	67.29	15.33	0.00	150.0	± 9.6 %
		Y	2.71	68.48	16.17		150.0	
		Z	2.50	67.27	15.32		150.0	
10161-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	2.71	66.34	15.05	0.00	150.0	± 9.6 %
		Y	2.90	67.23	15.75		150.0	
		Z	2.71	66.32	15.05		150.0	
10162-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	2.82	66.54	15.20	0.00	150.0	± 9.6 %
		Y	3.01	67.37	15.86		150.0	
		Z	2.82	66.52	15.19		150.0	
10166-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	3.40	69.00	18.89	3.01	150.0	± 9.6 %
		Y	3.70	70.05	19.33		150.0	
		Z	3.38	68.85	18.78		150.0	
10167-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	4.04	71.48	19.17	3.01	150.0	± 9.6 %
		Y	4.70	73.38	19.92		150.0	
		Z	4.01	71.26	19.04		150.0	

Certificate No: EX3-3801\_Jun18

Page 17 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10168-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	4.52	73.94	20.64	3.01	150.0	± 9.6 %
		Y	5.25	75.73	21.26		150.0	
		Z	4.48	73.68	20.49		150.0	
10169-CAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	2.77	67.75	18.34	3.01	150.0	± 9.6 %
		Y	3.18	70.11	19.36		150.0	
		Z	2.75	67.60	18.22		150.0	
10170-CAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	3.59	72.80	20.42	3.01	150.0	± 9.6 %
		Y	4.67	76.93	21.92		150.0	
		Z	3.54	72.56	20.26		150.0	
10171-AAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	2.99	69.00	17.71	3.01	150.0	± 9.6 %
		Y	3.76	72.40	19.07		150.0	
		Z	2.96	68.80	17.56		150.0	
10172-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	9.91	94.44	29.85	6.02	65.0	± 9.6 %
		Y	26.96	112.91	35.22		65.0	
		Z	8.39	91.68	29.04		65.0	
10173-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	17.47	101.05	30.02	6.02	65.0	± 9.6 %
		Y	73.48	124.50	35.94		65.0	
		Z	15.60	99.60	29.69		65.0	
10174-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	14.33	96.21	27.96	6.02	65.0	± 9.6 %
		Y	38.46	111.23	31.91		65.0	
		Z	12.63	94.55	27.54		65.0	
10175-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	2.74	67.47	18.09	3.01	150.0	± 9.6 %
		Y	3.14	69.79	19.11		150.0	
		Z	2.72	67.32	17.97		150.0	
10176-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	3.59	72.83	20.43	3.01	150.0	± 9.6 %
		Y	4.68	76.96	21.93		150.0	
		Z	3.55	72.58	20.27		150.0	
10177-CAG	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	2.76	67.60	18.18	3.01	150.0	± 9.6 %
		Y	3.17	69.94	19.20		150.0	
		Z	2.74	67.46	18.06		150.0	
10178-CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	3.56	72.65	20.32	3.01	150.0	± 9.6 %
		Y	4.63	76.72	21.81		150.0	
		Z	3.52	72.40	20.17		150.0	
10179-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	3.26	70.78	18.93	3.01	150.0	± 9.6 %
		Y	4.17	74.53	20.35		150.0	
		Z	3.22	70.55	18.78		150.0	
10180-CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	2.99	68.95	17.67	3.01	150.0	± 9.6 %
		Y	3.75	72.33	19.02		150.0	
		Z	2.95	68.75	17.52		150.0	
10181-CAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	2.75	67.59	18.17	3.01	150.0	± 9.6 %
		Y	3.17	69.93	19.20		150.0	
		Z	2.73	67.44	18.06		150.0	
10182-CAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	3.56	72.62	20.31	3.01	150.0	± 9.6 %
		Y	4.62	76.70	21.80		150.0	
		Z	3.51	72.38	20.16		150.0	
10183-AAC	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	2.98	68.93	17.66	3.01	150.0	± 9.6 %
		Y	3.74	72.31	19.01		150.0	
		Z	2.95	68.73	17.51		150.0	

Certificate No: EX3-3801\_Jun18

Page 18 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4-SN:3801

June 26, 2018

10184-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	2.76	67.63	18.19	3.01	150.0	± 9.6 %
		Y	3.18	69.97	19.22		150.0	
		Z	2.74	67.48	18.08		150.0	
10185-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	3.58	72.69	20.35	3.01	150.0	± 9.6 %
		Y	4.64	76.77	21.83		150.0	
		Z	3.53	72.45	20.19		150.0	
10186-AAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	3.00	68.99	17.69	3.01	150.0	± 9.6 %
		Y	3.76	72.38	19.04		150.0	
		Z	2.96	68.79	17.54		150.0	
10187-CAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	2.77	67.68	18.26	3.01	150.0	± 9.6 %
		Y	3.19	70.03	19.28		150.0	
		Z	2.75	67.54	18.15		150.0	
10188-CAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	3.68	73.28	20.71	3.01	150.0	± 9.6 %
		Y	4.80	77.49	22.22		150.0	
		Z	3.63	73.04	20.56		150.0	
10189-AAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	3.05	69.36	17.95	3.01	150.0	± 9.6 %
		Y	3.85	72.83	19.33		150.0	
		Z	3.02	69.15	17.80		150.0	
10193-CAC	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	4.37	66.23	15.79	0.00	150.0	± 9.6 %
		Y	4.50	66.54	16.08		150.0	
		Z	4.38	66.22	15.79		150.0	
10194-CAC	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	X	4.53	66.52	15.92	0.00	150.0	± 9.6 %
		Y	4.67	66.86	16.20		150.0	
		Z	4.54	66.50	15.92		150.0	
10195-CAC	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	X	4.57	66.55	15.95	0.00	150.0	± 9.6 %
		Y	4.71	66.89	16.22		150.0	
		Z	4.58	66.54	15.94		150.0	
10196-CAC	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	4.37	66.26	15.80	0.00	150.0	± 9.6 %
		Y	4.50	66.60	16.10		150.0	
		Z	4.38	66.25	15.80		150.0	
10197-CAC	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	X	4.54	66.53	15.94	0.00	150.0	± 9.6 %
		Y	4.68	66.88	16.22		150.0	
		Z	4.55	66.52	15.93		150.0	
10198-CAC	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	X	4.57	66.56	15.96	0.00	150.0	± 9.6 %
		Y	4.71	66.90	16.23		150.0	
		Z	4.58	66.55	15.95		150.0	
10219-CAC	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	4.32	66.27	15.75	0.00	150.0	± 9.6 %
		Y	4.45	66.61	16.06		150.0	
		Z	4.32	66.26	15.75		150.0	
10220-CAC	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	X	4.54	66.50	15.92	0.00	150.0	± 9.6 %
		Y	4.68	66.85	16.21		150.0	
		Z	4.54	66.49	15.92		150.0	
10221-CAC	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	X	4.58	66.50	15.95	0.00	150.0	± 9.6 %
		Y	4.72	66.83	16.22		150.0	
		Z	4.59	66.49	15.94		150.0	
10222-CAC	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	4.93	66.68	16.09	0.00	150.0	± 9.6 %
		Y	5.04	67.01	16.33		150.0	
		Z	4.94	66.67	16.09		150.0	

Certificate No: EX3-3801\_Jun18

Page 19 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



EX3DV4- SN:3801

June 26, 2018

10223-CAC	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	X	5.24	66.96	16.26	0.00	150.0	± 9.6 %
		Y	5.34	67.20	16.45		150.0	
		Z	5.25	66.96	16.26		150.0	
10224-CAC	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	X	4.97	66.79	16.07	0.00	150.0	± 9.6 %
		Y	5.09	67.12	16.31		150.0	
		Z	4.98	66.78	16.07		150.0	
10225-CAB	UMTS-FDD (HSPA+)	X	2.61	65.30	14.50	0.00	150.0	± 9.6 %
		Y	2.77	66.01	15.22		150.0	
		Z	2.62	65.28	14.51		150.0	
10226-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	19.06	102.80	30.64	6.02	65.0	± 9.6 %
		Y	84.74	127.31	36.73		65.0	
		Z	16.97	101.30	30.30		65.0	
10227-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	18.47	100.66	29.36	6.02	65.0	± 9.6 %
		Y	61.00	119.15	34.00		65.0	
		Z	16.71	99.46	29.10		65.0	
10228-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	11.22	97.35	30.90	6.02	65.0	± 9.6 %
		Y	42.26	122.26	37.83		65.0	
		Z	9.70	95.02	30.26		65.0	
10229-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	17.60	101.16	30.06	6.02	65.0	± 9.6 %
		Y	73.82	124.58	35.96		65.0	
		Z	15.72	99.72	29.73		65.0	
10230-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	16.98	99.07	28.81	6.02	65.0	± 9.6 %
		Y	54.30	116.97	33.37		65.0	
		Z	15.38	97.90	28.55		65.0	
10231-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	10.61	96.11	30.42	6.02	65.0	± 9.6 %
		Y	38.34	120.13	37.18		65.0	
		Z	9.21	93.87	29.80		65.0	
10232-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	17.57	101.15	30.06	6.02	65.0	± 9.6 %
		Y	73.88	124.60	35.97		65.0	
		Z	15.69	99.70	29.73		65.0	
10233-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	16.93	99.04	28.80	6.02	65.0	± 9.6 %
		Y	54.26	116.98	33.37		65.0	
		Z	15.34	97.87	28.54		65.0	
10234-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	10.13	95.03	29.94	6.02	65.0	± 9.6 %
		Y	35.09	118.08	36.51		65.0	
		Z	8.83	92.87	29.34		65.0	
10235-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	17.61	101.20	30.07	6.02	65.0	± 9.6 %
		Y	74.39	124.74	36.01		65.0	
		Z	15.72	99.75	29.75		65.0	
10236-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	17.15	99.23	28.85	6.02	65.0	± 9.6 %
		Y	55.30	117.26	33.44		65.0	
		Z	15.54	98.06	28.59		65.0	
10237-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	10.63	96.19	30.45	6.02	65.0	± 9.6 %
		Y	38.84	120.43	37.26		65.0	
		Z	9.22	93.94	29.82		65.0	
10238-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	17.54	101.13	30.05	6.02	65.0	± 9.6 %
		Y	73.93	124.62	35.97		65.0	
		Z	15.66	99.68	29.72		65.0	

Certificate No: EX3-3801\_Jun18

Page 20 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4-SN:3801

June 26, 2018

10239-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	16.87	99.00	28.79	6.02	65.0	± 9.6 %
		Y	54.20	116.98	33.38		65.0	
		Z	15.28	97.83	28.53		65.0	
10240-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	10.60	96.15	30.43	6.02	65.0	± 9.6 %
		Y	38.66	120.35	37.24		65.0	
		Z	9.20	93.89	29.81		65.0	
10241-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	8.68	82.76	26.12	6.98	65.0	± 9.6 %
		Y	11.24	87.33	27.87		65.0	
		Z	8.20	81.79	25.80		65.0	
10242-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	8.24	81.67	25.60	6.98	65.0	± 9.6 %
		Y	9.94	84.69	26.78		65.0	
		Z	7.73	80.54	25.21		65.0	
10243-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	6.66	78.27	25.11	6.98	65.0	± 9.6 %
		Y	7.69	80.76	26.19		65.0	
		Z	6.24	77.03	24.63		65.0	
10244-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	6.51	76.73	18.61	3.98	65.0	± 9.6 %
		Y	8.90	80.96	20.59		65.0	
		Z	6.20	76.45	18.60		65.0	
10245-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	6.23	75.82	18.19	3.98	65.0	± 9.6 %
		Y	8.52	80.01	20.18		65.0	
		Z	5.95	75.55	18.18		65.0	
10246-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	5.89	78.26	19.20	3.98	65.0	± 9.6 %
		Y	10.33	86.66	22.77		65.0	
		Z	5.69	78.38	19.42		65.0	
10247-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	5.27	73.98	18.20	3.98	65.0	± 9.6 %
		Y	6.98	78.14	20.37		65.0	
		Z	5.06	73.79	18.26		65.0	
10248-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	5.20	73.29	17.89	3.98	65.0	± 9.6 %
		Y	6.82	77.27	20.01		65.0	
		Z	5.00	73.09	17.94		65.0	
10249-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	7.64	82.87	21.98	3.98	65.0	± 9.6 %
		Y	12.50	90.52	24.99		65.0	
		Z	7.27	82.69	22.09		65.0	
10250-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	6.39	77.19	21.35	3.98	65.0	± 9.6 %
		Y	7.97	80.62	22.94		65.0	
		Z	6.07	76.69	21.28		65.0	
10251-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	5.95	74.70	19.94	3.98	65.0	± 9.6 %
		Y	7.31	77.83	21.49		65.0	
		Z	5.69	74.26	19.87		65.0	
10252-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	7.81	82.79	23.08	3.98	65.0	± 9.6 %
		Y	11.09	88.26	25.20		65.0	
		Z	7.35	82.26	23.04		65.0	
10253-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	6.02	73.87	20.02	3.98	65.0	± 9.6 %
		Y	7.15	76.53	21.33		65.0	
		Z	5.76	73.39	19.91		65.0	
10254-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	6.41	74.89	20.77	3.98	65.0	± 9.6 %
		Y	7.57	77.46	22.02		65.0	
		Z	6.13	74.39	20.66		65.0	

Certificate No: EX3-3801\_Jun18

Page 21 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10255-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.95	78.78	21.87	3.98	65.0	± 9.6 %
		Y	8.80	82.37	23.35		65.0	
		Z	6.59	78.27	21.78		65.0	
10256-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	4.69	71.51	15.31	3.98	65.0	± 9.6 %
		Y	6.81	76.30	17.77		65.0	
		Z	4.50	71.34	15.32		65.0	
10257-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	4.47	70.51	14.76	3.98	65.0	± 9.6 %
		Y	6.44	75.12	17.21		65.0	
		Z	4.29	70.34	14.77		65.0	
10258-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	4.06	72.26	15.82	3.98	65.0	± 9.6 %
		Y	7.18	80.25	19.65		65.0	
		Z	3.95	72.43	16.05		65.0	
10259-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	5.72	75.25	19.37	3.98	65.0	± 9.6 %
		Y	7.37	79.06	21.29		65.0	
		Z	5.47	74.94	19.38		65.0	
10260-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	5.72	74.91	19.23	3.98	65.0	± 9.6 %
		Y	7.31	78.59	21.12		65.0	
		Z	5.48	74.60	19.24		65.0	
10261-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	7.27	81.87	22.09	3.98	65.0	± 9.6 %
		Y	10.93	88.24	24.66		65.0	
		Z	6.86	81.50	22.12		65.0	
10262-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	6.37	77.12	21.30	3.98	65.0	± 9.6 %
		Y	7.95	80.56	22.90		65.0	
		Z	6.05	76.62	21.23		65.0	
10263-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	5.94	74.67	19.93	3.98	65.0	± 9.6 %
		Y	7.30	77.80	21.49		65.0	
		Z	5.68	74.24	19.86		65.0	
10264-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	7.72	82.55	22.97	3.98	65.0	± 9.6 %
		Y	10.95	88.00	25.09		65.0	
		Z	7.26	82.02	22.93		65.0	
10265-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	6.14	74.37	20.28	3.98	65.0	± 9.6 %
		Y	7.36	77.20	21.61		65.0	
		Z	5.87	73.89	20.17		65.0	
10266-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	6.57	75.48	21.12	3.98	65.0	± 9.6 %
		Y	7.80	78.16	22.36		65.0	
		Z	6.28	74.97	21.00		65.0	
10267-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	7.27	79.38	21.91	3.98	65.0	± 9.6 %
		Y	9.30	83.06	23.38		65.0	
		Z	6.92	78.93	21.85		65.0	
10268-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	6.75	74.24	20.68	3.98	65.0	± 9.6 %
		Y	7.82	76.54	21.74		65.0	
		Z	6.49	73.77	20.56		65.0	
10269-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	6.72	73.83	20.55	3.98	65.0	± 9.6 %
		Y	7.73	76.02	21.58		65.0	
		Z	6.46	73.36	20.43		65.0	
10270-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	6.94	76.39	20.90	3.98	65.0	± 9.6 %
		Y	8.26	78.95	21.97		65.0	
		Z	6.65	75.97	20.82		65.0	

Certificate No: EX3-3801\_Jun18

Page 22 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4-SN:3801

June 26, 2018

10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	2.40	65.55	14.34	0.00	150.0	± 9.6 %
		Y	2.55	66.36	15.12		150.0	
		Z	2.40	65.52	14.34		150.0	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	1.37	65.59	13.82	0.00	150.0	± 9.6 %
		Y	1.57	67.69	15.34		150.0	
		Z	1.37	65.56	13.81		150.0	
10277-CAA	PHS (QPSK)	X	2.46	62.30	7.92	9.03	50.0	± 9.6 %
		Y	2.99	63.83	9.17		50.0	
		Z	2.33	62.06	7.69		50.0	
10278-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.5)	X	4.98	72.46	15.62	9.03	50.0	± 9.6 %
		Y	8.77	80.80	19.53		50.0	
		Z	5.06	73.09	15.89		50.0	
10279-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.38)	X	5.10	72.72	15.78	9.03	50.0	± 9.6 %
		Y	8.97	81.08	19.68		50.0	
		Z	5.19	73.36	16.06		50.0	
10290-AAB	CDMA2000, RC1, SO55, Full Rate	X	0.97	64.08	10.61	0.00	150.0	± 9.6 %
		Y	1.37	68.00	13.49		150.0	
		Z	0.98	64.13	10.68		150.0	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	0.58	62.04	9.17	0.00	150.0	± 9.6 %
		Y	0.77	65.07	11.88		150.0	
		Z	0.58	62.07	9.23		150.0	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	0.64	63.79	10.46	0.00	150.0	± 9.6 %
		Y	0.99	69.13	14.24		150.0	
		Z	0.64	63.81	10.51		150.0	
10293-AAB	CDMA2000, RC3, SO3, Full Rate	X	0.81	66.57	12.32	0.00	150.0	± 9.6 %
		Y	1.56	75.54	17.45		150.0	
		Z	0.81	66.55	12.35		150.0	
10295-AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	X	11.79	88.13	24.57	9.03	50.0	± 9.6 %
		Y	13.93	91.96	26.60		50.0	
		Z	12.03	89.02	24.99		50.0	
10297-AAC	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	2.43	67.83	15.42	0.00	150.0	± 9.6 %
		Y	2.71	69.51	16.44		150.0	
		Z	2.43	67.81	15.41		150.0	
10298-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	1.17	64.21	11.42	0.00	150.0	± 9.6 %
		Y	1.51	67.23	13.79		150.0	
		Z	1.18	64.25	11.49		150.0	
10299-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	2.14	67.38	12.81	0.00	150.0	± 9.6 %
		Y	2.87	70.55	14.69		150.0	
		Z	2.09	67.00	12.62		150.0	
10300-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	1.64	63.53	10.15	0.00	150.0	± 9.6 %
		Y	2.07	65.55	11.64		150.0	
		Z	1.63	63.41	10.08		150.0	
10301-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	X	4.80	65.91	17.41	4.17	50.0	± 9.6 %
		Y	5.18	67.15	18.29		50.0	
		Z	4.75	65.66	17.30		50.0	
10302-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC, 3 CTRL symbols)	X	5.25	66.32	18.01	4.96	50.0	± 9.6 %
		Y	5.53	67.15	18.67		50.0	
		Z	5.21	66.16	17.95		50.0	

Certificate No: EX3-3801\_Jun18

Page 23 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN.3801

June 26, 2018

10303-AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	X	5.02	66.03	17.86	4.96	50.0	± 9.6 %	
			Y	5.30	66.93	18.58		50.0	
			Z	4.98	65.85	17.79		50.0	
10304-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	X	4.79	65.79	17.29	4.17	50.0	± 9.6 %	
			Y	5.06	66.59	17.94		50.0	
			Z	4.76	65.63	17.23		50.0	
10305-AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	X	4.90	69.87	20.22	6.02	35.0	± 9.6 %	
			Y	5.31	71.48	21.54		35.0	
			Z	4.75	69.22	19.95		35.0	
10306-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	X	4.99	68.00	19.55	6.02	35.0	± 9.6 %	
			Y	5.28	69.01	20.47		35.0	
			Z	4.90	67.60	19.37		35.0	
10307-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	X	4.92	68.28	19.55	6.02	35.0	± 9.6 %	
			Y	5.25	69.46	20.56		35.0	
			Z	4.82	67.84	19.36		35.0	
10308-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	X	4.92	68.59	19.73	6.02	35.0	± 9.6 %	
			Y	5.26	69.83	20.78		35.0	
			Z	4.82	68.12	19.53		35.0	
10309-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	X	5.04	68.19	19.68	6.02	35.0	± 9.6 %	
			Y	5.35	69.29	20.64		35.0	
			Z	4.95	67.79	19.50		35.0	
10310-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	X	4.96	68.14	19.55	6.02	35.0	± 9.6 %	
			Y	5.25	69.19	20.50		35.0	
			Z	4.87	67.72	19.37		35.0	
10311-AAC	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	2.77	67.21	15.18	0.00	150.0	± 9.6 %	
			Y	3.07	68.80	16.10		150.0	
			Z	2.77	67.19	15.17		150.0	
10313-AAA	iDEN 1:3	X	4.50	74.82	16.72	6.99	70.0	± 9.6 %	
			Y	8.14	81.70	19.31		70.0	
			Z	4.21	74.79	16.81		70.0	
10314-AAA	iDEN 1:6	X	6.62	83.57	22.82	10.00	30.0	± 9.6 %	
			Y	15.63	96.40	26.94		30.0	
			Z	6.51	84.13	23.15		30.0	
10315-AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	1.00	62.64	14.01	0.17	150.0	± 9.6 %	
			Y	1.09	64.02	15.23		150.0	
			Z	0.99	62.54	13.97		150.0	
10316-AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	X	4.44	66.34	15.98	0.17	150.0	± 9.6 %	
			Y	4.58	66.68	16.29		150.0	
			Z	4.45	66.32	15.98		150.0	
10317-AAC	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	X	4.44	66.34	15.98	0.17	150.0	± 9.6 %	
			Y	4.58	66.68	16.29		150.0	
			Z	4.45	66.32	15.98		150.0	
10400-AAD	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	4.51	66.55	15.91	0.00	150.0	± 9.6 %	
			Y	4.66	66.92	16.21		150.0	
			Z	4.52	66.54	15.91		150.0	
10401-AAD	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	X	5.26	66.85	16.18	0.00	150.0	± 9.6 %	
			Y	5.36	67.11	16.38		150.0	
			Z	5.27	66.86	16.18		150.0	

Certificate No: EX3-3801\_Jun18

Page 24 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4-SN:3801

June 26, 2018

10402-AAD	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	X	5.49	67.07	16.16	0.00	150.0	± 9.6 %
		Y	5.61	67.41	16.38		150.0	
		Z	5.50	67.07	16.16		150.0	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	0.97	64.08	10.61	0.00	115.0	± 9.6 %
		Y	1.37	68.00	13.49		115.0	
		Z	0.98	64.13	10.68		115.0	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	0.97	64.08	10.61	0.00	115.0	± 9.6 %
		Y	1.37	68.00	13.49		115.0	
		Z	0.98	64.13	10.68		115.0	
10406-AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	X	30.79	107.36	27.23	0.00	100.0	± 9.6 %
		Y	100.00	120.16	29.82		100.0	
		Z	19.65	100.98	25.49		100.0	
10410-AAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	X	100.00	124.91	31.71	3.23	80.0	± 9.6 %
		Y	100.00	121.32	30.41		80.0	
		Z	100.00	125.61	31.93		80.0	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	0.92	61.75	13.36	0.00	150.0	± 9.6 %
		Y	0.98	62.81	14.44		150.0	
		Z	0.92	61.72	13.35		150.0	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	4.37	66.26	15.86	0.00	150.0	± 9.6 %
		Y	4.50	66.58	16.15		150.0	
		Z	4.38	66.25	15.86		150.0	
10417-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	X	4.37	66.26	15.86	0.00	150.0	± 9.6 %
		Y	4.50	66.58	16.15		150.0	
		Z	4.38	66.25	15.86		150.0	
10418-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	X	4.36	66.42	15.89	0.00	150.0	± 9.6 %
		Y	4.49	66.74	16.17		150.0	
		Z	4.37	66.40	15.88		150.0	
10419-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	X	4.38	66.37	15.89	0.00	150.0	± 9.6 %
		Y	4.51	66.69	16.17		150.0	
		Z	4.39	66.35	15.89		150.0	
10422-AAB	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	X	4.50	66.38	15.91	0.00	150.0	± 9.6 %
		Y	4.63	66.69	16.18		150.0	
		Z	4.51	66.36	15.91		150.0	
10423-AAB	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	X	4.64	66.66	16.02	0.00	150.0	± 9.6 %
		Y	4.79	67.00	16.30		150.0	
		Z	4.65	66.65	16.02		150.0	
10424-AAB	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	X	4.57	66.61	15.99	0.00	150.0	± 9.6 %
		Y	4.72	66.95	16.27		150.0	
		Z	4.58	66.60	15.99		150.0	
10425-AAB	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	X	5.19	66.94	16.22	0.00	150.0	± 9.6 %
		Y	5.31	67.25	16.45		150.0	
		Z	5.20	66.93	16.22		150.0	
10426-AAB	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	X	5.21	67.03	16.26	0.00	150.0	± 9.6 %
		Y	5.32	67.28	16.46		150.0	
		Z	5.22	67.02	16.26		150.0	

Certificate No: EX3-3801\_Jun18

Page 25 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10427-AAB	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	X	5.21	66.94	16.22	0.00	150.0	± 9.6 %
		Y	5.33	67.26	16.44		150.0	
		Z	5.22	66.94	16.22		150.0	
10430-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	X	4.02	70.30	17.56	0.00	150.0	± 9.6 %
		Y	4.18	70.49	17.96		150.0	
		Z	4.02	70.25	17.56		150.0	
10431-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	X	4.00	66.69	15.72	0.00	150.0	± 9.6 %
		Y	4.18	67.12	16.13		150.0	
		Z	4.01	66.67	15.72		150.0	
10432-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	X	4.33	66.63	15.89	0.00	150.0	± 9.6 %
		Y	4.48	67.00	16.21		150.0	
		Z	4.33	66.61	15.89		150.0	
10433-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	X	4.58	66.64	16.01	0.00	150.0	± 9.6 %
		Y	4.73	66.99	16.29		150.0	
		Z	4.59	66.63	16.01		150.0	
10434-AAA	W-CDMA (BS Test Model 1, 64 DPCH)	X	4.06	70.92	17.34	0.00	150.0	± 9.6 %
		Y	4.27	71.30	17.90		150.0	
		Z	4.06	70.88	17.35		150.0	
10435-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	124.67	31.60	3.23	80.0	± 9.6 %
		Y	100.00	121.12	30.31		80.0	
		Z	100.00	125.37	31.82		80.0	
10447-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.24	66.36	14.69	0.00	150.0	± 9.6 %
		Y	3.47	67.09	15.42		150.0	
		Z	3.25	66.35	14.70		150.0	
10448-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	3.86	66.46	15.57	0.00	150.0	± 9.6 %
		Y	4.02	66.90	15.99		150.0	
		Z	3.86	66.45	15.58		150.0	
10449-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	4.15	66.44	15.77	0.00	150.0	± 9.6 %
		Y	4.29	66.82	16.11		150.0	
		Z	4.16	66.43	15.77		150.0	
10450-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.36	66.40	15.85	0.00	150.0	± 9.6 %
		Y	4.49	66.75	16.14		150.0	
		Z	4.37	66.38	15.84		150.0	
10451-AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	X	3.07	66.27	14.09	0.00	150.0	± 9.6 %
		Y	3.35	67.23	15.01		150.0	
		Z	3.09	66.28	14.12		150.0	
10456-AAB	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)	X	6.10	67.60	16.46	0.00	150.0	± 9.6 %
		Y	6.17	67.80	16.60		150.0	
		Z	6.11	67.59	16.46		150.0	
10457-AAA	UMTS-FDD (DC-HSDPA)	X	3.68	64.94	15.56	0.00	150.0	± 9.6 %
		Y	3.76	65.22	15.86		150.0	
		Z	3.68	64.92	15.56		150.0	
10458-AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	X	3.64	69.83	16.43	0.00	150.0	± 9.6 %
		Y	3.92	70.59	17.30		150.0	
		Z	3.65	69.81	16.46		150.0	
10459-AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	X	4.90	68.31	17.78	0.00	150.0	± 9.6 %
		Y	4.99	68.05	17.92		150.0	
		Z	4.90	68.27	17.79		150.0	

Certificate No: EX3-3801\_Jun18

Page 26 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10460-AAA	UMTS-FDD (WCDMA, AMR)	X	0.70	64.51	13.31	0.00	150.0	± 9.6 %
		Y	0.86	67.82	15.75		150.0	
		Z	0.70	64.47	13.28		150.0	
10461-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	126.99	33.67	3.29	80.0	± 9.6 %
		Y	100.00	126.52	32.84		80.0	
		Z	100.00	129.61	33.85		80.0	
10462-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	11.24	85.71	18.56	3.23	80.0	± 9.6 %
		Y	100.00	107.01	23.71		80.0	
		Z	7.60	81.91	17.44		80.0	
10463-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.22	68.12	12.22	3.23	80.0	± 9.6 %
		Y	8.52	79.99	16.22		80.0	
		Z	1.89	66.79	11.65		80.0	
10464-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	126.35	32.27	3.23	80.0	± 9.6 %
		Y	100.00	124.09	31.55		80.0	
		Z	100.00	126.89	32.42		80.0	
10465-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.43	78.04	16.22	3.23	80.0	± 9.6 %
		Y	61.58	101.53	22.35		80.0	
		Z	4.13	75.48	15.36		80.0	
10466-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.84	66.23	11.40	3.23	80.0	± 9.6 %
		Y	5.22	75.15	14.66		80.0	
		Z	1.61	65.19	10.92		80.0	
10467-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	126.67	32.42	3.23	80.0	± 9.6 %
		Y	100.00	124.36	31.67		80.0	
		Z	100.00	127.22	32.57		80.0	
10468-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.42	79.84	16.80	3.23	80.0	± 9.6 %
		Y	95.13	106.08	23.39		80.0	
		Z	4.76	76.99	15.88		80.0	
10469-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.85	66.30	11.43	3.23	80.0	± 9.6 %
		Y	5.30	75.30	14.71		80.0	
		Z	1.62	65.24	10.95		80.0	
10470-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	126.70	32.42	3.23	80.0	± 9.6 %
		Y	100.00	124.39	31.67		80.0	
		Z	100.00	127.26	32.58		80.0	
10471-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.33	79.66	16.73	3.23	80.0	± 9.6 %
		Y	93.01	105.78	23.31		80.0	
		Z	4.69	76.83	15.81		80.0	
10472-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.84	66.22	11.39	3.23	80.0	± 9.6 %
		Y	5.23	75.17	14.65		80.0	
		Z	1.60	65.17	10.90		80.0	
10473-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	126.67	32.40	3.23	80.0	± 9.6 %
		Y	100.00	124.35	31.66		80.0	
		Z	100.00	127.22	32.56		80.0	
10474-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.23	79.51	16.69	3.23	80.0	± 9.6 %
		Y	89.77	105.43	23.23		80.0	
		Z	4.63	76.70	15.77		80.0	
10475-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.83	66.18	11.37	3.23	80.0	± 9.6 %
		Y	5.17	75.07	14.62		80.0	
		Z	1.59	65.13	10.89		80.0	

Certificate No: EX3-3801\_Jun18

Page 27 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



EX3DV4- SN:3801

June 26, 2018

10477-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.49	78.15	16.23	3.23	80.0	± 9.6 %
		Y	65.26	102.05	22.44		80.0	
		Z	4.15	75.54	15.36		80.0	
10478-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.81	66.09	11.33	3.23	80.0	± 9.6 %
		Y	5.09	74.88	14.55		80.0	
		Z	1.58	65.06	10.85		80.0	
10479-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	18.48	99.99	27.17	3.23	80.0	± 9.6 %
		Y	22.20	101.96	27.87		80.0	
		Z	14.17	96.33	26.21		80.0	
10480-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	14.09	89.36	21.95	3.23	80.0	± 9.6 %
		Y	20.63	93.88	23.53		80.0	
		Z	11.71	87.23	21.36		80.0	
10481-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	9.14	82.86	19.53	3.23	80.0	± 9.6 %
		Y	14.27	88.02	21.43		80.0	
		Z	7.91	81.27	19.06		80.0	
10482-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.52	69.21	14.96	2.23	80.0	± 9.6 %
		Y	5.13	78.71	19.34		80.0	
		Z	2.46	69.28	15.12		80.0	
10483-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.99	74.88	17.01	2.23	80.0	± 9.6 %
		Y	7.65	80.31	19.44		80.0	
		Z	4.60	74.09	16.78		80.0	
10484-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.44	73.15	16.36	2.23	80.0	± 9.6 %
		Y	6.72	78.36	18.77		80.0	
		Z	4.14	72.49	16.16		80.0	
10485-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.13	72.16	17.32	2.23	80.0	± 9.6 %
		Y	5.32	79.69	20.70		80.0	
		Z	3.02	71.96	17.37		80.0	
10486-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.95	68.06	15.01	2.23	80.0	± 9.6 %
		Y	4.18	72.74	17.56		80.0	
		Z	2.88	68.00	15.09		80.0	
10487-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.94	67.68	14.83	2.23	80.0	± 9.6 %
		Y	4.10	72.11	17.30		80.0	
		Z	2.88	67.63	14.91		80.0	
10488-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.50	71.98	18.18	2.23	80.0	± 9.6 %
		Y	4.95	77.05	20.46		80.0	
		Z	3.37	71.66	18.14		80.0	
10489-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.43	68.78	16.82	2.23	80.0	± 9.6 %
		Y	4.19	71.55	18.33		80.0	
		Z	3.34	68.53	16.79		80.0	
10490-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.52	68.64	16.78	2.23	80.0	± 9.6 %
		Y	4.25	71.23	18.22		80.0	
		Z	3.43	68.39	16.75		80.0	
10491-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.74	70.64	17.84	2.23	80.0	± 9.6 %
		Y	4.79	74.22	19.51		80.0	
		Z	3.63	70.36	17.79		80.0	
10492-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.79	68.16	16.96	2.23	80.0	± 9.6 %
		Y	4.41	70.27	18.11		80.0	
		Z	3.70	67.92	16.91		80.0	

Certificate No: EX3-3801\_Jun18

Page 28 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10493-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.85	68.05	16.92	2.23	80.0	± 9.6 %
		Y	4.46	70.06	18.03		80.0	
		Z	3.76	67.81	16.88		80.0	
10494-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.02	71.95	18.24	2.23	80.0	± 9.6 %
		Y	5.39	76.25	20.12		80.0	
		Z	3.90	71.68	18.20		80.0	
10495-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.82	68.49	17.15	2.23	80.0	± 9.6 %
		Y	4.47	70.75	18.33		80.0	
		Z	3.72	68.24	17.10		80.0	
10496-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.90	68.26	17.09	2.23	80.0	± 9.6 %
		Y	4.51	70.34	18.20		80.0	
		Z	3.81	68.02	17.05		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.64	63.93	11.45	2.23	80.0	± 9.6 %
		Y	3.48	72.94	16.17		80.0	
		Z	1.62	64.10	11.64		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.36	60.00	8.37	2.23	80.0	± 9.6 %
		Y	2.11	64.18	11.38		80.0	
		Z	1.34	60.00	8.46		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.38	60.00	8.24	2.23	80.0	± 9.6 %
		Y	2.00	63.38	10.85		80.0	
		Z	1.36	60.00	8.32		80.0	
10500-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.25	71.93	17.62	2.23	80.0	± 9.6 %
		Y	4.97	78.02	20.41		80.0	
		Z	3.13	71.66	17.62		80.0	
10501-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.19	68.55	15.79	2.23	80.0	± 9.6 %
		Y	4.19	72.26	17.86		80.0	
		Z	3.11	68.40	15.83		80.0	
10502-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.23	68.38	15.66	2.23	80.0	± 9.6 %
		Y	4.22	71.98	17.69		80.0	
		Z	3.16	68.25	15.70		80.0	
10503-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.45	71.77	18.08	2.23	80.0	± 9.6 %
		Y	4.88	76.80	20.35		80.0	
		Z	3.33	71.45	18.04		80.0	
10504-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.41	68.67	16.76	2.23	80.0	± 9.6 %
		Y	4.17	71.45	18.27		80.0	
		Z	3.32	68.43	16.73		80.0	
10505-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.50	68.54	16.72	2.23	80.0	± 9.6 %
		Y	4.23	71.13	18.16		80.0	
		Z	3.41	68.30	16.69		80.0	
10506-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.99	71.81	18.17	2.23	80.0	± 9.6 %
		Y	5.34	76.07	20.04		80.0	
		Z	3.87	71.54	18.13		80.0	
10507-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.80	68.43	17.11	2.23	80.0	± 9.6 %
		Y	4.45	70.68	18.30		80.0	
		Z	3.71	68.18	17.07		80.0	

Certificate No: EX3-3801\_Jun18

Page 29 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10508-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.89	68.19	17.05	2.23	80.0	± 9.6 %
		Y	4.50	70.26	18.15		80.0	
		Z	3.79	67.95	17.00		80.0	
10509-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.34	70.70	17.76	2.23	80.0	± 9.6 %
		Y	5.36	73.79	19.16		80.0	
		Z	4.23	70.47	17.73		80.0	
10510-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.29	68.19	17.17	2.23	80.0	± 9.6 %
		Y	4.88	70.06	18.13		80.0	
		Z	4.20	67.96	17.12		80.0	
10511-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.35	67.98	17.12	2.23	80.0	± 9.6 %
		Y	4.91	69.72	18.03		80.0	
		Z	4.26	67.75	17.07		80.0	
10512-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.50	72.02	18.14	2.23	80.0	± 9.6 %
		Y	5.87	75.98	19.85		80.0	
		Z	4.38	71.80	18.12		80.0	
10513-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.18	68.39	17.24	2.23	80.0	± 9.6 %
		Y	4.80	70.47	18.29		80.0	
		Z	4.08	68.16	17.19		80.0	
10514-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.21	68.03	17.15	2.23	80.0	± 9.6 %
		Y	4.78	69.92	18.12		80.0	
		Z	4.11	67.80	17.09		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	0.88	61.83	13.34	0.00	150.0	± 9.6 %
		Y	0.94	62.98	14.49		150.0	
		Z	0.88	61.80	13.32		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	0.41	64.58	12.89	0.00	150.0	± 9.6 %
		Y	0.57	70.03	16.74		150.0	
		Z	0.41	64.53	12.84		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	0.70	62.81	13.29	0.00	150.0	± 9.6 %
		Y	0.79	64.81	15.03		150.0	
		Z	0.70	62.78	13.27		150.0	
10518-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.36	66.33	15.84	0.00	150.0	± 9.6 %
		Y	4.49	66.65	16.13		150.0	
		Z	4.37	66.32	15.84		150.0	
10519-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.53	66.54	15.95	0.00	150.0	± 9.6 %
		Y	4.68	66.89	16.24		150.0	
		Z	4.54	66.53	15.95		150.0	
10520-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.38	66.47	15.86	0.00	150.0	± 9.6 %
		Y	4.53	66.84	16.16		150.0	
		Z	4.39	66.46	15.86		150.0	
10521-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.31	66.44	15.83	0.00	150.0	± 9.6 %
		Y	4.46	66.84	16.15		150.0	
		Z	4.32	66.44	15.83		150.0	
10522-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.37	66.58	15.94	0.00	150.0	± 9.6 %
		Y	4.52	66.93	16.24		150.0	
		Z	4.38	66.57	15.94		150.0	

Certificate No: EX3-3801\_Jun18

Page 30 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4-- SN:3801

June 26, 2018

10523-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.27	66.46	15.79	0.00	150.0	± 9.6 %
		Y	4.40	66.80	16.08		150.0	
		Z	4.28	66.44	15.79		150.0	
10524-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.32	66.49	15.90	0.00	150.0	± 9.6 %
		Y	4.47	66.85	16.20		150.0	
		Z	4.32	66.48	15.90		150.0	
10525-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.32	65.56	15.51	0.00	150.0	± 9.6 %
		Y	4.45	65.90	15.80		150.0	
		Z	4.33	65.54	15.51		150.0	
10526-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.47	65.88	15.64	0.00	150.0	± 9.6 %
		Y	4.62	66.26	15.94		150.0	
		Z	4.47	65.87	15.64		150.0	
10527-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.39	65.83	15.57	0.00	150.0	± 9.6 %
		Y	4.54	66.22	15.88		150.0	
		Z	4.40	65.82	15.57		150.0	
10528-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.40	65.85	15.60	0.00	150.0	± 9.6 %
		Y	4.56	66.24	15.91		150.0	
		Z	4.41	65.83	15.60		150.0	
10529-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.40	65.85	15.60	0.00	150.0	± 9.6 %
		Y	4.56	66.24	15.91		150.0	
		Z	4.41	65.83	15.60		150.0	
10531-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.38	65.90	15.59	0.00	150.0	± 9.6 %
		Y	4.55	66.34	15.92		150.0	
		Z	4.39	65.89	15.59		150.0	
10532-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.25	65.75	15.52	0.00	150.0	± 9.6 %
		Y	4.41	66.19	15.85		150.0	
		Z	4.26	65.74	15.52		150.0	
10533-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.41	65.91	15.60	0.00	150.0	± 9.6 %
		Y	4.57	66.29	15.90		150.0	
		Z	4.42	65.89	15.60		150.0	
10534-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	4.96	66.00	15.73	0.00	150.0	± 9.6 %
		Y	5.09	66.34	15.97		150.0	
		Z	4.97	65.99	15.73		150.0	
10535-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	5.03	66.17	15.81	0.00	150.0	± 9.6 %
		Y	5.16	66.52	16.05		150.0	
		Z	5.03	66.17	15.81		150.0	
10536-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	4.90	66.11	15.76	0.00	150.0	± 9.6 %
		Y	5.03	66.47	16.01		150.0	
		Z	4.91	66.11	15.76		150.0	
10537-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	4.95	66.08	15.75	0.00	150.0	± 9.6 %
		Y	5.08	66.43	16.00		150.0	
		Z	4.96	66.07	15.75		150.0	
10538-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	5.04	66.10	15.80	0.00	150.0	± 9.6 %
		Y	5.17	66.45	16.05		150.0	
		Z	5.04	66.09	15.80		150.0	
10540-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	4.97	66.08	15.81	0.00	150.0	± 9.6 %
		Y	5.11	66.47	16.07		150.0	
		Z	4.97	66.08	15.81		150.0	

Certificate No: EX3-3801\_Jun18

Page 31 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10541-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	4.95	65.97	15.74	0.00	150.0	± 9.6 %
		Y	5.08	66.34	16.00		150.0	
		Z	4.95	65.97	15.74		150.0	
10542-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	5.10	66.08	15.81	0.00	150.0	± 9.6 %
		Y	5.23	66.41	16.05		150.0	
		Z	5.11	66.07	15.81		150.0	
10543-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	5.17	66.10	15.85	0.00	150.0	± 9.6 %
		Y	5.31	66.44	16.09		150.0	
		Z	5.18	66.09	15.85		150.0	
10544-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.30	66.13	15.75	0.00	150.0	± 9.6 %
		Y	5.40	66.46	15.97		150.0	
		Z	5.30	66.12	15.75		150.0	
10545-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.48	66.56	15.92	0.00	150.0	± 9.6 %
		Y	5.59	66.86	16.12		150.0	
		Z	5.49	66.55	15.92		150.0	
10546-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.34	66.28	15.79	0.00	150.0	± 9.6 %
		Y	5.46	66.66	16.04		150.0	
		Z	5.35	66.28	15.79		150.0	
10547-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.41	66.35	15.82	0.00	150.0	± 9.6 %
		Y	5.53	66.70	16.05		150.0	
		Z	5.42	66.35	15.82		150.0	
10548-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	5.62	67.15	16.20	0.00	150.0	± 9.6 %
		Y	5.76	67.56	16.45		150.0	
		Z	5.63	67.16	16.20		150.0	
10550-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.38	66.38	15.86	0.00	150.0	± 9.6 %
		Y	5.49	66.68	16.06		150.0	
		Z	5.39	66.37	15.85		150.0	
10551-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.37	66.33	15.80	0.00	150.0	± 9.6 %
		Y	5.50	66.72	16.04		150.0	
		Z	5.38	66.34	15.80		150.0	
10552-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.30	66.20	15.73	0.00	150.0	± 9.6 %
		Y	5.41	66.53	15.95		150.0	
		Z	5.31	66.19	15.73		150.0	
10553-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.37	66.20	15.77	0.00	150.0	± 9.6 %
		Y	5.50	66.56	16.00		150.0	
		Z	5.38	66.20	15.77		150.0	
10554-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	5.71	66.50	15.85	0.00	150.0	± 9.6 %
		Y	5.81	66.82	16.06		150.0	
		Z	5.72	66.50	15.85		150.0	
10555-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	5.83	66.78	15.97	0.00	150.0	± 9.6 %
		Y	5.93	67.11	16.18		150.0	
		Z	5.83	66.78	15.98		150.0	
10556-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	5.85	66.84	16.00	0.00	150.0	± 9.6 %
		Y	5.95	67.16	16.20		150.0	
		Z	5.86	66.84	16.00		150.0	
10557-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	5.81	66.72	15.96	0.00	150.0	± 9.6 %
		Y	5.92	67.07	16.18		150.0	
		Z	5.82	66.71	15.96		150.0	

Certificate No: EX3-3801\_Jun18

Page 32 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10558-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	5.85	66.86	16.05	0.00	150.0	± 9.6 %
		Y	5.96	67.22	16.27		150.0	
		Z	5.86	66.86	16.05		150.0	
10560-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	5.85	66.73	16.02	0.00	150.0	± 9.6 %
		Y	5.96	67.08	16.24		150.0	
		Z	5.85	66.73	16.02		150.0	
10561-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	5.78	66.71	16.04	0.00	150.0	± 9.6 %
		Y	5.88	67.05	16.26		150.0	
		Z	5.79	66.71	16.04		150.0	
10562-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	5.86	66.98	16.18	0.00	150.0	± 9.6 %
		Y	6.00	67.41	16.44		150.0	
		Z	5.87	66.99	16.18		150.0	
10563-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	5.96	66.91	16.11	0.00	150.0	± 9.6 %
		Y	6.20	67.62	16.50		150.0	
		Z	5.97	66.93	16.12		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	4.70	66.44	16.03	0.46	150.0	± 9.6 %
		Y	4.82	66.76	16.31		150.0	
		Z	4.70	66.43	16.03		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	4.91	66.87	16.35	0.46	150.0	± 9.6 %
		Y	5.05	67.19	16.62		150.0	
		Z	4.91	66.86	16.35		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	4.74	66.69	16.15	0.46	150.0	± 9.6 %
		Y	4.89	67.04	16.44		150.0	
		Z	4.75	66.68	16.15		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	4.77	67.08	16.52	0.46	150.0	± 9.6 %
		Y	4.91	67.41	16.78		150.0	
		Z	4.78	67.07	16.52		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	4.65	66.47	15.92	0.46	150.0	± 9.6 %
		Y	4.80	66.85	16.23		150.0	
		Z	4.66	66.47	15.92		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	4.74	67.23	16.61	0.46	150.0	± 9.6 %
		Y	4.87	67.51	16.84		150.0	
		Z	4.75	67.21	16.60		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	4.76	67.06	16.53	0.46	150.0	± 9.6 %
		Y	4.90	67.36	16.78		150.0	
		Z	4.77	67.05	16.53		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.10	63.42	14.47	0.46	130.0	± 9.6 %
		Y	1.22	65.16	15.85		130.0	
		Z	1.08	63.24	14.41		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.11	63.89	14.77	0.46	130.0	± 9.6 %
		Y	1.24	65.79	16.22		130.0	
		Z	1.09	63.70	14.70		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	1.08	73.84	17.41	0.46	130.0	± 9.6 %
		Y	4.49	96.37	26.07		130.0	
		Z	1.00	73.13	17.22		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	1.13	68.08	16.84	0.46	130.0	± 9.6 %
		Y	1.43	72.28	19.34		130.0	
		Z	1.10	67.75	16.73		130.0	

Certificate No: EX3-3801\_Jun18

Page 33 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.50	66.27	16.10	0.46	130.0	± 9.6 %
		Y	4.63	66.61	16.40		130.0	
		Z	4.50	66.26	16.10		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.52	66.45	16.17	0.46	130.0	± 9.6 %
		Y	4.65	66.77	16.46		130.0	
		Z	4.52	66.43	16.17		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	4.70	66.71	16.33	0.46	130.0	± 9.6 %
		Y	4.85	67.04	16.62		130.0	
		Z	4.71	66.70	16.33		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	4.60	66.85	16.43	0.46	130.0	± 9.6 %
		Y	4.75	67.20	16.72		130.0	
		Z	4.61	66.83	16.43		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.36	66.09	15.70	0.46	130.0	± 9.6 %
		Y	4.52	66.52	16.06		130.0	
		Z	4.37	66.07	15.70		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.41	66.16	15.74	0.46	130.0	± 9.6 %
		Y	4.57	66.57	16.09		130.0	
		Z	4.42	66.15	15.74		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.50	66.88	16.37	0.46	130.0	± 9.6 %
		Y	4.65	67.26	16.67		130.0	
		Z	4.51	66.86	16.37		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.30	65.86	15.49	0.46	130.0	± 9.6 %
		Y	4.47	66.30	15.86		130.0	
		Z	4.31	65.85	15.49		130.0	
10583-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.50	66.27	16.10	0.46	130.0	± 9.6 %
		Y	4.63	66.61	16.40		130.0	
		Z	4.50	66.26	16.10		130.0	
10584-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.52	66.45	16.17	0.46	130.0	± 9.6 %
		Y	4.65	66.77	16.46		130.0	
		Z	4.52	66.43	16.17		130.0	
10585-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	4.70	66.71	16.33	0.46	130.0	± 9.6 %
		Y	4.85	67.04	16.62		130.0	
		Z	4.71	66.70	16.33		130.0	
10586-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	4.60	66.85	16.43	0.46	130.0	± 9.6 %
		Y	4.75	67.20	16.72		130.0	
		Z	4.61	66.83	16.43		130.0	
10587-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.36	66.09	15.70	0.46	130.0	± 9.6 %
		Y	4.52	66.52	16.06		130.0	
		Z	4.37	66.07	15.70		130.0	
10588-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.41	66.16	15.74	0.46	130.0	± 9.6 %
		Y	4.57	66.57	16.09		130.0	
		Z	4.42	66.15	15.74		130.0	
10589-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.50	66.88	16.37	0.46	130.0	± 9.6 %
		Y	4.65	67.26	16.67		130.0	
		Z	4.51	66.86	16.37		130.0	
10590-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.30	65.86	15.49	0.46	130.0	± 9.6 %
		Y	4.47	66.30	15.86		130.0	
		Z	4.31	65.85	15.49		130.0	

Certificate No: EX3-3801\_Jun18

Page 34 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10591-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	4.65	66.36	16.22	0.46	130.0	± 9.6 %
		Y	4.78	66.66	16.49		130.0	
		Z	4.65	66.34	16.22		130.0	
10592-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	4.79	66.67	16.35	0.46	130.0	± 9.6 %
		Y	4.93	66.99	16.62		130.0	
		Z	4.79	66.66	16.35		130.0	
10593-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	4.70	66.55	16.21	0.46	130.0	± 9.6 %
		Y	4.85	66.90	16.51		130.0	
		Z	4.71	66.54	16.21		130.0	
10594-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	4.76	66.73	16.38	0.46	130.0	± 9.6 %
		Y	4.91	67.07	16.66		130.0	
		Z	4.76	66.72	16.38		130.0	
10595-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	4.72	66.69	16.28	0.46	130.0	± 9.6 %
		Y	4.87	67.03	16.56		130.0	
		Z	4.73	66.67	16.28		130.0	
10596-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	4.66	66.67	16.27	0.46	130.0	± 9.6 %
		Y	4.81	67.03	16.56		130.0	
		Z	4.66	66.65	16.27		130.0	
10597-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	4.61	66.55	16.13	0.46	130.0	± 9.6 %
		Y	4.76	66.93	16.45		130.0	
		Z	4.61	66.53	16.13		130.0	
10598-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	4.59	66.77	16.39	0.46	130.0	± 9.6 %
		Y	4.74	67.15	16.70		130.0	
		Z	4.60	66.76	16.39		130.0	
10599-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.32	66.88	16.47	0.46	130.0	± 9.6 %
		Y	5.44	67.19	16.70		130.0	
		Z	5.33	66.88	16.48		130.0	
10600-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.45	67.29	16.65	0.46	130.0	± 9.6 %
		Y	5.56	67.56	16.85		130.0	
		Z	5.45	67.29	16.66		130.0	
10601-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.34	67.05	16.54	0.46	130.0	± 9.6 %
		Y	5.46	67.33	16.76		130.0	
		Z	5.35	67.04	16.55		130.0	
10602-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.46	67.19	16.54	0.46	130.0	± 9.6 %
		Y	5.55	67.37	16.70		130.0	
		Z	5.47	67.18	16.53		130.0	
10603-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.52	67.44	16.80	0.46	130.0	± 9.6 %
		Y	5.63	67.66	16.97		130.0	
		Z	5.53	67.43	16.80		130.0	
10604-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.40	67.11	16.62	0.46	130.0	± 9.6 %
		Y	5.45	67.17	16.71		130.0	
		Z	5.40	67.08	16.61		130.0	
10605-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.45	67.23	16.67	0.46	130.0	± 9.6 %
		Y	5.55	67.47	16.87		130.0	
		Z	5.46	67.22	16.67		130.0	
10606-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.18	66.51	16.16	0.46	130.0	± 9.6 %
		Y	5.31	66.84	16.41		130.0	
		Z	5.19	66.49	16.16		130.0	

Certificate No: EX3-3801\_Jun18

Page 35 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



EX3DV4- SN:3801

June 26, 2018

10607-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.48	65.64	15.83	0.46	130.0	± 9.6 %
		Y	4.61	65.97	16.11		130.0	
		Z	4.49	65.63	15.83		130.0	
10608-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	4.64	66.01	15.99	0.46	130.0	± 9.6 %
		Y	4.80	66.37	16.28		130.0	
		Z	4.65	66.00	15.99		130.0	
10609-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.54	65.84	15.81	0.46	130.0	± 9.6 %
		Y	4.69	66.23	16.12		130.0	
		Z	4.54	65.83	15.81		130.0	
10610-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	4.59	66.00	15.98	0.46	130.0	± 9.6 %
		Y	4.74	66.38	16.28		130.0	
		Z	4.59	65.99	15.98		130.0	
10611-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.50	65.80	15.82	0.46	130.0	± 9.6 %
		Y	4.66	66.19	16.13		130.0	
		Z	4.51	65.79	15.82		130.0	
10612-AAB	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.50	65.94	15.85	0.46	130.0	± 9.6 %
		Y	4.67	66.35	16.18		130.0	
		Z	4.51	65.93	15.86		130.0	
10613-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.50	65.79	15.72	0.46	130.0	± 9.6 %
		Y	4.67	66.23	16.06		130.0	
		Z	4.51	65.78	15.72		130.0	
10614-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.45	65.99	15.96	0.46	130.0	± 9.6 %
		Y	4.61	66.40	16.28		130.0	
		Z	4.46	65.98	15.96		130.0	
10615-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.50	65.64	15.59	0.46	130.0	± 9.6 %
		Y	4.66	66.04	15.92		130.0	
		Z	4.50	65.63	15.59		130.0	
10616-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	5.13	66.09	16.06	0.46	130.0	± 9.6 %
		Y	5.26	66.43	16.30		130.0	
		Z	5.14	66.09	16.06		130.0	
10617-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	5.20	66.29	16.13	0.46	130.0	± 9.6 %
		Y	5.32	66.60	16.36		130.0	
		Z	5.21	66.29	16.14		130.0	
10618-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	5.09	66.30	16.15	0.46	130.0	± 9.6 %
		Y	5.21	66.61	16.38		130.0	
		Z	5.10	66.29	16.15		130.0	
10619-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	5.10	66.08	15.98	0.46	130.0	± 9.6 %
		Y	5.23	66.42	16.22		130.0	
		Z	5.11	66.08	15.98		130.0	
10620-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	5.18	66.12	16.05	0.46	130.0	± 9.6 %
		Y	5.32	66.47	16.30		130.0	
		Z	5.19	66.12	16.05		130.0	
10621-AAB	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	5.20	66.27	16.24	0.46	130.0	± 9.6 %
		Y	5.32	66.58	16.46		130.0	
		Z	5.20	66.27	16.25		130.0	
10622-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	5.21	66.44	16.32	0.46	130.0	± 9.6 %
		Y	5.33	66.73	16.53		130.0	
		Z	5.22	66.44	16.33		130.0	

Certificate No: EX3-3801\_Jun18

Page 36 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10623-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	5.08	65.93	15.93	0.46	130.0	± 9.6 %
		Y	5.21	66.29	16.19		130.0	
		Z	5.09	65.93	15.94		130.0	
10624-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.27	66.16	16.11	0.46	130.0	± 9.6 %
		Y	5.40	66.47	16.35		130.0	
		Z	5.28	66.15	16.12		130.0	
10625-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	5.52	66.79	16.49	0.46	130.0	± 9.6 %
		Y	5.74	67.39	16.86		130.0	
		Z	5.54	66.83	16.51		130.0	
10626-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.45	66.17	16.04	0.46	130.0	± 9.6 %
		Y	5.55	66.49	16.26		130.0	
		Z	5.46	66.17	16.04		130.0	
10627-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	5.69	66.77	16.30	0.46	130.0	± 9.6 %
		Y	5.78	67.03	16.49		130.0	
		Z	5.69	66.76	16.31		130.0	
10628-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.46	66.20	15.95	0.46	130.0	± 9.6 %
		Y	5.58	66.58	16.20		130.0	
		Z	5.47	66.20	15.96		130.0	
10629-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.54	66.30	15.99	0.46	130.0	± 9.6 %
		Y	5.66	66.63	16.22		130.0	
		Z	5.55	66.30	16.00		130.0	
10630-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	5.89	67.55	16.62	0.46	130.0	± 9.6 %
		Y	6.06	68.03	16.92		130.0	
		Z	5.91	67.58	16.64		130.0	
10631-AAB	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	5.82	67.43	16.76	0.46	130.0	± 9.6 %
		Y	5.97	67.86	17.02		130.0	
		Z	5.83	67.44	16.77		130.0	
10632-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.66	66.86	16.49	0.46	130.0	± 9.6 %
		Y	5.75	67.08	16.64		130.0	
		Z	5.67	66.85	16.49		130.0	
10633-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.53	66.40	16.08	0.46	130.0	± 9.6 %
		Y	5.65	66.74	16.31		130.0	
		Z	5.53	66.39	16.09		130.0	
10634-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.51	66.41	16.15	0.46	130.0	± 9.6 %
		Y	5.63	66.76	16.38		130.0	
		Z	5.51	66.41	16.15		130.0	
10635-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.38	65.73	15.53	0.46	130.0	± 9.6 %
		Y	5.52	66.14	15.81		130.0	
		Z	5.39	65.73	15.54		130.0	
10636-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	5.88	66.55	16.14	0.46	130.0	± 9.6 %
		Y	5.96	66.85	16.34		130.0	
		Z	5.88	66.55	16.15		130.0	
10637-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	6.02	66.92	16.31	0.46	130.0	± 9.6 %
		Y	6.11	67.22	16.51		130.0	
		Z	6.03	66.93	16.32		130.0	
10638-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	6.02	66.89	16.27	0.46	130.0	± 9.6 %
		Y	6.12	67.20	16.48		130.0	
		Z	6.02	66.89	16.28		130.0	

Certificate No: EX3-3801\_Jun18

Page 37 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10639-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	5.99	66.82	16.28	0.46	130.0	± 9.6 %
		Y	6.09	67.15	16.50		130.0	
		Z	6.00	66.82	16.29		130.0	
10640-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	5.99	66.81	16.22	0.46	130.0	± 9.6 %
		Y	6.10	67.17	16.45		130.0	
		Z	5.99	66.82	16.23		130.0	
10641-AAC	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	6.05	66.80	16.24	0.46	130.0	± 9.6 %
		Y	6.14	67.07	16.42		130.0	
		Z	6.06	66.80	16.24		130.0	
10642-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	6.08	67.00	16.51	0.46	130.0	± 9.6 %
		Y	6.18	67.31	16.70		130.0	
		Z	6.09	67.00	16.51		130.0	
10643-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	5.93	66.71	16.25	0.46	130.0	± 9.6 %
		Y	6.02	67.01	16.46		130.0	
		Z	5.93	66.71	16.25		130.0	
10644-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	6.03	67.03	16.43	0.46	130.0	± 9.6 %
		Y	6.18	67.49	16.72		130.0	
		Z	6.04	67.04	16.44		130.0	
10645-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	6.17	67.10	16.43	0.46	130.0	± 9.6 %
		Y	6.47	67.97	16.92		130.0	
		Z	6.18	67.13	16.45		130.0	
10646-AAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	19.17	110.50	37.83	9.30	60.0	± 9.6 %
		Y	100.00	147.85	47.85		60.0	
		Z	16.64	107.87	37.15		60.0	
10647-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	16.90	108.32	37.31	9.30	60.0	± 9.6 %
		Y	88.18	146.06	47.63		60.0	
		Z	14.61	105.54	36.57		60.0	
10648-AAA	CDMA2000 (1x Advanced)	X	0.50	60.79	7.93	0.00	150.0	± 9.6 %
		Y	0.64	62.89	10.17		150.0	
		Z	0.50	60.83	7.99		150.0	
10652-AAB	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.55	66.61	16.13	2.23	80.0	± 9.6 %
		Y	3.97	68.09	17.10		80.0	
		Z	3.49	66.41	16.10		80.0	
10653-AAB	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	4.10	66.10	16.44	2.23	80.0	± 9.6 %
		Y	4.44	67.21	17.15		80.0	
		Z	4.04	65.91	16.40		80.0	
10654-AAB	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	4.10	65.77	16.48	2.23	80.0	± 9.6 %
		Y	4.40	66.84	17.14		80.0	
		Z	4.04	65.58	16.43		80.0	
10655-AAB	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.17	65.74	16.53	2.23	80.0	± 9.6 %
		Y	4.46	66.82	17.18		80.0	
		Z	4.11	65.55	16.47		80.0	
10658-AAA	Pulse Waveform (200Hz, 10%)	X	75.07	110.20	27.10	10.00	50.0	± 9.6 %
		Y	100.00	114.77	28.62		50.0	
		Z	100.00	113.64	27.73		50.0	
10659-AAA	Pulse Waveform (200Hz, 20%)	X	100.00	110.55	25.39	6.99	60.0	± 9.6 %
		Y	100.00	111.82	26.31		60.0	
		Z	100.00	110.88	25.38		60.0	

Certificate No: EX3-3801\_Jun18

Page 38 of 39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4- SN:3801

June 26, 2018

10660-AAA	Pulse Waveform (200Hz, 40%)	X	100.00	107.54	22.75	3.98	80.0	± 9.6 %
		Y	100.00	110.49	24.46		80.0	
		Z	100.00	108.31	22.90		80.0	
10661-AAA	Pulse Waveform (200Hz, 60%)	X	100.00	104.54	20.30	2.22	100.0	± 9.6 %
		Y	100.00	111.15	23.54		100.0	
		Z	100.00	104.99	20.30		100.0	
10662-AAA	Pulse Waveform (200Hz, 80%)	X	5.09	77.36	11.00	0.97	120.0	± 9.6 %
		Y	100.00	111.11	21.88		120.0	
		Z	1.05	68.52	8.18		120.0	

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

**- End of report -**

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.